

Contents

Preface	x
1—Introduction	1
Background	1
Project Description	2
2—Preplacement Monitoring	7
Placement Site Bathymetry	7
Native Sediments in Placement Area	8
Field collection techniques	8
Sediment analysis techniques	10
Placement site native sediment analysis results	14
Current Velocity and Direction Measurements	17
Wave Height and Water-Level Measurements	18
3—Dredging and Dredged Material Placement Monitoring	20
Automated Disposal Surveillance System	20
Dredge Area Sediments	20
Dredge Area Sediment Distribution	22
4—Postplacement Monitoring and Results	26
Bathymetry	26
December 1998	26
March 1999	26
May 1999	27
October 1999	28
Mixed-sediment mound morphology changes	28
Postplacement Sediment Monitoring	34
Immediate postplacement sediment - December 1988	35
Postplacement sediment - May 1999	38
Postplacement sediment monitoring - October 1999	40
Wave Analysis	45
Wave modeling	47
Wave transformation modeling approach	51
Time-history of waves at mound and gage locations	61
Wave transformation model results	62
Current Analysis	65
ADP current monitoring	65
ADCP current monitoring	65

5—Erosion Rates and Bulk Properties of Dredged Sediments	70
Experimental Procedures	71
Measurements of Erosion Rates.....	72
Measurements of Critical Shear Stress for Erosion	73
Bulk Properties Measurements	74
General Sediment Characteristics	75
General Erosion Characteristics.....	76
Bulk Properties and Erosion Rates	77
6—Conclusions	86
References	96
Appendix A: Sediment Data.....	A1
Appendix B: Wave Model Description	B1
Appendix C: Time-History Plots at Selected Stations.....	C1
SF 298	

List of Figures

Figure 1.	Location map.....	3
Figure 2.	Dredge area in Mobile River	4
Figure 3.	Location of mixed-sediment mound on southwest edge of Mobile Bay entrance ebb shoal.....	5
Figure 4.	Preproject Fathometer bathymetry collected in April 1998.....	8
Figure 5.	Posthurricane multibeam bathymetry collected in October 1998	9
Figure 6.	Preplacement native sediment sample locations – October 1998.....	11
Figure 7.	Distribution of four basic native sediment types	15
Figure 8.	Plot of laser-derived mean grain size versus depth	16
Figure 9.	Plot of selected sand-size sediment shows that the sorting is related to depth	16
Figure 10.	Plot of representative grain-size frequency curves of the four native sediment types	17
Figure 11.	Acoustic Doppler Profiler (ADP).....	18
Figure 12.	Housing for Acoustic Doppler Profiler showing top of ADP in center hole of housing	18
Figure 13.	Microtide electronic wave height and water-level recorder.....	19

Figure 14.	Tract lines when split-hull barge was open	21
Figure 15.	Dredge operations in Mobile River	23
Figure 16.	Grain-size distribution curves of dredge area samples	24
Figure 17.	Grain-size distribution of the native sediment compared with river dredge material	25
Figure 18.	Multibeam bathymetry immediately postplacement showing mixed-sediment mound in December 1998	27
Figure 19.	Multibeam bathymetry 6 months after placement in March 1999	28
Figure 20.	Multibeam bathymetry 8 months after placement in May 1999	29
Figure 21.	Multibeam bathymetry roughly 1 year after placement in October 1999	30
Figure 22.	Three-dimensional closeup view of premound bathymetry in October 1998	31
Figure 23.	Three-dimensional closeup view of postmound bathymetry in December 1998	31
Figure 24.	Change map of pre- to postmound bathymetry between October and December 1998. Thick 0 change line outlines mound footprint	32
Figure 25.	Three-dimensional plot of change in pre- to postmound bathymetry between October and December 1998	32
Figure 26.	Three-dimensional closeup view of postmound bathymetry in May 1999	33
Figure 27.	Change map of postmound bathymetry between December 1998 and May 1999	33
Figure 28.	Three-dimensional plot of change in postmound bathymetry between December 1998 and May 1999	34
Figure 29.	Three-dimensional closeup view of postmound bathymetry in October 1999	35
Figure 30.	Change map of postmound bathymetry between May and October 1999	36
Figure 31.	Three-dimensional plot of change in postmound bathymetry between May and October 1999	36
Figure 32.	Frequency distribution curves of representative native sand and placed cohesive material	37
Figure 33.	Location and type of postplacement sediments – December 1998	37
Figure 34.	Frequency distribution curves of postplacement sediment samples	38

Figure 35.	Location of expanded sampling of postplacement sediments – May 1999.....	40
Figure 36.	Distribution of postplacement sediment types – May 1999.....	42
Figure 37.	Sediment sample locations of complete postdredging sample set (October 1999).....	43
Figure 38.	Map of dredged grain-size type distribution and closeup bathymetry of postplacement sediment sample area (October 1999).....	46
Figure 39.	Grain-size distribution plot of Sample 4-3probe from the middle of the mixed-sediment mound showing the change in distribution from a native sand distribution (10/98) to the characteristic Mobile River cohesive sediment curve (12/98 and 5/99) and the increase of more fine sand back into the distribution 1 year later (10/99).....	46
Figure 40.	Wave rose from WIS Sta 47 for the years 1976 to 1995.....	49
Figure 41.	Wave model domains and location of NDBC buoys.....	51
Figure 42.	Map of study area showing the two WIS output locations.....	52
Figure 43.	Comparison of time series of WIS L2 output (solid line) and NDCB Buoy 42001 data (+) in the period of January to March 1999.....	53
Figure 44.	Comparison of time series of WIS L3 output (solid line) and NDCB Buoy 42040 data (+) in the period of January to March 1999.....	54
Figure 45.	Comparison of model and measured wave roses at NDBC Buoy 42003 and 42036 locations for the period of January to March 1999.....	55
Figure 46.	Time series of WIS L3 output at MBAY1 (+) and MBAY2 (solid line) for the period of October to December 1998.....	56
Figure 47.	Time series of WIS L3 output at MBAY1 (+) and MBAY2 (solid line) for the period of January to March 1999.....	57
Figure 48.	Time series of WIS L3 output at MBAY1 (+) and MBAY2 (solid line) for the period of April to June 1999.....	58
Figure 49.	Time series of WIS L3 output at MBAY1 (+) and MBAY2 (solid line) for the period of July to September 1999.....	59
Figure 50.	Time series of WIS L3 output at MBAY1 (+) and MBAY2 (solid line) for the period of October to December 1999.....	60

Figure 51.	Wave rose diagrams at MBAY1 and MBAY2 locations for the period of October to December 1998	61
Figure 52.	Wave rose diagrams at MBAY1 and MBAY2 locations for the period of January to December 1999	62
Figure 53.	STWAVE grid.....	63
Figure 54.	Location map of STWAVE output stations	64
Figure 55.	Map of depth-averaged ADCP current vectors along line 4 for 10/28/99	67
Figure 56.	Cross-section plot of horizontally averaged ADCP current velocity on line 4.....	68
Figure 57.	Schematic of Sedflume.....	71
Figure 58.	Bulk density as a function of depth at times after deposition of 3 hr and 2, 8, 32, 64, 90, and 167 days.....	78
Figure 59.	At 64 days, density of the solid-water matrix, ρ^* (averaged over 1 cm), as well as bulk density, ρ , at 0.1- and 1.0-cm averages as a function of depth	79
Figure 60.	Gas fraction as a function of depth at times after deposition of 1, 2, 4, 15, 45, and 60 days.....	80
Figure 61.	Erosion rates as a function of depth with shear stress (N/m^2) as a parameter at times	81
Figure 62.	Erosion rates as a function of density with shear stress (N/m^2) as a parameter. Straight lines are approximations by means of Equation 1	85
Figure 63.	Mean versus sorting plot of native sediments showing four sediment types	86
Figure 64.	Mean versus sorting plot of Mobile River barge samples and immediate postplacement sediments showing characteristic dredged material sediment type	87
Figure 65.	Mean versus sorting plot of mound area sediments showing change in 6-month postplacement sediment types	88
Figure 66.	Mean versus sorting plot of mound area sediments showing change in 1-year postplacement sediment types.....	89
Figure 67.	Map of change in sediment type from October 1998 to October 1999.....	90
Figure 68.	Example of grain-size frequency curves of the pre- and postdredge placement sediments in the <i>No Change</i> group.....	91
Figure 69.	Example of grain-size frequency curves of the pre- and postdredge placement sediments in the <i>Increasing Coarse</i> group.....	91

Figure 70.	Example of grain-size frequency curves of the pre- and postdredge placement sediments in the <i>Coarse to Fine to Mixed</i> group.....	92
Figure 71.	Example of grain-size frequency curves of the pre- and postdredge placement sediments in the <i>Increasing Fines</i> group	93
Figure 72.	Example of grain-size frequency curves of the pre- and postdredge placement sediments in the <i>Fine to Coarse to Mixed</i> group.....	94

List of Tables

Table 1.	Project Time Line.....	6
Table 2.	Sieve Results for Native Ebb Shoal Samples.....	12
Table 3.	Native Ebb Shoal Sediment Analysis Results Based on Laser Particle Counter.....	13
Table 4.	Mobile River and Immediate Postdredging Sediment Statistics by Laser Particle Counter.....	25
Table 5.	Geotechnical Properties of Postplacement Samples – December 1998	39
Table 6.	Postplacement Sediment Statistics by Laser Particle Counter (27 May 1999).....	41
Table 7.	Postplacement Sediment Statistics by Laser Particle Counter (26-27 October 1999).....	44
Table 8.	Wave Measurements and WIS Hindcast Properties	48
Table 9.	WIS Points with Incident Wave Information	52
Table 10.	Specifications for STWAVE South-Facing Grid	63
Table 11.	STWAVE Output Stations	64
Table 12.	Tidal and Meteorologically-Induced Currents	65
Table 13.	Bulk Parameters and Surface Critical Shear Stresses for All Sites.....	76

Conversion Factors, Non-SI to SI Units of Measurement

Non-SI units of measurement used in this report can be converted to SI units as follows:

Multiply	By	To Obtain
cubic yards	0.7645549	cubic meters
degrees (angle)	0.01745329	radians
feet	0.3048	meters
gallons (U.S. liquid)	0.003785412	cubic meters
inches	25.4	millimeters
miles (U.S. statute)	1.609347	kilometers
square feet	0.09290304	square meters
pounds (mass) per cubic foot	16.01846	kilograms per cubic meter
pounds (mass) per square foot	4.882428	kilograms per square meter

Preface

This study was conducted by the U.S. Army Engineer Research and Development Center (ERDC) (formerly U.S. Army Engineer Waterways Experiment Station (WES)), Coastal and Hydraulics Laboratory (CHL), Coastal Evaluation and Design Branch (CE&DB). The study was authorized and funded by the Dredging Operations and Environmental Research (DOER) Program. The technical manager was Dr. Robert Engler (ERDC). Mr. James Clausner (ERDC) was technical area leader. Dr. Jack Davis (ERDC) was the Principal Investigator.

Work was performed under the general supervision of Ms. Joan Pope, former Chief, Coastal Evaluation and Design Branch and Dr. Yen-Hsi Chu, Chief, CE&DB; Mr Bruce Ebersole, Chief, Coastal Processes Branch; Dr. Zeki Demirbilek, Acting Chief, Coastal Hydraulics Branch; Mr. Rob McAdory, Chief, Tidal and Hydraulics Branch; Mr. Thomas Pokrefke, Acting Deputy Director, CHL; and Mr. Thomas W. Richardson, Acting Director, CHL. This report was prepared by Drs. Donald K. Stauble, Jack E. Davis, Joseph Z. Gailani, Lihwa Lin, Edward F. Thompson, and Messers. Howard Benson, and Thad C. Pratt of CHL, and Dr. Marian Rollins, formerly of Geotechnical and Structures Laboratory (GSL) and now of Cold Regions Research and Engineering Laboratory (CRREL).

The authors would like to thank Ms. Linda Lillycrop, U.S. Army Engineer District, Mobile, for coordination, providing data, base maps, dredging information and discussion on the project. Field data collection was assisted by Messers. Sam Varnell, Terry Waller, Chris Callahan (CHL), on board the *SV Mr. Dave* and Messers. Ellis Mnott, Tommy Hughes, Matt Tate, and Nathan Lovelace (U.S. Army District, Mobile), aboard the *SV Gatlin*. Additional District personnel assisted with logistics and data collection efforts.

At the time of publication of this report, Dr. James R. Houston was Director of ERDC, and COL John W. Morris III, EN, was Commander and Executive Director.

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

1 Introduction

As part of the U.S. Army Corps of Engineers' Dredging Operations and Environmental Research (DOER) Program, the U.S. Army Engineer Research and Development Center's (ERDC) Coastal and Hydraulics Laboratory (CHL) and U.S. Army Engineer District, Mobile, constructed a mixed sediment dredged material mound offshore of Mobile Bay, AL. Monitoring the long-term fate of the mixed sediment mound was initiated immediately following construction. The purpose of the field investigation was to provide data to advance our understanding of the geotechnical properties of dredged material before, during, and after dredging, and for verification of Corps numerical models, which predict the fate of dredged sediments during the many phases of dredging. Of greatest interest is the long-term fate of mixed sediments (i.e., dredged material with a fraction of fines equal to or greater than about 50 percent) placed at a nearshore location. The expectation is that over time the sand fraction will become part of the nearshore littoral sediment transport system, potentially providing sand to nourish beaches, while the fine fraction will disperse to deeper, quieter water where other fine material exists without adverse consequences. Acceptance of placing mixed sediments in the nearshore zone will provide for beneficial uses of material, reduce haul distance, and reduce shoreline erosion (McNair 1998). This report describes the construction, monitoring efforts, and initial study results.

Background

The Corps annually dredges approximately 268 million cu m (350 million cu yd) of material to improve and maintain Federal harbors and channels. The Corps has estimated that somewhere between 20 to 30 percent of the dredged material is used beneficially. A large volume of the dredged sediment is composed of silts and clays, but can contain a significant fraction of sand. In coastal settings, the most common placement of dredged material is in open-water sites some distance from the coast where it is not confined by structures and is removed from the littoral system. In nearshore and beach environments, the only dredged material placement usually allowed is sand, due to concerns that fine materials (silts and clays) will disperse and smother benthic organisms as well as cause excessive nearshore turbidity. The turbidity may affect the use of the area by marine life for feeding or spawning, and may directly impair the growth of some organisms like sea grasses or corals. Another concern is that some of the fine materials might be transported onto the beach, which might lessen the beach's public appeal. The actual turbidity or magnitude of suspended sediments

that might be generated from a given nearshore mixed-sediment mound is unknown, as well as the magnitude of any adverse environmental effects. So, until more is known about the erosion and transport processes of mixed sediments, dredged material containing significant fractions of fine-grain sizes may not be allowed in the nearshore.

The ability to numerically simulate and predict mixed-sediment erosion and transport would be helpful in that a variety of climatic scenarios could be explored and the environmental risks of nearshore placements investigated. A good description of the processes of erosion and transport of such sediments is necessary to develop a model for simulations. Jepsen, McNeil, and Lick (2000); Roberts et al. (1998); and Jepsen, Roberts, and Lick (1997) have shown that sediment mixtures of sand, silt, and clay have significantly more complex erosion characteristics than pure sand or predominately sandy sediments. These mixed sediments are often referred to as cohesive because of the tendency of the particles to adhere to each other. The erosion characteristics of these sediments cannot be described using the well-established methods for sandy sediments, where erosion is a function of grain-size distribution. Mixed sediment erosion rates will be affected, by not only grain size, but also bulk density, mineralogy, pore water chemistry, organic content, and the presence of gas bubbles. It is qualitatively understood that, depending on the conditions, one or more of these bulk properties may have an order of magnitude or more effect on erosion rates. However, insufficient data are available to quantify the effects of these parameters.

To begin the process of adding to our understanding of mixed-sediment transport processes, ERDC-CHL, and the Mobile District, are conducting research into the long-term fate of a mixed-sediment mound, placed on the western edge of the Mobile Bay entrance ebb shoal (Figure 1). Field data will be used to advance our understanding of the geotechnical properties of dredged material before, during, and after dredging, as well as provide quality data for verification of numerical models being developed by the Corps. Specifically, the Long Term Fate (LTFATE) (Scheffner et al. 1995) and Multiple Dump Fate (MDFATE) (Moritz 1994) models for dredged material placement can be verified with this data set for the fate of mixed sediments. These models are used to predict the fate of dredged material (i.e., where the material moves) during placement and over a given period (up to years) after placement. While data exists for sandy dredged-material mounds and for which the models have been well verified, little information is available regarding mixed sediments. Therefore, the data set collected through this study will provide a unique opportunity to advance our understanding of and ability to predict the fate of mixed-sediment dredged material. The ultimate goal is to have accurate numerical models that may be used to simulate the fate of nearshore mixed sediments to optimize placement such that the sandy portion of the material can replenish the littoral system without detrimental environmental effects from the silts and clays.

Project Description

Beginning in late October 1998, about 268,000 cu m (350,000 cu yd) of dredged material were placed in a designated study site outside the entrance to




Figure 1. Location map

Mobile Bay. The material was dredged from the Mobile River in the upper reaches of Mobile Bay near St. Louis Point (Figure 2). The material was removed with a bucket dredge and transported to the placement site using one 5,046-cu m (6,600-cu yd) and two 3,058-cu m (4,000-cu yd) split-hull barge scows. The placement area was roughly 93 m (1,000 ft) square and located on the southwestern edge of the entrance ebb shoal (Figure 3). All of the dredging and placement was accomplished over a 1-month period. Prior to dredging, the channel material was sampled to estimate the fraction of sands, silts, and clays. Tests indicated that the material was close to 50 percent sand, which was considered ideal for the study. Subsequent sampling of the placed dredged material indicated that it was only 20 percent sand, which was still satisfactory for the study. The material was cohesive and could be described as a black, fine-grained, cohesive sediment. The characteristics of the material are described in more detail in a later section.




Figure 2. Dredge area in Mobile River

Data were collected prior to, during, and periodically following the dredging and placement operations. Data collection and analyses included sediment characteristics of the material while it was in the barge and after placement in the mound, sediment characteristics of the surrounding seabed before and after placement, laboratory-measured dredged-material settling rates, periodic bathymetry of the study area, waves (measured and hindcast) and currents (Table 1).




Figure 3. Location of mixed-sediment mound on southwest edge of Mobile Bay entrance ebb shoal

Postplacement monitoring at the mound was continued for 1 year to assess the changing characteristics of the mound.

**Table 1
Project Time Line**

Date	Comments	Bathymetric Survey	Sediment Samples	ADP	Wave Gage	ADCP	Wave Modeling
1998							
Apr		Fathometer presurvey 4/21, 23					
May							
Jun							
Jul							
Aug							
Sep	Hurricane Georges 09/28						
Oct	Mound Construction 10/27-11/25	Multibeam presurvey 10/4-28	Presamples 10/20, 26	Deployed	Deployed		Start
Nov			Barge samples 10/21, 11/12, 11/24	↓	↓		STWAVE 10/98 – 12/98
Dec		Multibeam postsurvey 12/2	Postsamples 12/2	↓	↓		↓
1999							
Jan				↓	↓		WISWAVE 10/98 – 12/99 ↓ End
Feb							
Mar		Multibeam postsurvey 3/16-19					
Apr							
May		Multibeam postsurvey 5/19-23, 5/25-26, 6/1-2	Postsamples 5/26-27				
Jun				↓	↓		
Jul				Removed	Removed		
Aug							
Sep							
Oct		Multibeam postsurvey 10/4-28	Postsamples 10/26-27			Boat lines 10/28	
Nov							
Dec							