

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. **PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.**

1. REPORT DATE (DD-MM-YYYY) July 2001		2. REPORT TYPE Final report		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE Construction, Monitoring, and Data Analysis of a Nearshore Mixed-Sediment Mound, Mobile Bay Entrance, Alabama				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Donald K. Stauble, Jack E. Davis, Joseph Z. Gailani, Lihwa Lin, Edward F. Thompson, Howard Benson, Thad C. Pratt, Marian P. Rollings				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Engineer Research and Development Center Coastal and Hydraulics Laboratory 3909 Halls Ferry Road, Vicksburg, MS 39180-6199; U.S. Army Engineer Research and Development Center Cold Regions Research and Engineering Laboratory 72 Lyme Road, Hanover, NH 03755-1290				8. PERFORMING ORGANIZATION REPORT NUMBER ERDC TR-02-	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Corps of Engineers Washington, DC 20314-1000				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT As part of the U.S. Army Corps of Engineers' Dredging Operations and Environmental Research (DOER) Program, the U.S. Army Engineer Research and Development Center's (ERDC) Coastal and Hydraulics Laboratory (CHL) and U.S. Army Engineer District, Mobile, have constructed a mixed-sediment dredged material mound offshore of Mobile Bay, AL. The mound was located in 9.1 m (30 ft) of water just to the southwest of the ebb shoal of the Mobile Bay entrance. The purpose of the field investigation was to provide data to advance our understanding of the geotechnical properties of dredged material before, during, and after dredging, and for verification of Corps numerical models, which predict the fate of dredged sediments during the many phases of dredging. Of greatest interest is the long-term fate of mixed sediments (i.e., dredged material with a fraction of fines equal to or greater than about 50 percent) placed at a nearshore location. This report describes the construction, monitoring efforts, and initial study results. Wave, current, sediment samples, and multibeam bathymetry have been collected to assess the long-term movement and changes in the mixed-sediment disposal mound. Analysis of the data has related the flow patterns and bathymetric change to the alteration in grain-size patterns from the native sediment to the placed material. This mixed-sediment from the Mobile River had a distinctly characteristic black, fine-grained, cohesive sediment consistency, which acted as a cohesive sediment and was distinctive from the fine tan native sands. The (Continued)					
15. SUBJECT TERMS ADCP data Bathymetric change		Dredge material placement monitoring Mixed-sediment mound construction Mobile Bay entrance		Sediment erosion rates Sediment samples Wave modeling	
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT UNCLASSIFIED	b. ABSTRACT UNCLASSIFIED	c. THIS PAGE UNCLASSIFIED			132

14. (Concluded)

cohesive nature of this river material resulted in little change in material distribution during the dredging, hauling operation, and deposition from the split-hull barge, and 1-year after placement there was little change in mound morphology. A slight mixing of river sediment was found with the surrounding native sediment. Bulk property and erosion rate studies of the dredged sediments showed high concentrations of manganese and smectite, causing significant increases in the critical shear stress and decreases in the erosion rates of these placed sediments. Given the cohesive nature of these dredged sediments and the low magnitude of the typical waves and currents at this site, it appears that storm induced changes are needed to affect significant sediment transport and change depositional patterns at Mobile Bay entrance. Data from this study will provide a “no change” data point for sediment fate model validation.