QA / QC DRILLER: DAVID WILCOX IN DISCREPANCIES: CH	DIMENSIONS OF CONCRETE PAD (FT.) 3'X3' DEPTH TO TOP OF BENTONITE SEAL (bgs) DEPTH TO TOP OF SAND PACK (bgs) 90 FT. DEPTH TO TOP OF SAND PACK (bgs) 94 FT. GROUT GROUT SAND FILTER PACK 120 FT. 10 CONCRETE END CAP	(NOT TO SCALE; ALL MEASUREMENTS IN FEET) WELL PROTECTOR 24" DIAM. X 8" THICK	RISER DIAMETER 2 INCH DRILLING TECHNIQUE ROTO SONIC AUGER/BIT SIZE AND TYPE 6" OUTER CASING 4" CORE BARREL REMARKS	RISER MATERIAL SCH. 40 PVC MANUFACTURER JOHNSON	SCREEN MATERIAL SCH. 40 PVC MANUFACTURER JOHNSON SCREEN DIAMETER 2 INCH SLOT SIZE 0.010"	GROUND SURFACE ELEVATION 290.28 TOP OF SCREEN ELEVATION 192.66 REFERENCE POINT ELEVATION 290.08 TYPE FILTER PACK SAND GRADATION 20/40 FILTER PACK MANUFACTURER FILTER SIL	DDMT MONITORING WELL INSTALLATION PROJECT NAME DDMT WELL NO. DR1-2 WELL LOCATION DATE 05/06/2004 START TIME
INSPECTOR: BILL PAYNE CHECKED BY: K.A./RNQ DATE: 07-08-2004/09-3-2004	LENGTH OF SOLID RISER 97.42 FT. TOTAL DEPTH OF WELL (GROUND SURFACE TO BOTTOM OF END CAP) 118 FT. TOTAL DEPTH OF BORING (bgs) 4.5 INCH 136 FT.	— LOCKABLE CAP GROUND SURFACE	AMOUNT CEMENT USED (GROUT) 20—94 LB BAGS AMOUNT SAND USED 9 3/4—50 LB BAGS STATIC WATER LEVEL (>24 hrs after dev) 89.97 MEASURED ON (Date/Time) 06/25/2004	DENSITY OF GROUT=	MACTEC FIELD REPRESENTATIVE BILL PAYNE DRILLING CONTRACTOR PROSONIC AMOUNT BENTONITE BELOW (SCREEN) 4.9-50 LB BAGS AMOUNT BENTONITE USED (SEAL) 1-50 LB BAG AMOUNT BENTONITE USED (GROUT) 1-10 LB BAG	BENTONITE TYPE CHIPS MEDIUM MANUFACTURER PURE COLD CEMENT TYPE TYPE 1/11 PORTLAND CEMENT MANUFACTURER LONESTAR BOREHOLE DIAMETER 7 INCH	DDMT MONITORING WELL INSTALLATION DIAGRAM (FLUSH MOUNT COMPLETION) ME DDMT PROJECT NO. 6301-04-0602 R1-2 WELL LOCATION NORTH OF MW-101 S/06/2004 START TIME 1730