



PROJECT NUMBER 170039	BORING NUMBER MW-106
SOIL BORING LOG	

PROJECT : EBT Treatability Study LOCATION : Memphis Depot
 ELEVATION : DRILLING CONTRACTOR : Boart Longyear
 DRILLING METHOD AND EQUIPMENT USED : Rotasonic rig (4 inch sample casing / 6 inch outer casing)
 WATER LEVELS : START : 04/17/2002 END: 04/18/2002 LOGGER : Mike Karafa

DEPTH BELOW SURFACE (FT)				STANDARD		SOIL DESCRIPTION		COMMENTS	
INTERVAL (FT)				PENETRATION		SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY, OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY.		DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS, AND INSTRUMENTATION.	
RECOVERY (%)				TEST					
#/TYPE				RESULTS					
				6"-6"-6" (N)				Corrected FID (ppm): (Soil headspace)	
5 10 15 20 25 30 35	100				Asphalt and Gravel		0.0		
					Brownish red, silty, clay				
					Same as above		0.0		
					Same as above		0.0		
					Same as above		0.0		
					Sand, reddish orange, fine grain, well sorted		0.0		
					Sandy silt, some clay, white/grey mottled, stiff				
					Silty sand, orange, fine grain, well sortec		0.0		
					Sand, red, fine to medium grain, poorly sorted, small pebbles				
					Same as above		0.0		
					Sand, orange, fine to medium grain, poorly sortec				
					Sand, brown red, fine grain, well sorted		0.0		
					Sand, yellow, well sorted, fine grain				



PROJECT NUMBER 170039	BORING NUMBER MW-106
SOIL BORING LOG	

PROJECT : EBT Treatability Study	LOCATION : Memphis Depot
ELEVATION :	DRILLING CONTRACTOR : Boart Longyear
DRILLING METHOD AND EQUIPMENT USED : Rotasonic rig (4 inch sample casing / 6 inch outer casing)	
WATER LEVELS :	START : 04/17/2002 END: 04/18/2002 LOGGER : Mike Karafa

WATER LEVEL: _____		START: 04/17/2002		END: 04/19/2002		LOGGERS: Mike Rarala	
DEPTH BELOW SURFACE (FT)	INTERVAL (FT)			STANDARD	SOIL DESCRIPTION	COMMENTS	
		RECOVERY (%)	PENETRATION				
			TEST				
			RESULTS				
				6"-6"-6" (N)	SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY, OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY.	DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS, AND INSTRUMENTATION. Corrected FID (ppm):	
40		100			Same as above except reddish orange		
					Sand, tan, fine grain, well sorted	0.0	
					Sand, orange yellow, fine to medium grain, poorly sorted, loose		
					Same as above except brown		
					Sand, orange, fine grain, well sorted, loose, dry		
					Sand, white, fine to medium grain, poorly sorted, loose		
					Same as above except orange		
45					Same as above except orange with gravel up to 0.5 inch diameter	0.0	
					Same as above except white		
50		100			Sand, white, fine to medium grain, poorly sorted, loose, pebbles	12.1	
					Sand, tan, fine to medium grain, poorly sorted, loose gravel up tp 0.25 inch diameter		
					Sand, orange, fine to medium grain, poorly sorted, loose		
55					Sand, white, fine to medium grain, poorly sorted, loose, gravel up to 0.25 inch diameter		
					Sand, orange, fine to medium grain, poorly sorted, loose, pebble to cobbles		
					Same as above except tan	0.0	
					Same as above except orange		
60		100			Sand, interbedded tan and orange, fine to coarse grain, poorly sorted, gravel up to 0.5 inch diameter	0.0	
65					Sand, tan, fine grain, well sorted	0.0	
70		100			Same as above	0.0	
					Sand, tan, fine to medium grain, poorly sorted, gravel up to 0.25 inch diameter		



PROJECT NUMBER 170039	BORING NUMBER MW-106
SOIL BORING LOG	

PROJECT : EBT Treatability Study LOCATION : Memphis Depot
 ELEVATION : DRILLING CONTRACTOR : Boart Longyear
 DRILLING METHOD AND EQUIPMENT USED : Rotasonic rig (4 inch sample casing / 6 inch outer casing)
 WATER LEVELS : START : 04/17/2002 END: 04/18/2002 LOGGER : Mike Karafa

DEPTH BELOW SURFACE (FT)				STANDARD PENETRATION TEST RESULTS		SOIL DESCRIPTION		COMMENTS	
INTERVAL (FT)		RECOVERY (%)		6"-6"-6"-6" (N)		SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY, OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY.		DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS, TESTS, AND INSTRUMENTATION.	
		#/TYPE							
75						Sand, tan, fine grain, well sorted, loose			0.0
						Sand, orange, fine to medium grain, poorly sorted, gravel pebble to cobble: 2 inch reddish brown layer, sand, fine to medium grain, up to 0.25 inch gravel			
80			100			Sand, tan, fine to medium grain, poorly sorted, loose, pebble to cobble gravel, damp			
						Same as above except orange			0.0
						Sand, tan to light grey, fine grain wet			
						Silty clay, orange, thin grey mottling, wet			
85						Sand, tan, fine grain, gravel up to 1 inch, wet			0.0
						Same as above except wet			
90			100			Sand, grey, fine to medium grain, gravel up to 1 inch, damp			
						Sand, some clay, fine to coarse grain, gravel, wet			0.0
						Sand, orange, fine grain, damp			Water table @ 96 ft bgs
100						Sand, orange, fine to coarse grain, gravel pebble to cobble size, wet			
			100			Silty clay, orange and grey mottling, wet			
						Silty sand, some clay, stiff, wet			
105						Sand, orange, some clay, fine grain, wet			
						Clay, dark grey, massive			
110						Boring terminated at 110 ft bgs			