	PROJECT NUMBER		WELL NUMBER	
	170039		MW-11	3 SHEET 1 OF 1
CH2MHILL	WELL COMPLETION DIAGRAM			
PROJECT : EBT Treatability Study			LOCATION : Memphis Depot	
DRILLING CONTRACTOR : Boart Longyea	r			
DRILLING METHOD AND EQUIPMENT US WATER LEVELS :	SED : Rotasonic rig (4 inch sample casing / 6 inch oute START : 04/17/2002		04/17/2002	LOGGER : Mike Karafa
		START: 04/11/2002 END: 04/11/2		
3 3b 2 1		1- Ground elevation at well		feet MSL
		2- Top of casing elevation		feet MSL
3a 8 108 ft 4 10 ft	89 ft 94 ft 96 ft	3- Wellhead protection cover typea) drain tube?b) concrete pad dimensions		Flush-mount wellhead pad No 3 by 3 feet
		4- Dia./type of well casing		2 inch Schedule 40 PVC
		5- Type/slot size of screen		2 inch 10-slot Schedule 40 PVC
		6- Type screen filtera) Quantity used		Sand, DSI #2 bags
		7- Type of seala) Quantity used		Bentonite pellets, DSI Shur-plug 3/8" bags
	5	8- Grouta) Grout mix usedb) Method of placementc) Vol. of well casing groutDevelopment method		90% grout / 10% bentonite powder
				Tremmie Method
	6			Surge and develop with stainless steel bailer
		Development time		9 hour
		Estimated purge volume		37 gallons
		Comments	Total Depth (BGS) =	107 feet
	1 foot Sump			
Final field parameters collected during well development (/ /				
6 in		pH = conductivity = mS/cm		
Note: Diagram not to scale.			temperature = Dissolved Oxygen = Turbidity =	mg/l