DDMT MONITORIN	G WELL INSTALL	ATION DIAGRA	M (FLUSH M	OUNT COMPL	ETION)
WELL ID. MW-171		NORTHING:	282315.35	EASTING:	801057.83
DATE12/09/0	4	START TIME	14	:00	
GROUND SURFACE ELEVATION:	271.02	BENTONITE TYP	PE	3/8" Coarse G	Grade
		MANUFACTURE			
TOP OF SCREEN ELEVATION: 218.05		CEMENT TYPE Type I Portland Cement			Cement
		MANUFACTURER Quikrete			
REFERENCE POINT ELEVATION	270.69	BOREHOLE DIAMETER 6"			
		MACTEC FIELD	REPRESENTAT	IVE J	aime Piver
TYPE FILTER PACK	20/40 Sand	DRILLING CONT	RACTOR	ProSonic	
FILTER PACK MANUFACTURER	FilterSil	AMOUNT BENTO	NITE BELOW (SCREEN)	8 (50lb) bags
		AMOUNT BENTO			
SCREEN MATERIAL	Schedule 40 PVC				
MANUFACTURER					
		-		14.3 lbs/kg	
RISER DIAMETER	2"	_			
		- AMOUNT CEMEI	NT USED (GRO	UT) 7	(90 lb) bags
DRILLING TECHNIQUE					·
AUGER/BIT SIZE AND TYPE	6"/4"			- (,3	-
		STATIC WATER	LEVEL (>24 hrs	after dev)	57.4
			,	_	-
REMARKS		MEASURED ON	(Date/Time)	1	2/13/2004
ANOT TO COALE, ALL MEACUREMENTS IN FE	FT\				
(NOT TO SCALE: ALL MEASUREMENTS IN FE	WELL PROTECTOR				
	WELL PROTECTOR	∠ LOCKABLE CAI		GI	ROUND SURFACE
DIMENSIONS OF		2 1888888			
CONCRETE DAD		·	<u> </u>	↑	
3ft x 3ft	_	LENGTH OF			
		RISER		-	TOTAL LENGTH OF
Top of		54.50 ft			WELL (TOC TO
Bentonite			-		BOTTOM OF END
43.83 ft (bgs)					CAP)
10.00 11 (090)	>				69.88 ft
Top of Sand RISE	R —				00.00 it
Pack —	_		1		
48.83 ft (bgs) SCREE	. I =		- 		
	"──┼	LENGTH OF	·		
CONCRETE		SCREEN	1		
7/////		15.08 ft	• [
GROUT		_	*		
BENTONITE		LENGTH OF	I		
SAND FILTER PACK	END CAP →	END CAP_ 0.302 ft	<u>.</u>	↓ -	Total Depth of Boring (bgs)
					96 ft
	DRILLER:	David Wilcox	INSPECTOR:	I.	aime Piver
QA/QC	DISCREPANCIES:	_ avia vviioox	CHECKED BY:		ATE: 01/10/05
	DISCREFAINCIES.		_ OLILONED DI: _	INING D	/\IL. 01/10/03