



## WELL INSTALLATION DIAGRAM

WELL NO.: MW-207A

PROJECT: DDMT - Phase 2 Wells

PROJECT NUMBER: 3202-019

SITE LOCATION: MI

e2M PROJECT MANAGER: T. Holmes

e2M FIELD STAFF: Jim Anstaett

DATE COMPLETED: 3/15/07

WELL LOCATION: Intersection of Troyer Ave. and Sitler St.

NORTHING: 277652.65

EASTING: 803191.86

GROUND SURFACE ELEVATION (ft, msl): 303.99

TOP OF CASING ELEVATION (ft, msl): 303.78

TOP OF SCREEN ELEVATION (ft, msl): 154.1

DRILLING CO.: Prosonic

DRILLING METHOD: Sonic

BOREHOLE DIAMETER (in): 6

SURFACE COMPLETION: Flush Mount

BOLLARDS: No

WELL DIAMETER (in): 2

TYPE OF SCREEN/RISER MATERIAL: PVC Schedule 40

SLOT SIZE OF SCREEN: 0.010

TYPE OF FILTER PACK: Sand

GRADATION OF FILTER PACK: 10-20

QUANTITY OF FILTER PACK: 7-50lb. Bags

TYPE OF BENTONITE IN SEAL: 3/8" Shur Plug Chips

QUANTITY OF BENTONITE IN SEAL: 2-50lb. Bag

TYPE OF GROUT: Portland Type I


QUANTITY OF GROUT: 23-94lb. Bags

DEVELOPMENT METHOD: Grundfos RediFlow II

DATE DEVELOPED: 3/22/2007

DEPTH TO WATER (ft.btoc): 108.01-ft. - 5/4/2007

NOTES:



Prepared by: WTR

Date: 5/16/2007

Checked by: KMS

Date: 5/16/2007