

Law Environmental, Inc.
Government Services Division
TEST BORING RECORD

BORING NUMBER MW-22
JOB NUMBER 11-8531-01
DATE STARTED 3-3-89
DATE COMPLETED 3-7-89
DRILLED BY JC
LOGGED BY FWT
CHECKED BY RM

REMARKS:

PAGE 1 OF 4

7 1/4" Hollow Stem Auger
Split Spoon Sampling

ELEV. IN FEET	DEPTH IN FEET	DESCRIPTION				CR	S	LT	SPT N VALUE
298.06	0.0	Very stiff light brown silty CLAY, CL							
293.06									22
288.06									12
283.06	13.5	Firm orange brown sandy clay grading into a clayey sand, CL							8
278.06	18.5	Stiff bright orange and gray clayey sand or sandy clay with sand content increasing downward, CL							14
273.06									53
268.06	29.0	Dense light tan coarse grained SAND with gravel content increasing downward, SP							40
263.06	35.0								

Law Environmental, Inc.
Government Services Division
TEST BORING RECORD

181 105

BORING NUMBER <u>MW-22</u> JOB NUMBER <u>11-8531-01</u> DATE STARTED <u>3-3-89</u> DATE COMPLETED <u>3-7-89</u> DRILLED BY <u>JC</u> LOGGED BY <u>FWT</u> CHECKED BY <u>RM</u>	REMARKS: _____ PAGE <u>2</u> OF <u>4</u>
--	---

ELEV. IN FEET	DEPTH IN FEET	DESCRIPTION				CR	S	LT	SPT N VALUE
	35.0	See previous page							54
258.06									61
	43.5	-----							
253.06		Very dense light tan slightly gravelly fine grained SAND with gravel content increasing downward, SP							57
248.06									76
	53.5	-----							
243.06		Very dense orange slightly gravelly fine to medium grained SAND, SP-SM							65
238.06									70
233.06									50/4
228.06	70.0								

18 107
200 81

ELEV. IN FEET	DEPTH IN FEET	DESCRIPTION				OR	S	LT	SPT N VALUE
	105.0	See previous page							50/4
188.06								GS AL W	50/3
183.06	113.5	Tannish brown coarse grained SAND grading to							
	115.0	tannish brown gravel, GM							
		Boring Terminated							