



WELL INSTALLATION DIAGRAM

WELL NO.: MW-243

PROJECT: Off Depot Remedial Action

PROJECT NUMBER: 3200-064

SITE LOCATION: Offsite NW of Dunn Field

e2M PROJECT MANAGER: Tom Holmes

e2M FIELD STAFF: J. Sperry

DATE COMPLETED: 6/28/09

WELL LOCATION: On Menager Rd., SW from MLGW gate.

NORTHING: 281370.62

EASTING: 801116.45

GROUND SURFACE ELEVATION (ft, msl): 292.53

TOP OF CASING ELEVATION (ft, msl): 292.26

TOP OF SCREEN ELEVATION (ft, msl): 211.56

DRILLING CO.: WDC

DRILLING METHOD: Sonic

BOREHOLE DIAMETER (in): 6

SURFACE COMPLETION: Flush Mount

BOLLARDS: No

WELL DIAMETER (in): 2

TYPE OF SCREEN/RISER MATERIAL: PVC Schedule 40

SLOT SIZE OF SCREEN: 0.010 inch

TYPE OF FILTER PACK: Sand

GRADATION OF FILTER PACK: 10/20

QUANTITY OF FILTER PACK: 10-50 lb. Bags

TYPE OF BENTONITE IN SEAL: 3/8" Coarse Grade

QUANTITY OF BENTONITE IN SEAL: 2-50 lb. Bags

TYPE OF GROUT: Portland Cement


QUANTITY OF GROUT: 12- 94 lb. Bags

DEVELOPMENT METHOD: Typhoon submersible pump

DATE DEVELOPED: 7/22/2009

DEPTH TO WATER (ft.btoc): 77.1

NOTES:



Prepared by: WTR

Date: 8/27/2009

Checked by: KMS

Date: 8/27/2009