

LAW ENVIRONMENTAL, INC.
GOVERNMENT SERVICES DIVISION

TEST BORING RECORD

BORING NUMBER <u> MW-30 </u> JOB NUMBER <u> 11-8531-01 </u> DATE STARTED <u> 11-27-89 </u> DATE COMPLETED <u> 11-28-89 </u> DRILLED BY <u> G. POWERS </u> LOGGED BY <u> P. VOGEL </u> CHECKED BY <u> F. THOMAS </u>	REMARKS: PAGE <u> 1 </u> OF <u> 2 </u> <div style="text-align: center;">8 1/4" Hollow Stem Auger</div> <div style="text-align: center;">Split Spoon Samples</div>
---	--

ELEV. IN FEET	DEPTH IN FEET	DESCRIPTION	MONITORING WELL CONSTRUCTION	SYM- BOLS	LAB TESTS	SPT N VALUE
273.93	0.0	Stiff to very stiff brown silty CLAY, CL				
268.93						10
263.93						17
258.93	16.0	Very stiff to dense brown to orange fine to medium grained gravelly sandy CLAY grading to gravelly clayey SAND, SP-SM				20
253.93						31
248.93						48
243.93	30.0	Dense reddish orange fine to medium grained fairly well sorted SAND, SP		GS AL W		38
238.93	35.0					46

LAW ENVIRONMENTAL, INC.
GOVERNMENT SERVICES DIVISION

TEST BORING RECORD

BORING NUMBER MW-30
JOB NUMBER 11-8531-01
DATE STARTED 11-27-89
DATE COMPLETED 11-28-89
DRILLED BY G. POWERS
LOGGED BY P. VOGEL
CHECKED BY F. THOMAS

REMARKS:

PAGE 2 OF 2

ELEV. IN FEET	DEPTH IN FEET	DESCRIPTION	MONITORING WELL CONSTRUCTION	SYM- BOLS	LAB TESTS	SPT N VALUE
	35.0	Dense orange to tan fine to medium grained SAND, SP				
233.93						47
228.93						24
223.93						50
218.93						>50
213.93						
208.93						
207.43	66.0	Brown and gray silty clay, CL				47
	66.5	Boring Terminated				