

JOB NAME _____ DDMT _____
WELL NO. MW-31 JOB NO. 11-8531-01
DATE 12-3-89 TIME 16:30
WELL LOCATION MLG & W PROPERTY (SOUTHERN)

STATIC WATER DEPTH (after dev.) 61.6' GSL

WELL PROTECTOR
LOCKABLE COVER
GROUND SURFACE
3.2' STICKUP
DIMENSIONS OF CONCRETE PAD
2' x 2' x 2"
DEPTH TO TOP OF BENTONITE SEAL
39.5'
DEPTH TO TOP OF GRANULAR MATERIAL
50.9'
LENGTH OF SOLID RISER
64.1'
TOTAL DEPTH OF WELL
79.2' TOC
STABILIZED WATER LEVEL
64.6 FEET TOC
MEASURED ON
12-28-89
GROUT
BENTONITE
GRANULAR BACKFILL
RISER
SCREEN
CAP
LENGTH OF SCREEN
15.0'
LENGTH OF TAIL PIPE
0.104'

LE WAS CAVING IN AFTER
ND PACK WAS MEASURED.
US, THE TOP OF GRANULAR MATERIAL IS AN INACCURATE
ASUREMENT.

QA / QC

INSTALLED BY: EF

INSTALLATION OBSERVED BY: FWT

DISCREPANCIES: