

Table 3-3

**Well Construction Summary
Ground Scar South of Building 3134, Parcel 153(7)
Fort McClellan, Calhoun County, Alabama**

Well Location	Northing	Easting	Ground Elevation (ft above msl)	TOC Elevation (ft above msl)	Well Depth (ft bgs)	Screen Length (ft)	Screen Interval (ft bgs)	Well Material
GSBP-153-MW01 ^a	1166833.01	668863.59	805.01	807.26	29.0	15	13.75 - 28.75	2" ID Sch. 40 PVC
SI13-GWS01 ^b	1166872.21	668802.95	NS	NS	15.8	10	5.8 - 15.8	1" ID Sch. 40 PVC
SI13-GWS02 ^b	1166791.42	668819.52	NS	NS	12.6	10	2.6 - 12.6	1" ID Sch. 40 PVC
SI13-GWS03 ^b	1166802.76	668858.19	NS	NS	16.0	10	5.4 - 15.4	1" ID Sch. 40 PVC

^a Permanent well installed by IT Corporation using a hollow-stem auger.

^b Temporary well installed by QST Environmental Inc. using direct-push technology.

Horizontal coordinates referenced to the U.S. State Plane Coordinate System, Alabama East Zone, North American Datum of 1983 (NAD83).

Elevations referenced to the North American Vertical Datum of 1988 (NAVD88).

2" ID Sch. 40 PVC - 2-inch inside diameter, Schedule 40, polyvinyl chloride.

bgs - Below ground surface.

ft - Feet.

msl - Mean sea level.

NS - Not surveyed.

TOC - Top of casing.