

Table 3-3

**Monitoring Well Construction Summary
Ground Scar at South End of Confidence Course, Parcel 158(7)
Fort McClellan, Calhoun County, Alabama**

Well Location	Northing	Easting	Ground Elevation (ft above msl)	TOC Elevation (ft above msl)	Well Depth (ft bgs)	Screen Length (ft)	Screen Interval (ft bgs)	Well Material
GSBP-158-MW01	1167165.08	673169.13	874.02	876.00	37.5	10	27.1 - 37.1	2" ID Sch. 40 PVC
GSBP-158-MW02	1167094.33	673150.59	874.87	877.32	32	10	21.6 - 31.6	2" ID Sch. 40 PVC
GSBP-158-MW03	1167076.73	673196.89	873.56	875.72	46	10	34.6 - 44.6	2" ID Sch. 40 PVC

Permanent wells installed using hollow-stem auger.

Horizontal coordinates referenced to the U.S. State Plane Coordinate System, Alabama East Zone, North American Datum of 1983 (NAD83).

Elevations referenced to the North American Vertical Datum of 1988 (NAVD88).

2" ID Sch. 40 PVC - 2-inch inside diameter, Schedule 40, polyvinyl chloride.

bgs - Below ground surface.

ft - Feet

msl - Mean sea level.