

US Army Corps of Engineers ® Mobile District

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN WATER CONTROL MANUAL

Final

APPENDIX H

CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

COOSAWATTEE RIVER, GEORGIA

JULY 1979 REVISED MAY 2015



Carters Project Coosawattee River, Georgia



Carters Main Dam Coosawattee River, Georgia

NOTICE TO USERS OF THIS MANUAL

Regulations specify that this Water Control Manual be published in a hard copy binder with loose-leaf form, and only those sections, or parts thereof, requiring changes be revised and printed. Therefore, this copy should be preserved in good condition so that inserts can be made to keep the manual current. Changes to individual pages must carry the date of revision, which is the South Atlantic Division's approval date.

REGULATION ASSISTANCE PROCEDURES

If unusual conditions arise, contact can be made with the Mobile District Office by phoning (251) 690-2737, during regular duty hours and (251) 509-5368 during non-duty hours. The Carters' Dam Project Manager's Office can be reached at (706) 334-2640 or (706) 334-2906 during non-regular duty hours.

METRIC CONVERSION

Although values presented within this text are shown with English units only, a conversion table is listed in Exhibit B for your convenience.

VERTICAL DATUM

All vertical data presented in this manual are referenced to the project's historical vertical datum, National Geodetic Vertical Datum of 1929 (NGVD29). It is the U.S. Army Corps of Engineers (herein referred to as USACE or Corps) policy that the designed, constructed, and maintained elevation grades of projects be reliably and accurately referenced to a consistent nationwide framework, or vertical datum - i.e., the National Spatial Reference System (NSRS) or the National Water Level Observation Network (NWLON) maintained by the U.S. Department of Commerce, National Oceanic and Atmospheric Administration. The current orthometric vertical reference datum within the NSRS in the continental United States is the North American Vertical Datum of 1988 (NAVD88). The current NWLON National Tidal Datum Epoch is 1983 - 2001. The relationships among existing, constructed, or maintained project grades that are referenced to local or superseded datums (e.g., NGVD29, MSL), the current NSRS, and/or hydraulic/tidal datums, have been established per the requirements of Engineering Regulation 1110-2-8160 and in accordance with the standards and procedures as outlined in Engineering Manual 1110-2-6056. A Primary Project Control Point has been established at this project and linked to the NSRS. Information on the Primary Project Control Point, designated 9B-2A, and the relationship between current and legacy datums are in Exhibit Β.

CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

WATER CONTROL MANUAL COOSAWATTEE RIVER, GEORGIA U.S. Army Corps of Engineers, Mobile District, South Atlantic Division

TABLE OF CONTENTS

TITLE PAGE		<u>Page</u> i
PHOTOGRAPH		ii
NOTICE TO USE	RS OF THIS MANUAL	iv
REGULATION AS	SSISTANCE PROCEDURES	iv
METRIC CONVE	RSION	iv
	IM	iv
		N N
		v
TEXT OF MANUA		XIV
TEXT OF MANU		1-1
<u>Paragraph</u>	Title	Page
	I – INTRODUCTION	
1-01 1-02 1-03 1-04 1-05 1-06	Authorization Purpose and Scope Related Manuals and Reports Project Owner Operating Agency Regulating Agencies	1-1 1-1 1-1 1-2 1-2 1-2
	II – DESCRIPTION OF PROJECT	
2-01 2-02 2-03	Location Purpose Physical Components a. Saddle Dikes b. Emergency Spillway c. Intake Structures and Penstocks d. Powerbouse and Switchyard	2-1 2-2 2-2 2-4 2-5 2-6 2-9

	d. Powernouse and Switchyard	2-9
	e. Emergency Low Level Sluice	2-11
	f. Diversion Tunnel	2-12
2-04	Related Control Facilities	2-13
	a. Gated Spillway	2-15
	b. Regulation Dam Embankment Dikes	2-16
2-05	Real Estate Acquisition	2-16
2-06	Public Facilities	2-16

TABLE OF CONTENTS (Cont'd)

<u>Paragraph</u>	<u>Title</u>	Page
	III – HISTORY OF PROJECT	
3-01 3-02 3-03 3-04 3-05 3-06	Authorization Planning and Design Construction Related Projects Modifications to Regulations Principal Regulation Problems	3-1 3-1 3-3 3-7 3-7 3-7
	IV – WATERSHED CHARACTERISTICS	
4-01 4-02 4-03 4-04 4-05 4-06 4-07 4-08	General Characteristics Topography Geology and Soils Sediment Climate Storms and Floods Runoff Characteristics Water Quality a. Water Quality Needs b. Lake Water Quality Conditions c. Lake Stratification	4-1 4-2 4-3 4-3 4-7 4-8 4-10 4-10 4-11 4-11
4-09	 a. Downstream water Quality Conditions Channel and Floodway Characteristics a. General b. Damage Centers and Key Control Points 	4-13 4-13 4-13
4-10	Upstream Structures	4-18
4-11 4-12	Downstream Structures Economic Data a. Population b. Agriculture c. Industry d. Flood Damages	4-18 4-19 4-20 4-20 4-21
	V – DATA COLLECTION AND COMMUNICATION NETWORKS	
5-01	Hydrometeorological Stations a. Facilities b. Reporting c. Maintenance	5-1 5-1 5-3 5-4
5-02 5-03 5-04 5-05 5-06	Water Quality Stations Sediment Stations Recording Hydrologic Data Communication Network Communication With Project Office a. Regulating Office With Project Office b. Between Project Office and Others	5-4 5-4 5-5 5-6 5-7 5-7 5-7
5-07	Project Reporting Instructions	5-7

TABLE OF CONTENTS (Cont'd)

<u>Paragraph</u>	Title	<u>Page</u>
5-08	Warnings	5-8
5-09	Role of Regulating Office	5-8
5-10	Role of Power Project Manager	5-8
	VI – HYDROLOGIC FORECASTS	
6-01	General	6-1
	a. Role of The Corps	6-1
	b. Role of Other Agencies	6-1
6-02	Flood Condition Forecasts	6-2
	a. Requirements	6-2
	b. Methods	6-2
C 02	c. Downstream Forecasts	6-6
6-03	Conservation Purpose Forecasis	0-0
	a. Requirements b. Mothods	0-0 6-6
6-04	Long-Range Forecasts	0-0 6-6
6-05	Drought Forecast	0-0 6-7
0-03	a Requirements	6-7
	b Methods	6-8
	c. Reference Documents	6-8
	VII – WATER CONTROL PLAN	
7-01	General Objectives	7-1
7-02	Constraints	7-1
7-03	Overall Plan for Water Control	7-1
	a. General Regulation	7-1
	b. Conservation Pool	7-2
	c. Guide Curves and Action Zones	7-2
7-04	Standing Instructions to Damtender	7-4
7-05	Flood Risk Management	7-4
	a. Induced Surcharge Schedule	7-5
7-06	Recreation	7-8
	a. Initial Impact Level	7-8
	D. Recreation impact Level	7-8
7 07	C. Water Access Limited Level	7-0 7 9
7-07	Fish and Wildlife	7-0 7_0
7-00	Water Supply	7-9
7-03	Hydroelectric Power	7-10
7-11	Navigation	7-12
7-12	Drought Contingency Plans	7-12
	a. Headway Operations for Drought at Carters and Allatoona	
	Projects	7-14
	b. Operations at APC Projects on the Coosa, Tallapoosa, and Alabama Rivers	7-14
	c. Low Basin Inflow Trigger	7-15

TABLE OF CONTENTS (Cont'd)

<u>Paragraph</u>	<u>Title</u>	<u>Page</u>
7 13	 d. Low State Line Flow Trigger e. Low Composite Conservation Storage in APC Projects Trigger f. Operations for Corps Projects Downstream of Montgomery g. Summary of Potential Drought Management Measures 	7-15 7-17 7-17 7-17 7-17
7-13 7-14	Other	7-17
7-15	Correlation With Other Projects Deviation from Normal Regulation a. Emergencies	7-19 7-19 7-19
7-16	 b. Declared System Emergency c. Unplanned Deviations d. Planned Deviations Rate of Release Change 	7-19 7-20 7-20 7-20
	VIII - EFFECT OF WATER CONTROL PLAN	. 20
8-01	General Flood Bick Management	8-1
8-02	a. Spillway Design Flood b. Standard Project Flood	8-1 8-1 8-2
8-03	c. Other Floods Recreation	8-2 8-2
	 b. Recreation Impact Level c. Water Access Limited Level 	8-2 8-3
8-04 8-05	Water Quality Fish and Wildlife	8-4 8-5
8-06 8-07 8-08	Hydroelectric Power Navigation	8-5 8-6 8-7
8-09 8-10	Drought Contingency Plans Flood Emergency Action Plans	8-7 8-7
8-11 8-12	Prequencies and Probabilities Other Studies	8-7 8-10
	IX - WATER CONTROL MANAGEMENT	
9-01	Responsibilities and Organization a. U.S. Army Corps of Engineers b. Other Federal Agencies c. State Agencies d. Private Organizations e. Stakeholders	9-1 9-1 9-2 9-3 9-3
9-02	Interagency Coordination Local Press and Corps Bulletins	9-3 9-3
9-03	Framework for Water Management Changes	9-3

LIST OF TABLES

Table No.	Table	Page No.
Table 2-1	Public Use Area Recreation Facilities	2-17
Table 3-1	List of Design Memoranda	3-2
Table 3-2	List of Construction Contracts	3-3
Table 4-1	Normal Monthly Temperature (1981 – 2010)	4-5
Table 4-2	Normal Monthly Rainfall (1981 – 2010)	4-6
Table 4-3	Average Monthly Inflow (cfs)	4-9
Table 4-4	Flood Impacts for Varying Stage of Oostanaula River at Rome Georgia (USGS Gage# 02388525)	e, 4-16
Table 4-5	Flood Impacts for Varying Stage of Oostanaula River at Resaca, Georgia (USGS Gage# 02387500)	4-17
Table 4-6	Historical Crests for Oostanaula River at Rome, Georgia	4-17
Table 4-7	Historical Crests for Oostanaula River at Resaca, Georgia	4-18
Table 4-8	River Mile and Drainage Area for Selected Sites in ACT Basin	4-19
Table 4-9	Population and Per Capita Income	4-20
Table 4-10	Farm Earnings and Agricultural Production	4-21
Table 4-11	Manufacturing Activity	4-21
Table 4-12	Flood Damages Prevented – Carters Lake	4-21
Table 5-1	Corps and NOAA Gages Reporting only Rainfall	5-2
Table 5-2	Gages Reporting Rainfall and River Stage	5-2
Table 6-1	Rainfall – Runoff Relationship for Basin Above Rome, Georgia	a 6-4
Table 6-2	6-hour Unit Hydrographs in Oostanaula River Basin	6-5
Table 6-3	6-hour Unit Hydrographs in Etowah River Basin	6-7
Table 7-1	Top of Conservation and Action Zone Table for Carters Lake	7-3
Table 7-2	Surcharge Schedule for Carters Main Dam	T7-1
Table 7-3	Emergency Spillway Discharge Rating for Carters Main Dam	7-6
Table 7-4	Low Level Sluice Discharge Rating for Carters Main Dam	7-7
Table 7-5	Average Daily Hydroelectric Power Generation by Month (Megawatt Hours)	7-11
Table 7-6	ACT Basin Drought Management Matrix	7-13
Table 7-7	Low Basin Inflow Guide (in cfs-days)	7-16
Table 7-8	APC Drought Operations Plan State Line Flow Trigger	7-17
Table 8-1	Carters Lake Recreational Impact Levels	8-3
Table 8-2	High Water Impacts on Recreation Facilities	8-4

LIST OF FIGURES

Figure No.	Figure	Page No.
Figure 2-1	Vicinity Map	2-1
Figure 2-2	Location Map	2-2
Figure 2-3	Carters Aerial Photo and Features	2-3
Figure 2-4	Carters Site Plan	2-4
Figure 2-5	Emergency Gated Spillway (Looking Downstream)	2-5
Figure 2-6	Emergency Gated Spillway (Looking Upstream)	2-6
Figure 2-7	Aerial View of Intake Structures, Circa 1974	2-7
Figure 2-8	Upstream of Intake During Construction, Circa 1974	2-7
Figure 2-9	Right Bank Intake Prior to Filling, circa 1974	2-8
Figure 2-10	Intake Structure Looking Downstream	2-8
Figure 2-11	Carters Powerhouse at Tailrace	2-9
Figure 2-12	Switchyard	2-10
Figure 2-13	Downstream Opening of the Emergency Sluice Tunnel	2-11
Figure 2-14	Low Level Sluice Control Building	2-12
Figure 2-15	Diversion Tunnel Upstream Entrance Prior to Filling, Circa 19	74 2-13
Figure 2-16	Reregulation Dam, Looking Downstream	2-13
Figure 2-17	Reregulation Dam, Looking Upstream From Old US Hwy 411	2-14
Figure 2-18	Looking Downstream From Old US Hwy 411	2-14
Figure 2-19	Reregulation Dam Plan	2-15
Figure 3-1	Main Dam Site During Construction, Circa 1974	3-4
Figure 3-2	Reregulation Dam Site During Construction, Circa 1974	3-5
Figure 3-3	Carters Dam Reservoir Filling	3-6
Figure 3-4	Close-up of the Crack on the Upstream Side of Gate No. 4	3-8
Figure 3-5	Close-up of the Crack on the Upstream Side (east bridge end of Gate No. 4) 3-8
Figure 4-1	Carters Project, Main Dam, and Coosawattee River Basins	4-1
Figure 4-2	River Bottom Profile of the Coosawattee and Oostanaula Rive	ers 4-2
Figure 4-3	Retrogression Ranges Below the Reregulation Dam	4-3
Figure 4-4	Representative Temperature Stations for the Coosawattee Ba	asin 4-4
Figure 4-5	Representative Precipitation Stations for the Coosawattee Ba	sin 4-7
Figure 4-6	Basin Rainfall and Runoff Above Rome, Georgia	4-10

LIST OF FIGURES (Cont'd)

Figure No.	Figure	Page No.
Figure 4-7	Generalized Lake Stratification	4-12
Figure 4-8	Location of Towns Below Carters Project	4-14
Figure 4-9	USGS Gages in the Vicinity of Rome, Georgia	4-15
Figure 5-1	Encoder with Wheel Tape for Measuring the River Stage or Lake Elevation in the Stilling Well	5-1
Figure 5-2	Typical Field Installation of a Precipitation Gage	5-1
Figure 5-3	Typical Configuration of the GOES System	5-3
Figure 6-1	Rainfall Runoff Versus Expected Pool Elevation	6-6
Figure 7-1	Seasonal Reregulation Dam Releases	7-3
Figure 7-2	Schematic of the ACT Basin Drought Plan	7-12
Figure 7-3	ACT Basin Inflows	7-16
Figure 7-4	APC Composite Zones	7-18
Figure 7-5	APC Low Composite Conservation Storage Drought Trigger	7-19
Figure 8-1	The City of Chatsworth Water Intake Structure	8-6
Figure 8-2	Carters Annual Peak Pool Frequency	8-8
Figure 8-3	Carters Peak Inflow Frequency (period of record 1975 - 2010) 8-9
Figure 8-4	Carters Pool Elevation Annual Duration (period of record 1975 – 2010)	8-9

LIST OF EXHIBITS

Exhibit No.	Exhibit	
A	Supplementary Pertinent Data	E-A-1
В	Unit Conversions and Vertical Datum Conversion Information	E-B-1
С	Standing Instructions to the Damtenders for Water Control	E-C-1
D	Alabama-Coosa-Tallapoosa (ACT) River Basin, Drought Contingency Plan	E-D-1

LIST OF PLATES

Plate No.	Title
2-1	Basin Map
2-2	Main Dam Rock Fill Section
2-3	Saddle Dike Section
2-4	Emergency Spillway Plan and Downstream Elevation
2-5	Typical Emergency Gated Spillway Section
2-6	Section at Powerhouse Intake
2-7	Penstock Centerline Profiles and Sections
2-8	Longitudinal Sections at Powerhouse Units
2-9	Transverse Sections at Powerhouse Units
2-10	Low Level Sluice Plan and Longitudinal Section
2-11	Low Level Sluice Tunnel Sections
2-12	Low Level Sluice Gate Sections
2-13	Diversion Tunnel Plan and Profile
2-14	Diversion Tunnel Plan and Profile
2-15	Reregulation Dam Plan and Elevation
2-16	Reregulation Dam Gated Spillway Section
2-17	Reregulation Dam Embankment Sections
2-18	Limits of Land Acquisition
2-19	Recreational Use Map
4-1	Sedimentation Ranges Map
5-1	River Stage & Rainfall Gauge Map
5-2	USGS Gage 02382200 Rating
5-3	USGS Gage 02382500 Rating
5-4	USGS Gage 02383500 Rating
5-5	USGS Gage 02387500 Rating
5-6	USGS Gage 02388500 Rating
5-7	Oostanaula Gage at US 27 vs. Flow at Oostanaula/Etowah Confluence
5-8	USGS Gage 02387000 Rating
5-9	USGS Gage 02395000 Rating
5-10	USGS Gage 02394670 Rating
5-11	USGS Gage 02397000 Rating
6-1	6-Hour Unit Hydrographs
6-2	Inflow-Outflow-Pool Curves
6-3	Inflow-Outflow-Pool Curves
6-4	Inflow-Outflow-Pool Curves
6-5	Inflow-Outflow-Pool Curves
6-6	Inflow-Outflow-Pool Curves

LIST OF PLATES (Cont'd)

Plate No.	Title
6-7	Inflow-Outflow-Pool Curves
7-1	Water Control Zones
7-2	Main Dam Area Capacity Curves
7-3	Reregulation Dam Area Capacity Curves
7-4	Carters Reregulation Dam Spillway Discharge Table
7-5	Carters Reregulation Dam Spillway Discharge Table
7-6	Pump-Turbine Unit Discharge Rating Table
7-7	Typical Weekly Operation for Elevations Near 1074 feet NGVD29
7-8	Typical Weekly Operation for Elevations Near 1072 feet NGVD29
7-9	Performance Curves - Pump Back Operation
7-10	Performance Curves - Conventional Unit
7-11	Performance Curves - Pump-Turbine Unit
7-12	Main Dam Discharge Rate - Tailwater Relationship for Various Reregulation Pools
7-13	Pumping Rate - Tailwater Relationship for Various Reregulation Pools
8-1	Inflow-Outflow-Pool Relationships for Spillway Design Flood
8-2	Inflow-Outflow-Pool Relationships for Standard Project Flood
8-3	Inflow-Outflow-Pool Relationships for Flood of January 1947
8-4	Inflow-Outflow-Pool Relationships for Flood of March 1951
8-5	Pool Elevs, Generation, and Reregulation Discharge for Flood of April 1977
8-6	Reregulation Dam Headwater and Tailwater Rating Curves
8-7	Peak Flow Frequency at USGS Gage 02383500 Coosawattee River near Pine Chapel
8-8	Peak Flow Frequency at USGS Gage 02387500 Oostanaula River at Resaca
8-9	Peak Flow Frequency at USGS Gage 02388500 Oostanaula River near Rome
8-10	Peak Flow Frequency at USGS Gage 02397000 Coosa River near Rome
8-11	Main Dam Annual Peak Pool Elevations
8-12	Main Dam Maximum Pool Elevation Frequency
8-13	Annual Minimum Pool Elevation Frequency

36.58

PERTINENT DATA

(see Exhibit A, page E-A-1 for Supplementary Pertinent Data)

GENERAL

Location – Murray, Gilmer, & Gordon Counties, GA; Coosawattee River, river m	nile 26.8
Main Dam Drainage Area, sq. mi.	374
Reregulation Dam Local Drainage Area, sq. mi.	146
Total Project Drainage Area, sq. mi.	520
Primary flood control pool elevation, feet NGVD29	1,099
Max. power pool elev. (dry season), feet NGVD29	1,074
Area of primary flood control pool, acres	3,880
Area of maximum power pool, acres	3,275
Flood storage volume, acre-feet (1,099-1,074 feet NGVD29)	89,191
Power storage volume, acre-feet (1,074-1,022 feet NGVD29)	141,402
Operational storage volume, reregulation pool, acre-feet (698–674 feet NGVD29)	16,000
MAIN DAM AND DIKES	
ROCKFILL DAM	
Top elevation, feet NGVD29	1,112.3
Top width, feet	40
Length, feet	2,053
EARTHFILL SADDLE DIKES	
Top elevation, feet NGVD29	1,112.3
Total length, feet	700
Number of dikes	3
EMERGENCY GATED SPILLWAY	
Total length, including end piers, feet (net length 210 ft)	262
Elevation of crest, feet NGVD29	1,070.0
Type of gates	tainter
Number of gates	5
Length of Gates	42

POWER DATA

Height of Gates

Number of units	4
Capacity: 2 @ 140,000 and 2 @ 160,000 kw (declared values)	600,000
Operating head at maximum power pool, feet	396
Minimum head at full drawdown, feet	324

I - INTRODUCTION

1-01. Authorization. Section 7 of the Flood Control Act of 1944 instructed the Secretary of the Army to prescribe regulations for the use of storage allocated for flood control (now termed flood risk management) or navigation at all Corps reservoirs. Therefore, this water control manual has been prepared as directed in the Corps' Water Management Regulations, specifically Engineering Regulation (ER) 1110-2-240, *Water Control Management (date enacted 8 October 1982)*. That regulation prescribes the policies and procedures to be followed in carrying out water management activities, including establishment and updating of water control plans for Corps and non-Corps projects, as required by federal laws and directives. This manual is also prepared in accordance with pertinent sections of the Corps' Engineering Manual (EM) 1110-2-3600, Management of Water Control Systems (date enacted 30 November 1987); under the format and recommendations described in ER 1110-2-1941, *Drought Contingency Plans (date enacted 15 September 1981)*. Revisions to this manual are to be processed in accordance with ER 1110-2-240.

1-02. Purpose and Scope. This individual project manual describes the water control plan for the Carters Dam and Lake and Carters Reregulation Dam Project (Carters Project). The description of the project's physical components, history of development, water control activities, and coordination with others are provided as supplemental information to enhance the knowledge and understanding of the water control plan. The Carters Project water control plan must be coordinated with the multiple projects in the Alabama-Coosa-Tallapoosa (ACT) Basin to ensure consistency with the purposes for which the projects were authorized. In conjunction with the ACT Basin master water control manual, this manual provides a general reference source for Allatoona water control regulation. It is intended for use in day-to-day, real-time water management decision making and for training new personnel.

1-03. Related Manuals and Reports.

Other manuals related to the Carters Project water control regulation activities include the *Operation and Maintenance* manual for the project, and the ACT Master Water Control Manual for the entire basin.

One master water control manual and nine individual project manuals, which are incorporated as appendices, compose the complete set of water control manuals for the ACT Basin:

Appendix A - Allatoona Dam and Lake
Appendix B - Weiss Dam and Lake (Alabama Power Company)
Appendix C - Logan Martin Dam and Lake (Alabama Power Company)
Appendix D - H. Neely Henry Dam and Lake (Alabama Power Company)
Appendix E - Millers Ferry Lock and Dam and William "Bill" Dannelly Lake
Appendix F - Claiborne Lock and Dam and Lake
Appendix G - Robert F. Henry Lock and Dam and R. E. "Bob" Woodruff Lake
Appendix H - Carters Dam and Lake (Alabama Power Company)

Other pertinent information regarding the ACT River Basin development is in operation and maintenance manuals and emergency action plans for each project. Historical, definite project reports and design memoranda also have useful information.

1-04. Project Owner. The Carters Project is a federally owned project entrusted to the Corps, South Atlantic Division (SAD), Mobile District.

1-05. Operating Agency. Operation and maintenance of the Carters Project is the responsibility of the Mobile District Operations Division. Supervision and direction for this effort is provided by the project's Operations Project Manager.

1-06. Regulating Agencies. Authority for the water control regulation of the Carters Project has been delegated to the SAD Commander. Water control regulation activities are the responsibility of the Mobile District, Engineering Division, Water Management Section. Water control actions for the Carters Project are regulated in a system-wide, balanced approach to meet the federally authorized purposes. It is the responsibility of the Water Management Section to develop water control regulation procedures for the ACT Basin federal projects. The regulating instructions presented in the basin water control plan are issued by the Water Management Section with approval of SAD. The Water Management Section monitors the project for compliance with the approved water control plan and makes water control regulation decisions on the basis of that plan. When necessary, the Water Management Section instructs the project personnel regarding normal procedures and emergencies for unusual circumstances.

II - DESCRIPTION OF PROJECT

2-01. Location. The Carters Project is located on the Coosawattee River approximately 1.5 miles upstream of Carters in northwest Georgia. It is about 60 miles north of Atlanta, Georgia, and approximately 50 miles southeast of Chattanooga, Tennessee. The Carters Reregulation Dam (Reregulation Dam) was constructed about 1.8 miles downstream from the main dam. Both dams are located in Murray County with a large portion of the main reservoir extending into Gilmer County. The upper reaches of the Reregulation Dam pool extends into both Gordon and Gilmer Counties. A vicinity map and location map are shown in Figure 2-1 and Figure 2-2. A basin map is shown on Plate 2-1.



Figure 2-1. Vicinity Map



Figure 2-2. Location Map

2-02. Purpose. The Carters Project is designed primarily for flood risk management and hydroelectric power. Water supply, flow regulation, recreation, fish and wildlife conservation, and water quality are additional benefits of the project. Carters Lake provides additional flood risk management to the rich farm lands along the Coosawattee and Oostanaula River. Peak flood stages are reduced as far downstream as Rome, Georgia, about 72 river miles downstream from the project. Average monthly power generation over the period August 1975 through Mar 2009 has been 36,646 megawatt hours (MWH), and an annual average of 439,757 MWH. About 29% of this total annual generation if from natural stream flow and about 71% is from "pumped back" water. A minimum downstream flow of 240 cubic feet per second (cfs) is maintained by releases from the Reregulation Dam. The 240 cfs represents the 7-day average 10-year frequency low flow (7Q10) at the reregulation dam site. Areas below the project are assured of this minimum flow during dry periods as long as sufficient water exists at the project.

The Carters Project has created a scenic mountain lake, 11 miles long with 62.7 miles of shoreline. The lake is about 400 feet deep at the dam. The 10 public use and access areas found at the project provide for a variety of activities.

2-03. Physical Components. The main dam is a massive rolled-rock structure built across the deep Coosawattee River gorge. It rises 445 feet above the foundation and contains nearly 15

million cubic yards of material. The dam has a length of 2,053 feet along the arch of the axis. The radius of the arch is 2,100 feet. Minimum top elevation is 1,112.3 feet NGVD29 at both ends of the dam with a sloping overbuild to 1,115.3 feet NGVD29 at the center of the dam. Sides slopes are generally one vertical to two horizontal. The upper cofferdam was constructed to form a 30-foot berm on the upstream face at elevation 671.5 feet NGVD29. An impervious earth core, grout curtain and a core trench excavated to sound rock provide seepage control. A 22-foot wide roadway extends across the top of the dam giving easy access to both ends of the structure. A typical section through the dam is shown on Plate 2-2.

An aerial photograph of the main dam area is shown below in Figure 2-3 followed by a general plan of the area including the Reregulation Dam in Figure 2-4.



Figure 2-3. Carters Aerial Photo and Features



Figure 2-4. Carters Site Plan

a. <u>Saddle Dikes</u>. Three earth and rock-fill saddle dikes were required on the left bank rim of the main reservoir about 6,000 feet upstream from the main dam. The maximum height of the dikes is about 40 feet with a top elevation of 1,112.3 feet NGVD29. Top width of the dikes is 30 feet and side slopes are 1 vertical to 2.5 horizontal. A typical section through the saddle dikes is shown on Plate 2-3.

b. <u>Emergency Spillway</u>. The level of the main reservoir can normally be controlled by releasing water through the powerhouse turbines. However, unusually high inflows are possible. The emergency gated spillway is designed to help maintain control of the level of the main dam during these critical periods. Also if the powerhouse is forced out of service it may become necessary to use the emergency spillway. Discharge through the emergency spillway is not preferred due to the potential for erosion in the spillway channel, specifically around the emergency sluice access road located below the spillway. The concrete gravity-type structure is 262 feet long and consists of five gate bays each 42 feet wide, two end piers 10 feet wide and four intermediate piers eight feet wide. The crest of the spillway is at elevation 1,070 feet NGVD29. Flow over the crest is controlled by five tainter gates 42 feet wide and 36.58 feet high. The gates are moved by individual electrical hoists located at elevation 1,120.0 feet NGVD29 on top of the piers. Stop logs are not required for repair and maintenance of the gates since the pool level is allowed to drop below the spillway crest during normal power operations. In fact about 25% of the time, merely from normal operation, the project is below elevation 1070 feet NGVD29.

The service building is located about 80 feet west of the spillway and houses the emergency engine generator, air compressor and electrical substation. The spillway is shown below in Figure 2-5 and Figure 2-6. Plan, Elevation and Section of the emergency gated spillway are shown on Plate 2-4 and Plate 2-5.



Figure 2-5. Emergency Gated Spillway (Looking Downstream)



Figure 2-6. Emergency Gated Spillway (Looking Upstream)

c. <u>Intake Structures and Penstocks</u>. There are two reinforced concrete intake structures at Carters. Each is 94 feet long and 51 feet wide at the base. Elevation at the base is 981 feet NGVD29. Each structure has two reinforced concrete towers 138.5 feet high that contain the gate machinery and other devices to regulate flow into the penstocks. Flow into each of the four intake passages is controlled by a 14-foot by 20.5-foot tractor-type head-gate with upstream seals. Each gate is equipped with an electric hoist and an auxiliary hydraulic lowering device for emergency closure located on the tower deck at elevation 1,112.5 feet NGVD29. An enclosed substation on the tower deck provides the power used at the intake structure.

Each tower has a work bay at elevation 1,080 feet NGVD29 for servicing the head gates. A portable electric manlift is used to inspect the gates and penstocks and is operated in the recess immediately downstream from the gate. A road crane is provided to service the removable-type trash racks that protect the entrance to each intake passage. This crane can also be used to insert and remove the one set of steel stoplogs provided at the structure, when dewatering of the intake is required. An aerial photograph of the intake structure during construction is shown below on Figure 2-7. A typical section is shown on Plate 2-6.



Figure 2-7. Aerial View of Intake Structures, Circa 1974

Photographs of the intake structures taken during construction and prior to filling are shown below in Figure 2-8 and in Figure 2-9. A recent photo is shown in Figure 2-10.



Figure 2-8. Upstream of Intake during Construction, Circa 1974



Figure 2-9. Right Bank Intake Prior to Filling, Circa 1974



Figure 2-10. Intake Structure Looking Downstream

Four steel-lined penstocks extend from the intake structures to the powerhouse through 23foot diameter tunnels cut through solid rock. The length of each penstock is about 835 feet. Inside diameter of the steel lining is 18.0 feet and the area between the steel and rock walls is filled with concrete and grouted. The penstocks were designed to be as much alike as possible. The slight differences are due to the characteristics of the conventional versus the pump-turbine units. The penstocks for the pump-turbines have a thicker liner plate to handle greater waterhammer pressures provided by these units. Also, the exit end of the penstocks for the two pump-turbine units transition to a diameter of 13.5 feet. Centerline profiles and typical sections of the penstocks are shown on Plate 2-7.

d. <u>Powerhouse and Switchyard</u>. The powerhouse is located on a rock bench cut into the right river bank about 200 feet below the toe of the main dam. The reinforced concrete structure is 390 feet long and 115 feet wide. The powerhouse contains two conventional 140,000 kilowatts (Kw) (declared value) hydrogenerator units (units 1 and 2), two reversible 160,000 Kw (declared value) pump-turbine units (units 3 and 4), an erection bay, unloading bay and an entrance wing. Declared Power Capacity is defined as the plant's operational capacity declared on a weekly basis to the power marketing agency. The value may vary slightly from week to week depending on factors such as head and cooling capabilities. A photograph of the powerhouse is shown below in Figure 2-11 and longitudinal and transverse sections are shown on Plate 2-8 and Plate 2-9.



Figure 2-11. Carters Powerhouse at Tailrace

The Allis-Chalmers Mfg. Co., produced the generators and the Newport News Ship Building Co., produced the turbines for the conventional units 1 and 2. General Electric manufactured the generators and Allis-Chalmers produced the turbines for the reversible units 3 and 4.

The control room, located in the erection bay at elevation 708.00 feet NGVD29, governs the generation, as well as the reregulation dam gates (up to a two feet opening, then must dispatch

onsite personnel) and emergency spillway gate settings at the project. The Carters Project also governs generation at the Corps' Buford and Allatoona Projects from the Carters control room via remote control. Operators from Carters are dispatched to Allatoona or Buford to operate the generators in the advent of loss of communication between the facilities. Local maintenance personnel at Allatoona and Buford operate the spillway and sluice gates at Allatoona and the sluice gates at Buford when needed.

The distributor centerline of the conventional units 1 and 2 is located at elevation 658.0 feet NGVD29. A generator floor at elevation 691 feet NGVD29 and a turbine floor at elevation 676 feet NGVD29 provide access to the units. The distributor centerline for pump-turbine units 3 and 4 is at elevation 649 feet NGVD29 and the generator floor is at elevation 676 feet NGVD29. There is no floor at elevation 691 feet NGVD29 over units 3 or 4 nor is there a turbine floor. Access to the pump-turbines is provided by a passage from the service bay floor at elevation 660 feet NGVD29. A 400-ton overhead crane provides the lifting power for installation and maintenance of all four units. The crane has two trolleys, each with a 200-ton sister hook and a 25-ton auxiliary hook.

The service bay is located on the downstream side of the structure below the draft tube deck and houses the sewage treatment plant, water treatment, oil storage and other services. An extensive collector drain system along the upstream wall of the powerhouse reduces the pore pressures against the powerhouse to a differential head of 10 feet.

The switchyard is located at the center of the downstream base of the main dam. The ground elevation of 708.75 feet NGVD29 reflects approximately 10 feet of freeboard above the 699.0 feet NGVD29 maximum reregulation dam pool elevation. The fenced area containing the switching apparatus is approximately 592 feet long by 343 feet wide. The switching equipment and structures are designed to operate at 230 kilovolts (kv). A photograph of the switchyard is shown below in Figure 2-12.



Figure 2-12. Switchyard

e. <u>Emergency Low Level Sluice</u>. The gate-controlled low level sluice was constructed to evacuate water from the main reservoir if repairs to the main dam are required or if aid in controlling the pool elevation is needed. The 2,712-foot long tunnel is located below the left bank abutment of the main dam. The location of the sluice is shown on Figure 2-4.

A circular, concrete-lined 16.5-foot diameter tunnel extends from the upstream portal to the tandem gate machinery. The downstream section is a 22-foot unlined horseshoe-shaped tunnel except that the 200-foot portion immediately downstream from the gate structure has concrete sides and bottom to prevent erosion of the rock. Elevation of the tunnel floor varies from 725 feet NGVD29 at the upstream entrance to 710 feet NGVD29 at the downstream exit. The upstream portal is slotted for the placement of stop logs used for de-watering the tunnel. However, the stop logs and floating plant for placing them do not exist.

The gate structure has two water passages each five feet wide and 10 feet tall. Flow in each passage is controlled by tandem slide gates. A vertical 10-foot diameter shaft extends approximately 335 feet from the gate structure to the surface between the main dam and the emergency gated spillway. A plan and profile of the sluice are shown on Plate 2-10 and sections are shown on Plate 2-11. Gate sections are shown on Plate 2-12. A photograph of the exit end of the tunnel is shown below in Figure 2-13.



Figure 2-13. Downstream Opening of the Emergency Sluice Tunnel

A small building, covering the shaft contains a remote panel for operation of the gates and provides space for an elevator used for access to the gate structure. The building is shown in Figure 2-14. As of the date of this report, the emergency low level sluice has never been used.



Figure 2-14. Low Level Sluice Control Building

f. <u>Diversion Tunnel</u>. Construction of the main dam at Carters required the Coosawattee River to be rerouted at the dam site. A 23-foot high, 23-foot wide unlined horseshoe-shaped diversion tunnel was drilled approximately 2,407 feet long through the left ridge of the river valley. After completion of the main dam the upstream entrance (shown below in Figure 2-15) was sealed with steel stoplogs and plugged with concrete. Location of the tunnel is shown on Figure 2-4. A plan and profile is shown on Plate 2-13, and sections of the tunnel are shown on Plate 2-14.



Figure 2-15. Diversion Tunnel Upstream Entrance Prior to Filling, Circa 1974

2-04. Related Control Facilities. The Reregulation Dam was constructed about 1.8 miles downstream from the main dam to store water for pump back operations, to regulate the intermittent releases from the power plant, and to control minimum flow downstream. The dam consists of a gated spillway with earth and rock-fill dikes extending on either side to higher ground. Photographs of the Reregulation Dam taken from upstream of the dam and taken from old US Highway (Hwy) 411, looking upstream and downstream from old US Hwy 411 are shown on Figure 2–16, Figure 2-17, and Figure 2-18. A layout of the Reregulation Dam is shown in Figure 2-19.



Figure 2–16. Reregulation Dam, Looking Downstream



Figure 2-17. Reregulation Dam, Looking Upstream From Old US Hwy 411



Figure 2-18. Looking Downstream From Old US Hwy 411



Figure 2-19. Reregulation Dam Plan

a. <u>Gated Spillway</u>. The gated spillway is a concrete gravity-type structure 208 feet long, consisting of four gate bays, 42 feet wide, three intermediate piers, eight feet wide, and two end piers, 8 feet wide. The spillway crest is at elevation 662.5 feet NGVD29. Flow through the dam is controlled by four tainter gates 42 feet wide and each rising 36.5 feet above contact with the sill. The gates are raised and lowered by individual electrical hoists located on top of the piers at elevation 707.0 feet NGVD29. The floor of the basin is at elevation 647.5 feet NGVD29, reinforced, cantilever-type training walls are built on each side of the stilling basin with the top of the walls at elevation 672 feet NGVD29. The Reregulation Dam spillway gates are typically controlled from within the powerhouse. If there is the need to open any gate more than 2 feet, project staff must be dispatched to the spillway to operate the gates on site. A plan and

elevation are shown on Plate 2-15 and a typical section through the spillway is shown on Plate 2-16. The operating house on the right bank end pier monolith houses the controls and equipment necessary to operate the dam. A spillway bridge with a 20-foot roadway (crest elevation 717 feet NGVD29) was constructed to provide easy access to the structure and to enable stoplogs to be placed with a road crane. Access to the gate hoists is provided by a catwalk under the service bridge. A concrete, gravity-type, non-over-flow wall, 112 feet long is provided on each side of the spillway to permit transition to the embankment section.

b. <u>Regulation Dam Embankment Dikes</u>. Earth and rock-fill embankment dikes form the damming structures on the overbanks from the non-overflow walls of the gated spillway to high ground. The dikes have a combined length of about 2,855 feet. The top elevation of the dikes, 703.0 feet NGVD29, makes overtopping highly improbable. Left and right dike sections are shown on Plate 2-17. Location of the embankment dikes is shown in Figure 2-19.

2-05. Real Estate Acquisition. Real Estate requirements for the Carters Project include the reservoir areas, public use and access areas, construction areas and the road right-of-way easements. Hydraulic studies indicate that induced surcharge operations will contain the pool near or below elevation 1,107 feet NGVD29. A one-foot free board is considered sufficient to accommodate the adverse effects of saturation and wave action so the acquisition line for the main reservoir was set at elevation 1,108 feet NGVD29. In establishing this line, however, the acquisition of property along minor land subdivisions in accordance with existing policy is generally controlled by the requirement for a 300-foot horizontal clearance from the static full pool rather than by acquisitions directly related to the 1,108 feet NGVD29 contours.

A total of 7,485 acres for the main dam were acquired in fee simple and easements were acquired for 159 acres. In addition 1,415 acres were acquired in fee simple for the Reregulation Dam and reservoir, including all lands below elevation 694.0 feet NGVD29. Easements were taken on another 31 acres. The general limits of land acquisition are shown on Plate 2-18.

2-06. Public Facilities. The public use areas around Carters Lake are shown on Plate 2-19. The two areas at the Reregulation Dam are counted as one in the following Table 2-1. The recreation facilities at each public use area are listed in the following Table 2-1.

Recreation Facilities	Visitors Center	Project Management Office	Overlook	Boat Ramp	Drinking Water	Comfort Station	Picnic Area	Campfire Circles	Tent & Trailer Camping	Tent Camping Only	Wash House w/ Comfort Sta.	Swimming Beach	Change House	Foot Trails	Fishing Deck	Marina
Dam Site	0	0	0	0	0	0	0							0		
Carters Lake Marina					0											0
Harris Branch					0	0	0	0		0	0	0	0	0		
Doll Mountain**				0	0	0	0	0	0		0				0	
Ridgeway				0	0	0	0	0		0				0		
Woodring Branch**				0	0	0	0	0	0					0		
North Bank			0		0	0	0							0		
Reregulation Dam site					0	0	0							0	0	

 Table 2-1. Public Use Area Recreation Facilities

* Has separate campground and day use areas.

III - HISTORY OF PROJECT

3-01. Authorization. Authority for development of a dam on the Coosawattee River near Carters, Georgia, is contained in Section 2 of the River and Harbor Act adopted 2 March 1945 (Public Law 12, 79th Congress, 1st Session). This Act approved the initial and ultimate development of the Alabama-Coosa River and tributaries for flood risk management, power generation, navigation and other purposes as outlined in House Document 414, 77th Congress.

House Document No. 414, 77th Congress, 1st Session, did not prescribe a specific plan for the development of the Coosawattee River. At that time the comprehensive plan for the basin provided for an upper and lower dam on the Coosawattee River with an impounding dam on the Cartecay River. As a result of subsequent studies, a more complete development of the river by a single high dam at the lower site was found to be warranted. Modification of the two-dam plan was therefore authorized.

3-02. Planning and Design. Early studies limited the location of a project on the Coosawattee River to the reach between miles 26 and 35. The possibilities of a single dam, two dams and a single dam with a long tunnel to develop the full head in the reach were investigated. At the suggestion of the Federal Power Commission (FPC), the pumped-storage potential of these dams to develop a greater peaking power capacity was also studied. The results of these analyses and a description of the various plans are given in the "Site Selection Report" submitted on 31 March 1961.

After a single dam was established for the development of the reach, studies were made of the major structures. The basic types of dams investigated included a rock-fill type with separate fixed-crest and gated spillways and the concrete gravity type with a gated spillway. Straight and U-shaped fixed-crest spillways of various length were considered and various types of gated structures were investigated. Power plant and diversion tunnel locations were studied on both banks. The results of these studies were submitted in August 1962, and discussed at a conference with representatives of the Chief of Engineers, the Division Engineer, SAD and special consultants on 26 - 27 September 1962. A description of the alternative plans is given in Appendix IV of Design Memorandum No. 5 and the minutes of the meeting in regard to them is given in Appendix V.

Design Memorandum No. 5, "General Design", dated 22 July 1963, presented plans for a dam at mile 26.8 on the Coosawattee River. Maximum and minimum power pools would be at elevations 1,072 and 1,022 feet NGVD29 respectively and maximum flood risk management pool would be at elevation 1,099 feet NGVD29. This project would have a powerhouse containing two 52,000 Kw units.

Approval for installation of 250,000 Kw of generating capacity at Carters Dam on the Coosawattee River together with a reregulation dam to limit power discharges to the downstream channel capacity was given by the Secretary of the Army on 25 July 1964, in response to a memorandum from the Chief of Engineers dated 6 July 1964, on the subject: Carters Dam and Reservoir, Georgia. The results of investigations made in planning the changed facilities for the project were prepared as a supplement to Design Memorandum No. 5, and was submitted on 30 September 1964.

This plan provided for an intake structure for two powerhouse units. Subsequently, major modifications of the plan were authorized by the following correspondence:

In a letter dated 12 April 1966, from OCE to SAD, subject: "Carters Dam -Proposed Addition of Two More Units Initially in the Power Plant", four 125 MW units were approved as a basis for further planning.

In a 2nd Endorsement dated 22 April 1966 (basic letter SAMEN-D, 15 April 1966), from OCE to SAD, Subject: "Carters Project - Comparative Costs for 4-Unit Installation - 50-Foot versus 80-Foot Drawdown Provision", a 50-foot drawdown was approved.

In a 2nd Endorsement dated 29 August 1966 (basic letter SAMEN-D, 17 August 1966), from OCE to SAD, subject: "Carters Project - Pump Turbine Studies", the design of the intakes for four 18-foot-diameter penstocks was approved.

At a time when the original design was essentially complete the addition of two pumpturbine units was authorized and a decision was reached to construct the entire powerhouse and associated switchyard under a single contract. Design Memorandum No. 22 was prepared to present the design considerations involved with the addition of the two units.

The following tabulation lists the design publications pertaining to the Carters Project.

Design Memorandum	Title	Date of
INUMBER	<u>i nie</u>	Submittal
1	Site Selection Report	31 Mar 1961
2	Basic Hydrology	7 Nov 1961
3A	Preliminary Master Plan –	
	Part of the Master Plan	16 Mar 1962
3-B(C-1)	Public Use and Administrative Facilities	15 Mar 1966
4	Hydroelectric Power Capacity	25 Apr 1962
	Letter Report – Hydraulic Design of	
	Diversion Tunnel	18 Jan 1963
5	General Design	22 Jul 1963
	Supplement to General Design	
	Memorandum Number 5	30 Sep 1964
6	Access Road, Right Bank	23 Feb 1962
	Supplement to Design Memorandum	
	No. 6 – Access Road, Right Bank	3 Aug 1964
7	Reservoir, Additional Construction	
	And Public Use Areas	17 Sep 1963
8	Main Dam and Saddle Dikes; Excavations	
	For Spillway, Headrace, and Powerhouse	18 Sep 1964
9	Emergency Gated Spillway	17 Feb 1965
10	Powerhouse Structure	10 Sep 1965
11	Supervisory Control System	16 Jun 1965
12	Real Estate – Reregulation Dam and Reservoir	5 May 1965
13	Sources of Construction Material	5 Nov 1965
14	Penstocks	1 Dec 1965
15	Gated Spillway for Reregulation Dam	2 Aug 1966
16	Reregulation Dam - Rock and Earth	1 May 1968
17	Intake Structures for Powerhouse	11 Oct 1966
19	Relocations - Georgia Highway 156	19 Jun 1967
20	Relocations - Georgia Power Co. Lines	28 Feb 1969
22	Powerhouse and Appurtenances, Units 3 and 4	1 Dec 1967
23	Buildings, Grounds and Utilities	5 Mar 1970

Table 3-1. List of Design Memoranda

3-03. Construction. The first of a long series of contracts, for the Carters Project was awarded in 1962. The following tabulation lists some of the major contracts, the contractors and the dates of issuance.

Right Bank Access Rd., Site Clearing and Test Fills	Ledbetter Bros., Inc.	3 Nov 1962
Excavation of Diversion Tunnel Portals	Ledbetter Bros., Inc.	20 Feb 1963
Excavation of Diversion Tunnel	Cowin and Co., Inc	1 Mar 1964
Construction of Main Dam Phase I	Roy Tyan Sons Co., Inc.	23 Dec 1964
Construction of Main Dam Phase II	Clement Bros. Co.	15 Mar 1968
Construction of Left Bank Access Rd., & Saddle Dikes	Phillips & Jordan, Inc.	1 Sep 1966
Excavation of Penstock Tunnels	W.L. Hailey & Co., Inc.	23 Apr 1969
Construction of Intake Structure and Penstock Liners	Al Johnson Constr. Co.	26 May 1972
Construction of Emergency Gated Spillway	Rosiek Constr. Co. Inc.	1 Jun 1972
Construction of Carters Reregulation Dam	Kandy, Inc.	15 Nov 1972
Construction of Emergency Low Level Sluice	Al Johnson Constr. Co.	2 Mar 1972
Construction of Powerhouse	Al Johnson Constr. Co.	31 Aug 1975

Table 3-2. List of Construction Contracts

Photographs of the site during construction are shown below in Figure 3-1 and Figure 3-2.


Figure 3-1. Main Dam Site During Construction, Circa 1974



Figure 3-2. Reregulation Dam Site During Construction, Circa 1974

Design Memorandum No. 5, General Design, Appendix V considered the minimum flows from Talking Rock Creek adequate to meet low flow requirements downstream. Twenty years of flow records indicated the minimum monthly discharge from Talking Rock Creek was about 100 cfs.

In August of 1970, the Georgia State Water Quality Control Board expressed concern over possible effects of operation of Carters Dam on water quality on the upper Coosa River and requested increased minimum flows at Mayo's Bar. The Mobile District Office, in a letter dated 12 August 1971 to the Georgia State Water Control Board, stated that a guaranteed minimum continuous release of 240 cfs would be provided from the Reregulation Dam. This had been determined to be the seven-day average 10-year frequency low flow at that point.

The pool level reached elevation 725 feet NGVD29 on 16 November 1974. After this date, a minimum continuous flow of 240 cfs was maintained below the Reregulation Dam to support downstream water quality flow requirements. After the pool reached elevation 800 feet NGVD29 on 16 December 1974, the rate of rise was slowed by releasing water through the low-level sluice so that workers in the diversion tunnel would not be endangered. The diversion tunnel was completely sealed with a concrete plug by the middle of January 1975, and the pool was again allowed to rise freely. The pool reached minimum power pool, elevation 1,022 feet NGVD29, on 17 March 1975.

The conventional generating units 1 and 2 were declared commercially available on 17 November and 23 July 1975, respectively. The pump turbine units 4 and 3 became commercially available on 13 June and 8 September 1977, respectively.



A graph of the initial filling rate of the main pool at Carters is shown below in Figure 3-3.

Figure 3-3. Carters Dam Reservoir Filling

3-04. Related Projects. Except for the two dams at the Carters Project there are no other structures within the Coosawattee River Basin requiring special coordination. There is, however, a large multiple purpose reservoir outside the basin on the Etowah River operated by the Corps. This project, Allatoona Dam, affects river stages at Rome, Georgia, where the Etowah and Oostanaula Rivers meet to form the Coosa River. Operations at the Carters Project also affect stages at Rome, although to a lesser degree.

Since the Carters project is equipped with reversible pump-turbines and because a minimum flow of 240 cfs is maintained from the Reregulation Dam at all times, little coordination in the reservoir operations of Carters and Allatoona is normally needed during periods of low to moderate flows. Under extreme low flow conditions, additional water may be released from Carters and/or Allatoona for water supply purposes in the Rome area. During periods when flood waters are being evacuated from Carters and/or Allatoona, releases will be planned and monitored to help prevent aggravating flood conditions near Rome.

Other projects (Corps and non-Corps) in the ACT System that affect water control objectives to varying degrees are Allatoona, Weiss, Logan Martin, H Neely Henry, Millers Ferry, Claiborne, R. F. Henry, and Harris.

3-05. Modifications to Regulations. There have been no changes in the water control manual since the initial manual was published in 1979.

3-06. Principal Regulation Problems. The most significant problems at the project involve the swelling and fracturing of the concrete used in construction of the Reregulation Dam, which is caused by alkali aggregate reaction (AAR). Material for construction of the Reregulation Dam came from Vulcan Material's quarry in Dalton, Georgia. There was reportedly a bed of reactive aggregate in the Dalton Quarry during the time of construction of the Reregulation Dam. Aggregate was apparently obtained from this bed and shipped to the Carters site at least twice during construction of the Reregulation Dam. There is no record that the first shipment of bad aggregate was noted, but some of the concrete placed prior to 22 June 1971 has been affected by an intense alkali aggregate reaction. The second shipment of bad aggregate was recognized, and a sample of aggregate and ledge rock from the quarry was sent to the SAD lab in late September 1971. Petrographic examination identified both the sample as containing an excessive amount of "soft and potentially deleterious" particles, and the ledge rock as "fine grained argillaceous dolomitic limestone" that should be avoided because "it is soft....as well as being deleteriously reactive". Intense alkali reacted concrete from this second shipment can be found in concrete placed between 11 August 1971 and 9 November 1971. The referenced petrographic report recommended that selective guarrying be utilized at the guarry to eliminate production of the bad aggregate. Concrete placed subsequent to 9 November 1971 only shows occasional cracking due to AAR. AAR cracking is shown in Figure 3-4 and Figure 3-5.

Because of the AAR, cracking and displacement of the bridge across the spillway has resulted in weakening of the bridge to the degree that it is considered no longer safe to withstand the weight of the crane used to place stoplogs on the upstream face. However, under the American Recovery and Reinvestment Act of 2009, temporary repairs were made to the bridge to allow for a crane to be able to place the stoplogs. In addition, displacement of the abutment and intermediate pier at monolith D9 has resulted in the inability to raise gate number 4 fully. Operation of the gate is limited because there was difficulty in the past closing the gate once it was opened. Further efforts are currently underway to allow for full opening of all gates.

A second is the limitation on head for pump back operations. Whenever the power head reaches 395 feet excessive vibration occurs in the hydropower units and pumping must be discontinued unless the reregulation pool is over 690 feet NGVD29, then the maximum head is 397 feet.



Figure 3-4. Close-up of the Crack on the Upstream Side of Gate No. 4



Figure 3-5. Close-up of Crack on Upstream Side (east bridge end) of Gate No. 4

IV - WATERSHED CHARACTERISTICS

4-01. General Characteristics. The Carters Project, Carters Main Dam and Coosawattee River drainage basins are shown below in Figure 4-1. The Carters Main Dam drainage area does not include Talking Rock Creek Basin, which flows into the Reregulation Dam pool below the main dam. Talking Rock Creek is included in the Carters Project Basin.



Figure 4-1. Carters Project, Main Dam, and Coosawattee River Basins

The Coosawattee River Basin is located at the northern end of the Alabama-Coosa River Basin. It is roughly rectangular in shape, draining an area of approximately 862 square miles. Maximum length and width of the basin are approximately 40 and 25 miles respectively. The Coosawattee River is formed by the juncture of the Ellijay and Cartecay Rivers at Ellijay, Georgia, about 21 miles upstream from the Carters Project. These tributary streams rise in the Blue Ridge Mountains which have peaks up to 4,000 feet NGVD29. The southern boundary of the basin is shared with the northern boundary of the Allatoona Dam Basin, which drains into the Etowah River. The 48-mile long Coosawattee River has a total fall of 650 feet, or an average of about 13.5 feet per mile. The slope of the river below Carters Project is approximately 1.5 feet per mile. The slope above the project to the confluence of the Ellijay and Cartecay Rivers is approximately 23.5 feet per mile. Above the Carters Main Dam, the drainage basin is approximately 374 square miles of forest area. Above the Reregulation Dam the total drainage basin is 520 square miles. The large increase in drainage area is due to the addition of Talking Rock Creek Basin joining the Coosawattee River in the Reregulation Dam Basin.

4-02. Topography. From its source the Coosawattee River flows in a southwest direction through an elevated semi-plateau section for about 10 miles, then about 13 miles through a gorge section, and finally, after emerging from the gorge, about 25 miles through a broad plateau to join the Conasauga River and form the Oostanaula River. Elevations in the Coosawattee River Basin range from approximately 4,000 feet NGVD29 at the basin divide to 600 at the mouth. Channel capacity below the Carters Project is estimated to be about 5,000 cfs. A river bottom profile of the Coosawattee and Oostanaula Rivers is shown below in Figure 4-2.



Figure 4-2. River Bottom Profile of the Coosawattee and Oostanaula Rivers

4-03. Geology and Soils. The Carters Project is located in the irregular escarpment which separates the Piedmont Province from the Appalachian Valley Province. The main dam is about one-half mile upstream from the escarpment in a 600-foot deep gorge. Specifically, the main dam and reservoir are in the Dahlonega Plateau Subdivision of the Piedmont Province. This region is characterized by rugged, mountainous terrain. One of the major thrust faults of the United States, the Cartersville Fault, is located along the boundary escarpment. The escarpment is the result of this fault and of differential erosion between the harder crystalline rocks of the Piedmont and the softer sedimentary rocks of the Appalachian Valley. The

Reregulation Dam is located within the Appalachian Valley Province and about 1.8 miles downstream from the main dam. Broad valley lands with occasional north-trending ridges typify this province.

4-04. Sediment. Sediment ranges have been established in the Reregulation and Main Dam pools as well as below the Reregulation Dam to Pine Chapel Road. Surveys have been made above the Main and Reregulation Dams in 1973 and 1992 at the locations shown on Plate 4-1, although they extended no deeper than 200 feet in the main dam pool. Retrogression range locations below the Reregulation Dam are shown in Figure 4-3. All locations above and below the project were re-surveyed in September 2009, with ranges in the main dam pool surveyed to the bottom of the pool. The basin above Carters Project remains largely forested with little development or erosion basin-wide. Erosion downstream of the Reregulation Dam has not been noted in periodic inspections and does not appear to be a problem.



Figure 4-3. Retrogression Ranges Below the Reregulation Dam

4-05. Climate. The average annual temperature in the Coosawattee River Basin above Carters Dam for the time period 1981 – 2010 is 59.7 degrees Fahrenheit (°F). This is based on averages at seven stations near the basin boundary. These stations, Calhoun Experiment Station, Dahlonega, Jasper, Dalton, Cartersville, Lafayette, and Rome are considered representative of the area. Average monthly temperatures range from 40 °F in January, the coldest month to about 78 °F in July and August, the warmest months. Extreme temperatures recorded in the area range from 109 °F to -14 °F and the frost-free period normally lasts from mid-April to early October.



A map showing the seven representative stations is shown below in Figure 4-4.

Figure 4-4. Representative Temperature Stations for the Coosawattee Basin

Normal monthly maximum, minimum and mean temperatures for the selected stations in the basin are shown below in Table 4-1. Climatologists define a climatic normal as the arithmetic average of a climate element, such as temperature, over a prescribed 30-year time interval. The National Climatic Data Center (NCDC) uses a homogenous and complete dataset with no changes to the collection site or missing values to determine the 30-year normal values. When developing this 30-year normal dataset, the NCDC has standard methods available to them to make adjustments to the dataset for any inhomogeneities or missing data before computing normal values.

	Normal Monthly Temperature Based on 30-Year Period – 1981 Through 2010													
						(De	egrees F	-)						
Station		JAN	FEB	MAR	APR	MAY	JUNE	JULY	AUG	SEPT	ост	NOV	DEC	ANNUAL
Calhoun	Mox	50.7	FF 2	62 5	70.0	70.0	07 E	00.2	90 F	02 1	72.0	62.0	EQ 1	71.0
	Moon	40.5	14.4	51.7	50.0	67.9	76.1	90.2 70.4	79.6	71.9	60.8	51.2	42.0	60.5
	Min	30.3	33.4	40.0	17.5	55.0	64.7	68.6	67.7	60.3	47.7	30.5	42.9	00.5 /0 1
Dahlonega	Max	50.3	54.9	61.8	70.3	77 4	83.1	86.3	85.2	79.4	71.7	62.3	52.7	49.1 69.6
Danionega	Mean	38.4	11 0	48.3	55.8	63.2	70.6	74.5	74.0	67.3	57.0	48.7	40.4	56.8
	Min	26.4	28.9	34.7	41.3	49.1	58.1	62.7	62.8	55.2	44.5	35.2	28.6	44.0
Jasper	Max	47.8	52.0	60.6	69.0	76.1	82.7	85.6	84.9	79.2	69.5	60.0	50.3	68.2
	Mean	39.0	42.7	50.3	57.8	65.5	73.0	76.1	75.6	69.6	59.3	50.4	42.0	58.5
	Min	30.2	33.4	40.1	46.7	54.9	63.2	66.7	66.2	59.9	49.0	40.9	33.7	48.8
Dalton	Мах	50.1	54.8	64.0	72.1	79.6	86.2	89.6	89.2	83.4	74.0	63.1	52.7	71.6
	Mean	40.1	43.7	51.8	58.9	67.7	75.1	79.0	78.4	72.1	61.5	51.4	42.8	60.3
	Min	30.1	32.6	39.5	45.7	55.5	63.9	68.3	67.6	60.9	49.1	39.7	33.0	48.9
Cartersville	Max	53.2	58.6	67.3	74.9	81.7	88.6	91.5	91.1	85.2	75.5	65.9	55.5	74.2
	Mean	41.4	45.9	53.1	60.7	68.7	76.4	79.7	79.3	73.3	62.1	52.7	43.9	61.5
	Min	29.6	33.2	38.8	46.5	55.7	64.2	67.8	67.5	61.5	48.8	39.6	32.3	48.9
Rome	Мах	52.1	56.8	65.7	73.6	80.5	86.9	89.7	89.1	83.3	73.6	64.1	54.2	72.5
	Mean	41.6	45.6	53.2	61.0	68.9	76.6	80.1	79.4	72.9	61.9	52.4	44.1	61.5
	Min	31.1	34.3	40.8	48.3	57.3	66.3	70.5	69.6	62.4	50.1	40.7	34.0	50.5
Lafayette	Max	49.1	53.8	62.5	71.4	78.4	85.3	88.3	88.0	81.9	72.3	61.5	51.2	70.4
	Mean	38.8	42.3	49.6	57.7	65.7	73.4	77.0	76.6	70.3	59.4	49.4	41.1	58.5
	Min	28.5	30.8	36.7	44.0	52.9	61.5	65.7	65.2	58.6	46.5	37.4	31.0	46.6
Basin	Max	50.5	55.2	63.6	71.9	79.1	85.8	88.7	88.1	82.3	72.9	62.8	52.7	71.2
	Mean	40.0	43.8	51.1	58.8	66.8	74.5	78.0	77.4	71.0	60.4	50.9	42.5	59.7
	Min	29.5	32.4	38.7	45.7	54.5	63.1	67.2	66.7	59.8	48.0	39.0	32.2	48.1

 Table 4-1. Normal Monthly Temperature (1981 – 2010)

Due to the topographic lift of the Blue Ridge Mountains, the upland slopes are subject to intense local storms and to general storms of heavy rainfall lasting days. Heavy rains may occur at any time during the year, but are most frequent between late fall and mid- spring, when the majority of the large floods in the basin have been recorded. The large flood of March 1990 occurred when a storm front extended from Mobile to Montgomery to Rome and subtropical moisture was continuously drawn along the line producing an extended period of heavy rain. The normal monthly precipitation in the vicinity of the Carters Project is based on the 1981-2010 means of the National Weather Service gages at Resaca, Ellijay, Carters 1 WSW, Jasper, Summerville, Lafayette, and Cartersville. The Coosawattee River above Carters Dam lies in a region of moderately heavy annual precipitation. The average annual rainfall is 53.64 inches of which 56 percent occurs in the winter and spring, 24 percent in the summer and 20 percent in the fall. March is the wettest month averaging 5.09 inches while October is the driest averaging about 3.45 inches. The terms "wet season", "dry season", and "agricultural growing season" are frequently referred to within this manual. The agricultural growing season refers to spring, summer and early fall when crops are planted within the floodway. Summary precipitation data for the basin is shown below in Table 4-2.

	Normal Monthly Rainfall (inches) Based on 30-Year Period – 1981 Through 2010													
Station		JAN	FEB	MAR	APR	MAY	JUNE	JULY	AUG	SEPT	OCT	NOV	DEC	ANNUAL
Resaca*		4.89	4.87	4.73	3.81	4.07	3.69	4.05	3.66	3.72	3.45	4.73	4.73	50.40
Ellijay		5.50	5.47	5.25	4.56	4.59	4.78	5.05	4.14	4.49	3.78	5.22	5.46	58.29
Carters 1 WSW*		5.56	4.91	5.13	4.23	4.41	4.85	4.54	3.89	3.82	3.27	4.77	4.95	54.33
Jasper		5.45	5.18	5.31	4.56	4.07	4.81	5.48	4.41	4.07	3.88	4.87	4.89	56.98
Summerville		5.08	5.17	5.56	4.38	4.32	4.84	4.00	4.18	3.67	3.47	4.84	5.45	54.96
Lafayette		5.57	5.47	5.52	4.55	5.01	4.24	4.80	4.05	4.43	3.68	5.58	5.60	58.50
Cartersville		3.24	4.35	4.12	3.43	2.88	3.25	3.92	3.84	2.81	2.62	3.29	4.30	42.05
Basin		5.04	5.06	5.09	4.22	4.19	4.35	4.55	4.02	3.86	3.45	4.76	5.05	53.64

 Table 4-2.
 Normal Monthly Rainfall (1981 – 2010)



The location of representative precipitation stations are shown below in Figure 4-5.

Figure 4-5. Representative Precipitation Stations for the Coosawattee Basin

4-06. Storms and Floods. Major flood-producing storms over the ACT Watershed are usually of the frontal type, occurring in the winter and spring and lasting from two to four days, with their effect on the basin depending on their magnitude and orientation. The axes of the frontal-type storms generally cut across the long, narrow basin. Frequently a flood in the lower reaches is not accompanied by a flood in the upper reaches and vice versa. Occasionally, a tropical storm or hurricane, such as the storms of July 1916 and July 1994, will cause major floods over practically the entire basin. However, summer storms are usually of the thunderstorm type with high intensities over small areas producing serious local floods. With normal runoff conditions, from five to six inches of intense and general rainfall are required to produce wide spread flooding, but on many of the minor tributaries three to four inches are sufficient to produce local floods.

The pre-record flood of March 1886 was the greatest known on the Oostanaula River and, in all probability, was equally severe in that portion of the basin above Carters Dam site. Other major floods of record resulted from the storms of April 1938, January 1947, March 1951 and April 1977. As of August 2014, the highest pool in the main dam, 1,099.16 feet NGVD29, occurred on 8 April, 1977. April 1938 is remarkable because of the even distribution of rainfall over the area. It produced the maximum stage of record at Ellijay and near record stages throughout the Oostanaula River Basin. The storm of January 1947, while not producing as large a peak discharge as some of the other storms, lasted for several days and would have caused a larger volume of water to be held in storage at Carters Dam during flood risk management operations. The storm of March 1951 resulted in record stages at Pine Chapel and Resaca below the Carters site and was of considerable severity in the basin above Carters Dam site.

4-07. Runoff Characteristics. The steep slopes of the mountains and channel gradients of the upper reaches of the tributaries of the Oostanaula River are conducive to flashy storm runoff. Flash floods, resulting from local storms, occurring on the smaller of these streams have endangered lives in the past.

In contrast, the runoff characteristics of the tributary streams in the lower reaches and the main stream itself are more moderate. The wider valleys and relatively flat slopes of the stream channels are the principle factors in effecting moderation in the rate of change in stages. The lower base flows and higher peak discharges are characteristics of streams with valleys underlain to a considerable extent with limestone and with contributing areas that are largely cleared for cultivation. Seasons for extremes of storm runoff rates are uniform throughout the basin with low values occurring in late summer and early fall and high values occurring in winter and early spring. However, the variation is much greater in the lower reaches of the tributaries and along the main stream, with runoff of about 30 and 60 percent in the respective seasons. Runoff during floods for the same periods in the upper reaches is about 25 and 40 percent. Annual runoff from the basin above Carters Dam site averages approximately 27 inches or about 47 percent of the average rainfall.

Table 4-3 shows monthly and annual inflows to the Carters Project, along with minimums, maximums, and averages. Inflows are determined from the relationship "inflow minus outflow equals the change in storage" where outflows and change of storage are measurable quantities. Inflow values can be calculated as negative amounts mainly due to evaporation from the lake. Figure 4-6 present the average monthly runoff for the ACT Basin above Rome, Georgia. This information was computed by comparing unregulated flows with rainfall over the basin. The percent of rainfall appearing as streamflow is presented for each month.

	Average Monthly Inflow (cfs) at Carters Dam														
	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Min	Max	Avg
1975								498	527	730	765	779	498	779	660
1976	1413	969	1697	1350	1413	1117	1370	569	391	466	439	789	391	1697	999
1977	830	638	1764	2359	926	572	426	345	493	665	1250	848	345	2359	926
1978	1594	966	1103	851	938	594	394	496	256	170	290	604	170	1594	688
1979	1260	1267	2040	2093	1073	872	766	630	510	444	974	605	444	2093	1045
1980	868	927	2845	1926	1320	769	447	294	340	317	329	275	275	2845	888
1981	204	804	531	628	513	624	247	195	220	196	274	525	195	804	413
1982	1718	1986	1284	968	748	482	569	541	351	544	659	1635	351	1986	957
1983	861	1153	960	1432	1314	845	846	361	403	256	690	1380	256	1432	875
1984	1008	1033	1582	1385	1666	706	825	631	315	314	300	445	300	1666	851
1985	476	978	515	510	455	380	371	403	230	323	334	434	230	978	451
1986	346	514	527	331	248	127	41	100	148	306	665	634	41	665	332
1987	906	980	1098	731	481	418	254	87	64	75	124	197	64	1098	451
1988	587	401	374	525	269	63	82	114	195	143	412	263	63	587	286
1989	840	905	1330	1215	896	1564	1058	543	768	1036	990	964	543	1564	1009
1990	1699	3652	3120	1344	1029	615	749	397	382	448	341	1164	341	3652	1245
1991	951	1317	1532	1284	1429	832	625	593	414	297	464	956	297	1532	891
1992	876	1109	1375	1011	598	675	665	485	453	424	1037	1600	424	1600	859
1993	1531	1023	1277	1136	743	407	221	213	109	94	236	443	94	1531	619
1994	639	888	1505	1824	774	752	768	580	390	641	475	683	390	1824	827
1995	849	1463	1362	784	536	467	237	238	247	778	968	553	237	1463	707
1996	1747	1353	1712	1247	998	625	380	328	404	258	527	861	258	1747	870
1997	957	1089	1587	1414	1501	1024	607	400	366	558	448	502	366	1587	871
1998	1054	1389	1438	1947	1066	735	378	333	111	126	293	435	111	1947	775
1999	825	1052	773	533	836	474	801	273	113	183	184	188	113	1052	520
2000	377	340	470	1122	371	296	153	88	143	27	273	223	27	1122	324
2001	601	615	857	646	419	562	419	350	257	173	209	408	173	857	460
2002	808	535	709	649	800	360	234	82	337	302	573	917	82	917	526
2003	605	1193	1102	910	1780	1038	1422	1104	710	351	578	659	351	1780	954
2004	654	871	607	504	501	611	485	276	1622	372	1212	1614	276	1622	777
2005	752	1201	1200	1329	778	762	1195	772	355	275	316	550	275	1329	790
2006	813	615	528	674	542	297	156	100	187	294	424	272	100	813	409
2007	548	326	448	317	151	109	125	25	-18	-2	36	111	-18	548	181
2008	143	325	639	385	272	176	245	195	21	88	53	622	21	639	264
2009	974	471	788	815	1045	393	281	241	807	762	952	1238	241	1238	731
2010	1078	1320	899	803	948	464	277	241	97	165	211	271	97	1320	565
2011	374	358	1254	1155	563	312	133	47	179	74	363	577	47	1254	449
2012	1037	709	610	773	302	125	262	180	251	364	186	412	125	1037	434
2013	1526	1138	1056	1387	1842	1108	1042	859	610	479	93	1450	93	1842	1049
Min	143	325	374	317	151	63	41	25	-18	-2	36	111	-18	548	181
Max	1747	3652	3120	2359	1842	1564	1422	1104	1622	1036	1250	1635	543	3652	1245
Avg	903	997	1171	1060	844	588	515	361	348	336	478	692	216	1464	691

Table 4-3.	Average	Monthly	Inflow	(cfs)



4-08. Water Quality. Carters Lake is listed by the State of Georgia's 2012 Integrated 305 (b)/303 (d) list (GAEPD, 2010) as currently supporting its designated use with the exception of Coosawattee River embayment and US Woodring Branch/mid-lake area. Both Coosawattee River embayment and the US Woodring Branch/mid-lake area are listed on the 2012 draft Integrated 305(b) and 303(d) list because of chlorophyll a and phosphorus impairment. A draft Total Maximum Daily Load (TDML) has not yet been completed. The lake is now considered eutrophic due to an influx of phosphorus nutrients. Phosphorus levels have increased due to urban runoff and other non-point source pollutants. The reregulation pool downstream of the main lake serves as a buffer to improve water quality and flow condition downstream of the dam.

<u>a. Water Quality Needs</u>. Georgia Department of Natural Resources (GADNR) has classified the use of Carters Lake as "fishing" and the Coosawattee River embayment and US Woodring Branch/mid-lake area in Gilmer County as "recreation" in accordance with Georgia Water Quality Control laws. Georgia has promulgated water quality criteria for various water use classifications. The principal specific criteria related to the use classifications are as follows:

Fishing:

- Bacteria: Fecal coliform not to exceed a geometric mean of 500 colonies per 100 milliliters (ml) during May-October; 4,000 per 100 ml November – April (instantaneous maximum).
- Dissolved oxygen: A daily average greater or equal to 5.0 milligrams per liter (mg/l) and no less than 4.0 mg/l at all times.
- pH: Within the range of 6.0-8.5.
- Temperature: Less than 90 degrees Fahrenheit. Recreation:

- Bacteria: Fecal coliform not to exceed a geometric mean of 200 colonies per 100 ml.
- Dissolved oxygen: A daily average greater or equal to 5.0 mg/l and no less than 4.0 mg/l at all times.
- pH: Within the range of 6.0-8.5.
- Temperature: Less than 90 degrees Fahrenheit.

The following criteria apply to all use classifications:

- All waters shall be free from materials associated with municipal or domestic sewage, industrial waste or any other waste which will settle to form sludge deposits that becomes putrescent, unsightly or otherwise objectionable.
- All waters shall be free from oil, scum and floating debris associated with municipal or domestic sewage, industrial waste or other discharges in amounts sufficient to be unsightly or to interfere with legitimate water uses.
- All waters shall be free from material related to municipal, industrial or other discharges which produce turbidity, color, odor or other objectionable conditions which interfere with legitimate water uses.
- No material in concentration that after treatment would exceed GAEPD and Federal drinking water standards.

The above listing is not intended to be all-inclusive, and Georgia Water Quality Control regulations and standards should be consulted as necessary.

b. Lake Water Quality Conditions. Georgia's 2012 draft integrated 305(b)/303(d) list of impaired waters designates the mid-lake reaches in Carters Lake and the reregulation lake as supporting designated uses. Two reaches, the Coosawattee River embayment and the US Woodring Branch/mid-lake area, were identified as impaired. Both sections were identified as "not supporting its use" because growing season average chlorophyll a exceeded the criteria. chlorophyll a standards for Carters Lake are set as a growing season (May through October) average less than 5 micrograms per liter ($\mu q/l$) upstream from the Woodring Branch and 10 micrograms per liter (µg/l) at Coosawattee River embayment mouth (Georgia EPD, 2012). In addition, these two sections are listed as impaired for phosphorus. Standards for the annual total phosphorus load were set at 151,500 lbs/year for Coosawattee River at Old Highway 5 and 8,000 lbs/year for Mountaintown Creek at U.S. Highway 76. Measured data at compliance points for dissolved oxygen, total nitrogen, and pH are in compliance with Georgia's standards. The state collects profile data at compliance points in Carters Lake for dissolved oxygen, pH, conductivity, and water temperature during the growing season. The state also collects grab samples of nitrogen, phosphorus, chlorophyll a, and bacteria. During some years, algal blooms result in reports of bad tasting or bad smelling drinking water in the city of Chatsworth which withdraws its water supply from Carters Lake and in the downstream town of Calhoun, which draws water from the Coosawattee River.

Georgia has begun efforts to identify sources contributing to high chlorophyll *a* by developing a total maximum daily load. As part of the state's water planning effort, it is also modeling the Coosa River Basin, including the Etowah River portion downstream of Allatoona Dam.

c. <u>Lake Stratification</u>. Carters Lake is unusual because of its extreme water depth of approximately 400 feet in places, resulting in the very lowest levels not mixing with the higher more oxygenated waters. The deepest levels remain anoxic and in a temperature range of 40-50 degree Fahrenheit throughout the year. However, the lake does exhibit typical seasonal mixing in the upper zones.

During the colder winter months, the water in Carters Lake is generally cold, relatively clear, and with similar temperatures from the top to the bottom. Water on the top and bottom of the lake has similar densities. Wind action keeps the lake well mixed, resulting in adequate dissolved oxygen levels throughout the water column. During winter, water temperature and oxygen concentrations do not limit fish movement in the lake. Lake water, which is released through the hydropower units from near the bottom of the lake into the Coosawattee River below the dam, is cold, relatively clear, and typically low in dissolved oxygen.

Summer Lake Stratification Zones



Figure 4-7. Generalized Lake Stratification

During spring and early summer, the lake warms and stratifies into three distinct layers: a surface layer called the epilimnion, a bottom layer called the hypolimnion, and a layer between the two called the metalimnion, or the thermocline. Figure 4-7 shows the typical summer stratification layers; however, in Carters there is also a fourth layer described below.

The warm, upper layer is fairly uniform in temperature and varies from 15 to 30 feet thick throughout the summer. It is well oxygenated from wind action and photosynthesis.

The hypolimnion, the cold (45 to 55 °F) third layer, becomes isolated and no longer mixes with the warm, oxygenated epilimnion. Oxygen is not produced in the hypolimnion because the cold, deep layer does not receive sunlight and is devoid of phytoplankton production. Early in the lake stratification process, the hypolimnion still contains some oxygen but declines throughout the summer as biological and chemical processes consume oxygen. By summer's end, the lake is strongly stratified. The epilimnion is warm and well oxygenated. Water temperature and oxygen concentrations in the thermocline are both lower but still often provide acceptable habitat for cool-water fish species. In the hypolimnion, the water is cold and low in oxygen (less than 3 mg/l). As oxygen levels fall, some metals and sulfides in the lake sediments become soluble. They dissolve in the water and can be released downstream, entering the river. The river water becomes re-aerated rapidly as it flows downstream, thus releasing the metals and sulfides that have become soluble.

In the fall, the lake begins to lose heat, and the process of destratification begins. The warm water of the epilimnion cools and becomes deeper and denser. As the epilimnion's density approaches the density of the hypolimnion, mixing of the layers occurs and the stratification is broken. The event is called *lake turnover*, and generally occurs around November – December each year. After mixing, the upper three layers cease to exist, and the entire lake has relatively uniform temperature and oxygen levels.

Regardless of the natural process of thermal stratification, Carters Lake has a "permanent layer" that does not mix with the upper three layers of the lake, thus serving as a unique fourth layer. This layer has a higher concentration of dissolved inorganic compounds that has developed due to extended periods of anoxic conditions. For example, the concentrations of iron and manganese approach 140 and 16 mg/L, respectively in the deepest areas. This phenomenon is described by John Hains in the article "Southeastern Lakes - Changing Impacts, Issues, Demands." This permanent deep chemical zone (monimolimnion) never mixes because the high chemical content increases the water's density. It appears that this layer, which exists at an approximate depth of 280 feet, resists mixing during the fall turnover. The monimolimnion

is characterized by high conductivity and a rapid change in pH, devoid of oxygen, and contains high levels of iron, manganese, and other constituents and permanently low temperatures in the range of 40 to 50 degrees Fahrenheit as modeled by the Corps. The headgate and headrace channel is located at elevation 979 feet NGVD29, or about 200 feet below the pool elevation. This would indicate that normal operation would not draw water from the monimolimnion. On the other hand, the emergency sluice intake is located at elevation 725 feet NGVD29, or about 350 feet below pool elevation. Any use of this low-level sluice could have adverse impacts on downstream water quality as it would draw water directly from the monimolimnion.

d. <u>Downstream Water Quality Conditions</u>. Water quality conditions in the releases from Carters Dam are typical for hydropower projects in the southeast; i.e., cold water year-round with low dissolved oxygen levels during summer-time lake stratification periods and high dissolved oxygen levels during winter-time lake destratification periods. Turbidity is relatively low year-round. The potential for suspended metals occurs during lake stratification periods when the hypolimnion reaches anoxic conditions. The water use classification established by the State of Georgia for the Coosawattee River below Carters Dam is *fishing*, with corresponding water quality standards as described in paragraph 4-08.a. above. TMDLs for dissolved oxygen, fecal coliforms, and PCBs have been established for the Coosawattee River below Carters Dam. Due to PCB levels in fish tissue, the fishery advisories of one meal per week for spotted bass and one meal per month for smallmouth buffalo have been established by the State of Georgia.

Release water quality from the reregulation dam was monitored for several years from October 1974 and parameters measured were dissolved oxygen, temperature, pH, and conductivity. This data showed that dissolved oxygen consistently exceeded State water quality standards. While Dissolved Oxygen levels are periodically depressed in the releases from the main dam, exposure to the atmosphere in the reregulation pool together with reaeration which occurs in the spillway discharge from the reregulation dam is sufficient to elevate levels above standards. The monitoring is no longer being done by the Corps although the USGS collected water quality data at the site from 2005-2007.

4-09. Channel and Floodway Characteristics.

a. <u>General</u>. Carters Dam and Reregulation Dam Project is a headwater project with no other reservoirs located upstream. The channel capacity of the Coosawattee River downstream from the Carters Reregulation Dam is 5,000 cfs. Low lying areas on both banks of the lower reaches of the Coosawattee, Conasauga, and the beginning of the Oostanaula Rivers are cultivated during the spring, summer and early fall. It is estimated that a downstream flow of 5,000 cfs can be maintained during the planting and growing season without causing appreciable damage in these low lying areas. A downstream flow of 5,000 cfs can be maintained during the non-growing season without causing damages to these same areas.

During moderate to high flows, the backwater effects from the Coosawattee River increases flooding along the Conasauga River at Tilton, Georgia. When possible, releases from Carters Reregulation Dam are reduced during these periods to avoid increasing backwater flooding downstream in these areas.

b. <u>Damage Centers and Key Control Points</u>. In addition to the agricultural areas downstream from Carters Dam and Reregulation Dam Project, there are major flood damage reaches downstream on the Oostanaula River at Resaca and Rome, Georgia. The towns are shown in Figure 4-8.



Figure 4-8. Location of Towns below Carters Project

This flooding is due to flood flows exceeding the channel capacity. Since the drainage area has a long travel reach, the flood hydrograph peaks at Rome, Georgia, occur three to four days after the maximum rainfall, and the high flows tend to continue for many days.

The City of Resaca, Georgia, located below Carters Dam and Reregulation Dam Project, experiences flooding when the Oostanaula River stage reaches 22 feet.

The Carters Dam and Reregulation Dam Project is located northeast of Rome, Georgia, on the Coosawattee River and its operation provides some flood damage reduction benefits for Rome, Georgia. However, Carters Dam controls runoff from less than 10 percent of the drainage area above Rome, Georgia, so flood reductions at Rome due to the Carters Project are relatively small. Travel time for water released from Carters Dam and Reregulation Dam Project to reach Rome, Georgia, is approximately 32 hours. Rome, Georgia, is also the major flood damage area protected by the Allatoona Project. Travel time for water released from Allatoona Dam and Lake Project to reach Rome, Georgia, is approximately 12 hours. Efforts are made to coordinate Carters Dam and Reregulation Dam and Allatoona projects when making releases for flood operations. Usually, flood releases will not be made from Allatoona until after the peak flood from the Oostanaula River have peaked at Rome. The USGS gages for the Oostanaula River at Rome US 27 and Coosa River at Mayo's Bar (Weiss Lake) are used to guide operations of Carters Dam and Reregulation Dam Project to insure maximum flood reductions. The locations of the USGS gages around Rome, Georgia, are shown in Figure 4-9.



Figure 4-9. USGS Gages in the vicinity of Rome, Georgia

Tables 4-4 and 4-5 provide details for river stages and flood damages at Rome, and Resaca, Georgia. Tables 4-6 and 4-7 provide the dates and heights of historical floods for these locations and the lowest stages on record.

Table 4-4. Flood Impacts for Varying Stage of Oostanaula River at Rome, Georgia(USGS Gage# 02388525)

Stage (feet)	Flood impacts at Rome – Oostanaula River
0	Gage datum is 561.7 feet NGVD29
19	Action Stage is reached. Heritage Park Rome Greenway floods within floodplain.
22	Drainage valve must be closed at Second Avenue and Avenue A Pump station outfalls.
24	Drainage valves must be closed at American Legion Outfall and Police Station Outfall.
25	Flood Stage is reached. Mainly minor flooding will develop.
28	Moderate flooding begins. Water will enter basements of lower two city blocks near the gage site. Flood gates on Second Avenue and Avenue A must be closed.
30	Moderate flooding expands. Water enters Georgia Power Maintenance Yard at Etowah River.
32	Major flooding begins. Flooding of Rome Sewage Treatment Plant begins. Fifth Avenue Bridge is closed. Water overflows onto Second Avenue between railroad and bridge.
34.5	Major flooding continues. Six city blocks of basements in Rome near the Oostanaula River will flood. Water will cover the 200 block of East Second Avenue.
36	Major flooding continues. Water overflows at the lowest point of Summerville Road.
38	Major flooding expands. Water will reach Broad Street. This is the 100-year flood.
40.29	The record crest was 40.29 feet on April 1, 1892.
42	The levee of the Oostanaula will reach the top of the city levee. This is a very serious situation. Floyd Medical Center, Law Enforcement Center, and numerous businesses flood.
46	Highway 27 / 5th Avenue bridge floods. Many businesses and homes flooded.

Table 4-5. Flood Impacts for Varying Stage of Oostanaula River at Resaca, Georgia(USGS# Gage 02387500)

Stage (feet)	Flood impacts at Resaca – Oostanaula River
0	Gage datum is 604.14 feet NGVD29
19	Action Stage is reached
22	Mainly flooding of agricultural and pasture lands are affected when flood stage
	is reached.
28	High water will cause extensive flooding of farm lands in the area.
33.5	When the river rises to 33.5 feetflooding of a textile mill in Calhoun will
	develop. Widespread flooding will occur.
36	The flood of record was 36.3 feet on April 1, 1886. Widespread flooding will
	occur. In Calhounjust downstreamwill flood on North River Street and
	South River Street. A recreational area on South River Street will flood. Mills
	near the area will not floodbecause these locations have a higher elevation.

Table 4-6. Historical Crests for Oostanaula River at Rome, Georgia (USGS Gage# 02388525)

Historical Crests for C	ostanaula River at Rome
1) 40.30 ft on 04/01/1886	(19) 30.50 ft on 03/30/1951
(2) 37.20 ft on 01/15/1892	(20) 30.50 ft on 04/05/1920
(3) 34.50 ft on 01/22/1947	(21) 29.90 ft on 01/28/1996
(4) 34.30 ft on 07/12/1916	(22) 29.60 ft on 03/22/1980
(5) 34.26 ft on 03/18/1990	(23) 29.00 ft on 01/04/1982
(6) 34.10 ft on 02/12/1946	(24) 28.90 ft on 03/08/1996
(7) 33.90 ft on 11/30/1948	(25) 28.82 ft on 02/05/1998
(8) 33.80 ft on 01/09/1946	(26) 28.00 ft on 01/20/1925
(9) 33.80 ft on 12/30/1932	(27) 27.70 ft on 05/07/2003
(10) 33.70 ft on 04/08/1936	(28) 27.00 ft on 11/29/1929
(11) 33.30 ft on 02/06/1936	(29) 26.90 ft on 03/10/1998
(12) 33.00 ft on 04/14/1979	(30) 26.50 ft on 04/14/1980
(13) 32.80 ft on 12/11/1919	(31) 26.20 ft on 10/04/1989
(14) 32.64 ft on 02/27/1990	(32) 25.98 ft on 05/04/1997
(15) 32.00 ft on 12/14/1932	(33) 25.65 ft on 01/07/2009
(16) 31.80 ft on 04/05/1977	(34) 25.60 ft on 03/07/2003
(17) 31.80 ft on 12/18/1932	(35) 25.10 ft on 03/01/1987
(18) 30.50 ft on 03/27/1964	(36) 25.04 ft on 01/13/1993
Low Wat	ter Records
(1) 1.75 ft d	on 10/08/2007
(2) 1.82 ft d	on 09/27/2007

Historical Crests for Oostanaula River at Resaca, Georgia							
(1) 36.30 ft on 04/01/1886	(19) 30.20 ft on 03/06/1917						
(2) 34.50 ft on 03/31/1951	(20) 30.20 ft on 01/18/1954						
(3) 33.20 ft on 01/21/1947	(21) 30.10 ft on 03/17/1964						
(4) 32.70 ft on 02/11/1921	(22) 30.10 ft on 03/15/1950						
(5) 32.59 ft on 02/18/1990	(23) 30.00 ft on 11/21/1906						
(6) 32.50 ft on 02/12/1946	(24) 29.80 ft on 12/31/1942						
(7) 32.20 ft on 02/11/1946	(25) 29.80 ft on 12/29/1942						
(8) 32.00 ft on 04/14/1920	(26) 29.70 ft on 11/20/1906						
(9) 32.00 ft on 04/08/1892	(27) 29.40 ft on 12/14/1961						
(10) 31.90 ft on 01/22/1922	(28) 29.20 ft on 02/27/1961						
(11) 31.70 ft on 03/14/1909	(29) 28.70 ft on 03/17/1899						
(12) 31.70 ft on 04/07/1892	(30) 28.65 ft on 03/30/1994						
(13) 31.70 ft on 04/04/1920	(31) 28.58 ft on 03/24/1980						
(14) 31.20 ft on 04/09/1938	(32) 28.50 ft on 11/27/1930						
(15) 31.10 ft on 11/30/1948	(33) 28.40 ft on 03/19/1973						
(16) 30.90 ft on 12/29/1932	(34) 28.40 ft on 04/06/1977						
(17) 30.80 ft on 02/04/1957	(35) 28.40 ft on 02/15/1948						
(18) 30.60 ft on 04/03/1936	(36) 28.40 ft on 03/31/1944						
Low Wate	r Records						
(1) 1.11 ft or	10/17/2007						
(2) 1.15 ft or	ח 09/27/2007						
(3) 1.40 ft or	10/25/1954						
(4) 1.50 ft or	10/30/1978						
(5) 1.70 ft or	09/04/1977						
(6) 1.70 ft or	ח 09/30/1947						
(7) 1.70 ft or	n 09/23/1956						
(8) 1.80 ft or	10/05/1959						
(9) 1.80 ft or	10/07/1970 ח						
(10) 1.90 ft o	n 09/03/1962						

Table 4-7. Historical Crests for Oostanaula River at Resaca, Georgia(USGS# Gage 02387500)

4-10. Upstream Structures. Carters Dam is a headwater project with no other reservoirs located upstream.

4-11. Downstream Structures. The entire ACT Basin is extensively developed with nine reservoir projects (10 dams) located downstream from Carters Dam. In addition to reservoirs downstream there are five reservoirs on parallel streams. Reservoir regulation procedures at Carters are not dependent on other projects except for Allatoona Dam. Both Allatoona and Carters are located upstream from Rome, Georgia requiring coordination of flood risk management activities.

The drainage area and river mile for important locations of interest within the basin are shown in Table 4-8. The entire ACT Basin is shown on Plate 2-1.

ACT Reservoir Data								
Reservoirs	*Owner	River	River Mile	Drainage Area (sq miles)				
Carters Dam	F	Coosawattee	26.8	374				
Carters Project with Reregulation Dam	F	Coosawattee	25.3	520				
Allatoona Dam	F	Etowah	47.8	1,122				
Cartersville, GA (Hwy 61)		Etowah	38.2	1,345				
Kingston, GA		Etowah	31.4	1,634				
Resaca, GA		Oostanaula	43.16	1,602				
Rome, GA (Hwy 27)		Oostanaula	0.3	2,149				
Weiss Dam	Р	Coosa	225.70	5,270				
Neely Henry Dam	Р	Coosa	146.82	6,596				
Logan Martin Dam	Р	Coosa	98.47	7,743				
Lay Dam	Р	Coosa	50.84	9,053				
Mitchell Dam	Р	Coosa	36.76	9,778				
Jordan Dam	Р	Coosa	18.86	10,102				
Bouldin Dam	Р	Coosa	4.2	10,102				
Harris Dam	Р	Tallapoosa	138.98	1,454				
Martin Dam	Р	Tallapoosa	60.6	2,984				
Yates Dam	Р	Tallapoosa	52.70	3,293				
Thurlow Dam	Р	Tallapoosa	49.70	3,308				
Robert F. Henry	F	Alabama	236.3	16,233				
Millers Ferry	F	Alabama	133.0	20,637				
Claiborne	F	Alabama	72.5	21,473				
*P Alabama Power Company F Federal Project								

Table 4-8. River Mile and Drainage Area for Selected Sites in ACT Basin

4-12. Economic Data. The Carters Dam Watershed extends to the headwaters of the Oostanaula River and consists of eight Georgia counties. The watershed transitions from developed urban and residential land uses to more rural land use within the watershed. The Oostanaula River transitions into the Coosa River at Rome, Georgia which is considered the edge of the Carters Dam Watershed Basin.

a. <u>Population</u>. The 2010 population estimates for the eight counties composing the Carters Dam project watershed and basin below was 437,344 persons. Table 4-9 shows the 2010 population and the 2010 per capita income for each county. The most recent data available is provided.

	2010	2010
	Population	Per Capita Income
Chattooga	26,896	\$ 15,079
Floyd	96,531	\$ 20,696
Gilmer	29,145	\$ 19,320
Gordon	53,247	\$ 18,219
Murray	40,460	\$ 17,155
Pickens	31,375	\$ 26,525
Walker	65,012	\$ 19,674
Whitfield	94,678	\$ 19,612

Table 4-9.	Population	and Per	Capita	Income
	i opulation		Capita	meome

*US Census Bureau, 2010

The City of Rome, Georgia, is the most populated city located within the Carters Dam Project Watershed and Basin. Rome, Georgia, is located within Floyd County and had a population in 2010 of 36,303.

b. <u>Agriculture</u>. The Carters Dam Project Watershed and Basin below consist of approximately 3,708 farms averaging 115 acres per farm. In 2005, the area produced \$417 million in farm products sold and total farm earnings of more than \$117 million. Agriculture in the Carters Dam Project Watershed and Basin consists primarily of livestock, which account for around 95 percent of the value of farm products sold. Livestock production consists primarily of poultry operations and beef cattle within the basin. The principal crops consist of nursery and greenhouse ornamentals, floriculture, and sod, along with vegetable farms and orchards. Agricultural production information and farm earnings for each of the counties in the Carters Dam Project Watershed and Basin below are shown in Table 4-10.

c. <u>Industry</u>. The leading industrial sectors that provide non-farm employment are wholesale and retail trade, services, and manufacturing. The remaining non-farm employment is provided by construction, finance, insurance, real estate, transportation, and public utilities. In 2005, the Carters Dam project area counties contained 835 manufacturing establishments that provided 62,953 jobs with total earnings of just under \$3.1 billion. Additionally, the value added by the area manufactures was just under \$5.6 billion. Table 4-11 contains information on the manufacturing activity for each of the counties in the Carters Dam Project Watershed and Basin.

County	2005 Farm Earnings (\$1,000)	Number of Farms	Total Farm Acres (1,000)	Acres Per Farm	Value of Farm Products Sold (\$1,000)	<u>Percent</u> Crops	<u>From</u> Livestock	
Georgia								
Chattooga	1,365	329	55	167	6,000	13.7	86.3	
Floyd	8,416	663	91	138	29,000	7.9	92.1	
Gilmer	29,436	303	25	82	99,000	1.4	98.6	
Gordon	25,400	804	76	95	100,000	3.5	96.5	
Murray	9,922	306	42	137	27,000	5.8	94.2	
Pickens	19,971	243	17	71	48,000	1.2	98.8	
Walker	8,021	642	82	127	34,000	3.4	96.6	
Whitfield	15,001	418	43	104	74,000	1.3	98.7	

 Table 4-10.
 Farm Earnings and Agricultural Production

*US Census Bureau, City and County Data Books, 2007

County	No. of Manufacturing Establishments	Total Manufacturing Employees	Total Earnings (\$1,000)	Value Added by Manufactures (\$1,000)
		Georgia		
Chattooga	22	3,541	135,303	320,027
Floyd	119	9,484	585,524	735,657
Gilmer	31	2,892	106,838	129,857
Gordon	109	8,994	464,194	932,129
Murray	94	6,327	254,046	300,660
Pickens	35	814	38,836	69,577
Walker	71	5,343	235,639	538,472
Whitfield	354	25,558	1,277,433	2,563,777

Table 4-11. Manufacturing Activity

d. <u>Flood Damages</u>. Carters Lake provides flood damage protection for existing development in along the Oostanaula and Coosa River Floodplain. The Corps' Water Management Office has developed an Annual Damage Reduction Summary that estimates the flood damages prevented by the Carters Lake flood reduction project in the ACT Basin. Table 4-12 shows the Carters Dam and Lake flood damages prevented by Fiscal Year (FY) from 1986 through 2013.

Year	Carters Dam	Year	Carters Dam	Year	Carters Dam		
1986	\$0	1996	\$22,340	2006	\$0		
1987	\$0	1997	\$0	2007	\$0		
1988	\$0	1998	\$0	2008	\$0		
1989	\$0	1999	\$0	2009	\$8,800		
1990	\$219,000	2000	\$0	2010	\$285,474		
1991	\$22,881	2001	\$0	2011	\$28,286		
1992	\$0	2002	\$0	2012	\$0		
1993	\$13,000	2003	\$0	2013	\$255,367		
1994	\$20,100	2004	\$22,625				
1995	\$20,100	2005	\$0				
*Dollar values are indexed to each FY using CPI							

 Table 4-12. Flood Damages Prevented - Carters Lake

V - DATA COLLECTION AND COMMUNICATION NETWORK

5-01. Hydrometeorological Stations.

a. <u>Facilities</u>. Management of water resources requires continuous, real-time knowledge of hydrologic conditions. The Mobile District contracts out the majority of basin data collection and maintenance to the U.S. Geological Survey (USGS) and National Weather Service (NWS) through cooperative stream gaging and precipitation network programs. The USGS, in cooperation with other federal and state agencies, maintains a network of real-time gaging stations throughout the ACT Basin. The stations continuously collect various types of data including stage, flow, and precipitation. The data are stored at the gage location and are transmitted to orbiting satellites. Figure 5-1 shows a typical encoder with wheel tape housed in a stilling well used for measuring river stage or lake elevation. Figure 5-2 shows a typical precipitation station, with rain gage, solar panel, and Geostationary Operational Environmental Satellite (GOES) antenna for transmission of data. The gage locations are discussed in Chapter VI related to hydrologic forecasting.



Figure 5-1. Encoder with Wheel Tape for Measuring the River Stage or Lake Elevation in the Stilling Well



Figure 5-2. Typical Field Installation of a Precipitation Gage

The Water Management Section employs a staff of hydrologic field technicians and contract work to USGS to operate and maintain Corps' gages throughout the ACT Basin. All rainfall gages equipped as Data Collection Platforms are capable of being part of the reporting network. Data are available from many stations in and adjacent to the ACT Basin. The 13 stations listed in Table 5-1 and shown on Plate 5-1 are considered the rainfall reporting network for the Carters Dam Project. Because Carters Dam regulates flood flows to downstream locations, the reporting network extends to Rome, Georgia. Carters Dam regulation of peak flows does not affect areas below Weiss Dam on the Coosa River but does reduce flood inflows to that project. All river stage gages equipped as Data Collection Platforms are capable of being part of the reporting network. Data are available from many stations in and adjacent to the ACT Basin. The stations listed in Table 5-2 are in the ACT Basin and provide information for operations for both Carters and Allatoona Dams. The locations of river stage stations are also shown on Plate 5-1. River stage – river flow relationship curves for representative river gages are shown on Plates 5-2 through 5-11.

Name	Agency	Agency ID	Latitude	Longitude
Wahsega, GA	Corps	WAHG1	34.69028	-84.0644
Amicalola, GA	Corps	AMIG1	34.54583	-84.2772
Mountaintown, GA	Corps	MTNG1	34.77361	-84.5392
Carters Dam	Corps	CTRG1	34.61417	-84.6747
Allatoona Dam	Corps	CVLG1	34.16278	-84.7278
Chatsworth, GA	NOAA	91863	34.7589	-84.765
Rome, GA	NOAA	97600	34.34778	-85.1611
Summerville, GA	NOAA	98436	34.4546	-85.39
Lafayette, GA	NOAA	94941	34.6638	-85.3203
Jasper , GA	NOAA	94648	34.4758	-84.4461
Cartersville, GA	NOAA	91670	34.2043	-84.7925

Table 5-1. Corps and NOAA Gages Reporting only Rainfall

Table 5-2. Gages Reporting Rainfall and River Stage

11969				Drainage	River Mile		Flood	Pain
Gage	Name	Lat	Long	miles)	Rome, GA	Datum	Stage	Gage
	Etowah River At Ga 9, Near							
02389150	Dawsonville	34.3572	-84.1136	131	131	1022	13	Y
02394670	Etowah River At Ga 61, Near Cartersville	34.1428	-84.8389	1345	38.22	650.81	18	Y
02395000	Etowah Near Kingston	34.2089	-84.9787	1634	21.4	609.97		Y
02395120	Two Run Creek Near Kingston, Ga	34.2428	-84.8897	33.1	na	723.1		Ν
02395980	Etowah River At Ga 1 Loop, Near Rome	34.2322	-85.1169	1801	1.47	561.7	32	N
02380500	Coosawattee River Near Ellijay, Ga	34.675	-84.5086	236	93.3	1216.04	8	Y
02382200	Talking Rock Creek Near Hinton, Ga	34.5228	-84.6111	119	na	893.69		Y
02382500	Coosawattee River At Carters, Ga	34.6036	-84.6956	520	71.86	650.67		Y
02383500	Coosawattee River Near Pine Chapel	34.5642	-84.8331	831	53.55	616.16		Y
02383520	Coosawattee River at Pine Chapel	34.5764	-84.8603	847	53.35	616.16		N
02384500	Conasauga River At Ga 286, Near Eton	34.8278	-84.8508	252	89.62	672.64	12	Y
02385800	Holly Creek Near Chatsworth, Ga	34.7167	-84.77	64	na	689.25		Y
02387000	Conasauga River At Tilton, Ga	34.6667	-84.9283	687	59.09	622.28	18	Ν
02387500	Oostanaula River At Resaca, Ga	34.5771	-84.9419	1602	43.16	604.14	22	Y
02387520	Oostanaula River At Calhoun Ga	34.5189	-84.9544	1624	36.7		20	Y
02388500	Oostanaula River Near Rome, Ga	34.2983	-85.1381	2115	5	561.7	30	N
02388525	Oostanaula River At US 27 At Rome Ga	34.2606	-85.1708	2149	0.65	561.7	25	Y
02397000	Coosa River Near Rome - Mayo's Bar	34.2003	-85.2567	4040		553.05		Y
02392000	Etowah River At Canton, Ga	34.2398	-84.4947	613	77.8	844.55	16	Ν
02393500	Allatoona Lake Near Cartersville, Ga	34.1628	-84.7278	1122	47.8	0		Y
02393501	Etowah River Allatoona Dam Tw, Abv Cartersville, Ga	34.1639	-84.7281	1122	47.73	0		N
02394000	Etowah River At Allatoona Dam, Abv Cartersville, Ga	34.1631	-84.7411	1119	47	686.92		N
02381400	Carters Lake Near Carters, Ga	34.6139	-84.6711	374	73.76	0		Y
02381401	Carters Lake Tailrace Near Carters, Ga	34.6142	-84.6747	374	73.75	0		Ν
02382400	Carters Re-Regulation Lake Near Carters, Ga	34.6042	-84.6914	520	72.25	651		N

b. <u>Reporting</u>. The Water Management Section operates and maintains a Water Control Data System (WCDS) for the Mobile District that integrates large volumes of hydrometeorological and project data so the basin can be regulated to meet the operational objectives of the system. The WCDS, in combination with the new Corps Water Management System (CWMS), together automate and integrate data acquisition and retrieval to best meet all Corps water management activities. The rainfall reporting network and the river stage reporting network are shown on Plate 5-1.

Data from the Carters Project such as pool, tailwater, and other pertinent data as well as the same data from the Allatoona Project is used to operate the Carters Project and to remotely operate the Allatoona Project. A microwave system between Carters and Allatoona Dam provides for continuous monitoring and regulation of the Allatoona Project. Information such as pool, tailwater, and other pertinent data needed for regulation is continuously transmitted through the microwave system to Carters. Computer systems at the projects store and organize the data and transmit the information to the Water Management Section in Mobile. Forms and river bulletins are automatically formatted, printed and transmitted to other parties.

A system of automatic reporting rainfall and river stage stations has been installed covering the drainage basin above both Carters and Allatoona Dams, and extending downstream to Rome, Georgia. These reporting stations, along with thousands throughout the Nation are part of a comprehensive data gathering system. The basis for automated data collection is the satellite Data Collection Platform. The Data Collection Platform is a computer microprocessor physically located at the gage sites. A Data Collection Platform has the capability to interrogate sensors at regular intervals to obtain real-time information (e.g., river stages, reservoir elevations, and water and air temperatures, precipitation), save the information, perform simple analyses of this information, and then transmit this information to a fixed geostationary satellite. Data Collection Platforms transmit real-time data at regular intervals to the GOES System operated by the National Oceanic and Atmospheric Administration (NOAA). The GOES Satellite sends this data directly down to the NOAA Satellite and Information Service in Wallops Island, Virginia, This data is then re-broadcast over a domestic communications satellite (DOMSAT). The Mobile District maintains a Local Readout Ground Station (LRGS) that collects the Data Collection Platform-transmitted, real-time data from the DOMSAT. Figure 5-3 depicts a typical schematic of how the system operates.



Figure 5-3. Typical Configuration of the GOES System

Typically, reporting stations log 15-minute data that are transmitted every hour. A few remaining gages report every four hours, but they are being transitioned to the hourly increment. All river stage and precipitation gages equipped with a Data Collection Platform and GOES antenna are capable of being part of the reporting network.

Other reservoir project data are obtained directly at a project is collected through each project's SCADA system. The Water Management Section downloads the data both daily and hourly through the Corps' server network.

c. <u>Maintenance</u>. Maintenance of data reporting equipment is a cooperative effort among the Corps, USGS, and NWS. The USGS, in cooperation with other federal and state agencies, maintains a network of real-time Data Collection Platform stream gaging stations throughout the ACT Basin. The USGS is responsible for the supervision and maintenance of the real-time Data Collection Platform gaging stations and the collection and distribution of streamflow data. In addition, the USGS maintains a systematic measurement program at the stations so the stage-discharge relationship for each station is current. Through cooperative arrangements with the USGS, discharge measurements at key ACT Basin locations are made to maintain the most current stage-discharge relationships at the stations. The NWS also maintains precipitation data for the flood control precipitation (FC-1) network.

If gages appear to be out of service, the following agencies can be contacted for repair:

U.S. Army Corps of Engineers, Mobile District, 109 Saint Joseph Street, Mobile, AL 36602-3630 Phone: (251) 690-2737 Web: <u>http://water.sam.usace.army.mil</u>

USGS South Atlantic Water Science Center - Georgia, 1770 Corporate Dr., Suite 500, Norcross, Georgia 30093 Phone: (678) 924-6700 Web: http://ga.water.usgs.gov

NWS Southern Region, 819 Taylor Street, Room 10E09, Fort Worth, TX 76102Phone: (817) 978-1100Web: http://www.srh.noaa.gov/

5-02. Water Quality Stations. The Corps does not operate any water quality stations in the ACT Basin. In most cases, other federal and state agencies maintain water quality stations for general water quality monitoring in the ACT Basin. In addition, some real-time water quality parameters are collected at some stream gage locations maintained by the USGS.

5-03. Sediment Stations. In order to provide an adequate surveillance of sedimentation, a network of sediment ranges were established for Carters Lake and the Reregulation pool. Quantitative computations can be made from these ranges to compute storage depletion rates. The network also serves as an index of any bank sloughing that may occur. General conditions and changes have been measured and recorded using this network. The network of sediment stations is shown on Plate 4-1. In order to monitor degradation and gradation of the Coosawattee River below the Reregulation Dam a network of retrogression ranges were established to Pine Chapel Road downstream of the Reregulation dam. This network is shown on Figure 4-3. Sedimentation ranges in the Carters Lake were conducted in 2009, and the sedimentation and retrogression ranges for the Reregulation pool and downstream were conducted in 1973, with resurveys conducted on a periodic basis. Two such periodic surveys were made in 1992 and in 2009 for the Reregulation Dam. The Carters Lake has only been surveyed in 2009.

Sediment surveys were conducted in 2009. Tetra Tech, Inc. was retained to conduct an analysis of the data and determine the extent and degree of sedimentation and erosion that has occurred in the lake and its tributaries over the years, and where appropriate, to speculate on

the causes of those changes. This analysis and results are presented in a report entitled; "Sedimentation and Erosion Analysis for Carters Lake, Carters Dam and Lake and Reregulation Pool, GA". Sedimentation and erosion classifications were developed for each range. Based on the percentage change for the entire cross section, range cross sections were classified for sedimentation as "Heavy" (greater than 15 percent change), "Medium" (5 to 15 percent change), "Light" (0 to 5 percent), and "None" (0 or negative change). Erosion classifications were also developed from bank retreat and advance rates. A bank retreat or advance rate is the average change in location, measured in feet, of the shoreline. It is the area bounded between two cross section profiles at the shore erosion zone (square feet) divided by the height of shore erosion zone (feet). The shorelines were separated into two groups, erosional and depositional. The erosional group was further divided into three classes by percentile. The 25 percent of shorelines showing the greatest bank retreat were classed as "Acute," the middle 50 percent in bank retreat were classed as "Moderate," and the 25 percent with the least bank retreat were classed as "Slight." Shorelines in the depositional group were classed as "Deposition."

Analysis revealed that the Reregulation pool has undergone sedimentation primarily along the Talking Rock Creek arm with deposits limited primarily to the historic, now-submerged, stream channel. "Acute" erosion is found only on the left bank of range 3A with "Slight" and "Moderate" erosion noted on both shorelines of ranges 1A and 2A. Although the pool has large portion of bedrock shoreline, the large and frequent fluctuation in pool elevation promote continued erosion above the bedrock. The Talking Rock Creek embayment has undergone several feet of overbank sedimentation between elevations 687 and 689 feet NGVD29.

Bathymetry was obtained for Carters Lake for the first time during 2009 to provide a base for monitoring of Carters lake sedimentation. No sedimentation analysis was performed for Carters Lake; however a qualitative shoreline erosion analysis was made from observations and photographs. Thirteen of 18 locations were stable due to bedrock and boulder shorelines. Historically the erosion rates have been high shortly after the lake was impounded, but presently these locations appear stable. Four locations were classified as "Slight" and one as "Acute" for bank erosion. All these locations are characterized as shorelines composed of unconsolidated soil materials or bedrock weathered to the point of being friable. One extended shoreline between rangelines was noted for active mass wasting.

In summary Talking Rock Creek is the dominant sediment source for the Reregulation Pool, and the Coosawattee River is the dominant sediment source for Carters Lake with present and potential land use activities driving sediment load. The amount of sediment deposition that has occurred has not affected the operation of the project and it is not expected to in the near future.

5-04. Recording Hydrologic Data. The Water Control Data Support System (WCDSS) is an integrated system of computer hardware and software packages readily usable by water managers and operators as an aid for making and implementing decisions. An effective decision support system requires efficient data input, storage, retrieval; and capable information processing. Corps-wide standard software and database structure are used for real-time water control. Time series hydrometeorological data are stored and retrieved using the CWMS Oracle database. In the event this database is unavailable, data can alternately be stored in the Hydrologic Engineering Center Data Storage System (HEC-DSS).

To provide stream gage and precipitation data needed to support proper analysis, a DOMSAT Receive Station (DRS) is used to retrieve DCP data from gages throughout the ACF Basin. The DRS equipment and software then receives the DOMSAT data stream, decodes the DCPs of interest and reformats the data for direct ingest into a HEC-DSS database. Reservoir

data is received through a link with the Supervisory Control and Data Acquisition (SCADA) system which monitors and records reservoir conditions and operations in real time.

Each morning (or other times when needed) reservoir data is examined and recorded in water control models. This information is used for management purposes. However, most reservoir data is transmitted in hourly increments for inclusion in daily log sheets that are retained indefinitely. Gage data is transmitted in increments of 15 minutes, one hour or other time intervals. The data is automatically transferred to forecast models.

Automated timed processes also provide provisional real-time data needed for the Decision Support System. Interagency data exchange has been implemented with the USGS and NWS Southeast River Forecast Center (SERFC).

A direct link to the NWS, SERFC is maintained to provide real-time products generated by NWS offices. Information includes weather and flood forecasts and warnings, tropical storm information, NEXRAD radar rainfall, graphical weather maps and more.

5-05. Communication Network. The global network of the Corps consists of private, dedicated, leased lines between every Division and District office worldwide. Those lines are procured through a minimum of two General Services Administration-approved telephone vendors, and each office has a minimum of two connections, one for each vendor. The primary protocol of the entire Corps network is Ethernet. The reliability of the Corps' network is considered a command priority and, as such, supports a dedicated 24 hours per day Network Operations Center. The use of multiple telephone companies supplying the network connections minimizes the risk of a one cable cut causing an outage for any office. Such dual redundancy, plus the use of satellite data acquisition, makes for a very reliable water control network infrastructure.

The Water Management Section has a critical demand for emergency standby for operation of the ACT Basin and to ensure data acquisition and storage remain functional. The Water Management Section must be able to function in cases of flooding or other disasters, which typically are followed by the loss of commercial electricity. The WCDS servers and the LRGS each have individual UPS (uninterruptable power supply) and a large UPS unit specifically for the portion of Mobile District Office in which the Water Management Section resides to maintain power for operational needs.

In the event of a catastrophic incident that causes loss of communication or complete loss of access to the Mobile District Office and the WCDS and CWMS servers located on site, a Continuity of Operations Program (COOP) site is being set up as a backup to these systems. This site will have servers that mirror the WCDS and CWMS servers located at the Mobile District Office allowing Water Managers to continue operating with no interruption or loss of data. It is currently planned that the COOP site will be located at the South Atlantic Division Office in Atlanta, Georgia.

The primary communication network of the Carters Project is a SCADA system network. The SCADA network includes a microwave link between Carters, Allatoona, and Buford. The SCADA network also monitors powerhouse conditions and digitally records real-time project data hourly. Computer servers at Carters are connected to the Mobile District through the Corps Network, permitting data transfer at any time. The data include physical conditions at each of the reservoirs such as pool elevations, outflow, river stages, generation, and rainfall. Special instructions or deviations are usually transmitted by e-mail, telephone, or fax. Emergency communication is available at the following numbers:

Water Management Section
Chief of Water Management
Carters Powerhouse

251-690-2737 251-690-2730 or 251-509-5368 (cell) 706-334-2906

5-06. Communication with the Project Office.

a. <u>Regulating Office With Project Office.</u> The Carters Powerhouse should be contacted regarding any operational issues regarding Carters, Allatoona, and Buford. There are a variety of methods for communication between the Mobile District and Carters Dam. Satellite communication is available for some data transmission. Telephone and fax communication are available. Computer servers at Carters Dam are connected to the Mobile District through the Internet, permitting data transfer at any time. The data includes physical conditions at each of the reservoirs that include pool elevations, outflow, river stages, generation and rainfall. Special instructions or deviations are usually transmitted by telephone, email, or fax. For local communication in the reservoir area above and below the Carters Dam, there are two fixed base station remotes and several mobile units and hand held two-way radios. The fixed VHF base station is located in the Reservoir Manager's office map building and the mobile stations are located in boats and motor vehicles. For communication between Carters Dam, Reregulation Dam and other elements of the Carters Project, there is a private Mitel PBX telephone system installed which allows direct dialing between any and all elements of the project.

Data from the Carters and Allatoona Projects are automatically collected at the Carters Project and transmitted through the network to the Mobile District. Telephone is another communications option if there are problems receiving the data over the network. Data for the project and the Data Collection Platforms are downloaded to the Mobile District's computer system. Daily reports are automatically generated for review.

b. <u>Between Project Office and Others</u>. Information is automatically sent to those with need. The National Weather Service and the River Forecast Center receive the data. Both the Corps and the River Forecast Center prepare forecasts for areas of concern. In addition, water resources information is available to the public at the Corps' Web site, <u>http://water.sam.usace.army.mil</u>. The site contains real-time information, historical data, and general information.

In order to warn the public at the start of a hydropower release downstream, when an operator initiates a generator start, a warning horn sounds. An audio detector verifies the horn has sounded and allows the unit start-up sequence to continue. The horn will continue to sound for one minute. The reregulation dam does not have a downstream warning horn system because the routine releases are small and gradual. If there was a large single gate change, the rangers would notify individuals in the recreation area immediately downstream of the dam.

5-07. Project Reporting Instructions. In addition to automated data, project operators maintain record logs of the reregulation spillway gate position, water elevation, and other relevant hydrological information including inflow and discharge. That information is stored and available to the Mobile District through the Corps' network. The Mobile District maintains constant contact with project operators. Operators notify the Mobile District if changes in conditions occur. Unforeseen or emergency conditions at the project that require unscheduled manipulations of the reservoir should be reported to the Water Management Section as soon as possible.

If the automatic data collection and transfer are not working, projects are required to fax or email daily or hourly project data to the Water Management Section. Water Management staff will manually input the information into the database. In addition, Mobile District Power projects must verify pool level gauge readings each week, in accordance with Standard Operating Procedure, Weekly Verification of Gauge Readings, Mobile District Power Projects dated 19 February 2008, and CESAD SOP 1130-2-6 dated 21 July 2006. Those procedures require that powerhouse operators check the accuracy of pool monitoring equipment by verifying readings of the equipment against gauge readings at each plant. That information is logged into the Official Log upon completion. A Trouble Report to management communicates any discrepancies with the readings. Operations Division, Hydropower Section will be notified by email when verification is complete. The e-mail notification will include findings of the verification.

Project personnel or the Hydropower Section within Operations Division, or both, are responsible for requesting any scheduled system hydropower unit outages in excess of two hours. The out-of-service times for the hydropower units are reported back to Water Management upon completion of outages. Forced outages are also reported with an estimated return time, if possible. Any forced or scheduled outages causing the project to miss scheduled water release targets must be immediately reported to the Water Management Section and to SEPA. In such cases, minimum flow requirements can be met through spilling.

5-08. Warnings. During floods, dangerous flow conditions or other emergencies, the proper authorities and the public must be informed. In general flood warnings are coupled with river forecasting. The NWS has the legal responsibility for issuing flood forecast to the public and that agency will have the lead role for disseminating the information. For emergencies involving the project the operator on duty should notify the Water Management Section, Operations Division and the Operations Project Manager at the project. If needed the Operations Project Manager will notify local law enforcement, government officials and emergency management agencies.

5-09. Role of Regulating Office. The Water Management Section of the Mobile District Office is responsible for developing operating procedures for both flood and non-flood conditions. Plans are developed to most fully use the water resources potential of each project within the constraints of authorized functions. Those plans are presented in reservoir regulation manuals such as this one. Reservoir regulation manual preparation and updating is a routine operation of the section. In addition, the section maintains information on current and anticipated conditions, precipitation, and river-stage data to provide the background necessary for best overall operation. The Water Management Section arranges the communication channels to the Power Project Manager and other necessary personnel. Instructions pertaining to reservoir regulation are issued to the Power Project Manager; however, routine instructions are normally issued directly to the powerhouse operator on duty.

5-10. Role of Power Project Manager. The Power Project Manager must be completely familiar with the approved operating plan for the Carters. The Power Project Manager is responsible for implementing actions under the approved water control plan and carrying out special instructions from the Water Management Section. The Power Project Manager is expected to maintain and furnish records requested from him by the Water Management Section. Training sessions should be held as needed to ensure that an adequate number of personnel are informed of proper operating procedures for reservoir regulation. Unforeseen or emergency conditions at the project that require unscheduled manipulation of the reservoir should be reported to the Water Management Section as soon as practicable.

VI - HYDROLOGIC FORECASTS

6-01. General. Reservoir operations for the Carters Project are scheduled by the Water Management Section in accordance with forecasts of reservoir inflow and river stages. Operations at the Carters Project are coordinated with the Allatoona Project to reduce the flood damage at Rome, Georgia.

The Corps has developed techniques to conduct forecasting in support of the regulation of the ACT Basin. In addition, the Corps relies on other federal agencies such as the NWS and the USGS to help maintain accurate data and forecast products to aid in making the most prudent water management decisions. The regulation of multipurpose projects requires scheduling releases and storage on the basis of both observed and forecasted hydrologic events throughout the basin. During both normal and below-normal runoff conditions, releases through the power plants are scheduled on the basis of water availability, to the extent reasonably possible, during peak periods to generate electricity during periods of greatest demand. The release level and schedules are dependent on current and anticipated hydrologic events. The most efficient use of water is always a goal, especially during the course of a hydrologic cycle when below-normal streamflow is occurring. Reliable forecasts of reservoir inflow and other hydrologic events that influence streamflow are critical to the efficient regulation of the ACT System.

a. Role of The Corps. The Water Management Section maintains real-time observation of river and weather conditions in the Mobile District. The Water Management Section has capabilities to make forecasts for several areas in the ACT Basin. Those areas include all the federal projects and other locations. Observation of real-time stream conditions provides guidance of the accuracy of the forecasts. The Corps maintains contact with the River Forecast Center to receive forecast and other data as needed. Daily operation of the ACT River Basin during normal, flood risk management, and drought conservation regulation requires accurate, continual short-range and long-range elevation, streamflow, and river-stage forecasting. These short-range inflow forecasts are used as input in computer model simulations so that project release determinations can be optimized to achieve the regulation objectives stated in this manual. The Water Management Section continuously monitors the weather conditions occurring throughout the basin and the weather and hydrologic forecasts issued by the NWS. The Water Management Section then develops forecasts that are to meet the regulation objectives of regulating the ACT projects. The Water Management Section prepares five-week inflow and lake elevation forecasts weekly based on estimates of rainfall and historical observed data in the basin. These projections assist in maintaining system balance and providing project staff and the public lake level trends based on the current hydrology and operational goals of the period. In addition, the Water Management Section provides weekly hydropower generation forecasts based on current power plant capacity, latest hydrological conditions, and system water availability.

b. <u>Role of Other Agencies</u>. The NWS is responsible for preparing and publicly disseminating forecasts relating to precipitation, temperatures, and other meteorological elements related to weather and weather-related forecasting in the ACT Basin. The Water Management Section uses the NWS as a key source of information for weather forecasts. The meteorological forecasting provided by the Birmingham, Alabama and Peachtree City, Georgia offices of the NWS is considered critical to the Corps' water resources management mission. The proactive use of 24- and 48-hour Quantitative Precipitation Forecasts (QPFs) are invaluable in providing guidance for basin release determinations. Using precipitation forecasts and subsequent runoff directly relates to project release decisions.

1) The NWS is the federal agency responsible for preparing and issuing streamflow and river-stage forecasts for public dissemination. That role is the responsibility of the Southeast River Forecast Center (SERFC) co-located in Peachtree City, Georgia with the Peachtree City Weather Forecast Office. SERFC is responsible for the supervision and coordination of streamflow and river-stage forecasting services provided by the NWS Weather Service Forecast Office in Peachtree City, Georgia. SERFC routinely prepares and distributes five-day streamflow and river-stage forecasts at key gaging stations along the Alabama, Coosa, and Tallapoosa Rivers. Streamflow forecasts are available at additional forecast points during periods above normal rainfall. In addition, SERFC provides a revised regional QPF on the basis of local expertise beyond the NWS Hydrologic Prediction Center QPF. SERFC also provides the Water Management Section with flow forecasts for selected locations on request.

2) The Corps and SERFC have a cyclical procedure for providing forecast data between federal agencies. As soon as reservoir release decisions have been planned and scheduled for the proceeding days, the release decision data are sent to SERFC. Taking release decision data, coupled with local inflow forecasts at forecast points along the ACT, SERFC can provide inflow forecasts into Corps projects. Having revised inflow forecasts from SERFC, the Corps has up-to-date forecast data to make the following days' release decisions.

6-02. Flood Condition Forecasts. During flood conditions, forecasts are made for two conditions: rainfall that has already fallen, and for potential rainfall (or expected rainfall). Decisions can be made on the basis of known events and *what if* scenarios. The Water Management Section prepares forecasts and receives the official forecasts from the SERFC.

a. <u>Requirements</u>. Accurate flood forecasting requires a knowledge of antecedent conditions, rainfall and runoff that has occurred, and tables or unit hydrographs to apply the runoff to existing flow conditions. Predictive QPF data are needed for reviewing what if scenarios. Six-hour unit hydrographs for several sub-basins around the Carters Project are shown on Plate 6-1. The historical data for inflow, outflow, and pool curves for Carters Lake from July 1975 through December 2010 are shown on Plates 6-2 through 6-7.

b. <u>Methods</u>. In determining the expected inflow into the Carters Lake, it is necessary to forecast the flows of the Coosawattee River above Carters Dam. Runoff or rainfall excess for the area is estimated using the seasonal correlation values shown in Table 6-1, depending on antecedent conditions. For very dry conditions, initial runoff can be near zero and then increase as rainfall continues. During wet conditions, most of the rainfall appears as runoff into the lake. The rainfall excess is distributed over the area by using the unit hydrograph shown in Table 6-2. During the next several hours and days, the observed inflow is compared to the forecasts and adjustments are applied. Additional rainfall/runoff is accumulated with the continuing forecasts.

The Corps provides a link to the NWS website so that the Water Management Section, the affected county emergency management officials, and the public can obtain this vital information in a timely fashion. When hydrologic conditions exist so that all or portions of the ACT Basin are considered to be flooding, existing Corps streamflow and short and long-range forecasting runoff models are run on a more frequent, as-needed basis. Experience demonstrates that the sooner a significant flood event can be recognized and the appropriate release of flows scheduled, an improvement in overall flood risk management can be evacuated following the event and as downstream conditions permit to provide effective flood risk management. Flood
risk management carries the highest priority during significant runoff events that pose a threat to human health and safety. The accumulation and evacuation of storage for the authorized purpose of flood risk management is accomplished in a manner that will prevent, insofar as possible, flows exceeding those which will cause flood damage downstream. During periods of significant basin flooding, the frequency of contacts between the Water Management Section and SERFC staff are increased to allow a complete interchange of available data upon which the most reliable forecasts and subsequent project regulation can be based.

Carters is located about 72 river miles above the primary damage points at Rome, Georgia, and 17.9 river miles above Resaca, Georgia. The forecasting procedure requires routing Carters releases and adding the local runoff at Rome, and Resaca, Georgia. Forecasting stage at Rome, Georgia, is further complicated by being located at the junction of the Etowah and Oostanaula Rivers. Flood events lasting several days produce double flood peaks, and at times, the two rivers are at different water surface elevations. The first peak at Rome, Georgia, is a result of runoff in the Etowah River Basin. Allatoona Lake controls runoff from 1,122 square miles or about 61 percent of the Etowah River Basin. Releases from the Allatoona Project take approximately 12 hours to reach Rome, Georgia. The area above Carters Lake is 374 square miles or about 17 percent of the Oostanaula River Basin. Releases from Carters take about 32 hours to reach Rome, Georgia. Releases from Carters are typically timed until after the first peak at Rome from the Etowah River has receded.

In determining the expected inflow into Carters Lake, current conditions must be examined. The runoff from rainfall varies significantly depending on antecedent conditions. For very dry conditions, initial runoff can be near zero and then increase as rainfall continues. During wet conditions, most of the rainfall appears as runoff into the lake. During the next several hours and days, the observed inflow is compared to the forecasts and adjustments are applied. Additional rainfall/runoff is accumulated with the continuing forecasts. Table 6-1 and Figure 6-1 are used as a guide to estimate runoff and its impact on Carters Lake. This runoff value is applied to the unit hydrograph in Table 6-2 and added to the present inflow. Table 6-2 presents unit hydrographs for Carters Dam, Carters Reregulation Dam, Redbud, Tilton, Resaca, and flows from the Oostanaula River at Rome. Outflow from the Carters Project is determined at the Reregulation Dam. A combination of local flows, generation, and pump-back determines the outflow from the Reregulation Dam. During the next several hours and days, the observed inflow is compared to the forecasts and adjustments are applied. Additional rainfall/runoff is accumulated with the continuing forecasts.

		Runoff - Etowah Basin 0 0.20 0.4 0.6 0.8 0.00 0.10 0.30 0.05 0.07 0.12 0.16 0.20 0.24 0.37 0.37 0.44 0.51 0.58 0.66 0.75 0.84 0.53 1.02 1.14 1.27 1.44 1.62 1.80 1.99 2.16 2.34 2.52 2.70 2.88 3.06 3.26 3.46 3.66 3.86 0.00 0.01 0.02 0.04 0.00 0.08 0.10 0.13 0.16 0.24 0.30 0.36 0.42 0.47 0.53 0.59 0.67 0.72 0.77 0.83 0.90 0.97 1.05 1.14 1.22 1.32 1.43 1.56 1.68 1.80 1.94 2.08 2.22 2.36 0.05 0.07 0.			n		Runoff - Oostanaula Basin					
	Rainfall	0	0.20	0.4	0.6	0.8	Rainfall	0	0.2	0.4	0.6	0.8
	0	0.00	0.10	0.30	0.05	0.08	0	0.00	0.04	0.90	0.15	0.21
	1	0.12	0.16	0.20	0.24	0.30	1	0.28	0.36	0.44	0.54	0.64
	2	0.37	0.44	0.51	0.58	0.66	2	0.74	0.84	0.96	1.08	1.22
Wet	3	0.75	0.84	0.53	1.02	1.14	3	1.37	1.52	1.67	1.81	1.97
oonanion	4	1.27	1.44	1.62	1.80	1.98	4	2.12	2.27	2.41	2.56	2.71
	5	2.16	2.34	2.52	2.70	2.88	5	2.85	3.00	3.15	3.30	3.45
	6	3.06	3.26	3.46	3.66	3.86	6	3.60	3.75	3.89	4.04	4.19
		-	1	-	-	-			1	1	-	
	0	0.00	0.01	0.02	0.04	0.06	0	0.00	0.03	0.06	0.08	0.11
	1	0.08	0.10	0.13	0.16	0.20	1	0.14	0.18	0.22	0.26	0.30
	2	0.24	0.30	0.36	0.42	0.47	2	0.36	0.40	0.44	0.50	0.58
Normal condition	3	0.53	0.59	0.67	0.72	0.77	3	0.65	0.73	0.81	0.90	0.98
	4	0.83	0.90	0.97	1.05	1.14	4	1.07	1.14	1.21	1.29	1.38
	5	1.22	1.32	1.43	1.56	1.68	5	1.46	1.56	1.67	1.80	1.92
	6	1.80	1.94	2.08	2.22	2.36	6	2.04	2.18	2.32	2.48	2.60
			I						n	n		I
	0	0.00	0.00	0.01	0.02	0.04	0	0.00	0.02	0.04	0.05	0.06
	1	0.05	0.07	0.08	0.09	0.11	1	0.08	0.10	0.12	0.14	0.16
_	2	0.13	0.15	0.18	0.20	0.23	2	0.18	0.20	0.23	0.27	0.32
Dry condition	3	0.25	0.28	0.31	0.34	0.37	3	0.36	0.44	0.50	0.57	0.64
condition	4	0.40	0.43	0.46	0.49	0.52	4	0.72	0.80	0.88	0.96	1.04
	5	0.56	0.60	0.64	0.69	0.75	5	1.12	1.20	1.29	1.37	1.45
	6	0.82	0.90	0.98	1.06	1.14	6	1.54	1.60	1.70	1.76	1.86

Table 6-1. Rainfall - Runoff Relationship for Basin above Rome, Georgia

6-hour unit hydrographs in Etowah River Basin											
	Co	osawattee River		Conasa	uga - Oostanau	ıla Rivers					
	Carters Main Dam (02381400)	Carters Reregulation Dam (02382400)	Redbud 02383500)	Tilton (02387000)	Resaca (02387500)	Rome (02388525)					
Area between gages (square miles)	374	146	311	687	84	547					
l ime in hours			Flow in	n cfs							
6	1740	960	2470	190	1810	820					
12	5900	3100	7740	690	2800	2170					
18	9050	4190	9830	1360	1500	4200					
24	8260	3290	7090	2120	780	6400					
30	5530	1990	3940	2910	400	8040					
36	3550	1200	2190	3710	210	8160					
42	2280	720	1220	44'60	110	6990					
48	1470	440	680	5050	60	5390					
54	940	260	380	5420	30	3880					
60	610	160	210	5590		2720					
66	390	100	120	5560		1920					
72	250	60		5300		1370					
78	160	40		4730		990					
84	100			4020		720					
90				3410		520					
96				2880		370					
102				2440		270					
108				2070		200					
114				1750		150					
120				1480		120					
126				1250		90					
132				1060		60					
138				900		30					
144				760							
150				640							
156				550							
162				460							
168				390							
174				330							
180				280							
186				240							
192				210							
198				180							
204				150							
210				120							
216				100							
222				80							
228				60							

Table 6-2. 6-hour Unit Hydrographs in Oostanaula River Basin



Figure 6-1. Rainfall Runoff versus Expected Pool Elevation

c. <u>Downstream Forecasts</u>. In addition to locations below Carters Dam, it is important to know conditions in the Etowah River Basin. Table 6-3 presents unit hydrographs for the Allatoona Dam, Cartersville, Kingston, and Etowah River at Rome. The values from Table 6-3 can be applied to the Rainfall - Runoff Relationship from Table 6-1.

6-03. Conservation Purpose Forecasts. Forecasts for conservation operations are accomplished similarly to flood condition forecasts.

a. <u>Requirements</u>. Conservation requirements are the same as for flood conditions with the added need to respond to the basin-wide drought plan. Existing basin conditions and expected inflows are needed for meeting the water control plan.

b. <u>Methods</u>. The Water Management Section prepares five-week inflow and lake elevation forecasts weekly based on estimates of rainfall and historical observed data in the basin. These projections assist in maintaining system balance and providing project staff and the public lake level trends based on the current hydrology and operational goals of the period. In addition, the Water Management Section provides weekly hydropower generation forecasts based on current power plant capacity, latest hydrological conditions, and system water availability.

6-04. Long-Range Forecasts. During normal conditions, the long-range outlook produced by the Corps is a five-week forecast. For normal operating conditions, a forecast longer than that incorporates a greater level of uncertainty and less reliability. In extreme conditions, three-month and six-month forecasts can be produced on the basis of observed hydrology and comparative percentage hydrology inflows into the ACT Basin. One-month and three-month outlooks for temperature and precipitation produced by the NWS Climate Prediction Center are used in long-range planning for prudent water management of the ACT System.

6-hour unit hydrographs in Etowah River basin											
	Allatoona (02394000)	Cartersville (02394670)	Kingston (02395000)	Rome (02395980)							
Area between gages (square miles)	1,122	223	289	167							
Time in hours		Flow	ı in cfs								
6	15600	2600	1660	2860							
12	20000	4370	5110	5550							
18	17000	3640	6340	4320							
24	14000	3400	4980	2610							
30	11400	2920	3620	1580							
36	9100	2300	2620	960							
42	7100	1760	1900	570							
48	5550	1320	1380	350							
54	4300	920	1000	210							
60	3400	600	730	130							
66	2600	360	530	80							
72	2100	240	380	40							
78	1700	160	280								
84	1350	100	200								
90	1000	40	150								
96	800	10	110								
102	600		80								
108	500		60								
114	400										
120	300										
126	200										
132	1 50										
138	1 00										
144	70										
150	50										
156	20										

 Table 6-3.
 6-hour Unit Hydrographs in Etowah River Basin

6-05. Drought Forecast.

a. <u>Requirements</u>. Engineering Regulation (ER) 1110-2-1941, Drought Contingency Plans, dated 15 September 1981, called for developing drought contingency plans for all Corps' reservoirs. Drought recognition and drought forecast information can be used in conjunction with the drought contingency plan.

b. Methods. Various products are used to detect the extent and severity of basin drought conditions. One key indicator is the U.S. Drought Monitor. The Palmer Drought Severity Index is also used as a regional drought indicator. The index is a soil moisture algorithm calibrated for relatively homogeneous regions and may lag emerging droughts by several months. The Alabama Office of the State Climatologist also produces a Lawn and Garden Moisture Index for Alabama, Florida, Georgia, and South Carolina, which gives a basin-wide ability to determine the extent and severity of drought conditions. The runoff forecasts developed for both short and long-range time periods reflect drought conditions when appropriate. There is also a heavy reliance on latest ENSO (El Niño/La Niña-Southern Oscillation) forecast modeling to represent the potential impacts of La Nina on drought conditions and spring inflows. Long-range models are used with greater frequency during drought conditions to forecast potential impacts to reservoir elevations, ability to meet minimum flows, and water supply availability. A long-term, numerical model, Extended Streamflow Prediction developed by the NWS, provides probabilistic forecasts of streamflow on the basis of climatic conditions, streamflow, and soil moisture. Extended Streamflow Prediction results are used in projecting possible future drought conditions. Other parameters and models can indicate a lack of rainfall and runoff and the degree of severity and continuance of a drought. Models using data of previous droughts or a percent of current to mean monthly flows with several operational schemes have proven helpful in planning. Other parameters are the ability of Carters Lake to meet the demands placed on its storage, the probability that Carters Lake pool elevation will return to normal seasonal levels, the conditions at other basin impoundments, basin streamflows, basin groundwater table levels, and the total available storage to meet hydropower marketing system demands.

c. <u>Reference Documents</u>. The drought contingency plan for the Carters Project is summarized in Section 7-12 below. The complete ACT Drought Contingency Plan is provided in Exhibit D.

VII - WATER CONTROL PLAN

7.01. General Objectives. Carters Project is a multipurpose project authorized for flood risk management, hydropower, recreation, fish and wildlife conservation, navigation, water quality, and water supply. The Carters Project is a pumped-storage peaking facility. The Reregulation Dam serves three purposes: as a lower pool for the pumped storage operation, to reregulate peaking flows from Carters Lake to provide a more stable downstream flow, and to temporarily provide flood storage between elevation 677 to 696 feet NGVD29. The regulation plan seeks to balance the needs of all project purposes at the Carters Project and at other projects in the ACT Basin and is intended for use in day-to-day, real-time water management decision making and for training new personnel.

The Carters Project authorizing legislation (River and Harbor Act of 1945) did not specify allocations or priorities within conservation storage, and left it to the discretion of the Corps how to operate conservation storage to fulfill the authorized purposes of the Carters Project. Conservation purposes are not fundamentally in competition; Mobile District seeks to attain balanced operations to achieve all authorized purposes and take into account other considerations to the extent possible.

7-02. Constraints. The most significant problems at the project involve the swelling and fracturing of the concrete used in construction of the Reregulation Dam, which was caused by alkali aggregate reaction (AAR). Because of the AAR, cracking and displacement of the bridge across the Reregulation Dam spillway resulted in weakening of the bridge to the degree that it was considered unsafe to withstand the weight of the crane used to place stoplogs on the upstream face. However, under the American Recovery and Reinvestment Act of 2009, temporary repairs were made to the bridge to allow for a crane to be able to place the stoplogs.

Displacement of the abutment and intermediate pier at monolith D9 of the Reregulation Dam has resulted in the inability to raise gate number 4 fully. Operation of the gate is limited because there was difficulty in the past closing the gate once it was opened. Further efforts are currently underway to allow for full opening of all gates. This is considered a temporary problem.

In addition, pumping will discontinue when the reregulation dam pool falls below elevation 677 feet NGVD29.

Whenever the power head reaches 395 feet excessive vibration occurs in the hydropower units and pumping must be discontinued unless the reregulation pool is over 690 feet NGVD29, then the maximum head is 397 feet.

7-03. Overall Plan for Water Control

a. <u>General Regulation</u>. The water control regulation of the Carters Project is in accordance with the regulation schedule as outlined in the following paragraphs. The Corps regulates the Carters main reservoir and reregulation pool to provide for the authorized project purposes of the project. All authorized project purposes are considered when making water control regulation decisions, and those decisions affect how water is stored and released from the project. Deviations from the prescribed water control plan, which can occur due to planned or unplanned events as described in Paragraph 7-15, will be at the direction of the Water Management Section. Additionally, if communication between the District office and the dam is interrupted, the operator will follow an emergency operation schedule, Exhibit C *Instructions to*

the Damtenders for Water Control. The Reregulation Dam provides a minimum continuous flow of 240 cfs to the Coosawattee River.

b. <u>Conservation Pool</u>. The Carters Lake conservation storage pool was designed to provide the necessary capacity to store water for subsequent use to meet the multiple conservation purposes for which the project was constructed. The conservation pool elevation, shown on Plate 7-1, is the lake's normal maximum operating level for conservation storage purposes. If the elevation is higher than the conservation limit, the lake level is in the flood pool. Area-Capacity Curves for Carters Lake and the Reregulation pool, which indicate the amount of storage and the surface area of the lake for the complete range of possible pool elevations, are shown on Plate 7-2 and Plate 7-3.

c. <u>Guide Curves and Action Zones</u>. Multiple project purposes and water demands in the basin require that the Corps regulate the use of conservation storage in a balanced manner in an attempt to meet all authorized purposes, while continuously monitoring the climatological conditions to ensure that project purposes can at least be minimally satisfied during critical drought periods. The balanced water management strategy for Carters does not prioritize any project function but seeks to balance all project authorized purposes. A seasonal conservation pool regulation guide curve and conservation storage action zones have been developed to guide the water control management decisions in meeting the balanced strategy. Table 7-1 provides key elevations of the top of conservation pool and action zones. The action zones are shown on Plate 7-1.

1) A regulation guide curve for the Carters main pool has been prescribed to facilitate the water control regulation of the project. The guide curve defines the seasonal top of conservation storage water surface elevation. Water management operational decisions strive to maintain the pool elevation at the top of conservation elevation or at the highest elevation possible while meeting project purposes. Normally, the pool elevation will be lower than the guide curve as available conservation storage is utilized to meet project purposes except when storing flood waters or during conservative lake level regulation when drought conditions exist within the project watershed. Carters Lake is regulated between the minimum year-round conservation pool elevation of 1,072 feet NGVD29 and a seasonal maximum conservation pool elevation of 1,074 feet NGVD29 during 1 May to 1 November and 1,072 feet NGVD29 from 1 December to 1 April, with four week transition periods in April and November. The normal year-round operating range for the reregulation pool is 677 to 696 feet NGVD29.

2) The water control plan also establishes action zones within the conservation storage pool. The action zones are used to manage the lake at the highest level possible within the conservation storage pool while balancing the needs of all authorized purposes with water conservation as a national priority used as a guideline. Carters Lake conservation pool includes two action zones. These zones are used as a general guide to determine the minimum discharge release available from the Reregulation Dam. The action zones were based on the general ability of the project to meet seasonal environmental flows below the Reregulation Dam. Other factors or activities might cause the lakes to operate differently than the action zones described. Examples of the factors or activities include exceptional flood risk management measures; fish spawn operations; maintenance and repair of turbines; emergency situations such as a drowning or chemical spill; draw-downs because of shoreline maintenance; drought recovery; increased or decreased hydropower demand; and other circumstances. Carters Project is unique from other Mobile District projects in that the main dam pool level or zone does not often determine the hours of daily hydropower generation. This is due to the pumping capabilities from the Reregulation Dam. The following provides a general description of each zone.

Zone 1: Hydrologic conditions are likely to be normal to wetter than normal. Within Zone 1, a seasonally variable release will be made from the Reregulation Dam as shown in Figure 7-1.

Zone 2: Hydrologic conditions are likely to indicate severe drought conditions. Careful, long range analyses and projections of inflows, pool levels, and upstream and downstream water needs will be made when pool levels are in Zone 2. The seasonally-varying minimum flow is suspended, and a continuous minimum flow of 240 cfs is released from the Reregulation Dam.

Date	Elevation (ft N	IGVD29)
	Top of Conservation	Top of Zone 2
1 Jan	1,072	1,066
1 Apr	1,072	1,070
1 May	1,074	1,071
1 Sep	1,074	1,070
15 Oct	1,074	1,066
1 Nov	1,074	1,066
1 Dec	1,072	1,066
31 Dec	1,072	1,066

 Table 7-1. Top of Conservation and Action Zone Table for Carters Lake



Figure 7-1. Seasonal Reregulation Dam Releases

1) <u>Normal Operations</u>. Under normal flow conditions the main reservoir level is controlled by discharges through the generators. The Carters Project is operated by the "balance point method" to account for the composite storage in the Main Dam and Reregulation Dam. When the Main Dam and Reregulation Dam pools are "balanced", there is just enough water in the reregulation dam pool between its present elevation and elevation 677 feet NGVD29 to allow the pumping units to restore the main reservoir to the top of conservation

pool. In a balanced state it would be necessary to release all inflows into the project through the Reregulation Dam to maintain balance.

For example, if the reregulation pool were at elevation 685 feet NGVD29 and the main pool was at 1072.48 feet NGVD29 (in August), then they would be "in balance" as the reregulation pool would contain 4,950 acre-feet of storage above elevation 677 feet NGVD29 and this volume (4,950 acre-feet), would fill the main pool from elevation 1072.48 feet NGVD29 to 1074 feet NGVD29.

2) <u>Reregulation Dam</u>. The normal year-round operating range for the reregulation dam pool is 677 to 698 feet NGVD29. The pool level is managed by releases through the Reregulation Dam gates. Gate discharge capabilities are shown on Plates 7-4 and 7-5. Pumping ceases below elevation 677 feet NGVD29 but the storage between elevations 674 to 677 feet NGVD29 is available to provide a minimum flow of 240 cfs downstream over a two-day period. Whenever the power head reaches 395 feet excessive vibration occurs in the hydropower units and pumping must be discontinued unless the Reregulation Pool is over 690 feet NGVD29, then the maximum head is 397 feet. Reductions in Reregulation Dam releases should not exceed 400 cfs in any four-hour period to mitigate erosion along the stream banks of farmlands downstream.

7-04. Standing Instructions to Damtender. During normal operations, the powerhouse operators will operate the Carters Project in accordance with the daily hydropower schedule. Any deviation from the schedule must come through the Water Management Section. Normally, flood risk management instructions are issued by the Water Management Section in the Mobile District Office. However, if a storm of flood-producing magnitude occurs and all communications are disrupted between the Mobile District and the powerhouse operators, the operators will follow instructions in Exhibit C, Standing Instructions to the Damtender for Water Control.

7-05. Flood Risk Management. Operation of the Carters Project for flood risk management is in accordance with instructions issued by the Water Management Section in the Mobile District Office, and releases depend on the Carters Main Dam and Reregulation Dam pool levels and forecasted inflows. Flood risk management operations at the Carters Project utilize storage in both the main dam and Reregulation Dam. Releases of stored flood water from the Carters Dam will usually not be evacuated until the flood stage at the USGS "Oostanaula River near Rome, GA" (gage # 02388500) has receded or is expected to recede below flood stage.

The top of flood pool for the main dam is 1,099 feet NGVD29. The induced surcharge schedule will be followed once elevation 1,099 feet NGVD29 is reached. In the event that water must be evacuated from the main dam during a flood (such as during induced surcharge operation), the hydropower units will be used first. Discharge through the emergency spillway or emergency sluice should be considered a last resort due to potential erosion and water quality issues that could arise as a result of their use. Therefore it is extremely important that the hydropower units be consistently available during high inflow periods. The Reregulation Dam pool is also used for temporary flood storage from elevation 677 to 696 feet NGVD29, with elevation 696 feet NGVD29 allowing a two-foot reaction period, in the case of a fast rising pool, before reaching the maximum storage elevation of 698 feet NGVD29. If the Reregulation Dam pool is forecast to reach elevation 696 feet NGVD29, pumping operations may be used to stabilize the Reregulation Dam pool instead of increasing releases through the Reregulation Dam gates. The maximum total discharge thru the two pumpback units is 7,470 cfs at a total head of 385 feet. A discharge rating table for a pump-turbine unit is shown on Plate 7-6.

The gated spillway for the Carters Reregulation Dam was designed to pass the standard project flood (SPF) of peak inflow 90,400 cfs without the headwater overtopping the dam and without exposing the structures to damage from high velocity flow or undesirable current patterns. The earth dikes have their top elevation at 703 feet NGVD29, which would provide a five-foot freeboard above the maximum reregulation pool level of 698 feet NGVD29. The top of the earth dikes would be subject to overtopping only by floods having a peak inflow about 30 percent great than the SPF (reference Carters Dam, Design Memorandum No. 15, Gated Spillway for Reregulation Dam, dated August 1966).

In flood conditions the balance point method of operation will be discontinued. During the early stages of a flood event, the hydropower generation schedule from main dam and outflows from the Reregulation Dam are planned (on the basis of forecasts) to control, or limit, the peak outflow as the flood develops. The inflow and reservoir levels will be monitored continuously along with stages at the USGS streamgage 02387500 at Resaca on the Oostanaula River, and the USGS streamgage 02388500 near Rome on the Oostanaula River. The Carters Project will be operated to minimize flooding at these gages. The Flood Stage (FS) is established by the NWS River Forecast Center and currently for Resaca gage is 18 feet and Rome gage 25 feet. In order to minimize backwater flooding at Tilton on the Conasauga River, normally, evacuation of flood water from the Carters Project will not be made until after the Conasauga River has peaked at Tilton. Releases will also be coordinated with those from Allatoona to minimize flooding in the Rome area. Normally, evacuation of flood storage from Carters will not occur until the stage at the Rome gage is below FS.

Flood evacuation will normally extend over a period of about one to two weeks, until the pools are within one foot of balance. The normal (non-flood) operating plan will then go into effect. When the Main Dam and Reregulation Dam pools approach the balance point daily power declarations from the main dam and discharges from the Reregulation Dam will be reduced slowly.

Bankfull is defined as 5,000 cfs year round. Normally, the ramp down rate for reregulation flows is 400 cfs every six hours to mitigate erosion along stream banks of farmlands downstream. However, under certain conditions the Water Management Section in the Mobile District Office may depart from this ramp down rate.

a. <u>Induced Surcharge Schedule</u>. If the main dam pool rises above elevation 1,099 feet NGVD the induced surcharge schedule shown in Table 7-2 (see page T7-1) will be followed. The Water Management Section could issue other instructions if current forecasts indicate a need. The plan is not dependent on downstream stages at Resaca or Rome, Georgia, but has been developed to provide optimum protection for the integrity of the dam.

The required outflow would be discharged through the turbines up to their capacity, and then any additional discharges required would be made through the emergency gated spillway following the schedule in Table 7-2 and Table 7-3. Discharges through the low-level sluice would be used in addition to the gated spillway only as a last resort. The low level sluice discharge rating is shown in Table 7-4. As of the date of this report, neither the low level sluice nor the emergency gated spillway has ever been used.

The surcharge outflow will be adjusted each hour on the basis of the average inflow for the preceding three hours and the current reservoir elevation. Gate settings will not be reduced as long as the pool is rising. The maximum peak outflow will be maintained until the main pool recedes to 1,099.00 feet NGVD29. Outflow will then be reduced to the inflow or 5,000 cfs, whichever is greater. Once the inflow has dropped to 5,000 cfs or lower, surcharge operations

will cease. The spillway gates will be operated in accordance with the gate regulation schedule to ensure that the top of the gates remain out of the water.

Carters Lake contains 89,191 acre-feet of flood risk management storage space between pool levels 1,074 and 1,099 feet NGVD29 in which flood water is stored and later released in moderate amounts to prevent downstream flooding. Since the beginning of operations, the maximum one-day inflow was 22,498 cfs which occurred on 16 February 1990. The observed maximum pool elevation was 1,099.16 feet NGVD29 on 8 April 1977.

Table 7-3. Emergency Spillway Discharge Rating for Carters Main Dam

EMERGENCY GATED SPILLWAY DISCHARGE RATING IN CFS (ALL FIVE GATES OPEN TO INDICATED SETTING)

MAIN POOL ELEVATION IN FEET NGVD 29

OPEN IN FEET	1099	1100	1101	1102	1103	1104	1105	1106	1107	1108
0.5	2780	2830	2870	2920	2960	3010	3050	3100		
1.0	5570	5670	5760	5850	5950	6030	6120	6210		
2.0	11140	11340	11530	11720	11900	12080	12260	12440	12610	
4.0	22260	22660	23060	23450	23830	24200	24570	24940	25300	25650
6.0	33250	33880	34490	35090	35680	36270	36840	37400	37960	38510
8.0	44110	44970	45810	46640	47460	48260	49050	49820	50590	51340
10.0	54730	55840	56930	58000	59050	60080	61100	62100	63080	64050
13.0	70300	71820	73310	74770	76210	77610	79000	80350	81690	83000
16.0	85400	87380	89320	91210	93070	94880	96670	98420	100150	101840
20.0	104290	106950	109550	112090	114570	117000	119380	121710	124000	126250
24.0	121700	125150	128520	131800	135000	138120	141180	144170	147100	149970
28.0	131200	139000	146070	150210	154240	158170	162010	165750	169410	173000
32.0			147000	155100	163500	172000	180500	187170	191700	196120
36.0								189000	197700	206500

Table 7-4. Low Level Sluice Discharge Rating for Carters Main Dam

(FOR BOTH GATES OPEN TO INDICATED SETTING)

	MAIN POOL ELEVATION IN FEET NGVD29															
	800	820	840	860	880	900	920	940	960	980	1000	1020	1040	1060	1080	1100
OPEN IN							סופכו									
FEEI							DISCI		N CF3							
0.5	257	288	316	343	367	390	411	431	451	469	487	505	521	538	553	569
1.0	514	577	633	685	734	779	822	862	901	939	974	1009	1042	1075	1106	1137
1.5	770	864	949	1027	1099	1167	1232	1293	1351	1403	1460	1512	1562	1611	1658	1704
2.0	1026	1151	1264	1368	1464	1555	1640	1721	1799	1874	1945	2014	2080	2145	2208	2269
2.5	1288	1446	1588	1719	1840	1954	2062	2163	2261	2354	2444	2531	2615	2696	2775	2852
3.0	1554	1744	1915	2073	2219	2357	2486	2609	2727	2840	2948	3052	3152	3252	3347	3440
3.5	1808	2031	2230	2414	2584	2743	2892	3038	3175	3306	3462	3554	3672	3787	3897	4004
4.0	2062	2315	2541	2752	2945	3128	3300	3464	3620	3770	3914	4053	4187	4317	4443	4566
4.5	2329	2613	2871	3107	3327	3532	3728	3912	4089	4258	4420	4577	4728	4875	5015	5157
5.0	2597	2914	3202	3465	3708	3938	4156	4363	4558	4747	4928	5104	5273	5439	5595	5749
5.5	2882	3238	3553	3846	4115	4372	4615	4843	5062	5272	5473	5666	5854	6037	6213	6385
6.0	3173	3560	3910	4231	4530	4810	5079	5331	5570	5801	6023	6237	6444	6644	6838	7027
6.5	3444	3865	4245	4594	4917	5221	5512	5787	6048	6297	6539	6770	6996	7212	7422	7628
7.0	3714	4170	4578	4953	5304	5633	5947	6242	6523	6794	7053	7303	7544	7779	8007	8228
7.5	4006	4498	4937	5345	5722	6077	6416	6735	7039	7329	7608	7873	8140	8394	8639	8879
8.0	4300	4825	5302	5737	6141	6522	6890	7230	7555	7868	8169	8459	8738	9009	9273	9529
8.5	4592	5156	5667	6129	6562	6968	7361	7723	8075	8406	8728	9038	9337	9626	9907	10181
9.0	4887	5489	6025	6521	6981	7409	7831	8220	8592	8947	9289	9615	9933	10242	10540	10832
9.5	5126	5755	6318	6838	7318	7774	8214	8622	9009	9383	9740	10085	10418	10741	11056	11363
10.0	5360	6016	6606	7150	7653	8125	8571	9016	9421	9810	10186	10544	10895	11232	11562	11884

7-06. Recreation. Recreational activities are best served by maintaining a full conservation pool. Lake levels above top of conservation pool invade the camping and park sites. When the lake recedes several feet below the top of conservation pool access to the water and beaches becomes limited. Water management personnel are aware of recreational effects caused by reservoir fluctuations and attempt to maintain reasonable lake levels, especially during the peak recreational use periods, but there are no specific requirements relative to maintaining recreational levels. Other project functions usually determine releases from the dam and the resulting lake levels.

The effects of the Carters Project water control operations on recreation facilities and use at Carters Lake are described as impact levels - Initial Impact Level, Recreation Impact Level, and Water Access Limited Level. The impact levels are defined as pool elevations with associated effects on recreation facilities and exposure to hazards within the lake. The following are general descriptions of each impact level for Low Water Conditions.

a. <u>Initial Impact Level</u>. The Initial Impact Level is defined at lake elevation 1,068 feet NGVD29. At this level impacts are first observed and there is adequate time available to notify the public should the lake level continue to drop. Action is taken to prevent more serious and lasting impacts. Swimming area buoys at Harris Branch Beach are set out at approximately elevation 1,068 feet NGVD29 when the lake is at normal summer pool level of 1,074 feet NGVD29. At the initial impact level, gate attendants issue oral messages and written warnings to the public.

b. <u>Recreation Impact Level</u>. The lake elevation of 1,060 feet NGVD29 is defined as the Recreation Impact Level. At this level action must be taken to prevent significant impacts from occurring. At the level of 1,060 feet NGVD29, the dangers to those participating in water based recreation activities would increase due to hazardous conditions. Steps are taken to alert the marina staff and public of existing dangers. Woodring Campground and Doll Mountain Day Use boat ramps are closed to the public when water level is below 1,060 feet NGVD29. At elevation 1,060 feet NGVD29, the Harris Branch Beach is closed. The designated swimming area buoys are completely out of the water and cannot be moved.

c. <u>Water Access Limited Level</u>. The lake elevation of 1,055 feet NGVD29 is defined as the Water Access Impact level. At this elevation, public access to the water is severely limited. Action is taken to retain this limited access. If navigational hazards appear, they will be temporarily marked with buoys or signs for boater safety. Marina slips are still usable, but dock walkways slope severely from the shoreline. At elevation 1,055 feet NGVD29, Ridgeway boat ramp, Woodring Branch day use area boat ramp and damsite boat ramps are closed.

The water control plan takes the effects on recreation facilities into account in developing action zones for Carters Lake. In dry periods, the lake will often drop to or below the impact levels and Water Management personnel will keep the Operations Project Manager informed of projected pool levels through the district's weekly water management meetings. The Operations Project Manager will be responsible for contacting various lakeshore interests and keeping the public informed of lake conditions during drawdown periods. The Operations Project Manager will close beaches and boat ramps as necessary, patrol the lake, and mark hazards and perform other necessary tasks to mitigate the effects of low lake levels.

7-07. Water Quality. The Corps operates the project with the objective of maintaining water quality standards while accepting operational and physical constraints that may limit the ability to do so. Because most water quality concerns occur during periods of low flow, usually during summer and early fall when there is greater stress on biological resources and wastewater

discharge assimilation requirements, establishing a continuous minimum release of water is an important consideration. Because of the existence of the reregulation dam and the pump back operation previously discussed, minimum flows are considered from the reregulation dam, rather than from the main dam.

Continuous minimum flows from the Carters Project are provided depending on the Action Zone in which the lake level is in, previously discussed in Section 7-03. When in Action Zone 1, a varying monthly flow ranging from 250-865 cfs is provided as shown in Figure 7-1. When in Action Zone 2, the minimum flow of 240 cfs is provided, regardless of month.

The pump back operation associated with the project allows the flexibility of providing the continuous minimum flow by using the four large turbine-generator units, two of which are capable of pumping. The existence of the reregulation pool allows smoothing of downstream releases and avoids high-pulse flows in many cases.

7-08. Fish and Wildlife. The Carters Lake presents a unique problem to the management of fishery resources within the lake as well as in the tailwaters. Due to the type of project (pump storage), the depth of the reservoir (average depth of about 380 feet, maximum depth of 410 feet), and the makeup of fish populations occurring within the watershed prior to impoundment, a situation exists unlike that anywhere else within the District. Because of the demands and the nature of other project purposes, regulation of the project for fish and wildlife is not possible. However, in consultation with the USFWS the Corps has adopted specific seasonal minimum flows, varying monthly over a range from 240 to 865 cfs March and December. Figure 7-1 summarizes the monthly minimum flows recommended by the USFWS for the Coosawattee River below Carters Reregulation Dam for each month of the year.

7-09. Water Supply. Under the authority of the Water Supply Act of 1958, the Corps allocated storage in Carters Lake in 1991 for municipal and industrial water supply by entering into a storage contract (Contract Number DACW01-9-91-481) with the city of Chatsworth, Georgia. The contract provides for the use of an undivided 0.61 percent (estimated to contain 818 acrefeet after adjustment for sediment deposits) of the conservation storage space between elevations 1,022 - 1,072 feet NGVD29 (134,900 acre-feet) for water supply. This amount of storage stated in the contract was estimated, at the time the contract was executed, to yield 2.0 mgd during the critical drought, i.e., during the worst drought on record at the time the contract was executed. The severity and frequency of droughts change over time, however, and more recent storage-yield analysis by the Corps has indicated that the estimated yield of Carters Lake storage has decreased. For the purpose of managing water supply storage, the Mobile District has employed a systematic storage accounting methodology that tracks multiple storage accounts, applying a proportion of inflows and losses (e.g. evaporation), as well as direct withdrawals by specific users, to each account. The amount of water that may actually be withdrawn is ultimately dependent on the amount of water available in storage, which will naturally change over time.

The necessary data to determine water supply storage availability is received daily, with computations performed weekly during normal conditions, and daily under extreme drought conditions. This accounting is especially critical during drought, when available water supply storage is reduced and conservation measures or alternative sources may be necessary. The formula used to calculate water supply storage is shown below:

Ending Storage = Beginning Storage + Inflow Share – Loss Share – User's Usage. (with constraint that "Ending Storage" cannot be larger than User's total storage) The conservation pool is drawn down as water usage exceeds inflow. The entire pool is drawn down and the individual accounts are also drawn down at different rates based on their usage. Users will be notified on a weekly basis of the available storage remaining, once their storage account balance drops below 30 percent.

7-10. Hydroelectric Power. The Carters Project is a pumped storage project operated as a peaking plant for producing hydroelectric power. The term "peak generation" is defined as using the full plant capacity for generating hydroelectric power.

a. Except in the most unusual circumstances, reservoir releases required for conservation or flood risk management operations will be used to produce hydropower. Such production is normally scheduled during peak energy demand hours throughout the week. The historical Average Monthly Hydroelectric Power Generation is shown in Table 7-5. The typical operations for non-flood conditions are illustrated on Plates 7-7 and 7-8.

b. Each week, the Water Management Section makes a forecast of expected inflows into the Carters Project. On the basis of that forecast, the present pool elevation, downstream requirements, and other pertinent needs, the Water Management Section determines the volume of water to be released and the corresponding hydropower available to be generated. That energy is scheduled by the receiving utility throughout the following week. There could be needs for certain timing of releases, but in general the utility makes the schedule and generation is spread across the week during the peak hours. The Water Management Section constantly monitors climatic conditions and can adjust the volume of hydropower available daily. Energy is marketed to the government's preference customers under terms of contracts negotiated and administered by SEPA. Those declarations, which are designed to keep the pools within the established seasonal and pondage limits, when practicable, are prepared by the Water Management Section of the Mobile District.

- c. Typical operation during non-flood conditions are as follows:
 - 1. Generation during the weekdays normally occurs between the hours of 6 a.m. and 10 p.m. In general, little or no generation occurs during the weekend. However, generation can occur on the weekends if warranted by power demands.
 - 2. Pumpback normally occurs between the hours of 10 p.m. and 6 a.m. during both the weekdays and weekends, but can occur outside this time period.
 - 3. The Reregulation Dam pool will likely reach both the maximum elevation 696 feet NGVD29 and the minimum elevation 677 feet NGVD29 at least once during the course of the week.
 - 4. The Reregulation Pool is at its peak late on Friday and is at its low-point early Monday a.m. because of the significant pumping over the weekend. The total downward fluctuation of the Reregulation Pool is up to 20 feet over a weekend.
 - 5. The main pool is at its high point early Monday a.m. and at its low-point mid to late week. The typical fluctuation of the main pool ranges from two to four feet during the week.

Power operations, including pumping, can continue throughout a flood event as long as storage space can safely be allocated in the main pool and pumping energy is available to keep the Reregulation Dam pool at or below 696 feet NGVD29. In addition, pumping will discontinue when the Reregulation Dam pool falls below 677 feet NGVD29 or to the minimum elevation necessary to maintain the constant discharge downstream to insure an orderly and timely evacuation of stored flood waters.

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Min	Max	Avg
1975							345	375	393	520	504	631	345	631	461
1976	871	639	1144	1082	876	810	1129	510	248	178	274	427	178	1144	682
1977	542	380	835	1957	779	1352	1455	1555	1313	1533	2127	1486	380	2127	1276
1978	2267	2173	1748	1009	1372	1552	720	1274	1126	601	614	601	601	2267	1255
1979	1551	1466	2287	1645	1133	1150	1276	1769	1079	1247	1354	1005	1005	2287	1414
1980	1442	1841	2252	3388	2279	2040	2311	2255	2267	1407	1081	1247	1081	3388	1984
1981	1608	1734	1167	1235	1051	1792	2189	1927	1764	1416	1218	1095	1051	2189	1516
1982	1526	1878	1633	1330	1618	1478	1676	1534	1472	1347	1480	2522	1330	2522	1624
1983	1225	1258	1450	2034	1801	1767	1772	1977	1436	1293	1577	2179	1225	2179	1648
1984	1362	1287	1949	1958	2148	1752	1124	1870	1099	1204	1610	1148	1099	2148	1543
1985	981	1353	1469	1216	1315	1571	1405	1511	1136	1256	1082	1148	981	1571	1287
1986	1106	1026	889	1045	1132	1218	1922	1431	1829	915	1286	1399	889	1922	1267
1987	1634	1375	1705	1428	1382	1511	1775	2000	1358	559	726	542	542	2000	1333
1988	564	667	910	752	572	1100	1199	1299	1176	610	566	775	564	1299	849
1989	1066	1016	1850	1188	1252	1414	1642	1240	801	1330	1227	1231	801	1850	1271
1990	1548	2632	2626	1054	816	405	541	601	464	469	369	443	369	2632	997
1991	664	404	899	1255	1230	516	619	716	761	587	413	374	374	1255	703
1992	602	566	1013	843	920	1746	1889	1867	874	424	1037	1600	424	1889	1115
1993	1366	682	906	797	765	1783	1858	1598	1567	1143	1468	989	682	1858	1243
1994	804	864	798	1629	756	1661	1514	1660	945	768	800	848	756	1661	1087
1995	891	1037	1118	667	837	1586	1532	1949	845	839	900	764	667	1949	1080
1996	781	1612	1057	1097	783	1273	1384	1488	638	719	527	861	527	1612	1018
1997	898	1123	1224	1057	1098	870	794	967	722	732	785	779	722	1224	921
1998	959	1483	1061	1383	842	775	717	1064	945	931	1193	1079	717	1483	1036
1999	913	883	1028	1002	1132	1198	1382	1178	1209	1343	1264	1193	883	1382	1144
2000	1305	973	818	848	1161	1047	1107	1323	1174	1144	1103	905	818	1323	1076
2001	834	1172	1217	1060	1085	1156	1073	1188	956	1035	1021	1030	834	1217	1069
2002	1033	1168	958	1199	1099	968	1088	1010	1014	996	812	964	812	1199	1026
2003	1080	982	928	576	1383	1061	1255	1277	1163	1204	1412	1193	576	1412	1126
2004	1455	1418	1232	1236	1267	1226	1358	1535	1420	1111	930	1405	930	1535	1299
2005	1062	889	1136	1191	1119	1505	1286	1429	1197	1000	1047	1005	889	1505	1156
2006	1165	1197	1266	1161	1295	1406	1385	1246	1098	1032	914	908	908	1406	1173
2007	1114	1132	1218	1105	1267	1292	1834	2084	2014	1728	1343	1343	1105	2084	1456
2008	1618	1416	1128	1070	1481	1544	961	2063	1861	1618	1450	1459	961	2063	1472
2009	1524	1505	1385	1345	1371	1624	2033	1861	1804	1399	1235	1402	1235	2033	1541
2010	1156	1775	1631	2103	1541	1659	2448	1827	1990	1606	1135	1274	1135	2448	1679
2011	1459	1350	1674	1115	1656	1467	1383	2133	1817	1432	1111	1187	1111	2133	1482
2012	1495	1225	1081	1011	1286	1475	1207	1600	1486	1512	1279	1402	1011	1600	1338
2013	1360	1293	1396	1411	1596	1155	1618	1116	1110	1301	1001	1161	1001	1618	1293
Min	542	380	798	576	572	405	345	375	248	178	274	374	178	631	461
Max	2267	2632	2626	3388	2279	2040	2448	2255	2267	1728	2127	2522	1330	3388	1984
Avg	1180	1233	1318	1276	1224	1340	1417	1498	1241	1078	1073	1115	820	1827	1249

Table 7-5. Average Daily Hydroelectric Power Generation by Month (Megawatt Hours)

Performance curves for the pump back operation are shown on Plate 7-9. Performance curves for the conventional unit are shown on Plate 7-10. Performance curves for the pump-turbine unit are shown on Plate 7-11.

The Main Dam Discharge Rate-Tailwater relationship for Various Reregulation Pool elevations is shown on Plate 7-12. The Pumping Rate-Tailwater relationship for various reregulation pools is shown on Plate 7-13.

7-11. Navigation. Allatoona Dam and Carters Dam, while originally authorized to support downstream navigation, are not regulated for navigation purposes because they are distant from the navigation channel, and any releases for that purpose would be captured and reregulated by APC reservoirs downstream. Downstream navigation in the Alabama River benefits indirectly from the operation of the Allatoona and Carters Projects for the other authorized purposes.

7-12. Drought Contingency Plans. ER1110-2-1941, *Drought Contingency Plans*, dated 15 September 1981, called for developing drought contingency plans for Corps' reservoirs. For the Carters Project, the Corps will coordinate water management during drought with other federal agencies, private power companies, navigation interests, the states, and other interested state and local parties as necessary. Drought operations will be in compliance with the plan for the entire ACT Basin as outlined in Exhibit D, and summarized below. The plan includes operating guidelines for drought conditions and normal conditions.

In response to the 2006 - 2008 drought, Alabama Power Company (APC) worked closely with the State of Alabama to develop the APC draft *Alabama Drought Operations Plan* (*ADROP*) that specified operations at APC projects on the Coosa and Tallapoosa Rivers. The plan included the use of composite system storage, state line flows, and basin inflow as triggers to drive drought response actions. Similarly, in response to the 2006 - 2008 drought, the Corps recognized that a basin-wide drought plan must incorporate variable hydropower generation requirements from its headwater projects in Georgia (Allatoona and Carters), a reduction in the level of navigation service provided on the Alabama River as storage across the basin declines, and that environmental flow requirements must still be met to the maximum extent practicable.

Based upon experience gained during previous droughts, and in particular the 2006 - 2008 drought, a basin-wide drought plan composed of three components - headwater operations at Allatoona and Carters Projects in Georgia; operations at APC projects on the Coosa and Tallapoosa Rivers; and downstream operations at Corps projects below Montgomery, has been developed. The concept is graphically depicted in Figure 7-2 with the specifics shown on Table 7-6.

	ACT Basin Drought Plan											
Headwater Operations	APC Operations Downstream Operations											
Allatoona Carters	Weiss HN Henry Logan Martin Harris Lay RF Millers Henry Ferry Claiborne											
	Mitchell Jordan/Bouldin ^{Martin} Yates Thurlow											
<u>State of Georgia</u> <u>Drought Plan</u>	State of Alabama Drought Plan											

Figure 7-2. Schematic of the ACT Basin Drought Plan

	Jan	Feb	Mar	Apr	Мау	Ju	un	Jul	Aug	Sep	Oct	Nov	Dec	
e ^a t							Normal Op	erations				- -		
igh. /el					DIL 1: Low	Basin Inflov	vs or Low Co	omposite or	Low State L	ine Flow				
Lev				DIL 2: D	OIL 1 criteria	+ (Low Bas	in Inflows or	Low Comp	osite or Low	State Line	Flow)			
Re. D					DIL 3: Low	Basin Inflo	ws + Low Co	omposite + L	ow State Li	ne Flow				
	Normal	Operation: 2	2,000 cfs	4,000 ((8,000)	4,000 -	- 2,000			Normal C	peration: 2,	000 cfs		
er Flow ^b	Jor	dan 2,000 +	/-cfs	2	4,000 +/- cfs	6	6/15 Linear Ramp down	Jorc	lan 2,000 +/	'-cfs		Jordan 2,0	00 +/-cfs	
oosa Riv	Jordan	1,600 to 2,0	00 +/-cfs	2	2,500 +/- cfs	3	6/15 Linear Ramp down	Jordan 2,000 +/-cfs			Jordan 1,600 to 2,000 +/-cfs			
Ö	Jor	dan 1,600 +	/-cfs	Jo	rdan 1,600 i	to 2,000 +/-0	cfs	Jord	lan 2,000 +/	'-cfs	Jordan 2,000	1,600 to +/-cfs	Jordan 1,600 +/- cfs	
	Normal Operations: 1200 cfs													
r Flow ⁶	Gre 2 x Heflin (eater of: 1/2 Gage(Thurlo c	Yates Inflow ow Lake relea fs)	/ or ases > 350			1/2 Yates Inflow					1/2 Yates Inflow		
alla vei		Thurlow La	ake 350 cfs				1/2 Yate	s Inflow			Thurlow Lake 350 cfs			
Ta Ri		1	Maintain 400 (Thurlow I	cfs at Monto	gomery WT e 350 cfs)	P		Thur	ow Lake 35	0 cfs	Maintair (Thu	1 400 cfs at l rlow Lake re	Montgomery WTP elease 350 cfs)	
ď						Normal Op	eration: Nav	rigation or 70	Q10 flow					
na ov	4,200 cf	s (10% 7Q1	0 Cut) - Mon	tgomery		7Q′	10 - Montgor	mery (4,640	cfs)		R	educe: Full	– 4,200 cfs	
labar er FI	3,7	700 cfs (20%	6 7Q10 Cut)	– Montgome	ery	4,2	200 cfs (10%	5 7Q10 Cut)	- Montgom	ery	Red Mc	uce: 4,200 c ntgomery (1	cfs-> 3,700 cfs week ramp)	
AI Riv		2,00 Montg	0 cfs jomery			3,700 cfs Montgomery	/	4,200 cf	s (10% 7Q1 Montgomery	0 Cut) - ′	Red Mo	uce: 4,200 c htgomery (1	fs -> 2,000 cfs month ramp)	
Ę			No	ormal Opera	tions: Eleva	tions follow	Guide Curv	es as prescr	ibed in Lice	nse (Measu	red in Feet)			
ide rve atio					Corps V	ariances: As	Needed; F	ERC Varian	ce for Lake	Martin				
Gu Gu					Corps V	ariances: As	Needed; F	ERC Variand	ce for Lake	Martin				
Ē					Corps V	ariances: As	Needed; F	ERC Variand	ce for Lake	Martin				

Table 7-6. ACT Basin Drought Management Matrix

a. Note these are base flows that will be exceeded when possible.
b. Jordan flows are based on a continuous +/- 5% of target flow.
c. Thurlow Lake flows are based on continuous +/- 5% of target flow: flows are reset on noon each Tuesday based on the prior day's daily average at Heflin or Yates.
d. Alabama River flows are 7-Day Average Flow.

a. <u>Headwater Operations for Drought at Carters and Allatoona Projects</u>. Drought operations at Carters and Allatoona Projects consist of progressively reduced generation and discharges as pool levels decline. For instance, as Carters Lake pool level drops into Zone 2, minimum flows would be reduced from seasonal varying values to 240 cfs. However, due to pumback capability, the Carters pool will most likely return to full pool each year. When Allatoona Lake is operating in normal conditions (Zone 1 operations), hydropower generation would be zero to four hours per day. However, as the pool level drops to lower action zones during drought conditions, generation would be reduced to zero to two hours per day.

b. <u>Operations at APC Projects on the Coosa, Tallapoosa, and Alabama Rivers</u>. Under current operations, APC provides a combined minimum flow of 4,640 cfs (seven-day average) from the Bouldin, Jordan, and Thurlow Projects on the Tallapoosa and Coosa Rivers. The minimum flow target of 4,640 cfs was originally derived from the 7Q10 flow at Claiborne Lake of 6,600 cfs. Those flows were established with the understanding that if APC provided 4,640 cfs, the Corps and intervening basin inflow would be able to provide the remaining water to meet 6,600 cfs at Claiborne Lake. However, as dry conditions continued in 2007, water managers realized that, if the basin inflows from rainfall were insufficient, the minimum flow target would not likely be achievable. Therefore, in coordination with APC, drought operations for the middle reaches of the ACT Basin have been revised and are described below.

The ADROP served as the initial template for developing proposed drought operations for the APC Drought Operation Plan (APCDOP) and ACT Basin. APCDOP operational guidelines for the Coosa, Tallapoosa, and Alabama Rivers have been defined in a matrix, on the basis of a Drought Intensity Level (DIL). The DIL is a drought indicator, ranging from one to three. The DIL is determined on the basis of three basin drought criteria (or triggers). The DIL increases as more of the drought indicator thresholds (or triggers) occur. The APCDOP matrix defines monthly minimum flow requirements for the Coosa, Tallapoosa, and Alabama Rivers as a function of DIL and time of year. Such flow requirements are modeled as daily averages.

The combined occurrences of the drought triggers determine the DIL. Three intensity levels for drought operations are applicable to APC projects.

- DIL1 (moderate drought) one of three triggers occur
- DIL2 (severe drought) two of three triggers occur
- DIL3 (exceptional drought) all three triggers occur

The indicators used in the APCDOP to determine drought intensity include the following:

- Low basin inflow
- Low state line flow
- Low composite conservation storage

Each of the indicators is described in detail below.

The DIL is computed on the first and third Tuesday of each month. Once a drought operation is triggered, the DIL can only recover from drought condition at a rate of one level per period. For example, as the system begins to recover from an exceptional drought with DIL=3, the DIL must be stepped incrementally back to normal operations. In that case, even if the system triggers return to normal quickly, it will still take at least a month before normal operations can resume - conditions can improve only to DIL=2 for the next 15 days, then DIL=1 for the next 15 days, before finally returning to normal operations.

For normal operations, the matrix shows a Coosa River flow between 2,000 cfs and 4,000 cfs with peaking periods up to 8,000 cfs occurring. The required flow on the Tallapoosa River is a constant 1,200 cfs throughout the year. The navigation flows on the Alabama River are applied to the APC projects. The required navigation depth on the Alabama River is subject to the basin inflow.

For DIL=1, the Coosa River flow varies from 2,000 cfs to 4,000 cfs. On the Tallapoosa River, part of the year, the required flow is the greater of one-half of the inflow into Yates Lake and twice the Heflin USGS gage. For the remainder of the year, the required flow is one-half of Yates Lake inflow. The required flows on the Alabama River are reduced from the normal operation levels.

For DIL=2, the Coosa River flow varies from 1,800 cfs to 2,500 cfs. On the Tallapoosa River, the minimum is 350 cfs for part of the year and one-half of Yates Lake inflow for the remainder of the year. The requirement on the Alabama River is between 3,700 cfs and 4,200 cfs.

For DIL=3, the flows on the Coosa River range from 1,600 cfs to 2,000 cfs. A constant flow of 350 cfs on the Tallapoosa River is required. It is assumed an additional 50 cfs will occur between Thurlow Lake and the City of Montgomery's water supply intake. Required flows on the Alabama River range from 2,000 cfs to 4,200 cfs

In addition to the APCDOP, the DIL affects the navigation operations. During normal operations, APC projects are operated to meet the navigation flow target or 4,640 cfs flow. Once DIL is greater or equal to one, drought operations will occur, and navigation operations are suspended.

c. <u>Low Basin Inflow Trigger</u>. The total basin inflow needed for navigation is the sum of the total filling volume plus 4,640 cfs. Table 7-7 lists the monthly low basin inflow criteria. All numbers are in cfs-days. The basin inflow value is computed daily and checked on the first and third Tuesday of the month. If computed basin inflow is less than the value required, the low basin inflow indicator is triggered.

The basin inflow is the total flow above the APC projects excluding Allatoona Lake and Carters Lake. It is the sum of local flows, minus lake evaporation and diversions. Figure 7-3 illustrates the local inflows to the Coosa and Tallapoosa River Basin. The basin inflow computation differs from the navigation basin inflow, because it does not include releases from Allatoona Lake and Carters Lake. The intent is to capture the hydrologic condition across APC projects in the Coosa and Tallapoosa Basins.

d. Low State Line Flow Trigger. A low state line flow trigger occurs when the Mayo's Bar USGS gage measures a flow below the monthly historical 7Q10 flow. The 7Q10 flow is defined as the lowest flow over a seven-day period that would occur once in 10 years. Table 7-8 lists the Mayo's Bar 7Q10 value for each month determined from observed flows from 1949 – 2006. The lowest seven-day average flow over the past 14 days is computed and checked at the first and third Tuesday of the month. If the lowest seven-day average value is less than the Mayo's Bar 7Q10 value, the low state line flow indicator is triggered. If the result is greater than or equal to the trigger value from Table 7-8, the flow is considered normal, and the state line flow indicator is not triggered.

The term *state line flow* is used in developing the drought management plan because of the proximity of the Mayo's Bar gage to the Alabama-Georgia state line and because it relates to flow data upstream of the Alabama-based APC reservoirs. State line flow is used only as a

source of observed data for one of the three triggers and does not imply that *targets* exist at that geographic location. The APCDOP does not include or imply any Corps operation that would result in water management decisions at Carters Lake or Allatoona Lake.

Month	Coosa Filling Volume	Tallapoosa Filling Volume	Total Filling Volume	Minimum JBT Target Flow	Required Basin Inflow
Jan	628	0	628	4,640	5,268
Feb	626	1,968	2,594	4,640	7,234
Mar	603	2,900	3,503	4,640	8,143
Apr	1,683	2,585	4,269	4,640	8,909
May	248	0	248	4,640	4,888
Jun			0	4,640	4,640
Jul			0	4,640	4,640
Aug			0	4,640	4,640
Sep	-612	-1,304	-1,916	4,640	2,724
Oct	-1,371	-2,132	-3,503	4,640	1,137
Nov	-920	-2,748	-3,667	4,640	973
Dec	-821	-1,126	-1,946	4,640	2,694

 Table 7-7. Low Basin Inflow Guide (in cfs-days)



Figure 7-3. ACT Basin Inflows

Mawth	Mayo's Bar
wonth	(7Q10 In cfs)
Jan	2,544
Feb	2,982
Mar	3,258
Apr	2,911
May	2,497
Jun	2,153
Jul	1,693
Aug	1,601
Sep	1,406
Oct	1,325
Nov	1,608
Dec	2,043

Table 7-8. APC Drought Operations Plan State Line Flow Trigger

Note: Based on USGS Coosa River at Rome Gage (Mayo's Bar, USGS 02397000) observed flow from 1949 to 2006

e. <u>Low Composite Conservation Storage in APC Projects Trigger</u>. Low composite conservation storage occurs when the APC projects' composite conservation storage is less than or equal to the storage available within the drought contingency curves for the APC reservoirs. Composite conservation storage is the sum of the amounts of storage available at the current elevation for each reservoir down to the drought contingency curve at each APC major storage project. The reservoirs considered for the trigger are R. L. Harris Lake, H. Neely Henry Lake, Logan Martin Lake, Lake Martin, and Weiss Lake projects. Figure 7-4 plots the APC composite zones. Figure 7-5 plots the APC low composite conservation storage trigger.

If the actual active composite conservation storage is less than or equal to the active composite drought zone storage, the low composite conservation storage indicator is triggered. The computation is performed on the first and third Tuesday of each month, and is compared to the low state line flow trigger and basin inflow trigger.

f. <u>Operations for Corps Projects Downstream of Montgomery</u>. Drought operations of the Corps' Alabama River projects (R. E. "Bob" Woodruff Lake [Robert F. Henry Lock and Dam], and William "Bill" Dannelly Lake [Millers Ferry Lock and Dam]) will respond to drought operation of the APC projects. When combined releases from the APC projects are reduced to 4,640 cfs, the Corps' Alabama River projects will operate to maintain a minimum flow of 6,600 cfs below Claiborne Lake. When the APCDOP requires flows less than 4,640 cfs, the minimum flow at Claiborne Lake is equal to the inflow into Millers Ferry Lock and Dam. There is inadequate storage in the Alabama River projects to sustain 6,600 cfs, when combined releases from the APC projects are less than 4,640 cfs.

g. <u>Summary of Potential Drought Management Measures</u>. Management measures developed for ACT Basin-wide drought operations consist of three major components:

- Headwater operations at Allatoona Lake and Carters Lake in Georgia
- Operations at APC projects on the Coosa and Tallapoosa Rivers
- Operations at Corps projects downstream of Montgomery

7-13. Flood Emergency Action Plans. The Corps is responsible for developing Flood Emergency Action Plans for the ACT System. The plans are included in the Operations and Maintenance Manuals for each system project. Example data available include emergency contact information and flood inundation information.



Figure 7-4. APC Composite Zones



APC Composite Storage Trigger (Harris, Martin, Weiss, HN Henry, Logan Martin)

Figure 7-5. APC Low Composite Conservation Storage Drought Trigger

7-14. Other.

<u>Correlation with Other Projects</u>. Flood operations at Carters will be coordinated with Allatoona Dam to provide maximum flood protection at Rome, Georgia downstream. Flood releases from Carters will also be coordinated with the APC projects downstream. During lower flows and droughts the Carters Project releases will follow the basin-wide drought plan.

7-15. Deviation from Normal Regulation. The District Commander is occasionally requested to deviate from normal regulation. Prior approval for a deviation is required from the Division Engineer except as noted in subparagraph a below.

Deviation requests usually fall into the following categories:

a. <u>Emergencies</u>. Examples of some emergencies that can be expected to occur at a project are drowning and other accidents, failure of the operation facilities, chemical spills, treatment plant failures and other temporary pollution problems. Water control actions necessary to abate the problem are taken immediately unless such action would create equal or worse conditions. The Mobile District will notify the division office as soon as practicable.

b. <u>Declared System Emergency</u>. A Declared System Emergency can occur when there is a sudden loss of power within the electrical grid and there is an immediate need of additional power generation capability to meet the load on the system. In the Mobile District, a system emergency can be declared by the Southern Company or the Southeastern Power Administration's Operation Center. Once a system emergency has been declared, the requester will contact the project operator and request generation support. The project operator will then lend immediate assistance within the projects operating capabilities. Once support has been given, the project operator should inform the Mobile District Office immediately. The

responsibilities and procedures for a Declared System Emergency are discussed in more detail in Division Regulation Number 1130-13-1, *Hydropower Operations and Maintenance Policies*. It is the responsibility of the District Hydropower Section and the Water Management Section to notify South Atlantic Division Operations Branch of the declared emergency. The Division Operations Branch should then coordinate with SEPA, District Water Management, and the District Hydropower section on any further actions needed to meet the needs of the declared emergency.

c. <u>Unplanned Deviations</u>. Unplanned instances can create a temporary need for deviations from the normal regulation plan. Unplanned deviations may be classified as either major or minor but do not fall into the category of emergency deviations. Construction accounts for many of the minor deviations and typical examples include utility stream crossings, bridge work, and major construction contracts. Minor deviations can also be necessary to carry out maintenance and inspection of facilities. The possibility of the need for a major deviation mostly occurs during extreme flood events. Requests for changes in release rates generally involve periods ranging from a few hours to a few days, with each request being analyzed on its own merits. In evaluating the proposed deviation, consideration must be given to impacts on project and system purposes, upstream watershed conditions, potential flood threat, project condition, and alternative measures that can be taken. Approval for unplanned deviations, either major or minor, will be obtained from the Division Office by telephone or electronic mail prior to implementation.

d. <u>Planned Deviations</u>. Each condition should be analyzed on its merits. Sufficient data on flood potential, lake and watershed conditions, possible alternative measures, benefits to be expected, and probable effects on other authorized and useful purposes, together with the district recommendation, will be presented by letter or electronic mail to the South Atlantic Division for review and approval.

7-16. Rate of Release Change. Normally, the ramp down rate for Reregulation Dam flows is 200 cfs every six hours to mitigate erosion along stream banks of farmlands downstream. However, under certain conditions the Water Management Section in the Mobile District Office may adjust this ramp down rate.

Table 7-2. Surcharge Schedule for Carters Main Dam

			INFLOW IN	1000 CFS (AV	ERAGE FOR F	PREVIOUS 3 H	IOURS)					
POOL ELEV (FT NGVD 29)	20	30	40	50	60	70	80	90	100	120	140	160
, , , , , , , , , , , , , , , , , , ,				Required Sur	charge Releas	se in 1000 CFS	6					
1099.0				5.50	8.10	11.20	15.00	19.00	23.30	33.50	44.90	56.00
1099.1				5.90	8.30	11.40	15.30	19.40	23.70	34.20	45.20	56.40
1099.2				6.00	8.50	11.80	15.60	19.80	24.20	34.60	45.80	57.20
1099.3				6.20	8.90	12.00	16.00	20.20	24.40	35.10	46.30	57.80
1099.4				6.30	9.00	12.20	16.20	20.50	25.00	35.50	46.80	58.20
1099.5				6.40	9.10	12.50	16.50	20.80	25.30	36.00	47.20	58.80
1099.6				6.60	9.30	12.80	16.80	21.20	25.80	36.30	47.90	59.50
1099.7				7.00	9.80	13.10	17.20	21.50	26.20	37.00	48.30	60.20
1099.8				7.20	10.00	13.30	17.40	22.00	26.60	37.30	49.00	60.60
1099.9				7.30	10.20	13.60	17.70	22.30	27.10	37.90	49.40	61.20
1100.0				7.50	10.40	14.00	18.00	22.80	27.40	38.30	50.00	61.80
1100.1			0.00	7.70	10.60	14.20	18.30	23.00	28.00	38.80	50.40	62.30
1100.2			5.20	7.90	10.90	14.40	18.70	23.30	28.30	39.30	51.00	62.90
1100.3			5.30	8.00	11.10	14.80	19.00	23.80	28.80	39.90	51.40	63.50
1100.4			5.40	8.10	11.30	15.10	19.30	24.20	29.20	40.30	52.00	64.20
1100.5			5.50	8.30	11.60	15.30	19.80	24.50	29.70	40.80	52.50	64.60
1100.6			5.80	8.50	11.80	15.80	20.20	25.00	30.30	41.30	53.20	65.40
1100.7			6.00	8.90	12.00	16.10	20.30	25.30	30.60	41.80	53.50	66.00
1100.8			6.10	9.00	12.30	16.40	20.80	25.90	31.10	42.30	54.20	66.70
1100.9			6.20	9.10	12.60	16.70	21.10	26.30	31.60	42.90	54.90	67.30
1101.0			6.30	9.30	12.90	17.10	21.50	26.60	32.00	43.40	55.40	68.00
1101.1			6.50	9.80	13.20	17.30	21.90	27.00	32.30	43.90	56.00	68.80
1101.2			6.75	10.00	13.50	17.80	22.30	27.50	33.00	44.30	56.50	69.30
1101.3			6.90	10.30	13.80	18 20	22 60	28.00	33 30	45.00	57 10	70 10
1101.4		0.00	7 10	10.50	14 20	18 40	23.00	28 40	34 00	45 50	57 80	70.80
1101.5		5.00	7.20	10.90	14.40	18.80	23.30	28.90	34.40	46.20	58.30	71.40
1101.6		5.20	7.40	11.20	14.80	19.10	23.90	29.30	35.00	46.80	59.00	72.10
1101.7		5.30	7.75	11.30	15.00	19.50	24.20	30.00	35.40	47.30	59.80	72.90
						00.01						

Note: Discharge thru all four hydropower units at full pool is approximately 22.34

Table 7-2 (Cont.). Surcharge Schedule for Carters Main Dam

INFLOW IN 1000 CFS (AVERAGE FOR PREVIOUS 3 HOURS)

POOL												
ELEV (FT NGVD 29)	20	30	40	50	60	70	80	90	100	120	140	160
(11100020)		Required Surcharge Release in 1000 CFS										
									36.00	47.90	60.20	73.50
1101.9		5.80	8.10	11.90	15.90	20.30	25.20	31.00	36.40	48.40	61.00	74.30
1102.0		5.90	8.30	12.10	16.10	20.70	25.70	31.30	37.00	49.00	61.50	75.10
1102.1		6.00	8.80	12.40	16.40	21.20	26.20	32.00	37.50	49.70	62.30	75.90
1102.2		6.25	9.00	12.80	16.80	21.80	26.50	32.30	38.20	50.30	63.10	76.80
1102.3		6.40	9.20	13.00	17.10	22.10	27.00	33.00	38.80	51.00	63.80	77.40
1102.4		6.75	9.40	13.30	17.60	22.50	27.50	33.50	39.30	51.70	64.30	78.20
1102.5		7.00	9.80	13.80	18.00	23.00	28.00	34.00	39.80	52.20	65.20	79.00
1102.6		7.20	10.00	14.20	18.30	23.50	28.70	34.70	40.40	53.00	66.00	80.00
1102.7		7.30	10.20	14.40	18.80	24.00	29.00	35.20	41.00	53.60	66.80	80.60
1102.8	0.00	7.50	10.30	14.80	19.30	24.30	29.50	36.00	41.60	54.30	67.50	81.50
1102.9	5.00	7.80	10.80	15.00	19.80	25.00	30.20	36.30	42.30	55.20	68.30	82.30
1103.0	5.20	8.00	11.10	15.30	20.20	25.40	30.80	37.10	43.00	55.70	69.20	83.00
1103.1	5.30	8.25	11.30	16.00	20.50	26.10	31.30	37.80	43.70	56.30	70.00	84.00
1103.2	5.50	8.40	11.80	16.20	21.00	26.50	32.00	38.30	44.30	57.20	70.80	84.80
1103.3	5.80	9.00	12.20	16.60	21.50	27.00	32.50	39.20	44.90	58.00	71.70	85.80
1103.4	6.00	9.10	12.40	17.20	22.10	27.50	33.20	39.80	45.70	58.80	72.50	86.50
1103.5	6.25	9.40	12.80	17.50	22.50	28.10	33.80	40.40	46.30	59.80	73.50	87.30
1103.6	6.50	9.80	13.10	18.00	23.10	28.90	34.50	41.00	47.20	60.50	74.30	88.20
1103.7	6.75	10.10	13.30	18.30	23.70	29.40	35.20	41.80	48.00	61.20	75.20	89.10
1103.8	7.00	10.30	14.00	18.80	24.00	30.10	36.00	42.40	48.80	62.20	76.20	90.20
1103.9	7.25	10.75	14.30	19.30	24.70	30.80	36.80	43.30	49.30	63.00	77.20	91.00
1104.0	7.50	11.10	14.60	19.90	25.30	31.40	37.20	44.00	50.30	63.80	78.30	92.20
1104.1	8.00	11.40	15.10	20.20	25.90	32.00	38.20	44.80	51.00	64.90	79.20	93.20
1104.2	8.25	11.80	15.50	20.80	26.50	32.80	39.00	45.40	51.90	65.60	80.20	94.20
1104.3	8.50	12.25	16.20	21.40	27.10	33.20	39.70	46.30	52.80	66.60	81.30	95.20
1104.4	8.80	12.50	16.50	22.00	27.70	34.20	40.50	47.20	53.40	67.50	82.40	96.30
1104.5	9.10	13.00	17.00	22.50	28.50	35.00	41.30	48.00	54.30	68.80	83.30	97.50

Note: Discharge thru all four hydropower units at full pool is approximately 22.34

Table 7-2 (Cont.). Su	rcharge Schedule for	Carters Main Dam
-----------------------	----------------------	-------------------------

POOL ELEV (FT NGVD 29)	20	30	40	50	60	70	80	, 90	100	120	140	160
(Required S	Surcharge Rel	ease in 1000 (CFS					
1104.6	9.25	13.50	17.80	23.20	29.20	35.80	42.30	49.00	55.40	69.90	84.30	98.60
1104.7	10.00	14.00	18.10	24.00	30.10	36.40	43.10	50.00	56.20	71.00	85.50	99.80
1104.8	10.30	14.30	18.60	24.60	31.00	37.30	44.00	50.80	57.20	71.80	86.70	101.20
1104.9	10.70	15.00	19.30	25.30	31.70	38.20	45.00	51.80	58.30	73.20	87.80	102.50
1105.0	11.00	15.40	20.00	26.00	32.50	39.00	46.00	52.70	59.30	74.50	89.00	103.80
1105.1	11.70	16.10	20.90	26.60	33.50	40.00	46.80	54.00	60.30	75.50	90.20	105.20
1105.2	12.30	16.50	21.60	27.60	34.30	41.00	48.00	55.20	61.40	77.00	91.50	106.50
1105.3	13.00	17.25	22.30	28.50	35.50	42.00	49.00	56.30	62.50	78.30	92.60	108.20
1105.4	14.00	17.80	23.00	29.50	36.50	43.00	50.20	57.50	63.80	79.50	94.00	109.50
1105.5	14.60	18.30	24.00	30.50	37.70	44.30	51.50	59.00	65.20	81.00	95.50	111.20
1105.6	15.50	19.30	25.00	31.30	38.80	45.40	52.80	60.50	66.50	82.40	96.80	113.00
1105.7	16.80	20.50	26.00	32.50	40.20	46.50	54.30	62.10	67.90	83.70	98.30	114.50
1105.8	17.80	21.80	27.30	33.60	41.50	48.30	56.00	63.50	69.80	85.30	100.00	116.50
1105.9	20.00	22.50	28.50	35.10	43.00	49.60	57.50	65.30	71.20	86.80	101.40	118.30
1106.0		24.00	30.30	36.50	44.40	51.30	59.50	67.30	73.00	88.50	102.80	120.20
1106.1		26.00	32.00	39.30	46.30	52.80	61.20	69.50	74.50	90.10	104.50	122.30
1106.2		30.00	34.00	40.50	48.00	54.80	63.50	71.50	76.50	92.00	106.30	124.80
1106.3			36.00	43.00	50.20	56.60	66.00	74.00	78.80	93.60	108.20	127.30
1106.4			40.00	46.30	53.20	59.30	68.80	76.50	80.50	95.80	110.70	130.00
1106.5				50.00	56.00	62.50	71.80	78.50	83.30	97.80	113.00	132.50
1106.6					60.00	66.50	74.20	82.00	86.00	100.20	115.60	136.20
1106.7						70.00	79.00	86.00	89.00	103.00	118.50	140.00
1106.8							80.00	90.00	94.00	107.00	121.20	144.00
1106.9									100.00	112.00	127.00	150.50
1107.0										120.00	140.00	160.00

Note: Discharge thru all four hydropower units at full pool is approximately 22.34

VIII - EFFECT OF WATER CONTROL PLAN

8-01. General. The Carters Dam and Reregulation Dam is a multi-purpose project authorized for flood risk management, hydropower, recreation, fish and wildlife conservation, navigation, water quality, and water supply.

Authority for development of a dam on the Coosawattee River near Carters, Georgia, is contained in Section 2 of the River and Harbor Act adopted 2 March 1945 (Public Law 12, 79th Congress, 1st Session). This Act approved the initial and ultimate development of the Alabama-Coosa River and Tributaries for flood risk management, power generation, navigation and other purposes as outlined in House Document 414, 77th Congress. House Document No. 414, 77th Congress, 1st Session, did not prescribe a specific plan for the development of the Coosawattee River. At that time the comprehensive plan for the basin provided for an upper and lower dam on the Coosawattee River with an impounding dam on the Cartecay River. As a result of subsequent studies, a more complete development of the river by a single high dam at the lower site was found to be warranted. Modification of the two-dam plan was therefore authorized.

To provide for the authorized purposes, Carters Lake has a total storage capacity of 472,756 acre-feet at elevation 1,099 feet NGVD29. Of that, 141,402 acre-feet are usable for conservation purposes, 89,191 acre-feet are reserved for flood damage reduction, and 242,163 acre-feet are inactive storage. The top of conservation pool is at elevation 1,074 feet NGVD29 from 1 May to 1 November; transitioning to 1,072 feet NGVD29 from 1 November to 1 December; at elevation 1,072 feet NGVD29 from 1 December to 1 April; then transitioning back to elevation 1,074 feet NGVD29 between 1 April and 1 May. The benefits and effects of the project are described in the Sections below.

The impacts of the *ACT Master Water Control Manual* and its Appendices, including this water control manual have been fully evaluated in an Environmental Impact Statement (EIS) that was published on November 2014. A Record of Decision (ROD) for the action was signed on May 2015. During the preparation of the EIS, a review of all direct, secondary and cumulative impacts was made. As detailed in the EIS, the decision to prepare the Water Control Manual and the potential impacts was coordinated with Federal and State agencies, environmental organizations, Indian tribes, and other stakeholder groups and individuals having an interest in the basin. The ROD and EIS are public documents and references to their accessible locations are available upon request.

8-02. Flood Risk Management. One of the major benefits of the water control operations of Carters is flood damage reduction. Carters Lake contains 89,191 acre-feet of flood risk management storage space between 1,099 and 1,074 feet NGVD29, in which flood water is stored and later released in moderate amounts to prevent downstream flooding. During most years, one or more flood events occur in the ACT Basin. While most of those events are of minor significance, on occasion, major storms produce widespread flooding or unusually high river stages. The main benefits of the flood risk management operations of the Carters Project are at the Towns of Resaca and Rome, Georgia.

a. <u>Spillway Design Flood</u>. A spillway design flood series was adopted as the criteria in establishing the top of dam. The flood of January 1947, one of the largest volume floods of record, was assumed to precede the spillway design flood with its peak occurring five days before the peak of the spillway design flood. When routed through the five-gate spillway, this series reached a peak pool elevation of 1107.3 feet NGVD29 with a maximum discharge of

197,800 cfs. Inflow-outflow-pool stage relationships for the routing of this flood using the fivegate emergency spillway are shown on Plate 8-1.

b. <u>Standard Project Flood</u>. Routing of the standard project flood required use of the spillway gate regulation schedule, when the pool exceeded elevation 1,099 feet NGVD29, but it was not necessary to utilize the spillway to its full capacity for this flood. When routed, the flood reached a peak pool elevation of 1,106.5 feet NGVD29 with a maximum discharge of 54,000 cfs. Inflow-outflow-pool stage relationship for this flood is shown on Plate 8-2.

c. <u>Other Floods</u>. The pre-record flood of March 1886 was the greatest known on the Oostanaula River and, in all probability, was equally severe in that portion of the basin above Carters Dam site. Other major floods of record resulted from the storms of April 1938, January 1947, March 1951 and April 1977. The flood of April 1938 is remarkable because of the even distribution of rainfall over the area. It produced the maximum stage of record at Ellijay and near record stages throughout the Oostanaula River Basin. The storm of January 1947, while not producing as large a peak discharge as some of the other storms, lasted for several days and would have caused a larger volume of water to be held in storage at Carters Dam during flood risk management operations. The storm of March 1951 resulted in record stages at Pine Chapel and Resaca below the Carters site and was of considerable severity in the basin above Carters Dam site. All floods of record would be confined to full power plant discharge (approximately 21,000 cfs). Typical inflow-outflow-pool stage relationships for the January 1947 and March 1951 floods, two of the larger floods volume and peak-wise, are shown on Plates 8-3 and 8-4. The flood of April 1977, the largest since the completion of the project, produced a peak pool of 1098.8 feet NGVD29 as shown on Plate 8-5.

8-03. Recreation. Carters Lake is a valued recreational resource, providing significant economic and social benefits for the region and the Nation. The project contains 3,275 acres of water at summer conservation pool elevation of 1,074 feet NGVD29, plus an additional 8,514 acres of land, most of which is available for public use. A wide variety of recreational opportunities are provided at the lake including boating, fishing, camping, picnicking, water skiing, hunting and sightseeing. Mobile District park rangers and other project personnel conduct numerous environmental and historical education tours and presentations, as well as water safety instructional sessions each year for the benefit of area students and project visitors.

The effects of the Carters Project water control operations on recreation facilities and use at Carters Lake are described as impact levels - Initial Impact Level, Recreation Impact Level, and Water Access Limited Level. The impact levels are defined as pool elevations with associated effects on recreation facilities and exposure to hazards within the lake. The following are general descriptions of each impact level:

a. <u>Initial Impact Level</u>. The Initial Impact Level is defined at lake elevation 1,068 feet NGVD29. At this level impacts are first observed and there is adequate time available to notify the public should the lake level continue to drop. Action is taken to prevent more serious and lasting impacts. Swimming area buoys at Harris Branch Beach are set out at approximately elevation 1,068 feet NGVD29 when the lake is at normal summer pool level of 1,074 feet NGVD29. At the initial impact level, gate attendants issue oral messages and written warnings to the public.

b. <u>Recreation Impact Level</u>. The lake elevation of 1,060 feet NGVD29 is defined as the Recreation Impact Level. At this level action must be taken to prevent significant impacts from occurring. At the level of 1,060 feet NGVD29, the dangers to those participating in water based

recreation activities would increase due to hazardous conditions. Steps are taken to alert the marina staff and public of existing dangers. Woodring Campground and Doll Mountain Day Use boat ramps are closed to the public when water level is below elevation 1,060 feet NGVD29.

c. <u>Water Access Limited Level</u>. The lake elevation of 1,055 feet NGVD29 is defined as the Water Access Impact level. At this elevation, public access to the water is severely limited. Action is taken to retain this limited access. If navigational hazards appear, they will be temporarily marked with buoys or signs for boater safety. Marina slips are still usable, but dock walkways slope severely from the shoreline. At elevation 1,055 feet NGVD29, Ridgeway boat ramp, Woodring Branch day use area boat ramp and Damsite boat ramps are closed. At elevation 1,060 feet NGVD29, the Harris Branch Beach is closed. The designated swimming area buoys are completely out of the water and cannot be moved.

Table 8-1 shows the lake elevation for each impact level and the percent of time over a 70year simulation of the proposed operation that each impact level would be reached at Carters Lake.

Table 0-1. Vallet's Lake Recreational impact Levels						
	Number of Triggered Events Over Period of Record	Percent of time pool level falls below level				
Initial Impact level (1,068 ft NGVD29)	679	2.7%				
Recreation Impact level (1,060 ft NGVD29)	58	0.2%				
Water Access Limited level (1,055 ft NGVD29)	0	0.0%				

Table 8-1.	Carters	Lake Recreational	Impact	Levels
------------	---------	-------------------	--------	--------

Carters Lake also has a High Water Action Plan that establishes guidelines to determine areas impacted by high water levels during the normal recreation season and the actions to be taken by Operations personnel for each stage. The facilities affected from high lake levels are described in Table 8-2.

Table 8-2. High Water Impacts on Recreation Facilities

- 1074.0 Full Pool
- 1076.0 Harris Beach Sand on lower beach covered
- 1078.0 Doll Day Use water above concrete wall in lower picnic area
- 1083.0 Woodring Campground Site 15 water on power pedestal turn off power to sites 9, 11, 13, 15
- 1087.0 Woodring Camping road to sites 16 42 OK Sites 9,11,13,15 power turned off – at 1083 Sites 15, 30, 40, 42 flooded
- 1087.7 Woodring Camping road to sites 16 42, water 2-3" deep Harris Br. & Doll Mtn. Campgrounds all campsites OK Woodring Day Use Ramp – 2-3" water in lower parking lot near picnic tables ramp still OK
 - Woodring Day Use Picnic Shelter water on access trail 6" deep
- 1088.5 Woodring Day Use Area ramp closed
- 1088.7 Damsite Ramp water covering low spot near fee vault upper parking lot access covered by 1-3" water Doll Day Use Ramp – turn around to launch OK – Woodring Day Use Ramp – lower parking lot covered with water 2-6" deep – ramp OK, upper parking lot OK
- 1089 Damsite Park is Closed
- 1090.0 Doll Day Use Ramp Turn around covered, launching still possible by backing in from upper parking lot
 Woodring Day Use Ramp Launching area covered, lower parking lot under water Doll Mountain Campground Site 20 water on tent pad
 Damsite Call GA Power and have them turn power off before water covers road at 1090.0 or boat will be needed to access transformer
 Dong a partice Coordin Power Transformer water of transformer how
- 1093.8 Damsite Georgia Power Transformer water at base of transformer box

8-04. Water Quality. In the main reservoir, water quality is typically better in the middle of the reservoir than in the more enclosed inlets and upper arms. Sediment and nutrient concentrations are greatest in the upper tributaries and decrease towards the main body of the pool. As with other reservoirs, Carters Lake acts as a sink removing sediments and nutrients from downstream reaches. During the summer, thermal and dissolved oxygen stratification occurs. Both are greatest in the upper levels of the water column and colder, oxygen depleted water occurs at lower levels. Chlorophyll *a* concentrations tend to be greatest during the warm summer months. Because of the nature of the lake and its associated stratification, hydropower generation can release cold, oxygen depleted water to downstream reaches of the river. In addition, drought conditions can result in reduced hydropower generation and lowered downstream flows at a time when such flows are critically needed by downstream organisms.

The proposed operational procedures are designed to help reduce water quality impacts. By varying the minimum flow releases throughout the year water quality will be improved due to greater aeration in the water column and changes in water temperature. Aeration is needed because it increases dissolved oxygen levels which have a direct impact on flora and fauna. The variable month to month minimum flow releases would provide adequate flow for water quality and aquatic ecosystems while allowing water conservation during critical periods. Those improved flows would provide both improved water quality and additional spawning and migration habitat during spring and early summer when many organisms are most active. **8-05.** Fish and Wildlife. Because of the type of project and the depth of the reservoir (average depth of about 380 feet, maximum depth of 410 feet), and the makeup of fish populations occurring within the watershed prior to impoundment, regulation of the project for fish and wildlife within the main lake is not possible. The daily fluctuations of the main reservoir can be up to four feet which may have a detrimental effect on fish spawning in the lake.

However, project operations do enhance the aquatic ecosystem in the Coosawattee River downstream of the Carters Reregulation Dam. In 2000, 2003, and in the Planning Aid Letter for the Environmental Impact Statement (EIS) prepared for the update to the ACT Water Control Manuals, the U.S. Fish and Wildlife Service (USFWS) identified a seasonal varying minimum flow from the Reregulation Dam. As a result seasonal minimum releases shown on Figure 7-1 were incorporated into the operation and two Action Zones added to the conservation storage. In action Zone 1, minimum flow releases at Carters Reregulation Dam would be equal to or greater than the seasonal minimum shown on Figure 7-1. If Carters Lake were in action Zone 2, minimum flow releases from the Carters Reregulation Dam would be 240 cfs. The project is operated to comply with the Endangered Species Act of 1973. The USFWS by letter dated 20 March 2014, concurred that operation of the project, along with the other ACT projects would either have no effect or may affect but be not likely to adversely affect listed species in the basin.

8-06. Water Supply. Under the authority of the Water Supply Act of 1958, the Corps allocated storage in Carters Lake in 1991 for municipal and industrial water supply by entering into a storage contract (Contract Number DACW01-9-91-481) with the City of Chatsworth, Georgia. The contract provides for the use of an undivided 0.61 percent (estimated to contain 818 acrefeet after adjustment for sediment deposits) of the conservation storage space between elevations 1,022 - 1,072 feet NGVD29 (134,900 acre-feet) for water supply. This amount of storage stated in the contract was estimated, at the time the contract was executed, to yield 2.0 mgd during the critical drought, i.e., during the worst drought on record at the time the contract was executed. The severity and frequency of droughts change over time, however, and more recent storage-yield analysis by the Corps has indicated that the estimated yield of Carters Lake storage has decreased. For the purpose of managing water supply storage, the Mobile District has employed a systematic storage accounting methodology that tracks multiple storage accounts, applying a proportion of inflows and losses (e.g. evaporation), as well as direct withdrawals by specific users, to each account. The amount of water that may actually be withdrawn is ultimately dependent on the amount of water available in storage, which will naturally change over time.

The necessary data to determine water supply storage availability is received daily, with computations performed weekly during normal conditions, and daily under extreme drought conditions. This accounting is especially critical during drought, when available water supply storage is reduced and conservation measures or alternative sources may be necessary. The formula used to calculate water supply storage is shown below:

Ending Storage = Beginning Storage + Inflow Share – Loss Share – User's Usage. (with constraint that "Ending Storage" cannot be larger than User's total storage)

The conservation pool is drawn down as water usage exceeds inflow. The entire pool is drawn down and the individual accounts are also drawn down at different rates based on their usage. Users will be notified on a weekly basis of the available storage remaining, once their storage account balance drops below 30 percent.



Figure 8-1. The City of Chatsworth Water Intake Structure

8-07. Hydroelectric Power. The Carters Dam Hydropower Project, along with nine other hydropower dams located in Georgia, Alabama, and South Carolina comprise the GA-AL-SC System, one of SEPA's four power systems providing energy throughout the Southeastern United States. Other projects within the GA-AL-SC system include Allatoona, Buford, West Point, WF George, RF Henry, Millers Ferry, Hartwell, Russell, and Thurmond. SEPA sells hydroelectric power generated at Carters Dam to a number of cooperatives and municipal power providers, referred to as preference customers. Hydroelectric power is one of the cheaper forms of electrical energy, and it can be generated and supplied quickly as needed in response to changing demand.

From FY 2000-2011, the Carters Project has provided generation of 5,650,244 megawatthours (MWh) of the total generation in the Georgia-Alabama-South Carolina System of 37,720,506 MWh, or approximately 15 percent of the System generation.

The projects with hydropower capability provide three principal power generation benefits:

1. Hydropower helps to ensure the reliability of the electrical power system in the SEPA service area by providing dependable capacity to meet annual peak power demands. For most plants, this condition occurs when the reservoir is at its maximum elevation. Dependable capacity at hydropower plants reduces the need for additional coal, gas, oil, or nuclear generating capacity.

2. The projects provide a substantial amount of energy at a small cost relative to thermal electric generating stations, reducing the overall cost of electricity. Hydropower facilities reduce the burning of fossil fuels, thereby reducing air pollution. The value of the energy produced at Carters Project is approximately \$9.5 million a year.

3. Hydropower has several valuable operating characteristics that improve the reliability and efficiency of the electric power supply system, including efficient peaking, a rapid rate of unit unloading, and rapid power availability for emergencies on the power grid.

Hydropower generation by the Carters Dam Hydropower Plant, in combination with the other hydropower power projects in the ACT Basin, helps to provide direct benefits to a large segment of the basin's population in the form of relatively low-cost power and the annual return of revenues to the Treasury of the United States. Hydropower plays an important role in meeting the electrical power demands of the region.

8-08. Navigation. Specific releases from the Carters Project to meet navigation flows are not part of the routine regulation plan. The seasonal variation in reservoir storage does redistribute downstream flows providing benefits to navigation.

8-09. Drought Contingency Plans. The importance of drought contingency plans has become increasingly obvious as more demands are placed on the water resources of the basin. During low-flow conditions, the system might not be able to fully support all project purposes. The purpose of drought planning is to minimize the effect of drought, to develop methods for identifying drought conditions, and to develop both long- and short-term measures to be used to respond to and mitigate the effects of drought with other federal agencies, private power companies, navigation interests, the states, and other interested state and local parties as necessary. Drought operations will be in compliance with the plan for the entire ACT Basin as outlined in the *ACT Master Water Control Manual*. The plan includes operating guidelines for drought conditions. It is important to recognize that Carters Dam would be operated as an element of the total water control plan for the basin. Outflows from the project would be determined by total basin-wide needs, both upstream and downstream.

Drought operations at Carters would consist of progressively reduced hydropower generation as the lake level declines due to lower inflows. When the lake level drops into Action Zone 2, the minimum flows from the Reregulation Dam would be reduced from the seasonal varying flows to the minimum flow of 240 cfs.

8-10. Flood Emergency Action Plans. Normally, all flood control operations are directed by the Water Management Section. If, however, a storm of flood-producing magnitude occurs and all communications are disrupted between the Water Management Section and project personnel at the Carters Dam Powerhouse, emergency operating procedures, as described in Exhibit C, Standing Instructions to the Damtenders, will begin. If communication is broken after some instructions have been received from the Water Management Section, those instructions will be followed for as long as they are applicable.

8-11. Frequencies and Probabilities. The Carters Main Pool Peak Pool Frequency and Peak Inflow Frequency for the operation plan are shown on Figure 8-2, and 8-3. Figure 8-4 shows the Carters Pool Elevation Annual Duration Curve, which represents the percent of days in the period of record in which the elevation, recorded at midnight, was higher than a specific elevation. The period of record for Figures 8-2 through 8-4 is 1975 – 2010.
Carters Annual Peak Pool Frequency



Figure 8-3. Carters Peak Inflow Frequency (Period of Record 1975 – 2010)





The influence of the Reregulation Dam is shown in the Headwater and Tailwater rating curves for the Reregulation Dam area shown on Plate 8-6.

The estimated frequencies of peak flow at Pine Chapel, and Resaca with the Carters regulation plan are shown on Plates 8-7 and Plate 8-8. Frequencies of peak flow at Rome (Oostanaula River) and Rome (Coosa River at Mayo's Bar) are shown on Plate 8-9 and Plate 8-10. Annual maximum and minimum pool elevations and pool frequencies for the Carters Main Dam are shown on Plates 8-11 thru Plate 8-13.

8-12. Other Studies. In early 2010 the Corps, Mobile District, developed updated critical yields for the Allatoona and Carters Projects in the ACT Basin in response to the following language in the FY 2010 Energy & Water Development Appropriations Bill, 111th Congress, 1st Session:

Alabama-Coosa-Tallapoosa [ACT], Apalachicola-Chattahoochee-Flint [ACF] Rivers, Alabama, Florida, and Georgia - The Secretary of the Army, acting through the Chief of Engineers, is directed to provide an updated calculation of the critical yield of all federal projects in the ACF River Basin and an updated calculation of the critical yield of all federal projects in the ACT River Basin within 120 days of enactment of this act.

Robert F. Henry Lock and Dam, Millers Ferry Lock and Dam and Claiborne Lock and Dam are federal projects in the ACT Basin that were excluded from the critical yield analyses because they are *run-of-river* impoundments with little or no usable water storage and cannot significantly contribute to critical yield.

Critical yield provides the basis from which water stored in a reservoir is allocated to various project purposes. The volume of water stored in a reservoir can be allocated to a specific project purpose (e.g., hydropower or water supply) based on a percent of critical yield. A change in critical yield may result in modification of the allocations for a project purpose.

The impacts of the river withdrawals on the critical yield can be quantified by computing the critical yield with and without diversions. Withdrawals for the year 2006 was used in the analyses and showed that river withdrawals had a measurable impact, reducing critical yield as much as five percent at Allatoona Dam but only 0.8 percent at Carters Dam. The critical yield for Carters was determined to be 390 cfs without diversions and 387 cfs with diversions. The critical drought for the period of record occurred in 2007.

In 2000, 2003, and in the Planning Aid Letter for the EIS (USFWS 2010a), the U.S. Fish and Wildlife Service identified the need for a seasonal varying minimum flow from the Reregulation Dam. As a result seasonal minimum releases were incorporated into the operation and two Action Zones added to the conservation storage and are shown on Figure 7-1.

IX - WATER CONTROL MANAGEMENT

9-01. Responsibilities and Organization. Many agencies in federal and state governments are responsible for developing and monitoring water resources in the ACT Basin. Some of the federal agencies are the Corps, U.S. Environmental Protection Agency, National Parks Service, U.S. Coast Guard, USGS, U.S. Department of Energy, U.S. Department of Agriculture, U.S. Fish and Wildlife, and NOAA. In addition to the federal agencies, each state has agencies involved: GAEPD, the Coosa-North Georgia Regional Water Planning Council, and the Alabama Department of Environmental Management, Alabama Office of Water Resources.

a. U.S. Army Corps of Engineers. Authority for water control regulation of the Carters Project has been delegated to the SAD Commander. The responsibility for water control regulation activities has been entrusted to the Mobile District. Water control actions for the Carters Project are regulated to meet the federally authorized project purposes at Carters in coordination with other authorized projects in the ACT Basin. It is Mobile District's responsibility to develop water control regulation procedures for the Carters Project. The Water Management Section monitors the project for compliance with the approved water control plan. In accordance with the water control plan, the Water Management Section performs water control regulation activities that include determination of project water releases, daily declarations of water availability for hydropower generation and other purposes: daily and weekly reservoir pool elevation and release projections; weekly river basin status reports; tracking basin composite conservation storage and projections; determining and monitoring daily and 7-day basin inflow; managing high-flow operations and regulation; and coordination with other District elements and basin stakeholders. When necessary, the Water Management Section instructs the project operator regarding normal water control regulation procedures and emergencies, such as flood events. Personnel at Carters Dam are under the direct supervision of a Power Project Manager and Operations Project Manager. The Water Management Section communicates directly with the powerhouse operators at the Carters Dam Powerhouse and with other project personnel as necessary. The Water Management Section is also responsible for collecting historical project data and disseminating water control information, such as historical data, lake level and flow forecasts, and weekly basin reports within the agency; to other federal, state, and local agencies; and to the general public.

b. Other Federal Agencies.

1) National Weather Service (NWS). The NWS is the federal agency in NOAA that is responsible for weather warnings and weather forecasts. With support from the Corps NWS Cooperative Gaging program, the NWS forecast offices, along with SERFC, maintain a network of rainfall and flood reporting stations throughout the Carters Watershed and the ACT Basin. It continuously provides weather conditions and forecasts. The SERFC prepares river forecasts and provides the official flood stage forecasts along the ACF Rivers. Often, it prepares predictions on the basis of what if scenarios, such as QPF - a prediction of the spatial precipitation across the United States and the region. The Corps, NWS, and SERFC share information regarding rainfall, project data, and streamflow forecasts. In addition, the NWS provides information on hurricane forecasts and other severe weather conditions. It monitors drought conditions and provides the information to the public.

2) U.S. Geological Survey (USGS). The USGS is an unbiased, multidisciplinary science organization that focuses on biology, geography, geology, geospatial information, and water. The agency is responsible for the timely, relevant, and impartial study of the landscape, natural

resources, and natural hazards. Through the Corps USGS Cooperative Gaging program, the USGS maintains a comprehensive network of gages in the ACT Basin.

3) Southeastern Power Administration (SEPA). SEPA was created in 1950 by the Secretary of the Interior to carry out the functions assigned to the secretary by the Flood Control Act of 1944. In 1977, SEPA was transferred to the newly created U.S. Department of Energy. SEPA, headquartered in Elberton, Georgia, is responsible for marketing electric power and energy generated at reservoirs operated by the Corps. The power is marketed to nearly 500 preference customers in Georgia, Florida, Alabama, Mississippi, southern Illinois, Virginia, Tennessee, Kentucky, North Carolina, and South Carolina.

a. The objectives of SEPA are to market electricity generated by the federal reservoir projects, while encouraging its widespread use at the lowest possible cost to consumers. Power rates are formulated using sound financial principles. Preference in the sale of power is given to public bodies and cooperatives, referred to as preference customers. SEPA does not own transmission facilities and must contract with other utilities to provide transmission, or *wheeling* services, for the federal power.

b. SEPA's responsibilities include the negotiation, preparation, execution, and administration of contracts for the sale of electric power; preparation of repayment studies to set wholesale rates; the provision, by construction, contract or otherwise, of transmission and related facilities to interconnect reservoir projects and to serve contractual loads; and activities pertaining to the operation of power facilities to ensure and maintain continuity of electric service to its customer.

c. SEPA schedules the hourly generation for the Carters power project at the direction of the Corps on the basis of daily and weekly water volume availability declarations and water release requirements.

4) U.S. Fish and Wildlife Service (USFWS). The USFWS is an agency within the Department of the Interior whose mission is working with others to conserve, protect and enhance fish, wildlife, plants, and their habitats for the continuing benefit of the American people. The USFWS is the responsible agency for the protection of federally listed threatened and endangered species and their federally designated critical habitat in accordance with the Endangered Species Act of 1973. The Corps also coordinates with the USFWS on water resource actions under the auspices of the Fish & Wildlife Coordination Act. The Corps, Mobile District, with support from the Water Management Section, coordinates water control actions and management with USFWS in accordance with both laws.

c. State Agencies.

1) Georgia. Georgia Environmental Protection Division (GAEPD) conducts water resource assessments to determine a sound scientific understanding of the condition of the water resources, in terms of the quantity of surface water and groundwater available to support current and future in-stream and off-stream uses and the capacity of the surface water resources to assimilate pollution. Regional water planning councils in Georgia prepare recommended Water Development and Conservation Plans. Those regional plans promote the sustainable use of Georgia's waters through the selection of an array of management practices, to support the state's economy, to protect public health and natural systems, and to enhance the quality of life for all citizens.

2) Alabama. Alabama Office of Water Resources (OWR) administers programs for river basin management, river assessment, water supply assistance, water conservation, flood mapping, the National Flood Insurance Program and water resources development. Further,

OWR serves as the state liaison with federal agencies on major water resources related projects, conducts any special studies on instream flow needs, and administers environmental education and outreach programs to increase awareness of Alabama's water resources.

a. The Alabama Department of Environmental Management (ADEM) Drinking Water Branch works closely with the more than 700 water systems in Alabama that provide safe drinking water to four million citizens.

b. The Alabama Chapter of the Soils and Water Conservation Society fosters the science and the art of soil, water, and related natural resource management to achieve sustainability.

d. <u>Private Organizations</u>. The Alabama Power Company (APC) owns and operates hydropower projects downstream of Carters Project throughout the Coosa Basin. These projects are discussed in the ACT Master Water Control Manual.

e. <u>Stakeholders</u>. Many non-federal stakeholder interest groups are active in the ACT Basin. These groups include lake associations, M&I water users, navigation interests, environmental organizations, and other basin-wide interests groups. Coordinating water management activities with these interest groups, state and federal agencies, and others is accomplished as required on an ad-hoc basis and on regularly scheduled water management teleconferences that occur during unusual flood or drought conditions to share information regarding water control regulation actions and gather stakeholder feedback. The Master Water Control Manual includes a list of state and federal agencies and active stakeholders in the ACT Basin that have participated in the ACT Basin water management teleconferences and meetings.

9-02. Interagency Coordination.

Local Press and Corps Bulletins. The local press consists of periodic publications in or near the Carters watershed and the ACT Basin. Montgomery, Gadsden, Anniston and Birmingham, Alabama, and Rome and Atlanta, Georgia, have some of the larger daily papers. The papers often publish articles related to the rivers and streams. Their representatives have direct contact with the Corps through the Public Affairs Office. In addition, they can access the Corps Web pages. The Corps and the Mobile District publish e-newsletters regularly which are made available to the general public via email and postings on various websites. Complete, real-time information is available at the Mobile District's Water Management homepage <u>http://water.sam.usace.army.mil/</u>. During the hurricane season, the Water Management Section posts tropical updates to District and Division elements. The Mobile District Public Affairs Office issues press releases as necessary to provide the public with information regarding Water Management issues and activities. During floods, the Water Management Section prepares daily flood notices in cooperation with the Emergency Management Branch of Operations Division of the Mobile District Office.

9-03. Framework for Water Management Changes. Special interest groups often request modifications of the basin water control plan or project specific water control plan. The Carters Project and other ACT Basin projects were constructed to meet specific, authorized purposes, and major changes in the water control plans would require modifying, either the project itself or the purposes for which the projects were built. However, continued increases in the use of water resources demand constant monitoring and evaluating reservoir regulations and reservoir systems to insure their most efficient use. Within the constraints of congressional authorizations and engineering regulations, the water control plan and operating techniques are often reviewed to see if improvements are possible without violating authorized project functions. When deemed appropriate, temporary variances to the water control plan approved by SAD can be implemented to provide the most efficient regulation while balancing the multiple purposes of the ACT Basin-wide System.

EXHIBIT A

SUPPLEMENTARY PERTINENT DATA

EXHIBIT A SUPPLEMENTARY PERTINENT DATA

LOCATION AND PURPOSE

Location. The project site is located on the Coosawattee River in Gordon County, Georgia. The Main Dam is located at mile 26.8 and the downstream Reregulation Dam is located at mile 25.3. Carters Project is designed primarily for flood risk management and hydroelectric power. Flow regulation, recreation, fish and wildlife conservation, and, water quality control are additional benefits of the project.

GENERAL

Main Dam Drainage Area, sq. mi.	374				
Reregulation Dam Drainage Area, sq. mi.	520				
Talking Rock Creek Drainage Area, sq. mi.	146				
Primary flood risk mgt. pool elevation, feet NGVD29	1,099				
Maximum power pool elevation (winter), feet NGVD29	1,072				
Maximum power pool elevation (summer), feet NGVD29	1,074				
Minimum power pool elevation, feet NGVD 29	1,022				
Maximum drawdown, feet	52				
Area of primary flood risk management pool, acres (1,099 ft NGVD29)	3,880				
Area of maximum power pool, acres (1,074 ft NGVD29)	3,275				
Area of minimum power pool, acres (1,072 ft NGVD29)	2,196				
Shoreline miles (@ elevation 1,074 ft NGVD29)	62.7				
Flood storage volume, acre-feet (1,099 – 1,074 ft NGVD29)	89,191				
Power storage volume, acre-feet (1,074 – 1,022 ft NGVD29)	141,402				
Inactive storage volume, acre-feet (below 1,022 ft NGVD29)	242,163				
Maximum elevation of clearing, feet NGVD29	1075				
SPILLWAY DESIGN FLOOD					
Natural peak discharge at dam site, cfs	194,200				
Peak inflow to full reservoir, cfs	203,100				
Regulated peak outflow, cfs	197,800				
Regulated peak headwater, feet NGVD 29	1,107.2				
STANDARD PROJECT FLOOD					
Natural peak discharge at dam site, cfs	97,600				
Natural peak stage at dam site, feet NGVD29	716.8				
Peak inflow to full reservoir, cfs	102,000				
Peak inflow to reregulation pool, cfs	90,400				
Regulated peak outflow, cfs	54,000				
Regulated peak headwater, feet NGVD29	1,106.5				
Regulated peak tailwater, feet NGVD29	707.0				

MAIN DAM AND DIKES

ROCKFILL DAM	
Top elevation, feet NGVD29	1,112.3
Top width, feet	40
Length, feet	2,053
Maximum height, feet above foundation	445
Upstream slope	1 on 1.9
Downstream slope	1 on 1.8
Freeboard, top of dam above Spillway Design Flood, feet	5.1
EARTHFILL SADDLE DIKES	
Top elevation, feet NGVD29	1,112.3
Top width, feet	30
Number of dikes	3
I otal length, feet	700
Side elenee	40
Unstream slope protection	dumped rock
Freeboard, top of dikes above Spillway Design Flood, feet	5.1
EMERGENCY GATED SPILLW	AY
GENERAL	
Total length, including end piers, feet	262
Net length, feet	210
Elevation of crest, feet NGVD29	1,070.0
Type of gates	tainter
Number of gates	5
Length of Gates, feet	42
Height of Gates, feet	36.5
Top of Gates, Closed, elevation feet NGVD29	1,106.0
DIVERSION TUNNEL	
GENERAL	
Length, feet	2,407
Shape	horseshoe
Lining	none
Bottom width, feet	23
Maximum height, feet	23

EMERGENCY LOW LEVEL SLUICE

GENERAL Number of sluices Total length of tunnel, feet	1 2,712
TUNNEL UPSTREAM OF GATE STRUCTURE	
Length of tunnel, feet Shape Lining Nominal diameter of excavated tunnel, feet Diameter of lined tunnel, feet Invert elevation at upstream portal, feet NGVD29	1,198 circular concrete 19.5 16.5 725
GATE STRUCTURE	
Length of structure, feet Number of water passages Invert elevation of water passages, feet NGVD29 Number of gates per passage Total number of gates Type of gates Height of gates, feet Width of gates, feet Type of operating machinery Nominal diameter of excavated shaft for combined emergency access and air vent, feet	62 2 723 2 4 slide 10 5 hydraulic
TUNNEL DOWNSTREAM OF GATE STRUCTURE	
Length of tunnel, feet Shape Lining Bottom width, feet Maximum height, feet Length of concrete splash apron, feet Invert elevation at downstream portal, feet NGVD29	1,452 horseshoe none 22 22 200 710
DOWNSTREAM CHANNEL	
Length, feet Maximum bottom width, feet Side slopes:	640 50
Sound rock Weathered rock Overburden Bottom elevation at downstream end of channel, feet NGVD29	4 on 1 1 on 1 1 on 2 700

POWER INTAKE

GENERAL Number of intake structures	2
HEADRACE	
Length (approximate), feet Width (minimum section), feet Side slopes Bottom elevation, feet NGVD29	1,600 200 4 on 1 979.0
INTAKE STRUCTURES	
Top elevation, feet NGVD29 Width of each structure, feet Length of base, feet (excluding transition) Maximum height, feet Type of head gate Number of head gates, each structure Height of gate, feet Width of gate, feet Type of operation Elevation of operating deck, feet NGVD29	1,112.5 94 51 138.5 tractor 2 20.5 14 fixed hoist 1,112.5
PENSTOCKS	
Number Length of conventional unit penstocks, feet Length of pump-turbine unit penstocks, feet Nominal diameter of excavated tunnel, feet Inside diameter of steel-lined penstock, feet Minimum thickness of concrete liner, inches	4 835 838 23 18 30
POWER DATA	
GENERAL	
Number of units Capacity: 2 @ 140,000 and 2 @ 160,000 kw (declared values) Capacity: 4 @ 144,000 kw (nameplate values) Dependable plant output during critical period, kw Operating head at maximum power pool, feet Minimum head at full drawdown, feet Maximum head loss at 115% generator rating, feet Maximum discharge per unit at 115% generator rating (conventional unit), cfs Maximum discharge per unit at 115% generator rating (pump-turbine unit), cfs Discharge each pump-turbine unit at 385 feet total head, cfs	4 600,000 575,000 500,000 396 324 4.8 5,400 5,400 3,765
Maximum discharge at minimum power pool, elev. 1022,	-,
(estimated for 4 units), cfs	20,900

GENERATING UNITS 1 AND 2 ONLY	
Speed-RPM Spacing of units, center to center, feet Turbines	163.6 63
Type Capacity, guaranteed at 345.0 feet <u>net head</u> , HP, each Capacity, guaranteed at 393.0 feet <u>net head</u> , HP, each Spiral cases	Francis, clockwise rotation 172,000 199,000 Plate steel
Drantubes	discharge/intake passages
Generators Type – Vertical shaft, with combined thrust and guide bearing be enclosure for self-ventilation.	low rotor and with air
Ratings Continuous at 60°C. rise Continuous capability at 1.15 rating Power factor Voltage, 60 hertz, 3-phase Short circuit ratio, not less than Fly wheel effect (WK ² LBS-FT ²) Ratio, Xq"/Xd" not more than	125,000 kw; 131,579 kVA 143,750 kw; 151,516 kVA 0.95 13,800 1.175 95,700,000 1.35
GENERATOR/MOTOR UNITS 3 AND 4 ONLY	
Speed-RPM Spacing of units, center to center, feet Pump/Turbines Type – Francis, clockwise rotation as turbine; counter-clockwise	150 63
Capacity, guaranteed at 345.0 ft. <u>net head</u> , HP, each, as a turbine Capacity, guaranteed at 376.0 ft. <u>net head</u> , HP, each, as a turbine Capacity, guaranteed at 347 feet total head, eff Capacity, guaranteed at 383 feet total head, eff Spiral cases Draft tubes	173,000 209,000 87.6% 87.2% plate steel Concrete elbow, three discharge/intake
Generator/Motors Type – Vertical shaft, with thrust-bearing above and below rotor, and with air enclosure for self-ventilation. Ratings	paccageo
As Generator Continuous at 60°C. rise Continuous capability at 1.15 rating Power factor Voltage, 60 hertz, 3-phase Short circuit ratio, not less than Fly wheel effect (WK ² LBS-FT ²) As Motor	125,000 kw; 131,576 kVA 143,750 kw; 151,316 kVA 0.95 13,800 1.175 90,000,000

185,000
0.95
13,800
150

POWERHOUSE

GENERAL

Location right bank about 200 feet below the downstream toe of the main dam and 700 feet northward from the river channel

Size of Building	
Length, feet (including unloading bay)	361.5
Width, feet (including draft tube deck)	114.25
Entrance wing	"L" shaped
ELEVATIONS, FEET NGVD29	
Bottom of Structure	603.2
Low point of draft tube (Units 1 & 2)	620.0
(Units 3 & 4)	615.67
Centerline of distributor (Units 1 & 2)	658.0
(Units 3 & 4)	649.0
Turbine room floor (Units 1 & 2)	676.0
Generator room floor (Units 1 & 2)	691.0
(Units 3 & 4)	676.0
Control room	708.0
Erection floor	708.0
Unloading floor	708.0
Draft tube deck	708.0
Crane runway rail	737.5
Roof, high point	758.08
Top of parapet	761.92
DRAFT TUBE GATES	
Туре	Vertical Life, Slide
Number	3
Size, Ft (Approx.)	13' 9-1/2" X 20' 1-1/2"
Method of Handling	Gantry Crane
DRAFT TUBE TRASH RACKS (Units 3 & 4 Only)	
Туре	Vertical Life, Slide
Number	6
Size, Ft (Approx.)	13' 9-1/2" X 21' 8-1/2"
Method of Handling	Gantry Crane

MAIN POWER TRANSFORMERS

Location	On draft tube deck
Number	2
Туре	3-phase, FOA
Rating	140/156.8 mVA, 55/60°C. temp. rise
Low voltage delta connected	13.2 kV
High voltage, wye connected, grounded	230 kV
Taps, Full capacity, above normal below normal	1-2 1/2 % & 1-5% 1-2 1/2 % & 1-5%
Fire Protection, permanent Installation	water, fog
Units 3 and 4	-
Location	On draft tube deck
Number	2
Rating	158/176.96 mVA, 55/65°C. temp. rise
Low voltage delta connected	13.2 kV
High voltage, wye connected, grounded	230 kV
Taps, Full capacity, above normal below normal	1-2 1/2 % & 1-5% 1-2 1/2 % & 1-5%
Fire Protection, permanent Installation	water, fog
STATION DRAINAGE	
Unwatering Sumps, for unwatering draft tubes and spiral c	ases
Location	Erection Bay and Unloading Bay
Number of Sumps	2
Pumps	
Number	6
Capacity, each	2 @ 300GPM and 4@1,500 GPM
Control	water level automatic
STATION DRAINAGE SUMPS	
Location	Erection Bay and Unloading Bay
Number of Sumps	2
Pumps	_
Number	4
Capacity, each	300GPM
Control	water level automatic

STATION SERVICE SYSTEM	
Normal Supply	From generator step-up transformer leads through two 1000/1333 kVA, 3- phase, self-cooled, forced air ventilated, dry type (Class AA/FA) transformers, 13,800-480 volts, delta- delta connected, with two 2.5% full capacity taps above and below 13,800 volts.
Emergency Supply	Diesel engine driven generator
Main 480 Volt Distribution	Metal-enclosed low voltage power circuit breaker switchgear, with 2-section bus and bus tie circuit breaker. Circuit breakers withdrawal type, those in mains and bus ties electrically operated, those in branches manually operated.
Subsidiary Centers	Metal-enclosed power distribution and motor control centers and panel boards, with molded case circuit breakers.
DIRECT CURRENT SYSTEM	
Station Battery	125 volt, 58 cell, valve regulated lead acid, 1400 ampere- hours capacity at 8-hour discharge rate.
Battery Chargers for 125-Volt Station Battery	Two static chargers, AC Inputs: 416-506 volts; 60 amperes, 3- phase, 60 HZ. DC Output: 120-147 volts; 250 amperes.
Switchyard Battery	125 volt, 60 cell, valve regulated lead acid, 150 ampere- hours capacity at 8 hour discharge rate
Battery Chargers for 125-Volt Switchyard Battery	Static type, rack mounted, 125 volt battery charger; AC Input 208 volts 29 amperes, single phase, 60 Hz. DC output 130 volts, 25 amperes.
CRANES	
Туре	Powerhouse, traveling, with two trolleys and lifting beam
Number Capacity of each main hoist, tons Capacity of each auxiliary hoist, tons Capacity, main hoist and lifting beam, to Span, ft	ns 1 200 25 61'-6"
RAW WATER	
Cooling Water Units 1 and 2 Pumps Number Type Capacity Motor	3 Horizontal, centrifugal, single stage, single suction 1435 GPM 50 HP, 1750 RPM

Units 3 and 4	
Pumps; Number	3
Туре	Horizontal, centrifugal, single stage, single suction
Capacity	1800 GPM
Motor	60 HP, 1750 RPM
Station Service	
Standby Pump; Number	1
Туре	Horizontal, centrifugal, single stage, single suction
Capacity	335 GPM
Motor	25 HP, 3500 RPM
COMPRESSED AIR	
Service Air	
Compressors; Number	2
Туре	Gardner-Denver, screw type
Capacity	100 SCFM at 100 PSIG
Motor	25 HP, 1750 RPM
Main Receiver; Number	1
Capacity	96 CF
Air Brake Receiver; Number	4
Capacity	19 CF
GOVERNOR AIR	
Compressors; Number 1	
Туре	Air cooled, vertical, two stage
Capacity	22.3 SCFM at 350 PSIG
Motor	10 HP, 1750 RPM
TAILWATER DEPRESSION	
Compressors; Number	2
Туре	Sullair, screw type
Capacity	683 SCFM at 125 PSIG
Motor	150 HP
Receiver Tanks	6 at 651 CF each

REREGULATION DAM

GENERAL	
Dam site, miles above mouth of Coosawattee River	25
Drainage area above dam site, square miles	520
Drainage area of reregulation dam only, square miles	146
RESERVOIR	
Maximum storage pool elevation, feet NGVD29	698
Maximum normal operating pool elevation, feet NGVD29	696
Minimum normal operating pool elevation, feet NGVD29	677
Minimum operating pool elevation, feet NGVD29	674
Minimum pool elevation, feet NGVD29	662.5
Area at maximum storage pool, acres	870
Area at minimum pool. acres	50
Usable storage, acre-feet (elevation 674 to 698 ft NGVD29)	16.000
Inactive storage, acre-feet (elevation 662.5 ft NGVD29)	290
Area acquired, acres	1.373
Maximum elevation of clearing, feet NGVD29	700
Area cleared, acres	320
SPILLWAY	
Total length including and piers fact	208
Net length, feet	200
Elevation of crest feet NGVD29	662 5
Number of piers, including end piers	5
Width of piers, feet	8
Type of gates	tainter
Number of gates	4
Length of gates, feet	42
Height of gates, feet	36.5
Elevation of top of gates in closed position, feet NGVD29	699.0
Elevation of low steel of gates in fully open position, feet NGVD29	699.0
Elevation of trunnion, feet NGVD29	675.0
Elevation of access bridge, feet NGVD29	717.0
Elevation of stilling basin apron, feet NGVD29	647.5
Length (parallel to dam) of stilling basin, feet	192
Height of end sill, feet	4
EARTH DIKES	
Top elevation, feet NGVD29	703.0
Length, feet	2,855
Top width of right dike, feet	32
Top width of left dike, feet	12
Side slopes	1 on 3
Thickness of riprap, inches	24
Thickness of filter material, inches	9
Thickness of dumped rock, inches	60

EXHIBIT B

UNIT CONVERSIONS

AND

VERTICAL DATUM CONVERSION INFORMATION

AREA CONVERSION

UNIT	m ²	km ²	ha	in ²	ft ²	yd ²	mi ²	ac
1 m ²	1	10 ⁻⁶	10 ⁻⁴	1550	10.76	1.196	3.86 X 10 ⁻⁷	2.47 X 10 ⁻⁴
1 km ²	10 ⁶	1	100	1.55 X 10 ⁹	1.076 X 10 ⁷	1.196 X 10 ⁶	0.3861	247.1
1 ha	10 ⁴	0.01	1	1.55 X 10 ⁷	1.076 X 10 ⁷	1.196 X 10⁴	3.86 X 10 ⁻³	2,471
1 in ²	6.45 X 10 ⁻⁴	6.45 X 10 ¹⁰	6.45 X 10 ⁻⁸	1	6.94 X 10 ⁻³	7.7 X 10 ⁻⁴	2.49 X 10 ⁻¹⁰	1.57 X 10 ⁷
1 ft^2	.0929	9.29 X 10 ⁻⁸	9.29 X 10 ⁻⁶	144	1	0.111	3.59 X 10 ⁻⁸	2.3 X 10⁻⁵
1 yd ²	0.8361	8.36 X 10 ⁻⁷	8.36 X 10⁻⁵	1296	9	1	3.23 X 10 ⁻⁷	2.07 X 10⁻⁴
1 mi^2	2.59 X 10 ⁶	2.59	259	4.01 X 10 ⁹	2.79 X 10 ⁷	3.098 X 10 ⁶	1	640
1 ac	4047	0.004047	0.4047	6. 27 X 10 ⁶	43560	4840	1.56 X 10 ⁻³	1

LENGTH CONVERSION

UNIT	cm	m	km	in.	ft	yd	mi
cm	1	0.01	0.0001	0.3937	0.0328	0.0109	6.21 X 10 ⁻⁶
m	100	1	0.001	39.37	3.281	1.094	6.21 X 10 ⁻⁴
km	10 ⁵	1000	1	39,370	3281	1093.6	0.621
in.	2.54	0.0254	2.54 X 10 ⁻⁵	1	0.0833	0.0278	1.58 X 10 ^{-₅}
ft	30.48	0.3048	3.05 X 10⁻⁴	12	1	0.33	1.89 X 10⁻⁴
yd	91.44	0.9144	9.14 X 10⁻⁴	36	3	1	5.68 X 10 ⁻⁴
mi	1.01 X 10⁵	1.61 X 10 ³	1.6093	63,360	5280	1760	1

FLOW CONVERSION

UNIT	m³/s	m³/day	l/s	ft ³ /s	ft ³ /day	ac-ft/day	gal/min	gal/day	mgd
m³/s	1	86,400	1000	35.31	3.05 X 10 ⁶	70.05	1.58 X 10 ⁴	2.28 X 10 ⁷	22.824
m³/day	1.16 X 10⁻⁵	1	0.0116	4.09 X 10 ⁻⁴	35.31	8.1 X 10 ⁻⁴	0.1835	264.17	2.64 X 10 ⁻⁴
l/s	0.001	86.4	1	0.0353	3051.2	0.070	15.85	2.28 X 10 ⁴	2.28 X 10 ⁻²
ft ³ /s	0.0283	2446.6	28.32	1	8.64 X 10 ⁴	1.984	448.8	6.46 X 10⁵	0.646
ft ³ /day	3.28 X 10 ⁻⁷	1233.5	3.28 X 10 ⁻⁴	1.16 X 10⁻⁵	1	2.3 X 10⁻⁵	5.19 X 10 ⁻³	7.48	7.48 X 10 ⁻⁶
ac-ft/day	0.0143	5.451	14.276	0.5042	43,560	1	226.28	3.26 X 10⁵	0.3258
gal/min	6.3 X 10⁻⁵	0.00379	0.0631	2.23 X 10 ⁻³	192.5	4.42 X 10 ⁻³	1	1440	1.44 X 10 ⁻³
gal/day	4.3 X 10 ⁻⁸	3785	4.38 X10 ⁻⁴	1.55 X 10 ⁻⁶	11,337	3.07 X 10 ⁻⁶	6.94 X 10 ⁻⁴	1	10 ⁻⁶
mgd	0.0438		43.82	1.55	1.34 X 10 ⁵	3.07	694	10 ⁶	1

VOLUME CONVERSION

UNIT	liters	m ³	in ³	ft ³	gal	ac-ft	million gal
liters	1	0.001	61.02	0.0353	0.264	8.1 X 10 ⁻⁷	2.64 X 10 ⁻⁷
m ³	1000	1	61,023	35.31	264.17	8.1 X 10 ⁻⁴	2.64 X 10 ⁻⁴
in ³	1.64 X 10 ⁻²	1.64 X 10 ⁻⁵	1	5.79 X 10 ⁻⁴	4.33 X 10 ⁻³	1.218 X 10 ⁻⁸	4.33 X 10 ⁻⁹
ft ³	28.317	0.02832	1728	1	7.48	2.296 X 10 ⁻⁵	7.48 X 10 ⁶
gal	3.785	3.78 X 10 ⁻³	231	0.134	1	3.07 X 10 ⁻⁶	10 ⁶
ac-ft	1.23 X 10 ⁶	1233.5	75.3 X 10 ⁶	43,560	3.26 X 10⁵	1	0.3260
million gallon	3.785 X 10 ⁶	3785	2.31 X 10 ⁸	1.34 X 10⁵	10 ⁶	3.0684	1

COMMON CONVERSIONS

1 million gallons per day (mgd) = 1.55 cfs

1 day-second-ft (DSF) = 1.984 acre-ft = 1 cfs for 24 hours

1 cubic foot per second of water falling 8.81 feet = 1 horsepower

1 cubic foot per second of water falling 11.0 feet at 80% efficiency = 1 horsepower

1 inch of depth over one square mile = 2,323,200 cubic feet

1 inch of depth over one square mile = 0.0737 cubic feet per second for one year.

VERTICAL DATUM CONVERSION INFORMATION

SURVEY OF C	CARTERS LAKE	E				ABSTRACTED BY	(SCN				
ORDER	3rd					ADJUSTED BY	(SCN			VERTICAL DATUM	NAVD88
DATE						CHECK BY	(SCN				
9/1/2009						RUN BY	(TRD				
											1
STATION	# OF	FORB	SUM OF ROD REAL	DINGS	DIFF OF	ELEVATIONS					
	TURNS		BS	FS	ELEV	UNADJUSTED	CORRECTION	ADJUSTED	MEAN	REMARKS	
CARTERS DA	M HEADWAT	TER									
LOOP 1									MEAN F & B		
9B-2A						1111.907	0.000	1111.907	1111.907	Elevation Held OPUS DB	New Aluminium CORPS Monument (Right Side Dam)
	1	В	6.309	4.825	1.484	ł			MEAN F & B		
TP-7				MEAN	1.484	1113.391	0.000	1113.391	1113.391		Turning Point
	1	в	5.627	4.371	1.256	6			MEAN F & B		
TP-6				MEAN	1.256	1114.647	-0.001	1114.646	1114.647		Turning Point
	1	В	4.724	4.702	0.022	2			MEAN F & B		
TP-5				MEAN	0.022	1114.669	-0.001	1114.668	1114.668		Turning Point
	1	В	4.961	4.479	0.482	2			MEAN F & B		
TP-4				MEAN	0.482	1115.151	-0.002	1115.149	1115.151		Turning Point
	1	в	4.571	5.002	-0.431				MEAN F & B		
TP-3				MEAN	-0.431	1114.720	-0.002	1114.718	1114.719		Turning Point
	1	В	4.432	3.255	1.177	7			MEAN F & B		
9B-2B				MEAN	1.177	1115.897	-0.003	1115.894	1115.894273		New Aluminium CORPS Monument (Right Side Dam)
	1	F	3.431	4.604	-1.173	8					
TP-3				MEAN	-1.173	1114.724	-0.003	1114.721			Turning Point
	1	F	5.032	4.6	0.432	2					
TP-4				MEAN	0.432	1115.156	-0.004	1115.152			Turning Point
	1	F	4.561	5.044	-0.483	8					
TP-5				MEAN	-0.483	1114.673	-0.004	1114.669			Turning Point
	1	F	4.726	4.746	-0.02	2					
TP-6				MEAN	-0.020	1114.653	-0.005	1114.648			Turning Point
	1	F	4.488	5.745	-1.257	7					
TP-7				MEAN	-1.257	1113.396	-0.005	1113.391			Turning Point
	1	F	5.106	6.59	-1.484	ł					
9B-2A				MEAN	-1.484	1111.912	-0.005	1111.907		Elevation Held OPUS DB	New Aluminium CORPS Monument (Right Side Dam)
	11	Sum Tums									

LEVEL ABSTRACT

SURVEY DATASHEET (Version 1.0)

PID: BE Designation: 9B Stamping: 9B Stability: Mo Setting: Lig Description: TH OF LC Mo OF CA Observed: 200 Source: OF	BL97 -2A 2A 2009 onument will pro- ght structures (of E MARK IS NI CARTERS DA CATED ON TH ARK IS 59,5'NW WATER SAFE RTERS DAM 1 09-09-09T12:21 US - page 5 090	bably hold position ther than listed below EAR A PARKING / .M. HE WEST SIDE OF V OF END POST O TTY SIGN, AND 47 ROAD :00Z 9.08	Close-up View					
REF_FRAME: N (CORS96)	AD_83	EPOCH: 2002.0000	SOU GEO	JRCE: NAVD88 (Computed)ID03)	using	UNITS: m	SET PROFILE	DETAILS
LAT: 34 LON: -8- ELL HT: 30 X: 48 Y: -52 Z: 36 ORTHO HT: 33	° 36 39,78335" 4° 40' 14,05014° 9,545 8123,963 232592,531 02613,531 8,910	\pm 0.004 m \pm 0.015 m \pm 0.060 m \pm 0.014 m \pm 0.052 m \pm 0.030 m \pm 0.073 m		NORTHING EASTING CONVERGENCE POINT SCALE COMBINED FACTOR	UTM 16 : 3832378.43 : 713586.356 : 1.32362311 : 1.00016232 : 1.00011372	SPC 100 9m 511394.9 im 653787.4 ° -0.28622 2 0.999926 2 0.999877	02(GA W) 448m 337m 312° 331 73	
CONTRIB waller Lowe Engin	UTED BY			Bloodtown		Nap data ©2	009 Tele Atlas	Carter Lake

The numerical values for this position solution have satisfied the quality control criteria of the National Geodetic Survey. The contributor has verified that the information submitted is accurate and complete.



Carters Lake Main Dam



Carters Lake Reregulatory Dam

EXHIBIT C

STANDING INSTRUCTIONS TO THE DAMTENDERS FOR WATER CONTROL

EXHIBIT C

STANDING INSTRUCTIONS TO THE DAMTENDERS FOR WATER CONTROL

1. BACKGROUND AND RESPONSIBILITIES

a. <u>General Information</u>. These Standing Instructions to the Project Operator for Water Control are written in compliance with Paragraph 9-2 of EM-1110-2-3600 (Engineering and Design, *Management of Water Control Systems*, 30 November 1987) and with ER-1110-2-240 (Engineering and Design, *Water Control Management*, 8 October 1982). A copy of these Standing Instructions must be kept on hand at the project site at all times. Any deviation from the Standing Instructions will require approval of the District Commander.

(1) **Project Purposes**. The Carters Project is operated for flood risk management, navigation, hydropower, recreation, fish and wildlife conservation, water quality and water supply. Water Control actions are in support of these project purposes and for purposes of the ACT River System.

(2) **Chain of Command**. The Project Operator is responsible to the Water Control Manager for all water control actions.

(3) **Structure**. The Project Site is located on the Coosawattee River in Murray County, Georgia. The Main Dam is located at mile 26.8 and the downstream Reregulation Dam is located at mile 25.3. The drainage area above Carters Main Dam is 374 square miles and the local drainage area for the Carters Reregulation Dam 146 square miles, for a total of 520 square miles for the Carters Project.

(4) **Operation and Maintenance (O&M)**. All O&M activities are the responsibility of the U.S. Army Corps of Engineers under the supervision of the Mobile District, Operations Division, and the direction of the Carters Operations Project Manager.

b. <u>Role of the Project Operator</u>. The term Project Operator refers to both the Carters Powerhouse operator and to the Carters Powerhouse personnel. Operation of the hydropower units and data reporting is the responsibility of the Carters Powerhouse operator.

(1) **Normal Conditions (dependent on day-to-day instruction)**. The Water Control Manager will coordinate the daily water control actions regarding hydropower releases with the Southeastern Power Administration (SEPA), and will notify the Project Operator of these changes. The Project Operator will then receive instructions from SEPA via hourly generation schedule updates. This daily communication will be increased to an hourly basis if the need develops. Daily generation schedules and updates are provided to the Water Management Section. The Water Control Manager will coordinate the daily water control actions regarding reregulation dam releases with the Carters powerhouse personnel. The required releases will be based on flows and stage as measured at USGS 02382500 Coosawattee River at Carters, Georgia.

(2) **Emergency Conditions (flood, drought, or special operations)**. During emergency conditions, the Project Operator will be instructed by the Water Control Manager on a daily or hourly basis for all water control actions. In the event that communications with Water Management Section are cut off, the Project Operator will continue to follow the water control plan as outlined in Section 7-05 and contact the Water Management Section as soon as communication is reestablished.

2. DATA COLLECTION AND REPORTING

a. <u>General</u>. Report hourly the pool elevation, tailwater elevation, turbine discharge, spillway discharge, capacity, and general project status on the computer and have it accessible to the Water Control Manager by computer network.

b. <u>Daily Reporting</u>. The Project Operator will record the following items daily and will report them by 6:30 AM (0630) Central Time to the Water Management Section either by computer network, by fax machine (251-694-4058), or by telephone conversation (690-690-2737):

(1) Pool elevation in feet above mean sea level at 4 am and 12 midnight (0400 and 2400) for the period since the last report.

(2) Average plant discharge in cubic feet per second for the first 4 hours of each day and for the 24 hours of the previous day.

(3) Average turbine discharge for the 24 hours of the previous day.

(4) Inflow to the lake in cubic feet per second for the first 4 hours of each day and for the 24 hours of the previous day.

(5) Average pumpback in cubic feet per second and megawatt-hours for the first 4 hours of each day and for the 24 hours of the previous day.

(6) Current day's generation schedule and previous day's actual generation in megawatt-hours. Include the schedule for the current day's generation.

(7) Total current generating capacity of the plant in megawatts.

c. <u>Gage Verification</u>. In accordance with the USACE Guidance Memorandum for Critical Gage Instrumentation dated 15 Dec 2006, the Carters Powerhouse personnel will perform gage reading verifications by providing the pool level automated instrumentation gage reading and staff gage readings. Weekly reports are sent to the Water Management Section which provide gage verification readings for all projects so that potential gage equipment issues can be addressed. In the event that the automated gage equipment malfunctions or if the difference in stage readings is greater than 0.3 feet, the Project Operator will report readings from the staff gage until the automated gage is rectified.

d. <u>Regional Hydro-meteorological Conditions</u>. The Project Operator will be informed by the Water Control Manager of any regional hydro-meteorological conditions that may impact water control actions.

3. WATER CONTROL ACTION AND REPORTING

a. <u>Normal Conditions</u>. During normal conditions, all releases will be made through the turbine units. The Project Operator will follow the Carters Dam Water Control Manual for normal water control actions and will report directly to the Water Control Manager.

b. <u>Emergency Conditions</u>. During high flows, the Project Operator will follow the instructions from the Water Control Manager and SEPA generation schedule updates regarding the suspension of releases during flood events and for resuming releases. If needed, the Project Operator will follow the instructions for sluice gate settings to achieve the desired release rate.

c. <u>Inquiries</u>. All significant inquiries received by the Project Operator from citizens, constituents, or interest groups regarding water control procedures or actions must be referred directly to the Water Control Manager.

d. <u>Water Control Problems</u>. The Project Operator must immediately notify the Water Control Manager, by the most rapid means available, in the event that an operational malfunction, erosion, or other incident occurs that could impact project integrity in general or water control capability in particular.

EXHIBIT D

Alabama-Coosa-Tallapoosa (ACT) River Basin, Drought Contingency Plan

DROUGHT CONTINGENCY PLAN

FOR

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

ALLATOONA DAM AND LAKE CARTERS DAM AND LAKE ALABAMA POWER COMPANY COOSA RIVER PROJECTS ALABAMA POWER COMPANY TALLAPOOSA RIVER PROJECTS ALABAMA RIVER PROJECTS



US Army Corps of Engineers ®

South Atlantic Division Mobile District

May 2015

DROUGHT CONTINGENCY PLAN FOR THE ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

I – INTRODUCTION

1-01. Purpose of Document. The purpose of this Drought Contingency Plan (DCP) is to provide a basic reference for water management decisions and responses to water shortage in the Alabama-Coosa-Tallapoosa (ACT) River Basin induced by climatological droughts. As a water management document it is limited to those drought concerns relating to water control management actions for federal U.S. Army Corps of Engineers (Corps) and Alabama Power Company (APC) dams. This DCP does not prescribe all possible actions that might be taken in a drought situation due to the long-term nature of droughts and unique issues that may arise. The primary value of this DCP is in documenting the overall ACT Basin Drought Management Plan for the system of Corps and APC projects; in documenting the data needed to support water management decisions related to drought regulation; and in defining the coordination needed to manage the ACT project's water resources to ensure that they are used in a manner consistent with the needs which develop during a drought. This DCP addresses the water control regulation of the five Corps impoundments and the APC Coosa and Tallapoosa projects (Table 1) in regard to water control regulation during droughts. Details of the drought management plan as it relates to each project and its water control regulation during droughts are provided in the water control manual within the respective project appendix to the ACT Basin Master Water Control Manual.

II – AUTHORITIES

2-01. <u>Authorities</u>. The following list provides the policies and guidance that are pertinent to the development of drought contingency plans and actions directed therein.

A. ER 1110-2-1941, "Drought Contingency Plans", dated 15 Sep 1981. This regulation provides policy and guidance for the preparation of drought contingency plans as part of the Corps of Engineers' overall water management activities.

B. ER 1110-2-8156, "Preparation of Water Control Manuals", dated 31 Aug 1995. This document provides a guide for preparing water control manuals for individual water resource projects and for overall river basins to include drought contingency plans.

C. ER 1110-2-240, "Water Control Management", dated 8 Oct 1982. This regulation prescribes the policies and procedures to be followed in water management activities including special regulations to be conducted during droughts. It also sets the responsibility and approval authority in development of water control plans.

D. EM 1110-2-3600, "Management of Water Control Systems", dated 30 Nov 1987. This guidance memorandum requires that the drought management plan be incorporated into the project water control manuals and master water control manuals. It also provides guidance in formulating strategies for project regulation during droughts.

	Owner/State/ Year Initially	Total storage at Full Pool	Conservation Storage	Percentage of ACT Basin Conservation Storage
Coosawattee River	Completed	(acre-reet)	(acre-ieet)	(70)
Carters Dam and Lake	Corps/GA/1974	383 565	141 402	5.9
Carters Reregulation Dam	Corps/GA/1974	17 500	16 000	0.1
Etowah River		,000		
Allatoona Dam and Lake	Corps/GA/1949	367 471	284 580	10.8
Hickory Log Creek Dam	CCMWA/Canton/ 2007	17,702	NA	NA
Coosa River				
Weiss Dam and Lake	APC/AL/1961	306,655	263,417	10.0
H. Neely Henry Dam and Lake	APC/AL/1966	120,853	118,210	4.5
Logan Martin Dam and Lake	APC/AL/1964	273,467	144,383	5.5
Lay Dam and Lake	APC/AL/1914	262,887	92,352	3.5
Mitchell Dam and Lake	APC/AL/1923	170,783	51,577	1.9
Jordan Dam and Lake	APC/AL/1928	236,130	19,057	0.7
Walter Bouldin Dam	APC/AL/1967	236,130	NA	
Tallapoosa River				
Harris Dam and Lake	APC/AL/1982	425,721	207,317	7.9
Martin Dam and Lake	APC/AL/1926	1,628,303	1,202,340	45.7
Yates Dam and Lake	APC/AL/1928	53,908	6,928	0.3
Thurlow Dam and Lake	APC/AL/1930	17,976	NA	
Alabama River				
Robert F. Henry Lock and Dam/R.E. "Bob" Woodruff Lake	Corps/AL/1972	247,210	36,450	1.4
Millers Ferry Lock and Dam/William "Bill" Dannelly Lake	Corps/AL/1969	346,254	46,704	1.8
Claiborne Lock and Dam and Lake	Corps/AL/1969	102,480	NA	

Table 1. Reservoir impoundments within the ACT River Basin

III – DROUGHT IDENTIFICATION

3-01. <u>Definition</u>. Drought can be defined in different ways - meteorological, hydrological, agricultural, and socioeconomic. In this DCP, the definition of drought used in the *National Study of Water Management During Drought* is used:

"Droughts are periods of time when natural or managed water systems do not provide enough water to meet established human and environmental uses because of natural shortfalls in precipitation or streamflow." That definition defines drought in terms of its impact on water control regulation, reservoir levels, and associated conservation storage. Water management actions during droughts are intended to balance the water use and water availability to meet water use needs. Because of hydrologic variability, there cannot be 100 percent reliability that all water demands are met. Droughts occasionally will be declared and mitigation or emergency actions initiated to lessen the stresses placed on the water resources within a river basin. Those responses are tactical measures to conserve the available water resources (USACE 2009).

3-02. <u>Drought Identification</u>. There is no known method of predicting how severe or when a drought will occur. There are, however, indicators that are useful in determining when conditions are favorable: below normal rainfall; lower than average inflows; and low reservoir levels, especially immediately after the spring season when rainfall and runoff conditions are normally the highest. When conditions indicate that a drought is imminent, the Corps Water Management Section (WMS) and APC will increase the monitoring of the conditions and evaluate the impacts on reservoir projects if drought conditions continue or become worse for 30-, 60-, or 90-day periods. Additionally, WMS and APC will determine if a change in operating criteria would aid in the total regulation of the river system and if so, what changes would provide the maximum benefits from any available water.

Various products are used to detect and monitor the extent and severity of basin drought conditions. One key indicator is the U.S. Drought Monitor available through the U.S. Drought Portal, <u>www.drought.gov</u>. The National Weather Service (NWS) Climate Prediction Center (CPC) also develops short-term (6- to 10-day and 8- to 14-day) and long-term (1-month and 3month) precipitation and temperature outlooks and a U.S. Seasonal Drought Outlook, which are useful products for monitoring dry conditions. The Palmer Drought Severity Index is also used as a drought reference. The Palmer index assesses total moisture by using temperature and precipitation to compute water supply and demand and soil moisture. It is considered most relevant for non-irrigated cropland and primarily reflects long-term drought. However, the index requires detailed data and cannot reflect an operation of a reservoir system. The Alabama Office of the State Climatologist also produces a Lawn and Garden Moisture Index for Alabama, Florida, Georgia, and South Carolina, which gives a basin-wide ability to determine the extent and severity of drought conditions. The runoff forecasts developed for both short- and longrange periods reflect drought conditions when appropriate. There is also a heavy reliance on the latest El Niño Southern Oscillation (ENSO) forecast modeling to represent the potential effects of La Niña on drought conditions and spring inflows. Long-range models are used with greater frequency during drought conditions to forecast potential effects on reservoir elevations, ability to meet minimum flows, and water supply availability. A long-term, numerical model, Extended Streamflow Prediction, developed by the NWS, provides probabilistic forecasts of streamflow and reservoir stages on the basis of climatic conditions, streamflow, and soil moisture. Extended Streamflow Prediction results are used in projecting possible future drought conditions. Other parameters and models can indicate a lack of rainfall and runoff and the degree of severity and continuance of a drought. For example, models using data of previous droughts or a percent of current to mean monthly flows with several operational schemes have proven helpful in forecasting reservoir levels for water management planning purposes. Other parameters considered during drought management are the ability of the various lakes to

meet the demands placed on storage, the probability that lake elevations will return to normal seasonal levels, basin streamflows, basin groundwater table levels, and the total available storage to meet hydropower marketing system demands.

3-03. <u>Historical Droughts</u>. Drought events have occurred in the ACT Basin with varying degrees of severity and duration. Five of the most significant historical basin wide droughts occurred in 1940-1941, 1954-1958, 1984-1989, 1999-2003, and 2006-2009. The 1984 to 1989 drought caused water shortages across the basin in 1986. This resulted in the need for the Corps to make adjustments in the water management practices. Water shortages occurred again from 1999 through 2002 and during 2007 through 2008. The 2006 to 2009 drought was the most devastating recorded in Alabama and western Georgia. Precipitation declines began in December 2005. These shortfalls continued through winter 2006-07 and spring 2007, exhibiting the driest winter and spring in the recorded period of record. The Corps and APC had water levels that were among the lowest recorded since the impoundments were constructed. North Georgia received less than 75 percent of normal precipitation (30-year average). The drought reached peak intensity in 2007, resulting in a D-4 Exceptional Drought Intensity (the worst measured) throughout the summer of 2007.

3-04. <u>Severity</u>. Water shortage problems experienced during droughts are not uniform throughout the ACT River Basin. Even during normal, or average, hydrologic conditions, various portions of the basin experience water supply problems. The severity of the problems are primarily attributed to the pattern of human habitation within the basin; the source of water utilized (surface water vs. ground water); and the characteristics of the water resources available for use. During droughts, these problems can be intensified. A severe drought in the basin develops when a deficiency of rainfall occurs over a long time period and has a typical duration of 18 to 24 months. The number of months of below normal rainfall is more significant in determining the magnitude of a drought in the basin than the severity of the deficiency in specific months. However, the severity of the rainfall deficiency during the normal spring wet season has a significant impact on the ability to refill reservoirs after the fall/winter drawdown period. Another confounding factor which influences droughts in the basin is the variability of rainfall over the basin, both temporarily and spatially.

IV – BASIN AND PROJECT DESCRIPTION

4-01. <u>Basin Description</u>. The headwater streams of the Alabama-Coosa-Tallapoosa (ACT) River Basin rise in the Blue Ridge Mountains of Georgia and Tennessee and flow southwest, combining at Rome, Georgia, to form the Coosa River. The confluence of the Coosa and Tallapoosa Rivers in central Alabama forms the Alabama River near Wetumpka, Alabama. The Alabama River flows through Montgomery and Selma and joins with the Tombigbee River at the mouth of the ACT Basin to form the Mobile River about 45 miles above Mobile, Alabama. The Mobile River flows into Mobile Bay at an estuary of the Gulf of Mexico. The total drainage area of the ACT Basin is approximately 22,739 square miles: 17,254 square miles in Alabama; 5,385 square miles in Georgia; and 100 square miles in Tennessee. A detailed description of the ACT River Basin is provided in the ACT Master Water Control Manual, Chapter II – Basin Description and Characteristics.

4-02. <u>**Project Description**</u>. The Corps operates five projects in the ACT Basin: Allatoona Dam and Lake on the Etowah River; Carters Dam and Lake and Reregulation Dam on the Coosawattee River; and Robert F. Henry Lock and Dam, Millers Ferry Lock and Dam, and Claiborne Lock and Dam on the Alabama River. Claiborne is a lock and dam without any appreciable water storage behind it. Robert F. Henry and Millers Ferry are operated as run-of-river projects and only very limited pondage is available to support hydropower peaking and other project purposes. APC owns and operates eleven hydropower dams in the ACT Basin; seven dams on the Coosa River and four dams on the Tallapoosa River. Figure 1 depicts the percentage of conservation storage of each project in the ACT Basin. Figure 2 shows the project locations within the basin. Figure 3 provides a profile of the basin and each project.



A. **General.** Of the 16 reservoirs (considering Jordan Dam and Lake and Bouldin Dam as one reservoir and Carters Lake and Carters Reregulation Dam as one reservoir), Lake Martin on the Tallapoosa River has the greatest amount of storage, containing 45.7 percent of the conservation storage in the ACT Basin. Allatoona Lake, R.L. Harris Lake, Weiss Lake, and Carters Lake are the next four largest reservoirs in terms of storage. APC controls approximately 80 percent of the available conservation storage; Corps projects (Robert F. Henry Lock and Dam, Millers Ferry Lock and Dam, Allatoona Lake, and Carters Lake) control 20 percent. The two most upstream Corps reservoirs, Allatoona Lake and Carters Lake, account for 16.8 percent of the total basin conservation storage.



Figure 2. Alabama-Coosa-Tallapoosa River Basin Project Location Map



Figure 3. Alabama-Coosa-Tallapoosa River Basin Profile Map

B. Allatoona Dam and Lake. The Corps' Allatoona Dam on the Etowah River creates the 11,862 acres Allatoona Lake. The project's authorization, general features, and purposes are described in the Allatoona Dam and Lake Water Control Manual. The Allatoona Lake top of conservation pool is elevation 840 feet NGVD29 during the late spring and summer months (May through August); transitions to elevation 835 feet NGVD29 in the fall (October through mid-November); transitions to a winter drawdown to elevation 823 feet NGVD29 (1-15 January); and refills back to elevation 840 feet NGVD29 during the winter and spring wet season as shown in the water control plan guide curve (Figure 4). However, the lake level may fluctuate significantly from the guide curve over time, dependent primarily upon basin inflows but also influenced by project operations, evaporation, withdrawals, and return flows. A minimum flow of about 240 cfs is continuously released through a small unit, which generates power while providing a constant flow to the Etowah River downstream. Under drier conditions when basin inflows are reduced, project operations are adjusted to conserve storage in Allatoona Lake while continuing to meet project purposes in accordance with four action zones as shown on Figure 4.



Figure 4. Allatoona Lake Guide Curve and Action Zones

C. Carters Dam and Lake and Reregulation Dam. Carters Lake is formed by Carters Dam, a Corps' reservoir on the Coosawattee River in northwest Georgia upstream of Rome, Georgia. The Carters project is a pumped-storage peaking facility that utilizes a Reregulation Dam and storage pool in conjunction with the main dam and lake. The project's authorization, general
features, and purposes are described in the Carters Dam and Lake and Regulation Dam water control manual. The Carters Lake top of conservation pool is elevation 1,074 feet NGVD29 from 1 May to 1 November; transitioning to elevation 1,072 feet NGVD29 between 1 November and 1 December; remains at elevation 1,072 feet NGVD 29 from 1 December to April; then transitioning back to 1,074 feet NGVD29 between 1 April and 1 May. This is shown in the water control plan guide curve (Figure 5). As expected with a peaking/pumped storage operation, both Carters Lake and the reregulation pool experience frequent elevation changes. Typically, water levels in Carters Lake vary no more than 1 to 2 feet per day. The reregulation pool will routinely fluctuate by several feet (variable) daily as the pool receives peak hydropower discharges from Carters Lake and serves as the source for pumpback operations into Carters Lake during non-peak hours. The reregulation pool will likely reach both its normal maximum elevation of 696 feet NGVD29 and minimum elevation of 677 feet NGVD29 at least once each week. However, the general trend of the lake level may fluctuate significantly from the guide curve over time, dependent primarily upon basin inflows but also influenced by project operations and evaporation. Carters Regulation Dam provides a seasonal varying minimum release to the Coosawattee River for downstream fish and wildlife conservation. Under drier conditions when basin inflows are reduced, project operations are adjusted to conserve storage in Carters Lake while continuing to meet project purposes in accordance with action zones as shown on Figure 5. In Zone 2, Carters Regulations Dam releases are reduced to 240 cfs.



Figure 5. Carters Lake Guide Curve and Action Zones

D. **APC Coosa River Projects**. APC owns and operates the Coosa Hydro system of projects at Weiss Lake, H. Neely Henry Lake, Logan Martin Lake, Lay Lake, Mitchell Lake, and Jordan/Bouldin Dam and Lake on the Coosa River in the ACT Basin. APC Coosa River

projects function mainly to generate electricity by hydropower. In addition, the upper three projects (Weiss, H. Neely Henry, and Logan Martin) operate pursuant to Public Law 83-436 regarding the requirement for the projects to be operated for flood risk management and navigation in accordance with reasonable rules and regulations of the Secretary of the Army. The rules and regulations are addressed in a memorandum of understanding between the Corps and APC (Exhibit B of the Master Water Control Manual, Alabama-Coosa-Tallapoosa (ACT) River Basin, Alabama, Georgia), in individual water control manuals for the three projects, and in this ACT Basin DCP. The Weiss Lake is on the Coosa River in northeast Alabama, about 80 mi northeast of Birmingham, Alabama, and extends into northwest Georgia for about 13 miles upstream on the Coosa River. The dam impounds a 30,027 acres reservoir (Weiss Lake) at the normal summer elevation of 564 feet NGVD29 as depicted in the regulation guide curve shown in Figure 6 (source APC). The H. Neely Henry Lake is on the Coosa River in northeast Alabama, about 60 miles northeast of Birmingham, Alabama. The dam impounds an 11,200 acres reservoir at the normal summer elevation of 508 feet NGVD29 as depicted in the regulation guide curve shown in Figure 7 (source APC). The Logan Martin Lake is in northeast Alabama on the Coosa River, about 40 miles east of Birmingham, Alabama. The dam impounds a 15,269-acre reservoir at the normal summer elevation of 465 feet NGVD29 as depicted in the regulation guide curve shown in Figure 8 (source APC). The projects' authorizations, general features, and purposes are described in the Weiss, H. Neely Henry, and Logan Martin water control manual appendices to the ACT Basin Master Water Control Manual.



Figure 6. Weiss Lake Guide Curve



Figure 7. H. Neely Henry Lake Guide Curve



Figure 8. Logan Martin Lake Guide Curve

The downstream Coosa River APC run-of-river hydropower projects (Lay Dam and Lake, Mitchell Dam and Lake, and Jordan/Bouldin Dams and Lake) have no appreciable storage and are operated in conjunction with the upstream Coosa projects to meet downstream flow requirements and targets in support of the ACT Basin Drought Plan and navigation.

E. **APC Tallapoosa River Projects**. APC owns and operates the Tallapoosa River system of projects at Harris Dam and Lake, Martin Dam and Lake, Yates Dam, and Thurlow Dam in the ACT Basin. APC Tallapoosa River projects function mainly to generate electricity by hydropower. In addition, the Robert L. Harris Project operates pursuant to 33 CFR, Chapter II, Part 208, Section 208.65 regarding the requirement for the project to be operated for flood risk management and navigation in accordance with reasonable rules and regulations of the Secretary of the Army. The rules and regulations prescribed are described in a memorandum of understanding between the Corps and APC, individual water control manuals for the APC projects, and this DCP.



Figure 9. Robert L. Harris Lake Guide Curve



Figure 10. Martin Lake Guide Curve

F. **Corps Alabama River Projects**. The Corps operates three run-of-river lock and dam projects (Robert F. Henry, Millers Ferry, Claiborne) on the Alabama River in the lower ACT Basin to support commercial navigation. Claiborne Lake, together with R.E. "Bob" Woodruff Lake and William "Bill" Dannelly Lake, are collectively referred to as the Alabama River Lakes. The primary location used for communicating the available reliable navigation depth is the Claiborne Lock and Dam tailwater elevation. The water surface elevation is related to the available navigation depth based on the latest hydrographic surveys of the lower Alabama River reach downstream of Claiborne.

(1) <u>Robert F. Henry</u>. The R.E. "Bob" Woodruff Lake is created by the Robert F. Henry Lock and Dam on the Alabama River at river mile 236.3. R.E. "Bob" Woodruff Lake extends from the Robert F. Henry Lock and Dam upstream to the Walter Bouldin Dam. In addition to hydropower and navigation, R.E. "Bob" Woodruff Lake provides recreation and fish and wildlife conservation. R.E. "Bob" Woodruff Lake is 77 miles long and averages 1,300 feet wide. It has a surface area of 12,510 acres and a storage capacity of 234,200 acre-feet at a normal pool elevation of 126 feet NGVD29. Lake levels are typically fairly stable with minimal fluctuation between the operating pool elevation limits, 123 feet NGVD29 to 126 feet NGVD29. The emergency drawdown pool elevation is 122 feet NGVD29. An authorized 9-foot-deep by 200-foot-wide navigation channel exists over the entire length of the lake. The Jones Bluff hydropower plant generating capacity is 82 MW (declared value). The lake is a popular recreation destination, receiving up to two million visitors annually.

(2) <u>Millers Ferry</u>. The William "Bill" Dannelly Lake is created by the Millers Ferry Lock and Dam on the Alabama River at river mile 133. William "Bill" Dannelly Lake is 103 miles long and averages almost 1,400 feet wide. The reservoir has a surface area of 18,500 acres and a storage capacity of 346,254 acre-feet at a normal full pool elevation of 80 feet NGVD29. Lake levels remain fairly stable on a day-to-day basis with minimal fluctuation between the operating pool elevation limits, 79 feet NGVD29 to 80 feet NGVD29. It has an authorized 9-foot-deep by 200-foot-wide navigation channel which extends the entire length of the reservoir. The facility is a multipurpose reservoir constructed by the Corps for both navigation and hydropower. The reservoir also provides recreational benefits and has lands managed for wildlife mitigation. The Millers Ferry hydropower plant generating capacity is 90 MW (declared value). The reservoir provides ample recreation opportunities. Recreation visitors number three million annually.

(3) <u>Claiborne</u>. Claiborne Lake is created by the Claiborne Lock and Dam on the Alabama River at river mile 72.5. The lake is similar to a wide river, averaging about 800 feet wide, with a surface area of 5,930 acres. Claiborne Lake extends 60 miles upstream to the Millers Ferry Lock and Dam. Storage capacity in the lake is 96,360 acre-feet at a normal pool elevation of 35 feet NGVD29. The operating pool elevation limits are between 32 feet NGVD29 and 36 feet NGVD29. The lake has an authorized 9-foot-deep, 200-foot-wide navigation channel extending its entire length. The primary purpose of the Corps project is navigation. No hydropower generating capability exists at the project. The lake also provides recreation benefits and lands managed for wildlife mitigation.

G. As other ACT water management objectives are addressed, lake levels might decline during prime recreation periods. Drought conditions will cause further drawdowns in lake levels. While lake levels will be slightly higher than what would naturally occur if no specific drought actions are taken, reservoir levels will decline thus triggering impacts associated with reaching initial recreation and water access limited levels. Large reservoir drawdowns impact recreational use: access to the water for boaters and swimmers is inhibited; submerged hazards (e.g., trees, shoals, boulders) become exposed or nearly exposed, posing safety issues; and exposed banks and lake bottoms become unsightly and diminish the recreation experience. Consequently certain levels are identified in each Corps impoundment at which recreation would be affected. The Initial Impact level (IIL) represents the level at which recreation impacts are first observed (i.e., some boat launching ramps are unusable, most beaches are unusable or minimally usable, and navigation hazards begin to surface). The Recreation Impact level (RIL) defines the level at which major impacts on concessionaires and recreation are observed (more ramps are not usable, all beaches are unusable, boats begin having problems maneuvering in and out of marina basin areas, loss of retail business occurs). The level at which severe impacts are observed in all aspects of recreational activities is called the Water Access Limited level (WAL). At this point, all or almost all boat ramps are out of service, all swimming beaches are unusable, major navigation hazards occur, channels to marinas are impassable and/or wet slips must be relocated, and a majority of private boat docks are unusable. The individual project water control manuals describe the specific impact levels at each project and provide information regarding the effects of the water control plans on recreation.

V – WATER USES AND USERS

5-01. <u>Water Uses and Users</u>.

A. Uses – The ACT Basin rivers and lakes provide for wastewater dilution, M&I water supply, fish and wildlife propagation, hydropower generation, and recreational boating and fishing.

B. Users – The following tables list the surface water uses and water users within Georgia and Alabama in the ACT Basin.

Water use category	Quantity (mgd)	% of total
Total Use	788.98	100%
Public Supply	154.78	19.6%
Domestic and Commercial	0.30	0.0%
Industrial and Mining	32.49	4.1%
Irrigation	11.31	1.4%
Livestock	16.18	2.1%
Thermoelectric Power Generation	573.92	72.8%

Table 2. Surface water use: ACT Basin (Georgia 2005)

River basin	Permit holder	Permit number	County	Source water	Permit limit max day (mgd)	Permit limit monthly average (mgd)
Coosa River	Basin (Georgia)—upstream co	ounties to downs	stream countie	S		
Coosa	Dalton Utilities, Conasauga R	155-1404-01	Whitfield	Conasauga River	49.400	40.300
Coosa	Dalton Utilities, Mill Creek	155-1404-02	Whitfield	Mill Creek	13.200	7.500
Coosa	Dalton Utilities, Coahulla Cr	155-1404-03	Whitfield	Coahulla Creek	6.000	5.000
Coosa	Dalton Utilities, Freeman Sprngs	155-1404-04	Whitfield	Freeman Springs	2.000	1.500
Coosa	Dalton Utilities - River Road	155-1404-05	Whitfield	Conasauga River	35.000	18.000
Coosa	Chatsworth WW Commission	105-1405-01	Murray	Holly Creek	1.100	1.000
Coosa	Chatsworth WW Commission	105-1405-02	Murray	Eton Springs	1.800	1.800
Coosa	Chatsworth WW Commission	105-1409-01	Murray	Carters Lake	2.550	2.300
Coosa	Chatsworth, City of	105-1493-02	Murray	Coosawattee River	2.200	2.000
Coosa	Ellijay, City of - Ellijay R	061-1407-01	Gilmer	Ellijay River	0.550	0.450
Coosa	Ellijay - Gilmer County W & S Authority	061-1408-01	Gilmer	Cartecay River	4.000	4.000
Coosa	Calhoun, City of	064-1411-03	Gordon	Big Spring	7.000	6.000
Coosa	Calhoun, City of	064-1412-01	Gordon	City Of Calhoun Spring	0.638	0.537
Coosa	Calhoun, City of	064-1492-02	Gordon	Oostanaula River	6.200	3.000
Coosa	Calhoun, City of	064-1493-01	Gordon	Coosawattee River	18.000	16.000
Coosa	Jasper, City of	112-1417-02	Pickens	Long Swamp Creek	1.000	1.000
Coosa	Bent Tree Community, Inc.	112-1417-03	Pickens	Chestnut Cove Creek and unnamed creek	0.250	0.230
Coosa	Bent Tree Community, Inc.	112-1417-04	Pickens	Lake Tamarack	0.250	0.230
Coosa	Big Canoe Utilities Company, Inc.	112-1417-05	Pickens	Lake Petit	1.000	1.000
Coosa	Big Canoe Utilities Company, Inc.	112-1417-06	Pickens	Blackwell Creek	2.650	2.650
Coosa	Etowah Water & Sewer Authority	042-1415-01	Dawson	Etowah River	5.500	4.400
Coosa	Cherokee County Water & Sewerage Auth	028-1416-01	Cherokee	Etowah River	43.200	36.000
Coosa	Gold Kist, Inc	028-1491-03	Cherokee	Etowah River	5.000	4.500
Coosa	Canton, City of	028-1491-04	Cherokee	Etowah River	23.000	18.700
Coosa	Canton, City of (Hickory Log Creek)	028-1491-05	Cherokee	Etowah River	39.000	39.000
Coosa	Bartow County Water Department	008-1411-02	Bartow	Bolivar Springs	0.800	0.800
Coosa	Adairsville, City of	008-1412-02	Bartow	Lewis Spring	5.100	4.100
Coosa	New Riverside Ochre Company, Inc.	008-1421-01	Bartow	Etowah River	5.000	5.000
Coosa	New Riverside Ochre Company, Inc.	008-1421-02	Bartow	Etowah River	6.000	6.000

Table 3. M&I surface water withdrawal permits in the ACT Basin (Georgia)

River basin	Permit holder	Permit number	County	Source water	Permit limit max day (mgd)	Permit limit monthly average (mgd)
Coosa	Emerson, City of	008-1422-02	Bartow	Moss Springs	0.630	0.500
Coosa	Gerdau AmeriSteel US, Inc. – Cartersville Steel Mill	008-1423-01	Bartow	Pettit Creek	2.000	1.500
Coosa	Baroid Drilling Fluids, Inc.	008-1423-02	Bartow	Etowah River	3.400	2.500
Coosa	Cartersville, City of	008-1423-04	Bartow	Etowah River	26.420	23.000
Coosa	Georgia Power Co Plant Bowen	008-1491-01	Bartow	Etowah River	520.000	85.000
Coosa	CCMWA	008-1491-05	Bartow	Allatoona Lake	86.000	78.000
Coosa	Cartersville, City of	008-1491-06	Bartow	Allatoona Lake	21.420	18.000
Coosa	La Fayette, City of Dry Creek	146-1401-01	Walker	Dry Creek	1.000	0.900
Coosa	La Fayette, City of Big Spring	146-1401-02	Walker	Big Spring	1.650	1.310
Coosa	Mount Vernon Mills - Riegel Apparel Div.	027-1401-03	Chattooga	Trion Spring	9.900	6.600
Coosa	Summerville, City of	027-1402-02	Chattooga	Raccoon Creek	3.000	2.500
Coosa	Summerville, City of	027-1402-04	Chattooga	Lowe Spring	0.750	0.500
Coosa	Mohawk Industries, Inc.	027-1402-05	Chattooga	Chattooga R./ Raccoon Cr.	4.500	4.000
Coosa	Oglethorpe Power Corp.	057-1402-03	Floyd	Heath Creek	3,838.000	3,030.000
Coosa	Floyd County - Brighton Plant	057-1414-02	Floyd	Woodward Creek	0.800	0.700
Coosa	Cave Spring, City of	057-1428-06	Floyd	Cave Spring	1.500	1.300
Coosa	Floyd County	057-1428-08	Floyd	Old Mill Spring	4.000	3.500
Coosa	Berry Schools, The (Berry College)	057-1429-01	Floyd	Berry (Possum Trot) Reservoir	1.000	0.700
Coosa	TIN Inc.	057-1490-01	Floyd	Coosa River	34.000	32.000
Coosa	Georgia Power Co Plant Hammond	057-1490-02	Floyd	Coosa River	655.000	655.000
Coosa	Rome, City of	057-1492-01	Floyd	Oostanaula & Etowah R	18.000	16.400
Coosa	Rockmart, City of	115-1425-01	Polk	Euharlee Creek	2.000	1.500
Coosa	Vulcan Construction Materials, L.P.	115-1425-03	Polk	Euharlee Creek	0.200	0.200
Coosa	Cedartown, City of	115-1428-04	Polk	Big Spring	3.000	2.600
Coosa	Polk County Water Authority	115-1428-05	Polk	Aragon, Morgan, Mulco Springs	1.600	1.100
Coosa	Polk County Water Authority	115-1428-07	Polk	Deaton Spring	4.000	4.000
Tallapoosa R	River Basin (Georgia)					

Table 3 (continued). M&I surface water withdrawal permits in the ACT Basin (Georgia)

Tallapoosa	Haralson County Water Authority	071-1301-01	Haralson	Tallapoosa River	3.750	3.750
Tallapoosa	Bremen, City of	071-1301-02	Haralson	Beech Creek & Bremen Reservoir (Bush Creek)	0.800	0.580

River basin	Permit holder	Permit number	County	Source water	Permit limit max day (mgd)	Permit limit monthly average (mgd)
Tallapoosa	Bowdon, City of Indian	022-1302-01	Carroll	Indian Creek	0.400	0.360
Tallapoosa	Southwire Company	022-1302-02	Carroll	Buffalo Creek	2.000	1.000
Tallapoosa	Villa Rica, City of	022-1302-04	Carroll	Lake Paradise & Cowens Lake	1.500	1.500
Tallapoosa	Carrollton, City of	022-1302-05	Carroll	Little Tallapoosa River	12.000	12.000
Tallapoosa	Bowdon, City of Lake Tysinger	022-1302-06	Carroll	Lake Tysinger	4.100	3.500

Table 3 (continued). M&I surface water withdrawal permits in the ACT Basin (Georgia)

Source: GAEPD 2009a

Table 4. M&I surface water withdrawals in the ACT Basin (Georgia)

Basin (subbasin)	Withdrawal by	County	Withdrawal (mgd)
Coosa River Basin (Georgia)			
Coosa (Conasauga)	Dalton Utilities	Whitfield	35.38
Coosa (Conasauga)	City of Chatsworth	Murray	1.26
Coosa (Coosawattee)	Ellijay-Gilmer County Water System	Gilmer	3.12
Coosa (Coosawattee)	City of Fairmount	Gordon	0.06
Coosa (Oostanaula)	City of Calhoun	Gordon	9.10
Coosa (Etowah)	Big Canoe Corporation	Pickens	0.48
Coosa (Etowah)	City of Jasper	Pickens	1.00
Coosa (Etowah)	Bent Tree Community	Pickens	0.07
Coosa (Etowah)	Lexington Components Inc (Rubber)	Pickens	0.01
Coosa (Etowah)	Etowah Water and Sewer Authority	Dawson	1.50
Coosa (Etowah)	Town of Dawsonville	Dawson	0.10
Coosa (Etowah)	City of Canton	Cherokee	2.83
Coosa (Etowah)	Cherokee County Water System	Cherokee	15.81
Coosa (Etowah)a	Gold Kist, Inc.	Cherokee	1.94
Coosa (Etowah)	City of Cartersville	Bartow	13.26
Coosa (Etowah)	New Riverside Ochre Company, Inc (Chemicals)	Bartow	1.67
Coosa (Etowah)	Gerdau AmeriSteel US, Inc. – Cartersville Steel Mill (Primary metals)	Bartow	0.16
Coosa (Etowah)	Georgia Power Co – Plant Bowen	Bartow	38.92
Coosa (Etowah)	CCMWA	Bartow	44.42
Coosa (Upper Coosa)	City of Lafayette	Walker	1.20
Coosa (Upper Coosa)	City of Summerville	Chattooga	2.05
Coosa (Upper Coosa)	Mount Vernon Mills – Riegel Apparel Division (Textiles)	Chattooga	2.74
Coosa (Oostanaula)	City of Cave Spring (Domestic/Commercial)	Floyd	0.30

Basin (subbasin)	Withdrawal by	County	Withdrawal (mgd)
Coosa (Etowah / Oostanaula)	City of Rome	Floyd	9.98
Coosa (Upper Coosa)	Floyd County Water System	Floyd	2.57
Coosa (Upper Coosa)	Inland-Rome Inc. (Paper)	Floyd	25.74
Coosa (Upper Coosa)	Georgia Power Co - Plant Hammond	Floyd	535.00
Coosa (Upper Coosa)	Polk County Water Authority	Polk	2.22
Coosa (Etowah)	Vulcan Construction Materials	Polk	0.09
Tallapoosa River Basin (Georgia)			
Tallapoosa (Upper)	City of Bremen	Haralson	0.32
Tallapoosa (Upper)	Haralson County Water Authority	Haralson	2.05
Tallapoosa (Upper)	City of Bowdon	Carroll	0.75
Tallapoosa (Upper)	Southwire Company	Carroll	0.09
Tallapoosa (Upper)	City of Carrollton	Carroll	5.37
Tallapoosa (Upper)	City of Temple	Carroll	0.26
Tallapoosa (Upper)	City of Villa Rica	Carroll	0.58
Tallapoosa (Upper)	Carroll County Water System	Carroll	4.08

Table 4 (continued)	M&I surface water	withdrawals in the	ACT Basin	(Georgia)
---------------------	-------------------	--------------------	------------------	-----------

Table 5. Surface water use - ACT Basin (Alabama, 2005) (mgd)

ACT subbasin	HUC	Public supply	Industrial	Irrigation	Livestock	Thermo- electric	Total, by Subbasin
Upper Coosa	03150105	2.12	0	3.10	0.40	0	5.62
Middle Coosa	03150106	33.24	65.83	7.91	0.87	142.68	250.53
Lower Coosa	03150107	10.96	0.89	5.10	0.35	812.32	829.62
Upper Tallapoosa	03150108	0.90	0	0.15	0.40	0	1.45
Middle Tallapoosa	03150109	19.09	0	0.52	0.32	0	19.93
Lower Tallapoosa	03150110	38.22	2.23	4.22	0.28	0	44.95
Upper Alabama	03150201	10.40	30.63	3.84	0.84	4.14	49.85
Cahaba	03150202	52.90	0	3.49	0.25	0	56.64
Middle Alabama	03150203	0	21.04	1.73	0.48	0	23.25
Lower Alabama	03150204	0	54.61	0.64	0.02	0	55.27
Total - By Use Category	ý	167.83	175.23	30.70	4.21	959.14	1337.11

Source: Hutson et al. 2009

Basin (subbasin)	Withdrawal by	County	Withdrawal (mgd)
Coosa River Basin (Alabam	a)	1	
Coosa (Upper)	Centre Water Works & Sewer Board	Cherokee	1.19
Coosa (Upper)	Piedmont Water Works & Sewer Board	Calhoun	0.93
Coosa (Middle)	Jacksonville Water Works & Sewer Board	Calhoun	1.34
Coosa (Middle)	Anniston Water Works & Sewer Board	Calhoun	0.08
Coosa (Middle)	Fort Payne Water Works Board	DeKalb	8.10
Coosa (Middle)	Goodyear Tire and Rubber Company	Etowah	9.87
Coosa (Middle)	Gadsden Water Works & Sewer Board	Etowah	14.86
Coosa (Middle)	Alabama Power Co – Gadsden Steam Plant	Etowah	142.68
Coosa (Middle)	SIC 32 – Unnamed Stone, Glass, Clay, and/or Concrete Products	St. Clair	3.49
Coosa (Middle)	Talladega/Shelby Water Treatment Plant	Talladega	6.44
Coosa (Middle)	Talladega County Water Department	Talladega	0.81
Coosa (Middle)	Talladega Water Works & Sewer Board	Talladega	1.62
Coosa (Middle)	Bowater Newsprint, Coosa Pines Operation	Talladega	52.47
Coosa (Lower)	Sylacauga Utilities Board	Talladega	3.25
Coosa (Lower)	SIC 22 – Unnamed Textile	Talladega	0.89
Coosa (Lower)	Goodwater Water Works & Sewer Board	Coosa	0.46
Coosa (Lower)	Alabama Power Co – E.C. Gaston Plant	Shelby	812.32
Coosa (Lower)	Clanton Waterworks & Sewer Board	Chilton	1.79
Coosa (Lower)	Five Star Water Supply	Elmore	5.46
Tallapoosa River Basin (Ala	abama)		
Tallapoosa (Upper)	Heflin Water Works	Cleburne	0.51
Tallapoosa (Upper)	Wedowee Gas, Water, and Sewer	Randolph	0.39
Tallapoosa (Middle)	Roanoke Utilities Board	Randolph	1.29
Tallapoosa (Middle)	Clay County Water Authority	Clay	1.87
Tallapoosa (Middle)	Lafayette	Chambers	0.53
Tallapoosa (Middle)	Central Elmore Water & Sewer Authority	Elmore	4.83
Basin (subbasin)	Withdrawal by	County	Withdrawal (mgd)
Tallapoosa (Middle)	Alexander City Water Department	Tallapoosa	10.57
Tallapoosa (Lower)	West Point Home, Inc	Lee	2.23
Tallapoosa (Lower)	Opelika Water Works Board	Lee	2.61
Tallapoosa (Lower)	Auburn Water Works Board	Lee	5.75
Tallapoosa (Lower)	Tallassee	Tallapoosa	1.98
Tallapoosa (Lower)	Tuskegee Utilities	Macon	2.71
Tallapoosa (Lower)	Montgomery Water Works & Sewer Board	Montgomery	25.17
Alabama River Basin			
Alabama (Upper)	Montgomery Water Works & Sewer Board	Montgomery	10.40
Alabama (Upper)	International Paper	Autauga	30.63
Alabama (Upper)	Southern Power Co – Plant E. B. Harris	Autauga	4.14
Alabama (Cahaba)	Birmingham Water Works & Sewer Board	Shelby	52.90
Alabama (Middle)	International Paper – Pine Hill	Wilcox	21.04
Alabama (Lower)	Alabama River Pulp Company	Monroe	54.61

Table 6.	M&I surface water	withdrawals in the	e ACT Basin	(Alabama)
----------	-------------------	--------------------	-------------	-----------

Source: Hutson et al. 2009

VI. – CONSTRAINTS

6-01. General. The availability of water resources in the ACT Basin is constrained by existing water supply storage contracts, Corps water control manuals, minimum flow requirements from Allatoona and Carters Dams, APC FERC licenses, Corps-APC Memorandum of Understanding, and industrial water quality flow needs. Existing water supply storage contracts do not include the use of the inactive storage pool and would require developing and implementing an emergency storage contract in order to access this water resource. Each Corps project has a water control manual that specifies operational requirements for varying basin conditions and requires a deviation approval to operate outside the parameters established by the manual. The Allatoona Project has a minimum flow release requirement of 240 cfs for downstream purposes. The Carters Project has a seasonally varying minimum flow release requirement that ranges from 250 – 865 cfs during normal conditions and a minimum of 240 cfs during low flow conditions. The APC projects are operated under FERC licenses which define specific operational requirements for each project and require approval from FERC and possibly the Corps and State agencies before any revised operations could be implemented. The Corps and APC projects are also operated under the rules and regulations found in the Corps-APC Memorandum of Understanding, which describes operational requirements for flood conditions and navigation within the ACT Basin. Some industrial NPDES permits within the ACT Basin have water quality discharge limitations which are impacted by the volume of water flow in the river.

VII – DROUGHT MANAGEMENT PLAN

7-01. <u>General</u>. The Drought Contingency Plan (DCP) for the ACT Basin implements drought conservation actions on the basis of composite system storage, state line flows, and basin inflow as triggers to drive drought response actions. The DCP also recognizes that a basin-wide drought plan must incorporate variable hydropower generation requirements from its headwater projects in Georgia (Allatoona Dam and Carters Dam), a reduction in the level of navigation service provided on the Alabama River as storage across the basin declines, and that environmental flow requirements must still be met to the maximum extent practicable. The ACT basin-wide drought plan is composed of three components — Headwater regulation at Allatoona Lake and Carters Lake in Georgia; Regulation at APC projects on the Coosa and Tallapoosa Rivers; and Downstream Alabama River regulation at Corps projects downstream of Montgomery, Alabama.

A. **Headwater Regulation for Drought at Allatoona Lake and Carters Lake**. Drought regulation at Allatoona Lake and Carters Lake consists of progressively reduced hydropower generation as pool levels decline in accordance with the conservation storage action zones established in the projects' water control plans. For instance, when Allatoona Lake is operating in normal conditions (Conservation storage Zone 1); hydropower generation typically ranges from 0 to 4 hours per day. However, as the pool drops to lower action zones during drought conditions, generation could be reduced to 0 to 2 hours per day. As Carters Lake pool level might drop into a conservation storage Zone 2, seasonal varying minimum target flows would be

reduced to 240 cfs. The water control manual for each project describes the drought water control regulation plan in more detail.

B. Drought Regulation at APC Projects on the Coosa, Tallapoosa, and Alabama River.

Regulation guidelines for the Coosa, Tallapoosa, and Alabama Rivers have been defined in a drought regulation matrix (Table 7) on the basis of a Drought Intensity Level (DIL). The DIL is a drought indicator, ranging from one to three. The DIL is determined on the basis of three basin drought criteria (or triggers). A DIL from 1 to 3 indicates some level of drought conditions. The DIL increases as more of the drought indicator thresholds (or triggers) occur. The drought regulation matrix defines minimum average daily flow requirements on a monthly basis for the Coosa, Tallapoosa, and Alabama Rivers as a function of the DIL and time of year. The combined occurrences of the drought triggers determine the DIL. Three intensity levels for drought operations are applicable to APC projects.

- DIL 1 (moderate drought) 1 of 3 triggers occur
- DIL 2 (severe drought) 2 of 3 triggers occur
- DIL 3 (exceptional drought) all 3 triggers occur

(1) <u>Drought Indicators</u>. The indicators used to determine drought intensity include the following:

1. Low basin inflow. The total basin inflow needed is the sum of the total filling volume plus 4,640 cfs. The total filling volume is defined as the volume of water required to return the pool to the top of the conservation guide curve and is calculated using the area-capacity tables for each project. Table 8 lists the monthly low basin inflow criteria. The basin inflow value is computed daily and checked on the first and third Tuesday of the month. If computed basin inflow is less than the value required, the low basin inflow indicator is triggered. The basin inflow is total flow above the APC projects excluding Allatoona Lake and Carters Lake. It is the sum of local flows, minus lake evaporation and diversions. Figure 11 illustrates the local inflows to the Coosa and Tallapoosa Basins. The basin inflow computation differs from the navigation basin inflow, because it does not include releases from Allatoona Lake and Carters Lake. The intent is to capture the hydrologic condition across APC projects in the Coosa and Tallapoosa Basins.

	Jan	Feb	Mar	Apr	Мау	J	un	Jul	Aug	Sep	Oct	Nov	Dec
se ^a t						No	ormal Operat	tions	0				
ugh vel ons	DIL 1: LOW BASIN INNOWS OF LOW COMPOSITE OF LOW STATE LINE FLOW												
Le	DIL 2: DIE 1 Chema + (Low Dasin millows of Low Composite of Low State Line Flow) DIL 3: Low Basin Inflows + Low Composite + Low State Line Flow												
Re													
	Normal Operation: 2,000 cfs 4,000 (8,000) 4,000 – 2,000 Normal Operation: 2,000 cfs										cfs		
r Flow ^b	Jord	dan 2,000 +,	/-cfs		4,000 +/- cfs	5	6/15 Linear Ramp down	Jordan 2,000 +/-cfs		/-cfs	Jo	rdan 2,000 +	-/-cfs
osa Rive	Jordan '	1,600 to 2,0	00 +/-cfs		2,500 +/- cfs	3	6/15 Linear Ramp down	Jord	dan 2,000 +/	/-cfs	Jordan	1,600 to 2,0	000 +/-cfs
ပိ	Jord	dan 1,600 +,	/-cfs	Jc	ordan 1,600	to 2,000 +/-	cfs	Jord	dan 2,000 +/	/-cfs	Jordan 2,000	1,600 to +/-cfs	Jordan 1,600 +/- cfs
e						Normal	Operations:	: 1200 cfs			1		
sa Riv w°	Gre 2 x Heflin (eater of: 1/2 Gage(Thurlo cl	Yates Inflov ow Lake rele fs)	v or ases > 350			1/2 Yate	es Inflow			1/2 Yates Inflow		ow
00 E		Thurlow La	ake 350 cfs				1/2 Yate	es Inflow			Thu	rlow Lake 3	50 cfs
Tallap		٩	Maintain 400 (Thurlow	cfs at Mont Lake releas	gomery WT e 350 cfs)	P		Thur	low Lake 35	0 cfs	Maintain WTP (Th	400 cfs at M urlow Lake r cfs)	lontgomery elease 350
P					Norn	nal Operatio	on: Navigatio	n or 4,640 c	fs flow				
ov ma	4,200) cfs (10% C	Cut) - Montgo	omery			4,640 cfs - I	Montgomery			Redu	ice: Full – 4,	200 cfs
labaı 'er Fl		3,700 cfs (2	20% Cut) - N	Nontgomery			4,200 cfs (1	10% Cut) - N	Iontgomery		Reduce Montgo	: 4,200 cfs-> omery (1 we	· 3,700 cfs ek ramp)
Riv		2,00 Montg	0 cfs jomery			3,700 cfs Montgomery	y	4,20	0 cfs (10% 0 Montgomery	Cut) - /	Reduce: Montgo	4,200 cfs -> mery (1 more)	2,000 cfs nth ramp)
on e e			Norm	al Operatior	ns: Elevation	s follow Gui	ide Curves a	s prescribed	d in License	(Measured	in Feet)		
uid urv					Corps Varia	nces: As Ne	eded; FERC	Variance f	or Lake Mar	tin			
ခြင်စိ					Corps Varia	nces: As Ne	eded; FERC	Variance f	or Lake Mar	tin			
ш					corps varia	ILES. AS NE	eueu, reku			un			

Table 7. ACT Basin Drought Regulation Plan Matrix

a. Note these are based on flows that will be exceeded when possible.

b .Jordan flows are based on a continuous +/- 5% of target flow.

c. Thurlow Lake flows are based on continuous +/- 5% of target flow: flows are reset on noon each Tuesday based on the prior day's daily average at Heflin or Yates.

d. Alabama River flows are 7-Day Average Flow.

Month	Coosa Filling Volume	Tallapoosa Filling Volume	Total Filling Volume	Minimum JBT Target Flow	Required Basin Inflow
Jan	628	0	628	4,640	5,268
Feb	626	1,968	2,594	4,640	7,234
Mar	603	2,900	3,503	4,640	8,143
Apr	1,683	2,585	4,269	4,640	8,909
May	248	0	248	4,640	4,888
Jun			0	4,640	4,640
Jul			0	4,640	4,640
Aug			0	4,640	4,640
Sep	-612	-1,304	-1,916	4,640	2,724
Oct	-1,371	-2,132	-3,503	4,640	1,137
Nov	-920	-2,748	-3,667	4,640	973
Dec	-821	-1,126	-1,946	4,640	2,694

Table 8.	Low Basin	Inflow	Guide	(in cfs-days	5)
----------	-----------	--------	-------	--------------	----



Figure 11. ACT Basin Inflows

2. Low composite conservation storage. Low composite conservation storage occurs when the APC projects' composite conservation storage is less than or equal to the storage available within the drought contingency curves for the APC reservoirs. Composite conservation storage is the sum of the amounts of storage available at the current elevation for each reservoir down to the drought contingency curve at each APC major storage project. The reservoirs considered for the trigger are R.L. Harris Lake, H. Neely Henry Lake, Logan Martin Lake, Lake Martin, and Weiss Lake. Figure 12 plots the APC composite zones. Figure 13 plots the APC low composite conservation storage trigger. If the actual active composite conservation storage indicator is triggered. That computation is performed on the first and third Tuesday of each month, and is considered along with the low state line flow trigger and basin inflow trigger.



Figure 12. APC Composite Zones



Figure 13. APC Low Composite Conservation Storage Drought Trigger

3. Low state line flow. A low state line flow trigger occurs when the Mayo's Bar USGS gage measures a flow below the monthly historical 7Q10 flow. The 7Q10 flow is defined as the lowest flow over a 7-day period that would occur once in 10 years. Table 9 lists the Mayo's Bar 7Q10 value for each month (determined from observed flows from 1949 – 2006). The lowest 7-day average flow over the past 14 days is computed and checked at the first and third Tuesday of the month. If the lowest 7-day average value is less than the Mayo's Bar 7Q10 value, the low state line flow indicator is triggered. If the result is greater than or equal to the trigger value from Table 9, the flow is considered normal, and the state line flow indicator is not triggered. The term state line flow is used in developing the drought management plan because of the proximity of the Mayo's Bar gage to the Alabama-Georgia state line and because it relates to flow data upstream of the Alabama-based APC reservoirs. State line flow is used only as a source of observed data for one of the three triggers and does not imply that flow targets exist at that geographic location. The ACT Basin drought matrix does not include or imply any Corps regulation that would result in water management decisions at Carters Lake or Allatoona Lake.

Month	Mayo's Bar (7Q10 in cfs)
Jan	2,544
Feb	2,982
Mar	3,258
Apr	2,911
Мау	2,497
Jun	2,153
Jul	1,693
Aug	1,601
Sep	1,406
Oct	1,325
Nov	1,608
Dec	2,043

Table 9. State Line Flow Triggers

Note: Based on USGS Coosa River at Rome Gage (Mayo's Bar, USGS 02397000) observed flow from 1949 to 2006

(2) <u>Drought Regulation</u>. The DIL is computed on the first and third Tuesday of each month. Once a drought operation is triggered, the DIL can only recover from drought condition at a rate of one level per period. For example, as the system begins to recover from an exceptional drought with DIL 3, the DIL must be stepped incrementally back to zero to resume normal operations. In that case, even if the system triggers return to normal quickly, it will still take at least a month before normal operations can resume - conditions can improve only to DIL 2 for the next 15 days, then DIL 1 for the next 15 days, before finally returning to normal operating conditions.

For normal operations, the matrix shows a Coosa River flow between 2,000 cfs and 4,000 cfs with peaking periods up to 8,000 cfs occurring. The required flow on the Tallapoosa River is a constant 1,200 cfs throughout the year. The navigation flows on the Alabama River are applied to the APC projects. The required navigation depth on the Alabama River is subject to the basin inflow.

For DIL 1, the Coosa River flow varies from 2,000 cfs to 4,000 cfs. On the Tallapoosa River, the required flow is the greater of one-half of the inflow into Yates Lake or twice the Heflin USGS gage from January thru April. For the remainder of the year, the required flow is one-half of Yates Lake inflow. The required flows on the Alabama River are reduced from the amounts required for DIL 0.

For DIL 2, the Coosa River flow varies from 1,600 cfs to 2,500 cfs. On the Tallapoosa River, the minimum is 350 cfs for part of the year and one-half of Yates Lake inflow for the remainder of the year. The requirement on the Alabama River is between 3,700 cfs and 4,200 cfs.

For DIL 3, the flows on the Coosa River range from 1,600 cfs to 2,000 cfs. A constant flow of 350 cfs on the Tallapoosa River is required. It is assumed an additional 50 cfs will occur between Thurlow Lake and the City of Montgomery water supply intake. Required flows on the Alabama River range from 2,000 cfs to 4,200 cfs

In addition to the flow regulation for drought conditions, the DIL affects the flow regulation to support navigation operations. Under normal operations, the APC projects are operated to meet the needed navigation flow target or 4,640 cfs flow as defined in the navigation measure section. Once drought operations begin, flow regulation to support navigation operations is suspended.

7-02. <u>Extreme Drought Conditions</u>. An extreme drought condition exists when the remaining composite conservation storage is depleted, and additional emergency actions may be necessary. When conditions have worsened to this extent, utilization of the inactive storage must be considered. Such an occurrence would typically be contemplated in the second or third year of a drought. Inactive storage capacities have been identified for the two federal projects with significant storage (Figures 14 and 15). The operational concept established for the extreme drought impact level and to be implemented when instituting the use of inactive storage is based on the following actions:

(1) Inactive storage availability is identified to meet specific critical water use needs within existing project authorizations.

(2) Emergency uses and users will be identified in accordance with emergency authorizations and through stakeholder coordination. Typical critical water use needs within the basin are associated with public health and safety.

(3) Weekly projections of the inactive storage water availability to meet the critical water uses in the ACT Basin will be utilized when making water control decisions regarding withdrawals and water releases from the federal reservoirs.

(4) The inactive storage action zones will be developed and instituted as triggers to meet the identified priority water uses (releases will be restricted as storage decreases).

(5) Dam safety considerations will always remain the highest priority. The structural integrity of the dams due to static head limitations will be maintained.



Figure 14. Storage in Allatoona Lake



Figure 15. Storage in Carters Lake (excluding reregulation pool)

VIII – DROUGHT MANAGEMENT COORDINATION AND PROCEDURES

8-01. <u>USACE Coordination</u>. It is the responsibility of the Mobile District Water Management Section and APC to monitor climatological and hydrometeorological conditions at all times to make prudent water management decisions. The Water Management Section makes daily decisions and coordinates with APC every two weeks or more often if conditions warrant and with other district representatives from the various areas for which the river systems are operated -- hydropower, recreation, navigation, environmental, and others to exchange information concerning the operation of the river system. This coordination includes conducting weekly meetings with these other district elements. Daily water management decisions regarding water availability, lake level forecasts, and storage forecasts are determined using the information obtained along with current project and basin hydrometeorological data. A weekly District River System Status report is prepared that summarizes the conditions in each of the river basins. When conditions become evident that normal low flow conditions are worsening, the Water Management Section will elevate the district coordination to a heightened awareness. When drought conditions are imminent, Emergency Management representatives will be notified of the conditions and will be included in the regular coordination activities.

8-02. <u>Interagency Coordination</u>. The Water Management Section will support the environmental team regarding actions that require coordination with the U.S. Fish and Wildlife Service (USFWS) for monitoring threatened and endangered species and with the Environmental Protection Agency (EPA), Georgia Environmental Protection Division (GAEPD), and Alabama Department of Environmental Management (ADEM) regarding requests to lower minimum flow targets below Claiborne Dam.

8-03. <u>Public Information and Coordination</u>. When conditions determine that a change in the water control actions from normal regulation to drought regulation is imminent, it is important that various users of the system are notified so that any environmental or operational preparations can be completed prior to any impending reduction in reservoir discharges, river levels, and reservoir pool levels. In periods of severe drought within the ACT Basin it will be within the discretion of the Division Commander to approve the enactment of ACT Basin Water Management conference calls. The purposes of the calls are to share ongoing water management decisions with basin stakeholders and to receive stakeholder input regarding needs and potential impacts to users within the basin. Depending upon the severity of the drought conditions, the calls will be conducted at regular monthly or bi-weekly intervals. Should issues arise, more frequent calls would be implemented.

a. Local Press and Corps Bulletins. The local press consists of periodic publications in or near the ACT Basin. Montgomery, Columbus, and Atlanta have some of the larger daily papers. The papers often publish articles related to the rivers and streams. Their representatives have direct contact with the Corps through the Public Affairs Office. In addition, they can access the Corps Web pages for the latest project information. The Corps and the Mobile District publish e-newsletters regularly which are made available to the general public via email and postings on various websites. Complete, real-time information is available at the Mobile District's Water Management homepage http://water.sam.usace.army.mil/. The Mobile

District Public Affairs Office issues press releases as necessary to provide the public with information regarding Water Management issues and activities and also provides information via the Mobile District web site.

IX – REFERENCES

- Institute for Water Resources (IWR). 1991. National Study of Water Management During Drought A Research Assessment, U.S. Army Corps of Engineers, Water Resources Support Center, Institute for Water Resources, IWR Report 91-NDS-3.
- Institute for Water Resources (IWR). 1994. National Study of Water Management During Drought The Report to the U.S. Congress, U.S. Army Corps of Engineers, Water Resources Support Center, Institute for Water Resources, IWR Report 94-NDS-12.
- Institute for Water Resources (IWR). 1998. Water Supply Handbook, U.S. Army Corps, Water Resources Support Center, Institute for Water Resources, Revised IWR Report 96-PS-4.
- U.S. Army Corps of Engineers, (USACE). 1993. Development of Drought Contingency Plans, Washington, DC: CECW-EH-W Technical Letter No. 1110-2-335, (ETL 1110-2-335).
- U.S. Army Corps of Engineers, (USACE). January 2009. Western States Watershed Study: Drought.
- U. S. Geological Survey (USGS). 2000. *Droughts in Georgia*. Open-file report 00-380. U.S. Geological Survey, Atlanta, Georgia.

PLATES

CORPS OF ENGINEERS



Ĭ

U.S. ARMY



APPENDIX H PLATE 2-2

MAIN DAM ROCK FILL SECTION



CORPS OF ENGINEERS

U.S. ARMY



APPENDIX H PLATE 2-4





CORPS OF ENGINEERS



U.S. ARMY

PENSTOCK CENTERLINE **PROFILES AND SECTIONS**

APPENDIX H PLATE 2-7

CORPS OF ENGINEERS



U.S. ARMY



CORPS OF ENGINEERS


U.S. ARMY





ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

LOW LEVEL SLUICE GATE **SECTIONS**















U.S. ARMY





LIMITS OF LAND ACQUISITION

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN







U.S. ARMY





U.S. ARMY



U.S. ARMY



	CACE
0238	2200
FLOW	GAGE HT
(cfs)	(ft)
0.66	0.25
1.2	0.3
2.9	0.4
5.6	0.5
9.5	0.6
15	0.7
21	0.8
29	0.9
39	1
113	1.5
238	2
432	2.5
685	3
960	3.5
1260	4
1960	5
3840	7
5000	8
6320	9
7800	10
9430	11
11200	12
13100	13
15200	14
17500	15
19100	15.7

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

> **USGS GAGE 02382200** RATING



USGS	GAGE
0238	2500
FLOW	GAGE HT
(cfs)	(ft)
7	2.24
8.7	2.3
12	2.4
17	2.5
31	2.7
62	3
93	3.2
130	3.4
178	3.6
231	3.8
290	4
477	4.5
725	5
1310	6
1960	7
2690	8
3470	9
4330	10
5110	11
5820	12
6500	13
7140	14
7790	15
8380	16
8930	17
9480	18
10000	19
10600	20
10800	20.4

12,000

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

> USGS GAGE 02382500 RATING



USGS	GAGE
023	83500
FLOW	GAGE HT
(cfs)	(ft)
161	3.21
182	3.3
205	3.4
226	3.5
341	4
508	4.5
690	5
1060	6
1450	7
1840	8
2660	10
3520	12
4850	15
6210	18
7610	21
9100	24
9400	24.5
9900	25
10500	25.5
11500	26
13700	27
22500	30
30300	32
34900	33
40000	34

40000

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

> USGS GAGE 02383500 RATING



		USGS	GAGE										
		0238	7500										
	FLOW	GAGE HT	FLOW	GAGE HT									
_	(cfs)	(ft)	(cfs)	(ft)									
	193	1.01	9080	14									
	218	1.1	11000	16									
	342	1.5	13100	18									
	520	2	15300	20									
_	720	2.5	17600	22									
_	940	3	20000	24									
_	1450	4	21200	25									
	2010	5	22800	26									
	2630	6	27000	28									
_	3290	7	29600	29									
_	4000	8	33000	30									
	4760	9	37900	31									
_	5550	10	43400	32									
_	6380	11	49400	33									
_	7250	12	56000	34									
		ALABAMA-COOSA		/FR BASIN									
,000	ALABAMA-COOSA-TALLAPOOSA RIVER BASIN WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM												
		USGS GA R	AGE 0238 ATING	7500									



-				
		USGS	GAGE	
		0238	38500	
	FLOW	GAGE HT	FLOW	GAGE HT
	(cfs)	(ft)	(cfs)	(ft)
	260	3	9760	16
	400	3.5	12000	18
	550	4	14400	20
	710	4.5	15600	21
	910	5	16900	22
	1150	5.5	18000	23
	1420	6	19200	24
	2000	7	21900	26
	2650	8	25000	28
	3360	9	28500	30
	4120	10	32500	32
	4940	11	37000	34
	5810	12	42000	36
	6730	13	47500	38
	7700	14		

50,000

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

> USGS GAGE 02388500 RATING



	OOSTANAU	LA GAGE AT	1
	US 27 vs.	FLOW AT	
	OOSTANAL	JLA/ETOWAH	
	CONFL	UENCE	
	GAGE HT	FLOW	
	(ft)	(cfs)	
	3	100	
	4	1300	
	5	2550	
	6	3900	
	7	5300	
	8	6900	
	9	8500	
	10	10300	
	15	19000	
	20	27500	
	20	27500	
	20	50000	
	30	20000	
	35	70000	
	40	98000	J
	STAGE FROM US	GS GAGE 02388	3525
	OOSTANAULA	RIVER AT US 2	7
	0A 2149 sq. mi. Dati	um 561.70 ft NG	VD29
	ALABAMA-COOSA-1	TALLAPOOSA RIVER BASIN	
I		NTROL MANUAL	DC
120000	REREGU	JLATION DAM	
	OOSTANAULA GA	GE AT US 27 vs. F	LOW
	AT OOSTANAULA/E	ETOWAH CONFLU	ENCE



USGS	GAGE
023	88500
FLOW	GAGE HT
(cfs)	(ft)
5.3	1.51
9.1	1.6
23	1.8
46	2
154	2.5
325	3
533	3.5
756	4
1220	5
1760	6
2930	8
4220	10
5580	12
7080	14
8660	16
10400	18
10900	18.5
11500	19
12700	20
15400	22
18800	24
23200	26
29500	28
37500	30

40,000

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

> USGS GAGE 02387000 RATING







_												
		USGS GA	USGS GAGE									
		039700	00									
_	FLOW	GAGE HT	FLOW	GAGE HT								
	(cfs)	(ft)	(cfs)	(ft)								
_	510	10	21000	20								
	722	10.3	24800	22								
	894	10.5	28300	24								
	1090	10.7	31700	26								
	1450	11	33400	27								
	1890	11.3	35500	28								
	2230	11.5	37700	29								
	2610	11.7	40800	30								
	3280	12	48000	32								
	5640	13	56500	34								
	8050	14	65700	36								
	12800	16	70500	37								
_	17000	18										
_												

80,000

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

> USGS GAGE 02397000 RATING



U.S. ARMY



U.S. ARMY

APPENDIX H PLATE 6-2



U.S. ARMY



U.S. ARMY



INFLOW-OUTFLOW-POOL CURVES

U.S. ARMY



U.S. ARMY



U.S. ARMY





U.S. ARMY

AREA CAPACITY TABLE Total Storage (Acres) Total Storage (Acre-Feet) Pool Elevation Total Area (Acres) Total Storage (Acres) 0 0 1050 2754 311403 70 200 1060 2962 339972 115 1500 1065 3060 355050 180 7500 1072 3230 377073 300 20000 1072 3230 377073 300 20000 1080 3402 403588 480 40500 1085 3530 420923 620 59000 1090 3651 438870 720 71000 1095 3770 457442 870 84000 1105 4030 491030 1180 120000 1105 4030 491030 1530 161000 1110 4150 505000 1530 161000 1131 4730 600000 1500 195000 1160						
Total Area (Acres) Total Storage (Acre-Feet) Pool Elevation Total Area (Acres) Total Storage (Acre-Feet) 0 0 1050 2754 311403 70 200 1060 2962 339972 115 1500 1065 3060 355050 180 7500 1065 3060 355050 180 7500 1072 3230 377073 300 20000 1072 3230 377073 300 20000 1080 3402 403588 480 40500 1085 3530 420923 620 59000 1090 3651 438870 720 71000 1095 3770 457442 870 84000 1105 4030 491030 1180 12000 1110 4150 505000 1420 150000 1111 4730 600000 1530 161000 1150 5250 700000		AREA CAP	ACI ⁻	TY TABLE		
(Acres) (Acre-Feet) (Feet) (Acres) (Acre-Feet) 0 0 1050 2754 311403 70 200 1060 2962 339972 115 1500 1065 3060 355050 180 7500 1065 3060 355050 180 7500 1072 3230 377073 300 20000 1072 3230 377073 300 20000 1074 3275 383565 380 29500 1080 3402 403588 480 40500 1085 3530 420923 620 59000 1095 3770 457442 870 84000 1105 4030 491030 1180 120000 1110 4150 505000 1300 132000 1110 4150 505000 1420 150000 1131 4730 600000 1530 161000 <t< td=""><td>Total Area</td><td>Total Storage</td><td></td><td>Pool Elevation</td><td>Total Area</td><td>Total Storage</td></t<>	Total Area	Total Storage		Pool Elevation	Total Area	Total Storage
0 0 1050 2754 311403 70 200 1060 2962 339972 115 1500 1065 3060 355050 180 7500 1072 3230 370671 230 11000 1072 3230 37073 300 20000 1074 3275 383565 380 29500 1080 3402 403588 480 40500 1085 3530 420923 620 59000 1090 3651 438870 720 71000 1095 3770 457442 870 84000 1105 4030 491030 1180 120000 11105 4030 496000 1300 132000 1110 4150 505000 1420 150000 1131 4730 600000 1530 161000 1142 5000 650000 1800 195000 1150	(Acres)	(Acre-Feet)		(Feet)	(Acres)	(Acre-Feet)
70 200 1060 2962 339972 115 1500 1065 3060 355050 180 7500 1065 3060 355050 180 7500 1072 3230 377073 300 20000 1072 3230 377073 300 20000 1072 3230 377073 300 20000 1080 3402 403588 480 40500 1085 3530 420923 620 59000 1095 3770 457442 870 84000 1095 3770 457442 870 84000 1105 4030 491030 1180 120000 1105 4030 491030 1530 161000 1110 4150 505000 1420 150000 1131 4730 600000 1530 161000 1142 5000 650000 1800 195000 1150	0	0		1050	2754	311403
115 1500 1065 3060 355050 180 7500 [4]1070 3179 370671 230 11000 1072 3230 377073 300 20000 [2]1074 3275 383565 380 29500 1080 3402 403588 480 40500 1085 3530 420923 620 59000 1090 3651 438870 720 71000 1095 3770 457442 870 84000 1105 4030 491030 1180 120000 1105 4030 491030 1300 132000 1110 4150 505000 1420 150000 1120 4400 550000 1530 161000 1131 4730 600000 1540 195000 1150 5250 700000 1800 195000 1150 5250 700000 1420 216000	70	200		1060	2962	339972
180 7500 $^{(4)}1070$ 3179 370671 230 11000 1072 3230 377073 300 20000 1072 3230 377073 300 20000 1074 3275 383565 380 29500 1080 3402 403588 480 40500 1085 3530 420923 620 59000 1090 3651 438870 720 71000 1095 3770 457442 870 84000 1105 4030 491030 1180 120000 1105 4030 491030 1180 120000 1110 4150 505000 1420 150000 1111 4730 600000 1530 161000 1142 5000 650000 1800 195000 1160 5530 700000 1940 216000 1167 5700 780000	115	1500		1065	3060	355050
230 11000 1072 3230 377073 300 20000 (2)1074 3275 383565 380 29500 1080 3402 403588 480 40500 1085 3530 420923 620 59000 1090 3651 438870 720 71000 1095 3770 457442 870 84000 1105 4030 491030 1180 120000 1105 4030 491030 1300 132000 1110 4150 505000 1420 150000 1120 4400 550000 1530 161000 1131 4730 600000 1540 195000 1150 5250 700000 1940 216000 1167 5700 780000	180	7500		⁽⁴⁾ 1070	3179	370671
300 20000 ⁽²⁾ 1074 3275 383565 380 29500 1080 3402 403588 480 40500 1085 3530 420923 620 59000 1090 3651 438870 720 71000 1095 3770 457442 870 84000 1105 4030 491030 1180 120000 1110 4150 505000 1300 132000 1110 4150 505000 1420 150000 1131 4730 600000 1530 161000 1142 5000 650000 1800 195000 1150 5250 700000 1940 216000 1160 5530 750000 2158 237810 1167 5700 780000	230	11000		1072	3230	377073
380 29500 1080 3402 403588 480 40500 1085 3530 420923 620 59000 1090 3651 438870 720 71000 1095 3770 457442 870 84000 1105 4030 491030 1180 120000 1105 4030 496000 1300 132000 1110 4150 505000 1420 150000 1120 4400 550000 1530 161000 1131 4730 600000 1800 195000 1150 5250 700000 1420 216000 1160 5530 75000 1800 195000 1160 5530 750000 1180 237810 1167 5700 780000	300	20000		⁽²⁾ 1074	3275	383565
480 40500 1085 3530 420923 620 59000 1090 3651 438870 720 71000 1095 3770 457442 870 84000 11099 3880 472756 980 100000 1105 4030 491030 1180 120000 1110 4150 505000 1300 132000 1110 4150 505000 1420 150000 1120 4400 550000 1530 161000 1131 4730 600000 1650 180000 1142 5000 650000 1800 195000 1150 5250 700000 1940 216000 1160 5530 750000 2158 237810 1167 5700 780000	380	29500		1080	3402	403588
$\begin{array}{c c c c c c c c c c c c c c c c c c c $	480	40500		1085	3530	420923
720 71000 1095 3770 457442 870 84000 (¹¹)1099 3880 472756 980 100000 1105 4030 491030 1180 120000 (⁵¹)106 4045 496000 1300 132000 1110 4150 505000 1420 150000 1120 4400 550000 1530 161000 1131 4730 600000 1650 180000 1142 5000 650000 1800 195000 1150 5250 700000 1940 216000 1167 5700 780000	620	59000		1090	3651	438870
870 84000 ⁽¹⁾ 1099 3880 472756 980 100000 1105 4030 491030 1180 120000 1105 4030 491030 1300 132000 1110 4150 505000 1420 150000 1120 4400 550000 1530 161000 1131 4730 600000 1650 180000 1142 5000 650000 1940 216000 1167 5700 780000	720	71000		1095	3770	457442
980 100000 1105 4030 491030 1180 120000 [^{5]} 1106 4045 496000 1300 132000 1110 4150 505000 1420 150000 1120 4400 550000 1530 161000 1131 4730 600000 1650 180000 1142 5000 650000 1800 195000 1150 5250 700000 1940 216000 1167 5700 780000	870	84000		⁽¹⁾ 1099	3880	472756
1180 120000 ⁽⁵⁾ 1106 4045 496000 1300 132000 1110 4150 505000 1420 150000 1120 4400 550000 1530 161000 1131 4730 600000 1650 180000 1142 5000 650000 1800 195000 1150 5250 700000 1940 216000 1167 5700 780000	980	100000		1105	4030	491030
1300 132000 1110 4150 505000 1420 150000 1120 4400 550000 1530 161000 1131 4730 600000 1650 180000 1142 5000 650000 1800 195000 1150 5250 700000 1940 216000 1167 5700 780000	1180	120000		⁽⁵⁾ 1106	4045	496000
1420 150000 1120 4400 550000 1530 161000 1131 4730 600000 1650 180000 1142 5000 650000 1800 195000 1150 5250 700000 1940 216000 1167 5700 780000	1300	132000		1110	4150	505000
1530 161000 1131 4730 600000 1650 180000 1142 5000 650000 1800 195000 1150 5250 700000 1940 216000 1167 5700 780000	1420	150000		1120	4400	550000
1650 180000 1142 5000 650000 1800 195000 1150 5250 700000 1940 216000 1160 5530 750000 2158 237810 1167 5700 780000	1530	161000		1131	4730	600000
1800 195000 1150 5250 700000 1940 216000 1160 5530 750000 2158 237810 1167 5700 780000	1650	180000		1142	5000	650000
1940 216000 1160 5530 750000 2158 237810 1167 5700 780000	1800	195000		1150	5250	700000
2158 237810 1167 5700 780000	1940	216000		1160	5530	750000
	2158	237810		1167	5700	780000
<u>2196 242163 1169 5800 800000</u>	2196	242163		1169	5800	800000
2353 260355 1175 6000 835000	2353	260355		1175	6000	835000
2552 284880 1182 6500 880000	2552	284880		1182	6500	880000

⁽¹⁾ Top of flood control

²⁾ Top of conservation

³⁾ Minimum conservation

⁽⁴⁾ Spillw ay crest elevation

⁵⁾ Top of gates – closed position

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

> MAIN DAM AREA CAPACITY CURVE



		AREA CAR	PACI	TY TABLE		
l Elevation	Total Area	Total Storage		Pool Elevation	Total Area	Total Storage
(Feet)	(Acres)	(Acre-Feet)		(Feet)	(Acres)	(Acre-Feet)
661	45	220		681	640	4600
662	48	265		682	662	5300
62.5	50	290		683	682	5950
663	53	315		684	700	6600
664	56	350		685	718	7300
665	59	400		686	733	8000
666	62	450		687	748	8700
667	65	510		688	762	9500
668	68	590		689	775	10200
669	71	650		690	787	11000
670	80	750		691	798	11650
671	100	900		692	812	12300
672	123	1050		693	820	13200
673	150	1300		694	831	14000
²⁾ 674	190	1500		695	842	14800
675	250	1750		696	850	15700
676	375	2000		697	860	16500
677	475	2340		⁽¹⁾ 698	870	17500
678	535	2700		⁽⁴⁾ 699	878	18400
679	573	3250		700	890	19300
680	610	4000				

- (1) Top of conservation
- (2) Minimum conservation
- (3) Spillw ay crest elevation
- (4) Top of gates closed position

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

REREGULATION DAM AREA CAPACITY CURVES

	G	ATE N	UMBE	R					POOL	ELEVA	TION																							
	1	2	3	4	670	671	672	673	674	675	676	677	678	679	680	681	682	683	684	685	686	687	688	689	690	691	692	693	694	695	696	697	698	699
STEP NO.	GATE	OPEN	IING (F	EET)					DISCH	ARGE (CFS)																							
1	0.00	0.05	0.00	0.00	16	17	18	19	20	21	21	22	23	24	24	25	26	27	27	28	28	29	30	30	31	31	32	32	33	34	34	35	35	36
2	0.00	0.10	0.00	0.00	32	34	36	38	40	42	43	45	47	48	50	51	52	54	55	56	57	59	60	61	62	63	64	66	67	68	69	70	71	72
3	0.00	0.15	0.00	0.00	49	52	55	58	60	63	66	68	70	73	75	77	79	81	83	85	87	89	90	92	94	96	97	99	100	102	104	105	107	108
4	0.00	0.20	0.00	0.00	05	70	104	110	81	84	425	91	94	97	100	103	106	108	111	113	110	118	121	123	120	128	130	132	134	130	139	141	143	145
6	0.00	0.25	0.00	0.00	93	99 150	169	166	174	120	120	129	202	200	215	221	227	233	238	244	249	255	260	265	270	275	280	284	280	203	208	200	203	205
7	0.00	0.30	0.00	0.00	140	164	176	182	190	192	206	214	202	209	235	242	248	255	250	244	249	233	200	205	295	300	306	311	316	321	326	330	335	340
8	0.00	0.40	0.00	0.00	186	198	209	220	230	240	249	258	267	276	284	292	300	308	315	322	329	336	343	350	356	363	369	375	381	388	393	399	405	411
9	0.00	0.45	0.00	0.00	224	239	252	265	278	290	301	312	323	333	353	353	362	371	380	389	398	406	414	422	430	438	446	453	461	468	475	482	489	496
10	0.00	0.50	0.00	0.00	264	281	297	312	327	341	354	367	380	392	404	415	426	437	448	458	468	478	488	497	507	516	525	534	542	551	559	568	576	584
11	0.00	0.55	0.00	0.00	281	299	316	332	348	363	377	391	404	417	430	442	454	465	477	488	498	509	519	529	539	549	559	568	577	586	595	604	613	621
12	0.00	0.60	0.00	0.00	309	329	348	366	384	400	416	431	446	460	474	487	500	513	525	529	549	561	572	584	594	605	616	626	636	646	656	666	676	685
13	0.00	0.65	0.00	0.00	361	334	407	428	448	467	485	503	520	537	553	569	584	599	613	627	641	655	668	684	694	706	719	731	743	754	766	777	788	799
14	0.00	0.70	0.00	0.00	384	409	433	455	476	497	516	535	553	571	588	605	621	637	625	667	682	696	711	724	738	751	764	777	790	802	815	827	839	851
15	0.00	0.75	0.00	0.00	421	449	474	499	522	545	566	587	607	627	645	664	681	699	716	732	748	764	780	795	810	824	839	853	867	880	894	907	920	933
16	0.00	0.80	0.00	0.00	436	464	491	516	541	564	586	608	628	648	668	687	705	723	/41	758	1/4	791	807	822	838	853	868	883	897	911	925	939	952	966
11/	0.00	0.85	0.00	0.00	506	624	661	605	703	750	702	790	817	843 972	809	893	917	940	903	985	1007	1028	1049	10/0	1120	1140	1129	1148	1107	1185	1203	1221	1239	1200
19	0.00	0.90	0.00	0.00	604	644	681	717	750	782	813	843	872	900	927	924	949	1004	1028	1020	1042	1004	1120	1142	1163	1184	1205	1225	1207	1265	1245	1204	1322	1300
20	0.00	1.00	0.00	0.00	622	663	701	738	772	805	837	868	898	926	954	981	1007	1033	1058	1083	1106	1130	1153	1175	1197	1219	1240	1261	1243	1302	1322	1342	1361	1380
21	0.00	1.00	0.05	0.00	644	687	726	764	800	834	867	899	930	959	988	1016	1044	1070	1096	1121	1146	1170	1194	1218	1240	1263	1285	1307	1328	1349	1370	1390	1410	1430
22	0.00	1.00	0.10	0.00	666	709	751	790	827	862	896	929	961	992	1022	1050	1079	1106	1133	1159	1185	1210	1234	1258	1282	1305	1328	1351	1373	1394	1416	1437	1457	1478
23	0.00	1.00	0.15	0.00	720	768	812	854	892	933	970	1006	1040	1073	1106	1137	1167	1197	1226	1255	1282	1309	1336	1362	1388	1413	1437	1462	1486	1509	1532	1555	1577	1600
24	0.00	1.00	0.20	0.00	742	791	837	880	922	962	1000	1036	1072	1106	1139	1172	1203	1234	1264	1293	1322	1349	1377	1404	1430	1456	1481	1506	1531	1555	1579	1603	1626	1649
25	0.00	1.00	0.25	0.00	775	826	874	920	963	1004	1044	1083	1120	1155	1190	1224	1257	1289	1320	1341	1381	1410	1438	1467	1494	1521	1548	1574	1600	1625	1650	1674	1698	1722
26	0.00	1.00	0.30	0.00	810	863	914	961	1006	1050	1091	1131	1170	1208	1244	1279	1314	1347	1380	1412	1443	1474	1503	1533	1562	1590	1618	1645	1672	1698	1724	1750	1775	1800
27	0.00	1.00	0.35	0.00	813	871	922	970	1016	1059	1101	1142	1181	1219	1255	1291	1326	1360	1393	1425	1456	1487	1517	1547	1576	1605	1633	1660	1687	1714	1740	1766	1792	1817
28	0.00	1.00	0.40	0.00	823	877	928	976	1022	1066	1109	1150	1189	1227	1264	1300	1335	1369	1402	1434	1466	1497	1528	1558	1587	1616	1644	1672	1699	1726	1752	1778	1804	1829
29	0.00	1.00	0.45	0.00	827	882	933	981	1028	1072	1115	1150	1195	1233	12/1	1425	1342	13/0	1409	1442	14/4	1505	1530	1500	1595	1624	1053	1080	1/08	1/35	1/05	1/88	1814	1839
31	0.00	1.00	0.50	0.00	902	901	1046	1101	1153	1202	1215	1200	1303	1345	1425	1425	1405	1544	1581	1618	1654	1689	1723	1757	1790	1822	1854	1885	1916	1946	1921	2006	2035	2000
32	0.00	1.00	0.60	0.00	953	1016	1075	1132	1185	1236	1285	1333	1378	1422	1465	1507	1548	1587	1626	1663	1700	1736	1771	1806	1840	1873	1906	1938	1970	2001	2032	2062	2092	2121
33	0.00	1.00	0.65	0.00	980	1044	1105	1163	1218	1270	1321	1369	1416	1462	1506	1549	1591	1631	1671	1709	1747	1784	1821	1856	1891	1925	1959	1992	2025	2057	2088	2120	2150	2180
34	0.00	1.00	0.70	0.00	997	1063	1125	1183	1239	1293	1344	1394	1442	1488	1533	1576	1619	1660	1701	1740	1779	1816	1853	1889	1925	1960	1994	2028	2061	2094	2126	2158	2189	2219
35	0.00	1.00	0.75	0.00	1010	1077	1140	1199	1256	1310	1362	1412	1461	1508	1553	1598	1641	1683	1723	1763	1802	1841	1878	1915	1951	1986	2021	2055	2089	2122	2154	2187	2218	2249
36	0.00	1.00	0.80	0.00	1028	1096	1160	1220	1278	1333	1386	1438	1487	1535	1581	1626	1670	1712	1754	1795	1834	1873	1912	1949	1986	2022	2057	2092	2126	2160	2193	2226	2258	2289
37	0.00	1.00	0.85	0.00	1048	1118	1183	1245	1304	1360	1415	1467	1517	1566	1613	1659	1704	1747	1790	1831	1872	1912	1950	1989	2026	2063	2099	2134	2169	2204	2238	2271	2304	2336
38	0.00	1.00	0.90	0.00	1118	1192	1261	1327	1390	1450	1508	1564	1617	1669	1720	1769	1816	1863	1908	1952	1996	2038	2080	2120	2160	2199	2238	2276	2313	2350	2386	2421	2456	2491
39	0.00	1.00	0.95	0.00	1140	1215	1286	1353	1418	1479	1538	1595	1649	1702	1754	1804	1852	1900	1946	1991	2035	2078	2121	2162	2203	2243	2282	2321	2359	2396	2433	2469	2505	2540
40	0.00	1.00	1.00	0.00	1161	1238	1310	13/9	1444	1507	1567	1625	1681	1/35	1/8/	1838	1888	1936	1983	2029	2074	2118	2161	2204	2245	2286	2326	2365	2404	2442	2480	2516	2553	2589
41	0.25	1.00	1.00	0.00	1/2/1	1500	1430	1607	1779	1001	1020	2001	2070	2127	2202	2014	2009	2122	21/3	2224	2273	2522	2309	2415	2401	2000	2000	2093	2030	2077	2/18	2109	2199	2030
42	0.25	1.00	1.00	0.25	1532	1634	1731	1822	1909	1992	2072	2149	2010	2295	2365	2205	2320	2562	2625	2686	2350	2804	2862	2918	2973	3027	3080	3132	3184	3234	3284	3333	3382	3420
44	0.50	1.00	1.00	0.50	1727	1843	1952	2056	2154	2248	2338	2425	2509	2590	2669	2746	2820	2893	2963	3032	3100	3166	3231	3294	3356	3418	3478	3537	3595	3652	3708	3764	3818	3872
45	0.75	1.00	1.00	0.50	1806	1928	2042	2150	2254	2352	2447	2538	2626	2711	2794	2871	2952	3028	3102	3174	3245	3314	3382	3449	3514	3578	3641	3703	3764	3823	3882	3940	3998	4054
46	0.75	1.00	1.00	0.75	1925	2055	2177	2293	2403	2509	2610	2707	2801	2892	2980	3066	3149	3230	3309	3387	3462	3536	3609	3680	3749	3818	3885	3951	4016	4080	4143	4205	4266	4326
47	1.00	1.00	1.00	0.75	2142	2288	2424	2554	2677	2794	2907	3016	3121	3222	3321	3416	3509	3600	3688	3774	3858	3941	4022	4101	4179	4255	4330	4404	4476	4548	4618	4687	4755	4822
48	1.00	1.00	1.00	1.00	2328	2486	2635	2776	2910	3038	3161	3279	3393	3504	3611	3715	3816	3915	4011	4105	4197	4287	4375	4461	4546	4629	4710	4791	4869	4947	5024	5099	5173	5246
49	1.25	1.00	1.00	1.00	2469	2637	2796	2946	3088	3225	3355	3481	3603	3720	3834	3945	4052	4157	4259	4359	4457	4552	4646	4738	4828	4916	5003	5088	5172	5254	5336	5416	5494	5572
50	1.25	1.25	1.00	1.00	2610	2788	2956	3115	3266	3411	3549	3683	3812	3936	4057	4174	4288	4399	4507	4613	4716	4818	4917	5014	5109	5203	5295	5385	5474	5561	5647	5732	5816	5898
51	1.25	1.25	1.25	1.00	2750	2939	3116	3284	3444	3597	3743	3884	4020	4152	4279	4403	4523	4641	4755	4867	4976	5083	5187	5290	5391	5489	5587	5682	5776	5868	5959	6048	6137	6224

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

CARTERS REREGULATION DAM SPILLWAY DISCHARGE TABLE

	G	ATE N	UMBE	R					POOL	ELEVA	TION																							
	1	2	3	4	670	671	672	673	674	675	676	677	678	679	680	681	682	683	684	685	686	687	688	689	690	691	692	693	694	695	696	697	698	699
STEP NO.	GATE	OPEN	ling (F	EET)					DISCH	ARGE ((CF S)																							
52	1.25	1.25	1.25	1.25	2890	3089	3276	3453	3621	3782	3936	4085	4228	4367	4501	4632	4758	4882	5002	5120	5235	5348	5458	5566	5672	5776	5878	5979	6077	6175	6270	6365	6457	6549
53	1.50	1.25	1.25	1.25	3029	3238	3435	3621	3798	3967	4129	4285	4436	4582	4723	4860	4993	5123	5249	5373	5494	5612	5728	5841	5953	6062	6169	6275	6379	6481	6581	6680	6778	6874
54	1.50	1.50	1.25	1.25	3168	3387	3594	3789	3975	4152	4322	4486	4644	4796	4944	5088	5228	5364	5496	5626	5753	5876	5998	6117	6233	6348	6461	6571	6680	6787	6892	6996	7098	7199
55	1.50	1.50	1.50	1.25	3306	3536	3752	3956	4151	4336	4514	4685	4851	5010	5165	5315	5462	5604	5743	5878	6011	6140	6267	6392	6514	6634	6751	6867	6981	7093	7203	7311	7418	7524
56	1.50	1.50	1.50	1.50	3443	3684	3910	4123	4326	4520	4706	4885	5057	5224	5386	5543	5695	5844	5989	6131	6269	6404	6537	6667	6794	6919	7042	7163	7281	7398	7513	7627	7738	7848
57	1.75	1.50	1.50	1.50	3581	3832	4067	4290	4502	4704	4898	5084	5264	5438	5606	5770	5929	6084	6235	6382	6527	6668	6806	6941	7074	7204	7332	7458	7582	7704	7823	7942	8058	8173
58	1.75	1.75	1.50	1.50	3/1/	3979	4224	4456	4676	4887	5089	5283	5470	5651	5826	5997	6162	6323	6481	6634	6784	6931	7075	7215	7354	7489	7622	7753	7882	8009	8133	8256	8377	8497
59	1.75	1.75	1.75	1.50	3853	4125	4381	4622	4851	5070	5279	5481	5676	5864	6046	6223	6395	6563	6726	6885	7041	7194	7343	7489	7633	1114	7912	8048	8182	8314	8443	85/1	8696	8820
61	1.75	1.75	1.75	1.75	3989	4212	4037	4/8/	5100	5252	5470	5079	1 6000	6200	6405	6675	6060	7040	7216	7130	7298	7400	7011	0027	7912	8008	8202	8343	848Z	8018	8703	8880	9015	9144
62	2.00	1.75	1.75	1.75	4124	4417	4092	4902	5199	5616	5000	6074	6201	6500	6702	6000	7002	7040	7210	7620	7000	7001	0147	0037	0191	0042	0491	0037	0/01	0923	9002	9199	9554	9407
63	2.00	2.00	2.00	1.75	4433	4302	5002	5280	5545	5797	6030	6271	6405	6712	6922	7125	7324	7516	7400	7888	8067	8243	8414	8583	8748	8910	0060	0332	9000	9227	9680	9826	9033	10113
64	2.00	2.00	2.00	2.00	4526	4851	5156	5444	5717	5978	6227	6468	6699	6923	7140	7350	7555	7754	7948	8138	8323	8504	8682	8855	9026	9193	9358	9519	9678	9834	9988	10140	10289	10436
65	4 00	2.00	2.00	2.00	5575	5987	6373	6736	7081	7410	7725	8027	8318	8600	8873	9137	9394	9645	9889	10127	10359	10587	10809	11027	11241	11451	11658	11860	12059	12255	12448	12638	12825	13010
66	4 00	4 00	2.00	2.00	6590	7091	7559	8000	8418	8816	9197	9563	9915	10255	10584	10904	11214	11516	11810	12097	12377	12651	12920	13182	13440	13693	13941	14185	14425	14661	14893	15122	15347	15569
67	4 00	4 00	4 00	2.00	7569	8162	8716	9236	9728	10197	10645	11075	11489	11888	12275	12649	13013	13367	13712	14048	14377	14698	15012	15320	15622	15918	16209	16494	16775	17051	17323	17590	17854	18113
68	4.00	4.00	4.00	4.00	8511	9200	9841	10442	11010	11551	12067	12563	13039	13499	13943	14374	14792	15199	15595	15981	16358	16727	17088	17441	17787	18127	18460	18788	19109	19426	19737	20044	20346	20643
69	6.00	4.00	4.00	4.00	9417	10204	10934	11618	12265	12879	13465	14026	14566	15087	15590	16077	16550	17010	17458	17895	18321	18738	19145	19544	19935	20319	20695	21065	21428	21785	22137	22483	22823	23159
70	6.00	6.00	4.00	4.00	10284	11172	11995	12765	13490	14179	14836	15465	16069	16652	17215	17759	18288	18802	19302	19790	20265	20730	21185	21630	22066	22494	22914	23326	23731	24129	24521	24906	25286	25660
71	6.00	6.00	6.00	4.00	11112	12105	13023	13880	14687	15452	11681	16879	17549	18194	18817	19420	20005	20573	21126	21665	22191	22705	23207	23698	24180	24652	25116	25571	26018	26457	26889	27315	27734	28146
72	6.00	6.00	6.00	6.00	11900	13002	14017	14964	15855	16698	17600	18267	19004	19713	20397	21059	21701	22324	22930	23521	24097	2460	25211	25749	26277	26794	27301	27799	28288	28769	29424	29708	30166	30618
73	8.00	6.00	6.00	6.00		13860	14977	16016	16992	17915	18792	19630	20434	21208	21954	22676	23375	24054	24715	25358	25985	26598	27196	27782	28356	28918	29470	30011	30543	31066	31580	32086	32584	33075
74	8.00	8.00	6.00	6.00		14631	15902	17036	18099	19103	20057	20968	21840	22679	23488	24270	25028	25764	26479	27175	27854	28516	29164	29797	30418	31026	31622	32207	32782	33347	33902	34449	34987	35516
75	8.00	8.00	8.00	6.00		15461	16791	18022	19175	20262	21294	22278	23221	24126	24999	25843	26659	27452	28222	28972	29703	30416	31113	31795	32462	33116	33757	34386	35004	35611	36208	36796	37374	37943
76	8.00	8.00	8.00	8.00		16201	17642	18975	20220	21392	22504	23563	24576	25549	26487	27393	28269	29119	29945	30749	31532	32297	33043	33774	34488	35189	35875	36549	37210	37860	38499	39128	39746	40355
77	10.00	8.00	8.00	8.00					21232	22492	23684	24820	25906	26948	27951	28979	29857	30765	31648	32506	33343	34158	34955	35735	36497	37244	37976	38695	39400	40093	40774	41444	42103	42752
78	10.00	10.00	8.00	8.00					22212	23561	24836	26050	27209	28321	29391	30423	31422	32390	33329	34243	35133	36001	36849	37677	38488	39282	40060	40824	41573	42309	43033	43744	44444	45134
79	10.00	10.00	10.00	8.00					23158	24598	25959	27252	28485	29669	30807	31904	32965	33992	34990	35959	36903	37824	38723	39601	40461	41302	42127	42936	43729	44509	45275	46029	46770	47500
80	10.00	10.00	10.00	10.00					24070	25604	27052	28426	29737	30992	32198	33361	34485	35573	36629	37655	38654	39628	40578	41507	42415	43305	44176	45031	45869	46693	47502	48298	47081	49851
81	12.00	10.00	10.00	10.00						26578	28115	29572	30960	32289	33565	34795	35982	3/132	38247	39330	40384	41412	42414	43394	44352	45289	46208	4/109	47992	48860	49/13	50551	51376	52187
82	12.00	12.00	10.00	10.00						2/519	29147	30688	32156	33560	34907	36204	3/450	38668	39843	40984	42094	43176	44231	45262	46270	47256	48222	49169	50098	51011	51907	52788	53655	54507
83	12.00	12.00	12.00	10.00						28420	30147	31//5	33324	34804	30223	37589	38904	40182	41417	42017	43/84	44920	40029	4/111	48169	49205	50219	51213	52188	55363	54085	57009	50466	50812
04	12.00	12.00	12.00	12.00						29299	31110	32832	34404	30021	3/314	36949	40334	410/3	42970	44228	40403	40044	4/80/	46941	51012	51135	52198	55247	56215	57262	50247	50402	56100	61275
20	14.00	14.00	12.00	12.00	-							33009	36657	3/211	40017	40200	41737	43141	44500	43019	47100	40340	49000	52544	53756	54041	56101	57239	59353	57303	60520	61575	62613	62622
87	14.00	14.00	14.00	12.00								35810	37709	30508	40017	41330	43110	44303	40000	47307	50333	516052	53022	54316	55580	56816	58026	50211	60373	61513	62632	63731	64812	65875
88	14.00	14.00	14.00	14.00								36752	38731	40614	47223	44140	45801	47404	48955	50458	51918	53337	54720	56068	57385	58673	59933	61166	62376	63562	64727	65871	66996	68102
89	16.00	14.00	14.00	14.00								30732	30731	41692	43571	45373	47107	48778	50394	51960	53480	54958	56398	57801	59171	60511	61821	63104	64361	65595	66805	67994	69163	70312
90	16.00	16.00	14 00	14 00										42740	44701	46580	48387	50128	51810	53440	55021	56559	58055	59514	60938	62330	63691	65023	66329	67610	68866	70101	71314	72506
91	16.00	16.00	16.00	14.00										43758	45803	47761	49641	51453	53203	54897	56540	58138	59692	61207	62685	64129	65542	66924	68279	69607	70911	72190	73443	74684
92	16.00	16.00	16.00	16.00										44747	46877	48914	50870	52753	54571	56331	58037	59695	61308	62879	64412	65910	67374	68807	70211	71587	72938	74263	75566	76846
93	18.50	16.00	16.00	16.00													52369	54343	56248	58091	59877	61612	63298	64941	66544	68109	69638	71135	72601	74038	75447	76831	73190	79526
94	18.50	18.50	16.00	16.00													53826	55894	57887	59815	61682	63494	65256	66971	68644	70277	71873	73434	74962	76460	77930	79372	80788	82180
95	18.50	18.50	18.50	16.00													55242	57404	59488	61501	63450	65342	67180	68969	70712	72414	74077	75703	77295	78855	80385	81886	83360	84808
96	18.50	18.50	18.50	18.50													56614	58874	61049	63150	65183	67154	69070	70933	72749	74521	76251	77943	79599	81222	82812	84373	85905	87411

U. S. ARMY

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

CARTERS REREGULATION DAM SPILLWAY DISCHARGE TABLE (continued)

PUMP-TURBINE UNIT DISCHARGE RATING TABLE WHEN PUMPING

HEAD RANGE 325-412*

HEAD	0.00	0.10	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90	HEAD	0.00	0.10	0.20	0.30	0.40	0.50	0.60	0.70	0.80	0.90
DISCHARGE IN CFS											DISCHARGE IN CFS										
325	4861	4859	4857	4855	4853	4851	4849	4848	4846	4844	370	4016	4014	4013	4011	4009	4007	4005	4003	4001	3999
326	4842	4840	4838	4836	4834	4833	4831	4829	4827	4825	371	3998	3996	3994	3992	3990	3988	3986	3984	3983	3981
327	4823	4821	4819	4818	4816	4814	4812	4810	4808	4806	372	3979	3977	3975	3973	3971	3969	3967	3966	3964	3962
328	4804	4803	4801	4799	4797	4795	4793	4791	4789	4788	373	3960	3958	3956	3954	3952	3951	3949	3947	3945	3943
329	4786	4784	4782	4780	4778	4776	4774	4773	4771	4769	374	3941	3939	3937	3936	3934	3932	3930	3928	3926	3924
330	4767	4765	4763	4761	4759	4758	4756	4754	4752	4750	375	3922	3921	3919	3917	3915	3913	3911	3909	3907	3906
331	4748	4746	4744	4743	4741	4739	4737	4735	4733	4731	376	3904	3902	3900	3898	3896	3894	3892	3891	3889	3887
332	4729	4727	4726	4724	4722	4720	4718	4716	4714	4712	377	3885	3883	3881	3879	3877	3876	3874	3872	3870	3868
333	4711	4709	4707	4705	4703	4701	4699	4697	4696	4694	378	3866	3864	3862	3861	3859	3857	3855	3853	3851	3849
334	4692	4690	4688	4686	4684	4682	4681	4679	4677	4675	379	3847	3846	3844	3842	3840	3838	3836	3834	3832	3831
	1070		1000	100-	1000		1000	1000	1050	10.50											
335	4673	4671	4669	4667	4666	4664	4662	4660	4658	4656	380	3829	3827	3825	3823	3821	3819	3817	3815	3814	3812
336	4654	4652	4651	4649	4647	4645	4643	4641	4639	4637	381	3810	3808	3806	3804	3802	3800	3799	3797	3795	3793
337	4636	4634	4632	4630	4628	4626	4624	4622	4621	4619	382	3791	3789	3/8/	3785	3784	3782	3780	3778	3776	3774
338	4617	4615	4613	4611	4609	4607	4606	4604	4602	4600	383	3772	3770	3769	3/6/	3765	3/63	3761	3759	3/5/	3/55
339	4598	4596	4594	4592	4591	4589	4587	4585	4583	4581	384	3/54	3/52	3750	3748	3746	3/44	3742	3740	3739	3131
340	4570	1577	1575	1571	1570	4570	1569	1566	1561	1560	295	3725	3722	3721	3720	3707	3725	3701	3700	3700	3710
340	4560	4550	4575	4574	4552	4570	4500	4500	4504	4502	286	3730	3733	3712	3710	3700	3707	3705	3702	3701	3600
342	4542	4540	4538	4536	4534	4532	4530	4529	4527	4525	387	3607	3605	3694	3692	3690	3688	3686	3684	3682	3680
342	4523	4521	4510	4517	4515	4514	4512	4510	4508	4506	388	3679	3677	3675	3673	3671	3660	3667	3665	3663	3662
344	4504	4502	4500	4499	4497	4495	4493	4491	4489	4487	389	3660	3658	3656	3654	3652	3650	3648	3647	3645	3643
011	-00-	4002	-1000	4400	1107	1100	4400	4401				0000	0000	0000	0004	0002	0000	00-10	0041	00+0	00+0
345	4485	4484	4482	4480	4478	4476	4474	4472	4470	4469	390	3641	3639	3637	3635	3633	3632	3630	3628	3626	3624
346	4467	4465	4463	4461	4459	4457	4455	4454	4452	4450	391	3622	3620	3618	3617	3615	3613	3611	3609	3607	3605
347	4448	4446	4444	4442	4440	4439	4437	4435	4433	4431	392	3603	3602	3600	3598	3596	3594	3592	3590	3588	3587
348	4429	4427	4425	4423	4422	4420	4418	4416	4414	4412	393	3585	3583	3581	3579	3577	3575	3573	3572	3570	3568
349	4410	4408	4407	4405	4403	4401	4399	4397	4395	4393	394	3566	3564	3562	3560	3558	3557	3555	3553	3551	3549
350	4392	4390	4388	4386	4384	4382	4380	4378	4377	4375	395	3547	3545	3543	3542	3540	3538	3536	3534	3532	3530
351	4373	4371	4369	4367	4365	4363	4362	4360	4358	4356	396	3528	3527	3525	3523	3521	3519	3517	3515	3513	3511
352	4354	4352	4350	4348	4347	4345	4343	4341	4339	4337	397	3510	3508	3506	3504	3502	3500	3498	3496	3495	3493
353	4335	4333	4332	4330	4328	4326	4324	4322	4320	4318	398	3491	3489	3487	3485	3483	3481	3480	3478	3476	3474
354	4317	4315	4313	4311	4309	4307	4305	4303	4302	4300	399	3472	3470	3468	3466	3465	3463	3461	3459	3457	3455
355	4298	4296	4294	4292	4290	4288	4287	4285	4283	4281	400	3453	3451	3450	3448	3446	3444	3442	3440	3438	3436
356	4279	4277	4275	4273	4271	4270	4268	4266	4264	4262	401	3435	3433	3431	3429	3427	3425	3423	3421	3420	3418
357	4260	4258	4256	4255	4253	4251	4249	4247	4245	4243	402	3416	3414	3412	3410	3408	3406	3405	3403	3401	3399
358	4241	4240	4238	4230	4234	4232	4230	4228	4220	4225	403	339/	3395	3393	3397	3390 2274	3300	3380	3384	3382	3380
359	4223	4221	4219	4217	4215	4213	4211	4210	4208	4200	404	33/8	33/0	33/5	33/3	33/1	3309	JJD/	3305	JJDJ	3301
360	1201	1202	4200	/109	4106	/105	/102	/101	/190	/107	405	3250	3259	3256	3354	3350	3350	3340	3346	3344	3343
361	4204	4202	4200 4191	4190	4190	4190	4193	4191	4109	410/	405	32/11	3330	3330	3334	3332	3330	3320	3378	3376	33243
362	4166	4165	4163	4161	4170	4170	4174	4172	4170	4150	400	3322	3320	3318	3316	3314	3313	3311	3300	3307	3305
363	4148	4146	4144	4142	4140	4138	4136	4135	4133	41.31	408	3303	3301	3299	3298	3296	3294	3292	3290	3288	3286
364	4129	4127	4125	4123	4121	4119	4118	4116	4114	4112	409	3284	3283	3281	3279	3277	3275	3273	3271	3269	3268
	20		1120									0207			02/0	0211	02/0	0210		0200	0200
365	4110	4108	4106	4104	4103	4101	4099	4097	4095	4093	410	3266	3264	3262	3260	3258	3256	3254	3253	3251	3249
366	4091	4089	4088	4086	4084	4082	4080	4078	4076	4074	411	3247	3245	3243	3241	3239	3237	3235	3233	3231	3229
367	4073	4071	4069	4067	4065	4063	4061	4059	4058	4056	412	3227	3225	3223	3221	3219	3217	3215	3213	3211	3209
368	4054	4052	4050	4048	4046	4044	4043	4041	4039	4037		•	•	•					•		
369	4035	4033	4031	4029	4028	4026	4024	4022	4020	4018	1										
· · · ·			•	•		•			•	•	•										

* Pumping is limited to a head of 395 due to excessive vibration

APPENDIX H PLATE 7-6

REREGULATION DAW
PUMP-TURBINE UNIT DISCHARGE
RATING TABLE

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM










APPENDIX H PLATE 7-9



APPENDIX H PLATE 7-10

U.S. ARMY

PERFORMANCE CURVES CONVENTIONAL UNIT



APPENDIX H PLATE 7-11

PERFORMANCE CURVES PUMP-TURBINE UNIT

CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM



NOTE: DAM

U.S. ARMY

TO OBTAIN CARTERS MAIN DAM TAIL WATER ELEVATIONS, ADD THE VALUED ACQUIRED FROM THESE CURVES TO THE POOL ELEVATION AT THE REREGULATION

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

MAIN DAM DISCHARGE RATE -TAILWATER RELATIONSHIP FOR VARIOUS REREGULATION POOLS

APPENDIX H PLATE 7-12



NOTE:

U.S. ARMY

TO OBTAIN CARTERS MAIN DAM TAIL WATER ELEVATIONS, SUBTRACT THE VALUED ACQUIRED FROM THESE CURVES FROM THE POOL ELEVATION AT THE REREGULATION DAM

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

PUMPING RATE – TAILWATER RELATIONSHIP FOR VARIOUS REREGULATION POOLS

APPENDIX H PLATE 7-13



APPENDIX H PLATE 8-1



APPENDIX H PLATE 8-2

FOR STANDARD PROJECT FLOOD



APPENDIX H PLATE 8-3



INFLOW-OUTFLOW-POOL RELATIONSHIPS FOR FLOOD OF MARCH 1951

WATER CONTROL MANUAL CARTERS DAM AND LAKE AND CARTERS REREGULATION DAM

ALABAMA-COOSA-TALLAPOOSA RIVER BASIN





U.S. ARMY



U.S. ARMY



APPENDIX H PLATE 8-8

U.S. ARMY



APPENDIX H PLATE 8-9



APPENDIX H PLATE 8-10

U.S. ARMY



APPENDIX H PLATE 8-11



